

- MAXIMUM ALLOWABLE OPERATING PRESS: ALUM=1500 STEEL=3000
- ELEMENT COLLAPSE RATING: 350 PSI
- ELEMENT 56 SQUARE INCHES OF FILTERING AREA.


REPLACEMENT ELEMENTS

MICRON	PART #
595	8560-595
238	8560
149	8560-01
74	8560-02
40	8560-04
25	8560-05
10C	8560-11
05C	8560-20
03G	8560-22
08G	8560-23

MODEL CODE

MODEL	PORT THREADS NPT SAE	MICRON	ELEMENT MEDIA	SEALS
1511A ALUMINUM	06 3/4 1-1/16-12 UNF-2B	595 238 149	STAINLESS STEEL WIRE CLOTH	NO SYMBOL BUNA N
1511S STEEL	08 1 1-5/16-12 UNF-2B	74 40 25	CELLULOSE PAPER	F3 VITON
1511SS STAINLESS STEEL		05C 10C 03G 08G	MICROGLASS	

MODEL NUMBER EXAMPLE: 1511SS-06-74-F3



DEBURR ALL EDGES
.002 TO .007
FILLETS .01 TO .02
RADIUS
MACHINED
SURFACES

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
3 PLACE DEC. ±	0.005
2 PLACE DEC. ±	.015
1 PLACE DEC. ±	1/32
ANGULAR ±	1°

FLOW EZY FILTERS, INC.
P.O. BOX 1749
ANN ARBOR, MI. 48106
USA
ph: 800 237-1165
fx: 800 252-1730
flowezy@flowezyfilters.com

LETTER	REVISION	BY	DATE

DISC FILE	MATERIAL:	TITLE
DB ZIP-1	SEE NOTES	ASSY OUTLINE
DR. BY	ASSY	ITEM
D BALLANTINE	REF.	NO.
DATE	RFQ #	DRAWING
07-12-06		NO.
		REV.
		151L SERIES