



(B)

MODEL	A THREAD	B HOSE I.D.	C	D	E	F HEX	O-RING	G	H
SHO-5	1-5/16-12	1/2	6-5/8	4-3/8	1"	1-1/2	3-916	1-1/16	.406
SHO-10	1-5/8-12	3/4	9-3/16	6-7/8	1"	1-7/8	3-920	1-11/32	.625
SHO-15	1-7/8-12	1	9-1/2	7-3/16	1-3/32	2-1/8	3-924	1-21/32	.812
SHO-25	2-1/2-12	1-1/4	10-3/4	8-1/4	1"	2-3/4	3-932	2-1/32	1.078
SHO-30	2-1/2-12	1-1/2	10-3/4	8-1/4	1"	2-3/4	3-932	2-1/32	1.335
SHO-50	3-3/8-12	2	11	8	1"	3-3/4	2-236	2-7/8	1.812

INNER SUPPORT TUBE (TIN PLATE)  
 SCREEN-STAINLESS STEEL  
 PLEATED WIRE CLOTH (ST. ST.)  
 EPOXY BONDED JOINTS  
 30, 60, 100, OR 200 MESH  
 STANDARD S SERIES

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		DISC FILE 18F, 76F ASSY REF.		MATERIAL	
TOLERANCES 3 PLACE DEC. ± 2 PLACE DEC. ± 1 PLACE DEC. ± ANGULAR ± DR. DATE 10-23-90		C DAY		FLOW EZY FILTERS, INC. ANN ARBOR, MICHIGAN 48106	
MACHINED SURFACES ✓		DEBURR ALL EDGES .002 TO .007 ROUNDS		TITLE SHO SERIES TANK MOUNTED SUCTION STRAINER	
SCALE NONE		CHL. DATE		ITEM NO.	
SCALE NONE		DATE		DRAWING NO. 11181-13	
SCALE NONE		DATE		SHEET OF REV. B	
SCALE NONE		DATE		SHEET OF REV. B	

REVISION	BY	DATE
B	CHANGED C & D DIM ON SHO-15	D BALL 09-24-07
A	ADDED SHO-30 & 50	C DAY 10-16-96