


(D)

MODEL SIZE	NPT	LENGTH APPROX.		DIA. F	DIA. G	SCREEN AREA IN ²	MESH SIZE	RELIEF VALVE OPTION
	A	C	D					
2	1/4, 3/8 & 1/2" NIP	3-5/8	4-1/2	.500	1.34	30	30 60 100 200	RV3 (3 PSI BY PASS) RV5 (5 PSI BY PASS)
3	3/8, 1/2 & 3/4 NIP	2-1/8	2-7/8	1.00	2-1/32	35		
5	3/4-NIP-1-NIP-	2-11/16	3-11/16	1.50	3-1/16	50		
10	3/4-NIP-1-NIP-	5	6	1.50	3-1/16	110		
	1 1/4-NIP-							
20	1 1/4-NIP-	6-9/16	7-9/16	1.50	3-1/16	145		
30	1 1/2-NIP-	8-13/16	9-3/4	2.00	4-1/16	280		
50	1 1/2-NIP-2-NIP-							
75	2 1/2-NIP-							
100	3-NIP-	11-1/4	12-5/8	2.75	5-1/16	350		
150	3-NIP-		12-3/4			450		
			17-3/4			675		

MODEL EXAMPLE:

10-3/4-NIP-100-RV3

E	REMOVED ALUMINUM OPTION	D BALL	06-12-06
D	AREA CHANGED	DRR	10-20-04
C	50 & 30 C & D CHANGED	DRR	10-20-04
B	ADDED 2 & 3 GAL SIZE	C DAY	11-07-94
A	ADDED 10-3/4-NIP	C DAY	11-19-92
LETTER	REVISION	BY	DATE

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES				DISC FILE NO. 20F-39F ASS'Y REF.		MATERIAL		TITLE ASSEMBLY SUMP STRAINER ALL METAL (NIPPLE)			
TOLERANCES				DR. C DAY DATE 08-28-91		 FLOW EZY FILTERS, INC. ANN ARBOR, MICHIGAN 48106		ITEM NO.			
3 PLACE DEC. ±	2 PLACE DEC. ±	OTHER ±	ANGULAR ±	CH. DATE				DRAWING NO.		SHEET OF REV.	
MACHINED SURFACES ✓				DEBURR ALL EDGES .002 TO .007 FILLETS .01 TO .02 RADIUS		SCALE NONE		11156-03		E	