

FILTERS



STRAINERS / BAGS / CARTRIDGES



**ROSEDALE FILTRATION PRODUCTS**



Go to  
Rosedale web



Get the Rosedale  
Catalog on a  
flash drive



Buy bags online

## **ROSEDALE**

### **Filtration Products, Inc.**

3730 W. Liberty, Ann Arbor, Michigan 48103

Phone: 800-821-5373 or 734-665-8201 Fax: 734-665-2214

[filters@rosedaleproducts.com](mailto:filters@rosedaleproducts.com)

[www.rosedaleproducts.com](http://www.rosedaleproducts.com)

#### **China - BEIJING ROSEDALE FILTER SYSTEMS COMPANY**

A303, Building A, Tech & Fortune Center,

No.8 Xueyuan Rd, Hiadian District, Beijing, China 10085

Phone: 86-10-62911957 Fax: 86-10-62915848

Email: [sales@chinarosedale.com](mailto:sales@chinarosedale.com)

#### **Texas - ROSEDALE PRODUCTS, INC.**

13700 Gillman Park, Houston, TX 77073

Phone: 281-209-1113 Fax: 281-209-0323

Email: [lynn@rosedaletx.com](mailto:lynn@rosedaletx.com)

#### **Chile - ROSEDALE FILTRACIÓN LATINOAMÉRICA**

Avenida Camilo Henríquez 4154

Puente Alto, Santiago, Chile

Phone: (56-2) 2875 2365 Cell: (56-9) 5209 8568

Email: [jcampos@rosedalefiltracion.com](mailto:jcampos@rosedalefiltracion.com)

[www.rosedalefiltracion.com](http://www.rosedalefiltracion.com)



# **Welcome**

<b>CATALOG FEATURES</b>	<b>PAGE</b>
Product Catalog Index	ii-iii
Alphabetical Product Index	iv
Application Worksheet	v
Mini Catalog / Pictorial Index A quick guide to all of our products	vi-xvi
Product Catalog	1-216
Technical Manual	217-255
Chemical Resistance Guide	256-268

Rosedale Products, Inc. is a leading technology developer in the field of liquid filtration systems and waste minimization products for customers around the globe. Our engineering achievements have produced an exceptional product line that includes high performance filtration solutions for multiple industries.

Rosedale technicians help customers find high-performing, cost effective approaches to filtration needs.

Rosedale Products, Inc. is headquartered in Ann Arbor, Michigan, and has a worldwide sales and distribution network in place.

---

ROSEDALE Products, Inc. / 3730 W. Liberty / Ann Arbor / Michigan 48103  
 Tel: 800-821-5373 or 734-665-8201 / Fax: 734-665-2214  
[filters@rosedaleproducts.com](mailto:filters@rosedaleproducts.com) / [www.rosedaleproducts.com](http://www.rosedaleproducts.com)

# INDEX

	HOUSINGS	Model No.	Page
SINGLE BAG OR BASKET	Introduction General Housing Features	—	1
	Anatomy - Single Bag Single Housing Features	—	3
	Model 4 Pipe Size 3/4" to 2"	4	4
	Model 6 Pipe Size 3/4" to 3"	6	8
	Model 8 Pipe Size 3/4" to 6"	8	12
	Model LCO Clamp Cover	LCO	17
	Model NCO Eyunut Cover	NCO	19
	Model 8-125 PSI Bag Low Cost	815 / 830	21
	Aluminum Housing Spark Free	50 / 66 / 80	23
	Heat Transfer 300°F to 700°F	HT	26
	High Pressure 740/1440 PSIG	H	29
	Model 82 Dual Capacity	82	31
	Model CR8 Polypro Plastic Housing	CR8	33
	Model OT Over the Top Style	OT	35
MULTI BAG OR BASKET	Anatomy - Multi Bag Multi Housing Features	—	38
	Multi-Bag Up to 23 Bags or Baskets	SLP/Q/HLP	39
	High Flow Up to 31 Elements	H	48
	Basket Strainer Standard or Custom	RBS / BS	75
	Duplex Continuous Operation	D	78
	Duplex - Automatic Automatic Sequencing	AD	82
	Multiplex No Interruption Servicing	M8-30	88
CARTRIDGE	Model HSS Liquid Single Cartridge	HSS	52
	Model 7180 Hydraulic Lube-Oil Filter	7180	55
	Cartridge Filters Wide Range of Capabilities	4 to 48	59
	Model 8 125 Cartridge Reduced Pressure Housing	8	68
	Platinum 700 Series Ultra High Capacity	8135/SLP/HM	70
	Platinum 900/2040 Ultra High Capacity	SLP	73
APPLICATION SPECIFIC	Coolant Filters Coolant Filtration Guide	—	110
	Water Filters Water Filtration Guide	—	117
	Sanitary Size 4 & 8 / T-Type / In-Line	SAN	121
	Bulk Load Clean Liquids When Loading	BL	125
	Mini-Bag Filter Spray Nozzle Protection	MF-1	130
	Vibrating Filter Prevents Rapid Filter Loading	VF	131
	Giardia/Cryptosporidium Drinking Water System	8302P / GFS NCO8135	133
	Coalescer Filter Remove Liquid From Gas	—	143
	Tanks Custom Filter and Bulk Tanks	—	148
FILTRATION SYSTEMS	Backwashing - Auto Automatic System	ABW	85
	Backwashing - Manual Manual Backwash System	MBW	103
	Separator Remove Solids from Liquids	SEP	90
	Indicating Visual Service Indicator	IND-8	94
	Convertible Use Bags or Cartridges	6320	100
	Portable Cart Filter Cart	PLC8	105
	Portable Cart - Coolant Coolant Cart	PFC8	107
	Sorbent Containment Carbon Holding Baskets	RS/SP	127



# INDEX

	MEDIA	Page
SINGLE LAYER BAGS	Introduction	General Element Information 150
	Bag Performance Guide	Micron, Efficiency, Beta Rate 152
	Standard Bags	Design Details 154
	Rosedale Top	Best - Low Cost 158
	Beta Bags	For Fine Filtration 159
	Graded Density	Filter to 1.0 Micron 162
	OA Polypropylene	Oil Removal Bag 166
	High Flow	For 1 to 31 Element Housings 170
CARTRIDGES	OE Series	Oil / Water Separation 168
	SurfaceMaxx	Bag Sized Cartridge 172
	Bag Sized	12 Times the Capacity of Bag 174
	Bag Sized Disposable	Low Cost 178
	Platinum	Maximum Dirt Holding Capacity 180
	Stainless Steel	Fit Cartridge Type Housings 184
	Poroplate® Filter Elements	Superior Filtration 186
	Absolute Pleated	Long Service Life 188
	Wound	All Purpose 190
SINGLE LAYER DEPTH FILTRATION BAGS	X-Tend Bag	More Surface Area 163
	Vertical Pleated Bag	50% More Surface Area 165
MEMBRANE FILTER CARTRIDGES	Membrane:	
		DI Water 193
		Pharmaceutical 195
		General Service 197
		Food 199
		Electronics 201
CONVERTER	Bag/Cartridge Converter	Turn Bag Housings into Cartridge Housings 208
BASKETS	Replacement	Baskets Fit Most Housings 203

	ETC.	
	Custom Housings	Customer Specified Housings 211
	Accessories	Housing and Media Options 215
	Technical and Chemical Resistance Guides	Index 217
	Viscosity Guide	Conversion Factors 218
	Application Guide	Housing Applications/Industries 219
	Filtration Ranges	Common Materials 223

## ALPHABETICAL INDEX

Absolute Pleated Cartridges .....	AB Series.....	188
Accessories .....		215
Automatic Backwash System.....	ABW.....	85
Aluminum Housing.....	AL.....	23
Automatic Duplex System .....	AD.....	82
Bag Sized Cartridges.....	PL Series .....	174
Beta Bags .....	BB .....	158
Cartridge Filter Housings.....		59
Cartridge Liquid Housing.....	HSS.....	52
Coalescer Filter .....		143
Conversion Guide.....		218
Custom Filter Housings.....		211
Duplex Bag Filters and Basket Strainers .....		78
Fabricated Basket Strainers.....	RBS.....	75
Filter Anatomy – Multi-Bag Features .....		38
Filter Anatomy – Single Bag Features .....		3
General Element Information.....		150
General Filter Information.....		1
Graded Density .....	GD .....	162
Heat Transfer Housing .....	HT .....	26
LCO Filters .....	LCO.....	17
Model 4 Filters .....		4
Model 6 Filters .....		8
Model 8 Filters .....		12
Model 8 125 PSI Cartridge Filters .....		68
Model 8 125 PSI Filters.....		21
Model 82 Filters .....		31
Multi-Bag Filters .....		39
Multiplex Filters .....		88
NCO Filter .....	NCO.....	19
Plastic Model 8 Filter Housing .....	CR8 .....	33
Platinum Cartridges .....	PS.....	180
Portable Coolant Filter Cart .....	PFC .....	107
Portable LCO Cart.....	PLC.....	105
Separator System .....	SEP .....	90
Stainless Steel Filter Cartridges.....		184
Standard Bags .....		154
Wound Cartridges .....		190



# Application Worksheet

TEL 800-821-5373 OR 734-665-8201

FAX 734-665-2214

fiilters@rosedaleproducts.com

<http://www.rosedaleproducts.com> or<http://www.giardiafilter.com>

Company: \_\_\_\_\_ Date: \_\_\_\_\_

Contact: \_\_\_\_\_ Phone: \_\_\_\_\_

Liquid: \_\_\_\_\_ Viscosity (cps): \_\_\_\_\_

Flow Rate (gpm): \_\_\_\_\_ Batch/Continuous: \_\_\_\_\_

Batch Size or Total Volume of Liquid: \_\_\_\_\_

%/Contaminants (ppm): \_\_\_\_\_ Temperature: \_\_\_\_\_

Pipe Size: \_\_\_\_\_ NPT/Flange: \_\_\_\_\_

Outlet Style: \_\_\_\_\_ Max PSI: \_\_\_\_\_

ASME Code: \_\_\_\_\_ Housing Construction: \_\_\_\_\_

Gasket Material: \_\_\_\_\_ Simplex/Duplex: \_\_\_\_\_

Basket/Bags: \_\_\_\_\_ Bag Material: \_\_\_\_\_

Efficiency Rating: \_\_\_\_\_ Micron/Mesh Size: \_\_\_\_\_

Notes: \_\_\_\_\_



## General Rules of Thumb:

<b>Examples:</b>	Model 4-6	=	15 gpm
	Model 4-12	=	25 gpm
	Model 6-12	=	25 gpm
	Model 6-18	=	50 gpm
	Model 6-30	=	75 gpm
	Model 8-15	=	50 gpm
	Model 8-30	=	100 gpm

# FILTER HOUSINGS

								
	<b>Models 4-6-8</b>			<b>LCO and Coolant Filter</b>		<b>4 and 8 Indicating</b>	<b>8-125 Bag Filter</b>	
<b>Application</b>	General Liquid Straining and Filtration			Low Cost High Duty Straining and Filtration		Filter and Strainer, Visual Indicator	Simple Filtration and Straining with Easy Access	
<b>Housing Size</b>	4	6	8	LCO4 LCO6 LCO8		4,8	8-125	
<b>Pipe Size (inches)</b>	3/4 to 2 NPT or ANSI	3/4 to 2 NPT or ANSI	3/4 to 3 NPT 3/4 to 6 ANSI	3/4 to 2 NPT (LCO4)	1-1/2 & 2 NPT (LCO6 and 8)	3/4 to 1 NPT 3/4 to 2 ANSI	2 NPT	
<b>Outlet Style</b>	Side In/Out, Bottom Out			Side/ Bottom Unistyle		Side In/Out, Bottom Out	Side/Bottom Unistyle	
<b>Pressure Rating</b>	150 to 500		150 to 300	125 and 200		150 200 300	125	

**Available Media for the Above Housings** See Cartridges Page xiv-xv and Bags Page xvi

## BAGS



Standard



Polypro Top



Beta Rated



Pleated



Graded Density



X-Tend



Giardia



			
<b>Model 82 Housing</b>	<b>Multi Bag Housing</b>	<b>Duplex/ Auto Duplex</b>	<b>Auto Backwash</b>
Dual Capacity Liquid Filtration and Straining	High Flow and High Capacity Liquid Filtration	Continuous Operation Liquid Filtration	Continuous Filtration with Automatic Backwashing
82	16, 18, 22, 24, 30, 36, 42, 48	4, 6, 8, 16, 18, 22, 24, 30, 36, 42, 48, 82	8
2 to 6 NPT	2 to 12	1 to 12 ANSI	2 to 12 ANSI
Side In, Bottom Out	Bottom In/Out (std) Side In/Out or Side In/Out Same Side (SLP, HLP, QII)	Side In, Side Out	Bottom In, Side Out
150 and 300	150	150	150

## CARTRIDGES



Disposable



Platinum 500



OE



Basket Convert

# FILTER HOUSINGS

					
	<b>Aluminum Housing</b>	<b>Multiplex</b>	<b>Manual Backwash</b>	<b>Sanitary Filter</b>	
<b>Application</b>	Economical, Heavy Duty Housings	Continuous Liquid Filtration and Straining	Liquid Filter with Manual Backwash	USDA/3A Dairy Standards	
<b>Housing Size</b>	6, 12, 15, 18, 30	8	8	4, 8	
<b>Pipe Size (inches)</b>	3/4 to 3 NPT	3 to 8 ANSI	2 to 4 NPT or ANSI	1 to 1-1/2 Tri-Clamp Connections	
<b>Outlet Style</b>	Side High 180, Side Low 180, Same Side High, Same Site Low Bottom	Side In, Bottom Out on Manifolds	Side Out, Bottom In	Side In, Bottom Out	
<b>Pressure Rating</b>	125 150 300	150	150	200	

**Available Media for the Above Housings** See Cartridges Page xiv-xv and Bags Page xvi

## BAGS



Standard



Polypro Top



Beta Rated



Pleated



Graded Density







X-Tend



Giardia



				
	<b>NCO Filter</b>	<b>Model OT</b>	<b>Giardia Filter</b>	<b>Portable Filtration</b>
	Low Cost Liquid Filtration	Over The Top Liquid Filtration	T2 COMPLIANT- Removal of Giardia and Other Cysts From Potable Water	Portable Liquid Filtration, One Housing Services Multiple Locations
	8	8	8	8
	1-1/2 to 2 NPT	2 NPT or ANSI	2 NPT or ANSI	1 NPT
	Side-In/Out Bottom Out	Over The Top In, Bottom Out	Side In, Bottom Out	Side In, Bottom Out
	150	150	150	125

### CARTRIDGES



Disposable



Platinum 500



OE







Basket Convert





# FILTER HOUSINGS

					
	<b>Coolant Filter Cart</b>	<b>Convertible</b>	<b>Polypro Model 8</b>	<b>Cartridge Filter</b>	
<b>Application</b>	Portable Coolant Filtering, One Housing Services Multiple Tanks	Single Housing, Uses Either Bag or Cartridge	Industrial, Potable, Ultra Pure and Deionized Applications	Cartridge Filtration- 1 to 208 Cartridges	
<b>Housing Size</b>	8	6, 8	8	4, 6, 8, 12, 16, 18, 22, 24, 30, 36, 42, 48	
<b>Pipe Size (inches)</b>	1 NPT	3/4 to 3 NPT or ANSI	2 NPT	3/4 to 3 NPT 3/4 to 12 ANSI	
<b>Outlet Style</b>	Side In, Bottom Out	Side In, Bottom Out	Side/Bottom Unistyle	Side In, Bottom Out	
<b>Pressure Rating</b>	125	150 and 300	100	150 and 300	

<b>Available Media</b>  See Cartridges Pages xiv-xv and Bags Page xvi	Holds all media from pages vi-vii	Holds all media from pages vi-vii plus the following  Membrane  Wound  SS	Holds all media from pages vi-vii plus the following  Platinum 700	 Membrane  Wound  SS	
---	-----------------------------------	---	--	---	--


			
<b>Platinum 700</b>	<b>High Flow System</b>	<b>Model 7180</b>	<b>Heat Transfer Filter</b>
High Contaminant Load Liquid Filtration	High Flow Filtration Systems	Hydraulic Lube-Oil Filter	300°F to 700°F
8	8, 18, 24, 30, 30, 36	8	8, 18, 24, 86, 1825, 2447
2 NPT or ANSI	2 to 14 ANSI	1, 1-1/2, or 2 NPT	1 to 6 ANSI
Side In, Bottom Out	Side In, Side Out	Side In, Side Out	Side Bottom, Side Side
100 125 150	150 and 300	150	85








  

			
Platinum 700	High Flow Element	718 or 736 Cartridge	Stainless Steel Wire Cloth- Wedge Wire or Glass Fiber-Wound Elements



# FILTER HOUSINGS

	 <b>Coalescer Filter</b>	 <b>HSS/HSS750</b>	 <b>Sorbent Containment</b>	 <b>Separator</b>	
<b>Application</b>	Liquid Coalescence of Gas Streams	Single Cartridge Liquid Housing	General	Solid/ Liquid Separation	
<b>Housing Size</b>	–	Custom	4, 8	–	
<b>Pipe Size (inches)</b>	1 to 8 NPT or ANSI	1 NPT (HSS) 3/4 NPT (HSS750)	3/4 to 6 NPT or ANSI	3/8 to 2-1/2 NPT 3 to 10 ANSI	
<b>Outlet Style</b>	Side In, Side Out	Top In, Top Out	Side In, Bottom Out	Side In, Top Out	
<b>Pressure Rating</b>	75	150 (HSS) 750 (HSS750)	150 to 300	150	
<b>Available Media</b>  See Cartridges Pages xiv-xv and Bags Page xvi	  Coalescer Cartridge	 M101/ M102  Wound	 Sorbent	None Required	













			
<b>Vibrating Filter</b>	<b>RBS Housing</b>	<b>Platinum 900/2040</b>	<b>High Pressure Filter</b>
Viscous Liquid Filtration	Fabricated Basket Strainer	High Capacity, High Contaminant-Load Liquid Filtration	Oil and Gas Applications
4	Custom	18, 30, 36, 42, 48	8
3/4 to 2 NPT 1 to 2 ANSI	2 to 24 ANSI	2 to 10 ANSI	1 to 6 ANSI
Side In, Bottom Out	Top In, Top Out	Bottom In, Bottom Out	Side Bottom, Side Side
300	150 (HSS) 750 (HSS750)	150	740 and 1440
			Holds all media from pages vi-vii
Stainless Steel Wire Cloth-Wedge Wire	Mesh Lined and Perforated Baskets	Platinum 900/2040	

# FILTER CARTRIDGES AND STRAINER BASKETS

	 <p><b>Disposable Pleated Cartridges</b></p>	 <p><b>Standard Platinum 500</b></p>	 <p><b>Series OE</b></p>	 <p><b>Basket Converter</b></p>	 <p><b>Sorbent Containment</b></p>	 <p><b>Perforated &amp; Perforated Mesh Lining</b></p>	
<p><b>Application</b></p>	<p>Disposable Pleated Cartridges</p>	<p>High Capacity Absolute Efficiency</p>	<p>Oil/Water Separation</p>	<p>General</p>	<p>Purification</p>	<p>General</p>	
<p><b>Description</b></p>	<p>Low Cost High Capacity Filtration</p>	<p>Rated 0.5 at 99.98%</p>	<p>Environmental Applications</p>	<p>Converts bag housing to cartridge</p>	<p>Organic removal of odors and contaminants</p>	<p>Cleanable Strainer</p>	









<p><b>Fits Housings</b></p>	<div data-bbox="339 1255 440 1381">  <p>4-6-8</p> </div> <div data-bbox="488 1255 588 1381">  <p>LCO</p> </div> <div data-bbox="636 1255 737 1381">  <p>Indicating</p> </div> <div data-bbox="785 1255 885 1381">  <p>8-125</p> </div> <div data-bbox="933 1255 1034 1381">  <p>82</p> </div> <div data-bbox="339 1419 440 1545">  <p>Multi-Bag</p> </div> <div data-bbox="488 1419 588 1545">  <p>Duplex</p> </div> <div data-bbox="636 1419 737 1545">  <p>SRF</p> </div> <div data-bbox="785 1419 885 1545">  <p>Multiplex</p> </div> <div data-bbox="933 1419 1034 1545">  <p>Manual B/W</p> </div> <div data-bbox="339 1583 440 1709">  <p>Sanitary</p> </div> <div data-bbox="488 1583 588 1709">  <p>NCO</p> </div> <div data-bbox="636 1583 737 1709">  <p>OT</p> </div> <div data-bbox="785 1583 885 1709">  <p>Giardia</p> </div> <div data-bbox="933 1583 1034 1709">  <p>Portable</p> </div> <div data-bbox="411 1747 512 1873">  <p>Coolant</p> </div> <div data-bbox="557 1747 657 1873">  <p>Convertible</p> </div> <div data-bbox="705 1747 805 1873">  <p>Polypro</p> </div> <div data-bbox="853 1747 954 1873">  <p>Platinum</p> </div>	<div data-bbox="1106 1402 1217 1545">  <p>Sorbent Containment</p> </div>	<p>None</p>	
-----------------------------	---	---	-------------	--



















# INDEX

							
	<b>Standard Wound</b>	<b>Standard Stainless Steel</b>	<b>Absolute Pleated</b>	<b>GSC-FSC-PS-ES-WS</b>	<b>Standard Platinum 700</b>	<b>Standard Platinum 900/2040</b>	<b>High Flow Element</b>
	General	General	High Capacity Efficiency	Industrial Filter Membrane Cartridges	High Capacity Absolute Efficiency		
	All Purpose	Rated 5-800 Microns	Rated to 0.5 Microns	General Service-Food, Beverage-Pharmaceutical-Electronics-Water Service-	Dirt capacity exceeds 20 lbs	Dirt capacity exceeds 100 lbs - 900 250 lbs - 2040	Up to 31 elements at 400 gpm per element
							
	Cartridge Filter			Convertible Filter	Platinum 700	Platinum 900/2040	High Flow System



# BAGS

	 <b>Standard Filter Bags</b>	 <b>Polypropylene Filter Bags</b>	 <b>High Efficiency Filter Bags</b>	
<b>Application</b>	General	General	General	High Capacity Absolute Efficiency
<b>Model Series / Description</b>	Rosedale Top / Economy	Polypropylene Top / 1-110 Micron	 Beta Rated / 1-12 Microns	 Pleated Bag Sized / 1-110 Microns
	Standard Felt / 1-100 Micron			 X-Tend / 1-110 Microns
	Standard Mesh / 50-800 Micron		 Giardia Removal / 3 Microns	
	Standard OA / Oil Adsorbent			
	Standard Teflon® / High Temp			
	Standard Nomex / High Temp			

<b>Fits Housings</b>	 4-6-8	 LCO	 Indicating	 8-125	 82	 Multi-Bag	 Duplex	 Auto B/W	 SRF
	 Multiplex	 Sanitary	 NCO	 OT	 Cart	 Coolant	 Convertible	 Polypro	 Platinum 900

## **R** Rosedale Filter Housings

**Rosedale Filter Housings** come in many sizes and styles, and can serve as bag filters, cartridge filters or basket strainers. Lids are easily removed without special tools, and the element is easily cleaned or replaced.

### Features

- Housings NSF 61 listed on most models
- Single, multi-basket, cartridge, duplex and multiplex units available
- All units are available in U.S. standard and metric connections
- Low pressure drops
- Permanently piped housings
- Sure-sealing covers, opened without special tools
- Carbon steel, stainless steel (304 or 316), or all-plastic (polypropylene or PVDF) construction
- Large-area, heavy-duty baskets
- Easy to clean!
- Adjustable-height legs (single units) or low profile (multi units)
- Differential pressure indicators (optional)
- ASME code stamp available
- Liquid displacers that minimize product loss during basket or bag removal (optional)
- Dual stage straining/filtering (optional)



Certified to  
NSF/ANSI 61



Model QII 24

### Strainer Basket or Filter Bag





Duplex Model 18  
Bag System



Model 12  
Cartridge Housing



Low Pressure  
Model 4

High Pressure  
Model 4

**DUPLEX MODELS** are two housings that are piped together for alternate use providing continuous operation, reducing operating costs. Flow is switched between the filter housings, allowing one side to be serviced while the other is in use. One lever actuates all valves simultaneously. All Duplex Models are also available in a trouble-free automatic service system.

#### CONSTRUCTION MATERIALS


All housings specified can be ordered in carbon steel, 304 or 316 stainless steel. Special alloy materials or teflon lined housings are optional. Various seal materials, including Buna, Ethylene Propylene, Viton®, and Teflon are available for most filter housings.

All baskets and cartridge internals are made of stainless steel. 304 stainless will be supplied with carbon and 304 housings, 316 stainless with 316 housings.


**NOTE:** For the anatomy of Single-bag filter see page 3.  
For the anatomy of Multi-bag filter see page 38.

**COVERS** for high capacity basket strainers, cartridge filters and bag filters are secured by eyenut assemblies. Some models can be ordered with a quick-opening clamp cover.

**CONVENIENT PIPING ARRANGEMENTS** are available to fit most piping situations. Below are standard options for Models 4, 6, and 8. Flange or NPT connections are standard on all housings, and are also available in metric.



## **Single-Bag Filter Features**



**Typical Filter**



## **R Model 4 Basket Strainer and Bag Filters**

Strainers or Bag Filters:  
Your Choice!

Model 4 strainer/filter housings are made in 2 sizes and 4 pressure ratings. In all cases, covers are easily removed without special tools, and the basket or bag is easily cleaned or replaced.

### **Features**

- Low pressure drops
- Permanently piped housings
- Covers are O-ring sealed
- Carbon steel, or stainless steel (304 or 316) construction for housings
- All housings are electropolished to resist adhesion of dirt and scale
- Easy to clean!
- Adjustable-height legs, optional
- O-ring seals: Buna N, EPR, Viton®, Teflon®
- ASME code stamp available on select models
- Liquid displacers for easier servicing
- Four pressure ratings: 200 psi (with clamp cover) and 150, 300, or 500 psi (with eyenut cover)
- Duplex units are available
- Pipe sizes 3/4 thru 2-inch, NPT or flanged (standard 150 class flange)
- Two basket depths: 6, or 12 inches (nominal)

### **Options**

- Bag filter hold-down devices
- Sanitary construction
- Different outlet connections
- Higher pressure ratings
- Extra-length legs
- Heat jacketing
- Epoxy coating
- Displacers
- Magnets



Covers are secured by three eyenut assemblies. One of them acts as a hinge, when the cover is opened.


### **Choosing A Basket Strainer Or Bag Filter**

Choose between straining (removing particles down to 74 micron size) or filtering a fluid (removing particles down to 1 micron). This will direct you to choose the correct basket when ordering.

### **Operation**

Unfiltered liquid enters the housing above the bag or basket and flows through. Solids are contained inside the bag or basket, where they're easily and completely removed when the unit is serviced.

Fluid bypass around the basket is prevented because the filter bag seals radially against the housing inside diameter. A single cover gasket is used to seal the opening, and covers can be installed and removed without tools.



## Pressure Drop Data

Basket strainers and bag filters are usually selected so that the pressure drop does not exceed 2 psi when they are clean. Higher pressure drops may be tolerated when contaminant loading is low. Bag change-out should occur at 15 psid.

The pressure drop data is accurate for all housings with strainer or bag filter baskets. When filter bags are added, total pressure drop becomes the sum of the pressure drop as determined by the steps below.

### Follow these easy steps:

1. Using the desired pipe size and approximate flow rate, determine the basic pressure drop from the appropriate graph.
2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table. This is the adjusted (clean) pressure drop for all baskets, without filter bags.
3. Add the pressure drop for the bag filter.

**Note:** Filter bags are specified separately. See page 150.

Bag Style and	1 (H <sub>2</sub> O)	Viscosity, cps							
		50	100	200	400	600	800	1000	2000
All unlined baskets	.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80
40-mesh lined	.73	.95	1.20	1.40	1.50	1.80	1.90	2.00	2.30
60-mesh lined	.77	1.00	1.30	1.60	1.70	2.10	2.20	2.30	2.80
80-mesh lined	.93	1.20	1.50	1.90	2.10	2.40	2.60	2.80	3.50
100-mesh lined	1.00	1.30	1.60	2.20	2.40	2.70	3.00	3.30	4.40
200-mesh lined	1.30	1.70	2.10	3.00	3.40	3.80	4.40	5.00	6.80


## Basket Data

Depth Nominal (inches)	Diameter (inches)	Surface Area (sq. ft.)	Volume (cu. in.)	Bag Size No.
6	3.9	0.5	65	3
12	3.9	1.0	130	4

## Model 4—For flow rates to 50 gpm\*



Clamp covers to the left and center, and eyenut cover to the right.




\*Based on housing only. Fluid viscosity, bag filter used, and expected dirt loading should be considered when sizing a filter.

## Dimensions (IN)

### Cover Types



#### EYENUT COVER

ANSI flanged connections and 500 Series with pipe threads



#### CLAMP COVER

Rated 200 psi with NPT connections



## Outlet Styles


Flanged 150 lb. ANSI

Threaded NPT


Flanged 150 lb. ANSI

Threaded NPT


#### STYLE 1




#### STYLE 2



#### STYLE 3



#### STYLE 4



A clearance distance equal to basket depth must be available above housing for basket removal.

Legs for Model 4 are optional at extra cost.

## Dimensions (IN)

Model Size	Pipe	A	A1	A2	B	C	D	E	F	G	H	L	M
4-6	3/4	5.5	1.9	2.3	3.5	5.0	10.1	12.0	4.5	10.1	10.5	4.0	2.0
	1	5.5	1.9	2.3	3.5	5.0	10.3	12.0	4.5	10.1	10.9	4.0	2.5
	1-1/4	6.1	2.5	2.9	3.5	5.0	9.7	12.0	4.5	9.4	10.6	4.0	2.9
	1-1/2	6.1	2.5	2.9	3.5	5.0	9.6	12.0	4.5	9.4	10.9	4.0	3.3
	2	6.1	2.5	2.9	3.5	5.0	9.6	12.0	4.5	9.4	11.6	5.0	4.1
4-12	3/4	5.5	1.9	2.3	3.5	5.0	16.1	18.0	4.5	16.1	16.5	4.0	2.0
	1	5.5	1.9	2.3	3.5	5.0	16.3	18.0	4.5	16.1	16.9	4.0	2.5
	1-1/4	6.1	2.5	2.9	3.5	5.0	15.7	18.0	4.5	15.4	16.6	4.0	2.9
	1-1/2	6.1	2.5	2.9	3.5	5.0	15.6	18.0	4.5	15.4	16.9	4.0	3.3
	2	6.1	2.5	2.9	3.5	5.0	15.6	18.0	4.5	15.4	17.6	5.0	4.1

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## How To Order

Build an ordering code as shown in the example

**HOUSING**                      **OPTIONS**

**Example: 4 - 12 - 2P - 1 - 500 - C - B - S - M 200 - D - C**

<p><b>MODEL NO.</b> Eyenut Cover = <b>4</b> Clamp Cover = <b>LCO 4</b></p> <p><b>HOUSING SIZE</b> 6 inch = <b>6</b> 12 inch = <b>12</b></p> <p><b>PIPE SIZE, NPT and FLANGED<sup>1</sup></b>            3/4-in. female NPT = <b>3/4P</b>            1-in. female NPT = <b>1P</b>            1-1/4-in. female NPT = <b>1-1/4P</b>            1-1/2-in. female NPT = <b>1-1/2P</b>            2-in. female NPT = <b>2P</b>            3/4-in. 150 class ANSI flange = <b>3/4F</b>            1-in. 150 class ANSI flange = <b>1F</b>            1-1/4-in. 150 class ANSI flange = <b>1-1/4F</b>            1-1/2-in. 150 class ANSI flange = <b>1-1/2F</b>            2-in. 150 class ANSI flange = <b>2F</b></p> <p><b>OUTLET STYLE</b>            Bottom = <b>1</b>            Side High 180 = <b>2</b>            Bottom elbow = <b>3</b>            Same Side High = <b>4</b></p> <p><b>PRESSURE RATING<sup>2</sup></b>            150 psi (flanged) = <b>150</b>            200 psi (NPT) (Clamp Cover only) = <b>200</b>            300 psi (flanged) = <b>300</b>            500 psi (NPT) = <b>500</b></p> <p><b>HOUSING MATERIAL</b>            Carbon steel = <b>C</b>            304 stainless steel = <b>S</b>            316 stainless steel = <b>S316</b></p>	<p><b>ASME CODE STAMP</b> <b>C</b> = Code</p> <p><b>DISPLACER</b> <b>D</b> = Displacer</p> <p><b>BASKET, MEDIA SIZE</b>  <b>No symbol if type B basket was selected</b>            Perforation diameters (for type P baskets) 1/4, 3/16, 9/64, 3/32, 1/16            Mesh sizes (for type M and BM baskets) 20, 30, 40, 50, 60, 70, 80, 100, 150, 200</p> <p><b>BASKET TYPE</b>  <b>PB</b> = Filter bag basket, 9/64 perforations<sup>3</sup>  <b>P</b> = Strainer basket, perforated metal  <b>BM</b> = Filter bag basket, perforated, mesh lined<sup>3</sup>  <b>M</b> = Strainer basket, perforated, mesh lined with spring handle  <b>HWM</b> = Filter bag basket, heavy wire mesh<sup>3</sup></p> <p><b>BASKET SEAL</b>  <b>N</b> = No seal (with bag type baskets)  <b>S</b> = Seal required (on strainer type baskets)</p> <p><b>COVER SEAL</b>  <b>B</b> = Buna N  <b>E</b> = Ethylene Propylene  <b>V</b> = Viton® Fluoroelastomer</p> <p><b>Eyenut Cover Only</b>  <b>TEV</b> = Teflon® Encapsulated Viton®  <b>TSW</b> = Teflon® (solid white)</p>
---	---

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.

2. Higher pressure ratings available. Consult factory.

3. Filter bags are specified separately. See page 150.

4. 150 psi unit has 150 class flanges. 300 psi unit has 300 class flanges. 200 and 500 unit available in NPT only.



## **R Model 6 Basket Strainer and Bag Filters**

Strainers or Bag Filters:  
Your Choice!

Model 6 strainer/filter housings are made in 3 sizes and 3 pressure ratings, and can serve as basket strainers (for particle retention down to 74 micron size) or as bag filters (for particle retention down to 1 micron size). In all cases, covers are easily removed without special tools, and the basket or bag is easily cleaned or replaced.

### **Features**

- Low pressure drops
- Permanently piped housings
- Covers are O-ring sealed
- Carbon steel, or stainless steel (304 or 316) construction for housings
- All housings are electropolished to resist adhesion of dirt and scale
- Easy to clean!
- Adjustable-height legs, standard
- O-ring seals: Buna N, EPR, Viton®, Teflon®
- ASME code stamp available
- Three pressure ratings: 150, 210 or 300 psi
- Duplex units are available
- Can provide 3.4 square feet of basket or bag surface area without need for ASME code construction
- Three basket depths: 12, 18, or 30 inches (nominal)
- Special alloys

### **Options**

- Sanitary construction
- Different outlet connections
- Higher pressure ratings
- Extra-length legs
- Heat jacketing
- Liquid displacers for easier servicing



Covers are secured by three eyenut assemblies. One of them acts as a hinge, when the cover is opened.


### **Choosing a Basket Strainer or Bag Filter**

Choose between straining (removing particles down to 74 micron size) or filtering a fluid (removing particles down to 1 micron). This will direct you to the correct basket when ordering.

### **Operation**

Unfiltered liquid enters the housing above the bag or basket and passes down through them. Solids are contained inside the bag or basket, where they are easily and completely removed when the unit is serviced.

Fluid bypass around the basket is prevented because the outside diameter of the filter bag seals against the housing inside diameter.



A single cover gasket is used to seal the opening, and covers can be installed and removed without tools.

## Pressure Drop Data

Basket strainers and bag filters are usually selected so that the pressure drop does not exceed 2 psi, when they are clean. Higher pressure drops may be tolerated, when contaminant loading is low. Bag change should occur at 15psid.

The pressure drop data is accurate for all housings with strainer or bag filter baskets. When bag filters are added, total pressure drop becomes the sum of the pressure drop as determined by the steps below, plus the pressure drop through the bag as defined in Rosedale Filter Bag section.

### Follow these easy steps:

1. Using the desired pipe size and approximate flow rate, determine the basic pressure drop from the appropriate graph.
2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table. This is the adjusted (clean) pressure drop for all baskets, without bag filters.
3. Add the pressure drop for the bag filter.


**Note:** Filter bags are specified separately. See page 150.

	1 (H <sub>2</sub> O)	Viscosity, cps							
		50	100	200	400	600	800	1000	2000
All unlined baskets	.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80
40-mesh lined	.73	.95	1.20	1.40	1.50	1.80	1.90	2.00	2.30
60-mesh lined	.77	1.00	1.30	1.60	1.70	2.10	2.20	2.30	2.80
80-mesh lined	.93	1.20	1.50	1.90	2.10	2.40	2.60	2.80	3.50
100-mesh lined	1.00	1.30	1.60	2.20	2.40	2.70	3.00	3.30	4.40
200-mesh lined	1.30	1.70	2.10	3.00	3.40	3.80	4.40	5.00	6.80

## Basket Data

Depth Nominal (inches)	Diameter (inches)	Surface Area (sq. ft.)	Volume (cu. in.)	Bag Size No.
12	5	1.3	235	7
18	5	2.0	350	8
30	5	3.4	630	9

## Model 6-For flow rates to 100 gpm\*



\*Based on housing only. Fluid viscosity, bag filter used, and expected dirt loading should be considered when sizing a filter.




Eyenu covers with bag filter and basket or basket strainer.

## Dimensions (IN)

### Cover Types

#### EYENUT COVER



A clearance distance equal to basket depth must be available above housing for basket removal.


## Outlet Styles

Flanged 150 lb. ANSI

Threaded NPT

Flanged 150 lb. ANSI

Threaded NPT



## Dimensions (IN)

Model	Pipe Size	A	A1	B	C	D	E	F	G	H	L	N	M
6-12	1	7.6	3.9	4.3	6.0	16.6	19.0	4.3	17.4	18.1	5.0	2.5	N/A
	1-1/4	7.6	3.9	4.3	6.0	16.6	19.0	4.7	17.4	18.4	5.0	2.9	N/A
	1-1/2	7.6	3.9	4.3	6.0	16.6	19.0	4.7	17.4	18.8	5.0	3.3	N/A
	2	7.6	3.9	4.3	6.0	16.6	19.0	6.6	16.5	18.6	5.0	4.0	N/A
	3	7.9	4.1	4.3	6.0	17.5	19.6	6.6	17.0	20.5	7.3	6.1	N/A
6-18	1	7.6	3.9	4.3	6.0	21.8	24.3	4.3	22.7	23.3	5.0	2.5	15.0
	1-1/4	7.6	3.9	4.3	6.0	21.8	24.3	4.7	22.7	23.7	5.0	2.9	15.0
	1-1/2	7.6	3.9	4.3	6.0	21.8	24.3	4.7	22.7	24.0	5.0	3.3	15.0
	2	7.6	3.9	4.3	6.0	21.8	24.3	6.6	21.8	23.8	5.0	4.0	15.0
	3	7.9	4.1	4.3	6.0	23.0	25.1	6.6	22.5	26.0	7.3	6.1	17.0
6-30	1	7.6	3.9	4.3	6.0	32.8	34.3	4.3	32.7	33.3	5.0	2.5	15.0
	1-1/4	7.6	3.9	4.3	6.0	32.8	34.3	4.7	32.7	33.7	5.0	2.9	15.0
	1-1/2	7.6	3.9	4.3	6.0	32.8	34.3	4.7	32.7	34.0	5.0	3.3	15.0
	2	7.6	3.9	4.3	6.0	32.8	34.3	6.6	31.8	33.8	5.0	4.0	15.0
	3	7.9	4.1	4.3	6.0	33.0	35.1	6.6	32.5	36.0	7.3	6.1	17.0

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

Material	Carbon Steel	304 Stainless Steel	304L Stainless Steel	316 Stainless Steel	316L Stainless Steel
Temperature	Class 150 ANSI, B16.5 Flanges				
400°F@150 PSI	■	■	■	■	■
325°F@210 PSI	■			■	
275°F@210 PSI		■			
155°F@210 PSI			■		■
	Class 300 ANSI, B16.5 Flanges				
400°F@300 PSI	■	■	■	■	■



## How To Order

Build an ordering code as shown in the example

**Example:** **6 - 30 - 3P - 1 - 300 - C - B - S - M 200 - D - C**

**MODEL NO.**  
6 = 6

**HOUSING SIZE**  
12 inch = 12  
18 inch = 18  
30 inch = 30

**PIPE SIZE, NPT and FLANGED<sup>1</sup>**  
3/4-in. female NPT = 3/4P  
1-in. female NPT = 1P  
1-1/4-in. female NPT = 1-1/4P  
1-1/2-in. female NPT = 1-1/2P  
2-in. female NPT = 2P  
3-in. female NPT = 3P  
3/4-in. 150 class ANSI flange = 3/4F  
1-in. 150 class ANSI flange = 1F  
1-1/4-in. 150 class ANSI flange = 1-1/4F  
1-1/2-in. 150 class ANSI flange = 1-1/2F  
2-in. 150 class ANSI flange = 2F  
3-in. 150 class ANSI flange = 3F

**OUTLET STYLE**  
Bottom = 1  
Side High 180 = 2  
Bottom elbow = 3  
Same Side High = 4  
Same Side Low = D

**PRESSURE RATING<sup>2</sup>**  
150 psi (flanged or NPT) = 150  
210 psi (flanged or NPT) = 210  
300 psi (flanged or NPT) = 300

**HOUSING MATERIAL**  
Carbon steel = C  
304 stainless steel = S  
316 stainless steel = S316

**ASME CODE STAMP**  
C = Code

**DISPLACER**  
D = Displacer

**BASKET, MEDIA SIZE**  
No symbol if type B basket was selected  
Perforation diameters (for type P baskets) 1/4, 3/16, 9/64, 3/32, 1/16  
Mesh sizes (for type M and BM baskets) 20, 30, 40, 50, 60, 70, 80, 100, 150, 200

**BASKET TYPE**  
PB = Filter bag basket, 9/64 perforations<sup>3</sup>  
P = Strainer basket, perforated metal  
BM = Filter bag basket, perforated, mesh lined<sup>3</sup>  
M = Strainer basket, perforated, mesh lined  
HWM = Filter bag basket, heavy wire mesh<sup>3</sup>

**BASKET SEAL**  
N = No seal  
S = Seal required (mesh baskets)

**COVER SEAL**  
B = Buna N  
E = Ethylene Propylene  
V = Viton® Fluoroelastomer  
TEV = Teflon® Encapsulated Viton®  
TSW = Teflon® (solid white)

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.  
2. Higher pressure ratings available. Consult factory.  
3. Filter bags are specified separately. See page 150.  
4. 150 psi unit has 150 class flanges. 300 psi unit has 300 class flanges. 210 psi unit available only in NPT.

## **R Model 8 Basket Strainer and Bag Filters**

Strainers or bag filters:  
Your choice!

Model 8 strainer/filter housings are made in 2 sizes and 2 pressure ratings, and can serve as basket strainers (for particle retention down to 74 micron size) or as bag filters (for particle retention down to 1 micron size). In all cases, covers are easily removed, without tools, and the basket or bag is easily cleaned or replaced.

### **Features**

- NSF 61 listed
- Low pressure drops
- Permanently piped housings
- Covers are O-ring sealed
- Carbon steel, or stainless steel (304 or 316) construction for housings
- All housings are electropolished to resist adhesion of dirt and scale
- Easy to clean!
- Adjustable-height legs, standard
- Large-area, heavy-duty baskets
- O-ring seals: Buna N, EPR, Viton®, Teflon®
- ASME code stamp available
- Two pressure ratings: 150 and 300
- Duplex units are available
- Pipe sizes 3/4 thru 6-inch, NPT or flanged
- Two basket depths: 15 or 30 inches (nominal)



Certified to  
NSF/ANSI 61



### **Choosing A Basket Strainer Or Bag Filter**

Choose between straining (removing particles down to 74 micron size) or filtering a fluid (removing particles down to 1 micron). This will direct you in selecting the correct basket when ordering.

### **Options**

- Sanitary construction
- Different outlet connections
- Higher pressure ratings
- Extra-length legs
- Heat jacketing
- Adapters for holding filter cartridges.
- Liquid displacers for easier servicing
- Can be fitted with an adapter to hold cartridge filter elements

### **Dual Stage Straining/Filter**

All Rosedale Model 8 housings can be supplied with a second, inner basket, which is supported on the top flange of the regular basket. Both baskets can be strainers (with or without wire mesh linings) or both can be baskets for filter bags. They can also be mixed: one a strainer basket, the other a filter bag basket. Dual-stage action will increase strainer or filter life and reduce servicing needs.






## Operation


Unfiltered liquid enters the housing above the bag or basket and flows through. Solids are contained inside the bag or basket, where they are easily removed when the unit is serviced.

A basket bail is pushed down by the closed cover to hold the basket against a positive stop in the housing. A radial seal prevents bypass of unfiltered liquid.



	1 (H <sub>2</sub> O)	Viscosity, cps							
		50	100	200	400	600	800	1000	2000
All unlined baskets	.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80
40-mesh lined	.73	.95	1.20	1.40	1.50	1.80	1.90	2.00	2.30
60-mesh lined	.77	1.00	1.30	1.60	1.70	2.10	2.20	2.30	2.80
80-mesh lined	.93	1.20	1.50	1.90	2.10	2.40	2.60	2.80	3.50
100-mesh lined	1.00	1.30	1.60	2.20	2.40	2.70	3.00	3.30	4.40
200-mesh lined	1.30	1.70	2.10	3.00	3.40	3.80	4.40	5.00	6.80

## Model 8—For flow rates to 220 gpm\*



\*Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.

## Pressure Drop Data

Basket strainers and bag filters are usually selected so that the pressure drop does not exceed 2 psi, when they are clean. Higher pressure drops may be tolerated, when contaminant loading is low. Bag change occurs at 15 psid.

The pressure drop data is accurate for all housings with strainer or filter bag baskets. When filter bags are added, total pressure drop becomes the sum of the pressure drop as determined by the steps below.

### Follow these easy steps:

1. Using the desired pipe size and approximate flow rate, determine the basic pressure drop from the appropriate graph.
2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table. This is the adjusted (clean) pressure drop for all baskets without filter bags.
3. Add the pressure drop for the bag.

**Note:** Filter bags are specified separately. See page 150.

## Basket Data

Depth Nominal (inches)	Diameter (inches)	Surface Area (sq. ft.)	Volume (cu. in.)	Bag Size No.
15	6.7	2.3	500	1
30	6.7	4.4	1000	2





Eyenu covers with filter bag and basket.

## Dimensions (IN)

### Cover Type


#### EYENUT COVER 150 PSIG - 3 Bolt Design



A clearance distance equal to basket depth must be available above housing for basket removal.

## Outlet Styles

Flanged 150 lb. ANSI    Threaded NPT    Flanged 150 lb. ANSI    Threaded NPT



## Dimensions (IN) 150 PSIG Design


Model	Pipe Size	A	A1	A2	B	C	D	E	F	G	H	I	J	K	L	M
8-15	2	9.1	5.4	2.9	5.9	7.5	20.6	23.4	8.0	20.9	22.8	3.25	5.0	4.06	4.25	N/A
	3	9.1	5.4	3.7	6.8	7.5	21.3	23.4	8.0	20.9	24.3	3.25	7.25	6.12	4.25	N/A
	4	9.1	5.4	5.0	6.8	8.6	21.3	23.9	8.0	20.9	25.6	3.25	9.0	7.75	4.25	N/A
	6	9.4	5.6	5.9	7.1	8.6	23.6	27.1	9.0	23.4	30.9	4.12	12.5	11.0	4.5	N/A
8-30	2	9.1	5.4	2.9	5.9	7.5	35.6	38.4	8.0	35.9	37.8	3.25	5.0	4.06	4.25	15.0
	3	9.1	5.4	3.7	6.8	7.5	36.3	38.4	8.0	35.9	39.3	3.25	7.25	6.12	4.25	17.0
	4	9.1	5.4	5.0	6.8	8.6	36.3	38.9	8.0	35.9	40.6	3.25	9.0	7.75	4.25	18.0
	6	9.4	5.6	5.9	7.1	8.6	38.6	42.1	9.0	38.4	45.9	4.12	12.5	11.0	4.5	20.0

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## Dimensions (IN)

### Cover Type


#### EYENUT COVER 300 PSIG - 6 Bolt Design



A clearance distance equal to basket depth must be available above housing for basket removal.

## Outlet Styles

Flanged 300 lb. ANSI    Threaded NPT    Flanged 300 lb. ANSI    Threaded NPT



## Dimensions (IN) 300 PSIG Design

Model Size	Pipe	A	A1	B	C	D	E	F	G	H	I	J	K	L	M
8-15	2	9.25	5.4	5.9	7.5	20.6	23.4	8.0	20.9	22.8	3.25	5.0	4.06	4.25	N/A
	3	9.25	5.4	6.8	7.5	21.3	23.4	8.0	20.9	24.3	3.25	7.25	6.12	4.25	N/A
	4	9.25	5.4	6.8	8.6	21.3	23.9	8.0	20.9	25.6	3.25	9.0	7.75	4.25	N/A
	6	9.4	5.6	7.1	8.6	23.6	27.1	9.0	23.4	30.9	4.12	12.5	11.0	4.5	N/A
8-30	2	9.25	5.4	5.9	7.5	35.6	38.4	8.0	35.9	37.8	3.25	5.0	4.06	4.25	15.0
	3	9.25	5.4	6.8	7.5	36.3	38.4	8.0	35.9	39.3	3.25	7.25	6.12	4.25	17.0
	4	9.25	5.4	6.8	8.6	36.3	38.9	8.0	35.9	40.6	3.25	9.0	7.75	4.25	18.0
	6	9.4	5.6	7.1	8.6	38.6	42.1	9.0	38.4	45.9	4.12	12.5	11.0	4.5	20.0

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



## How To Order

Build an ordering code as shown in the example

		HOUSING	OPTIONS	OPTIONAL INNER BASKET
<b>Example: 8-15-3P-1-150-C-B-S-M-200-D-C - 2M 50</b>				
<b>MODEL NO.</b> 8 = 8				
<b>HOUSING SIZE</b> 15 inch = 15 30 inch = 30				
<b>PIPE SIZE, NPT and FLANGED<sup>1</sup></b> 3/4-in. female NPT = 3/4P 1-in. female NPT = 1P 1-1/4-in. female NPT = 1-1/4P 1-1/2-in. female NPT = 1-1/2P 2-in. female NPT = 2P 3-in. female NPT = 3P 3/4-in. 150 class ANSI flange = 3/4F 1-in. 150 class ANSI flange = 1F 1-1/4-in. 150 class ANSI flange = 1-1/4F 1-1/2-in. 150 class ANSI flange = 1-1/2F 2-in. 150 class ANSI flange = 2F 3-in. 150 class ANSI flange = 3F 4-in. 150 class ANSI flange = 4F 6-in. 150 class ANSI flange = 6F				
<b>OUTLET STYLE</b> Bottom = 1 Side High 180 = 2 Bottom elbow = 3 Same Side High = 4 Same Side Low = D				
<b>PRESSURE RATING<sup>2</sup></b> 150 psi (NPT or flanged) = 150 300 psi (NPT or flanged) = 300				
<b>HOUSING MATERIAL</b> Carbon steel = C 304 stainless steel = S 316 stainless steel = S316				
<b>COVER SEAL</b> Buna N = B Ethylene Propylene = E Viton® Fluoroelastomer = V Teflon® Encapsulated Viton® = TEV <sup>5</sup> Teflon® (solid white) (6 Bolt Cover) = TSW <sup>5</sup>				
<b>BASKET SEAL</b> Seal required = S				
				<b>OPTIONAL INNER BASKET, MEDIA SIZE-No symbol if type 2B basket was selected</b>  Perforation diameters (for type 2P baskets) 1/4, 3/16, 9/64, 3/32, 1/16  Mesh sizes (for type 2M and 2BM baskets) 20, 30, 40, 50, 60, 70, 80, 100, 150, 200  <b>OPTIONAL INNER BASKET TYPE</b> <b>2B</b> = Filter bag basket, 9/94 perforations <sup>3</sup> <b>2P</b> = Strainer basket, perforated metal <b>2BM</b> = Filter bag basket, perforated, mesh lined <sup>3</sup> <b>2M</b> = Strainer basket, perforated, mesh lined  <b>ASME CODE STAMP</b> <b>C</b> = Code <b>NSF</b> = NSF 61 listed  <b>DISPLACER</b> <b>D</b> = Displacer  <b>BASKET, MEDIA SIZE-No symbol if type B basket was selected</b> Perforation diameters (for type P baskets) 1/4, 3/16, 9/64, 3/32, 1/16  Mesh sizes (for type M and BM baskets) 20, 30, 40, 50, 60, 70, 80, 100, 150, 200  <b>BASKET TYPE</b> <b>PB</b> = Filter bag basket, 9/64 perforations <sup>3</sup> <b>P</b> = Strainer basket, perforated metal <b>BM</b> = Filter bag basket, perforated, mesh lined <sup>3</sup> <b>M</b> = Strainer basket, perforated, mesh lined <b>HWM</b> = Filter bag basket, heavy wire mesh <sup>3</sup>

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.

2. Higher pressure ratings available. Consult factory.

3. Filter bags are specified separately. See page 150.

4. 150 psi unit has 150 class flanges. 300 psi unit has 300 class flanges.

5. 300 psi design only (6 bolt lid).

## **R Model LCO Bag Filter Housings**

Low cost filter housings for flow rates to 100 gpm\*


These high-capacity bag filters are low in cost and offer more dirt holding capacity. These housings are made from carbon steel or stainless steel. They use a clamp cover that is easily removed, reducing time spent on cleaning and bag replacement. Housings also utilize our Unistyle design offering you the option of a side or bottom outlet. There is a 1-1/2-inch or 2-inch inlet and outlet on the side, with a 1-1/2-inch or 2-inch plugged drain at the bottom of the housing. The outlet can easily be changed to the bottom by merely moving the plug from the drain to the side outlet.

### **Features**

- Permanently piped housings are opened without special tools
- Quick opening cover
- Carbon or stainless steel housings
- Large area bag and basket for greater dirt-holding capacity
- O-ring seals: Buna N, EPR and Viton®
- Adjustable-height tripod legs
- 125 psi rated housing
- Basket material is compatible with housing
- Bag surface area is 5.6 square feet (LCO8), and 2.0 square feet (LCO6)
- Uses number 12 size bags (LCO8), and number 8 size bags (LCO6)
- 2-inch NPT ports (LCO8)

**Note:** Filter bags are specified separately. See page 150.

\*Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.






## Model LCO

Build an ordering code as shown in the example.

	Housing	Options
<b>Example :</b>	<b>LCO8-30 - 2P - * - 125 - C - B - PB</b>	
<b>MODEL</b>		
<b>LCO6</b>		
<b>LCO8</b>		
<b>HOUSING SIZE</b>		
18-inch (6)	<b>= 18</b>	
30-inch (8)	<b>= 30</b>	
<b>PIPE SIZE</b>		
1-1/2-inch female NPT (6)	<b>= 1-1/2P</b>	
2-inch female NPT (8)	<b>= 2P</b>	
<b>OUTLET STYLE</b>		
Side/Bottom Unistyle	<b>= *</b>	
<b>PRESSURE RATING</b>		
125 psi	<b>= 125</b>	
<b>HOUSING MATERIAL</b>		
Carbon steel	<b>= C</b>	
304 Stainless steel	<b>= S</b>	
<b>COVER SEAL</b>		
Buna N	<b>= B</b>	
Ethylene propylene	<b>= E</b>	
Viton® Fluoroelastomer	<b>= V</b>	
<b>BASKET TYPE</b>		
Filter bag basket	<b>= PB</b>	

1. Filter bags are specified separately. See page 150.



MODEL NUMBER & Dim. A	B	C	D	E	F	PSI	Weight, lb (Approx)
6 (6.0)	28.0	4.3	3.0	1.5	9.5	125	50
8 (8.6)	39.2	6.0	4.2	2.0	12.0	125	70

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## **Model NCO and NLCO Bag or Cartridge Filter Housings**

Low cost filter housings for flow rates to 100 gpm\*

NCO high-capacity bag filters offer an exceptional value in basic filtration applications. Offered in trade sizes 1, 2, and 12, the NCO is also available with our Platinum 700 cartridge series.

NCO housings provide large dirt-holding capacity combined with a rugged design rated to 150 psi. The housings incorporate an eyenut cover that is easily removed, reducing time spent on bag or cartridge change-out. The NCO bag housing offers versatility for any piping arrangement, utilizing our unistyle design (side and bottom outlet). Two connection sizes are available for both bag and cartridge filters.


The NCO housings are electropolished creating a smooth, easy-to-clean surface. A variety of filter bags or cartridges (rated 0.5 $\mu$  absolute to 100 $\mu$  nominal) can be utilized in this housing. Keep your filtration process cost effective without sacrificing quality.

### **Features**

- Permanently piped housings are opened without special tools
- Carbon or stainless steel housings
- Covers are O-ring sealed
- O-ring seals: Buna N, EPR and Viton®
- 150 psi rated housing
- Heavy-duty basket, over 50% open area
- Uses standard number 1, 2 or 12 size bags and 500 or 700 series cartridges

**Note:** Filter bags are specified separately. See page 150.

- Filter selection surface area is:  
2.3 square feet (number 1 size bag),  
4.4 square feet (number 2 size bag),  
5.6 square feet (number 12 size bag)  
50 square feet (500 series cartridge)  
100 square feet (700 series cartridge)
- 1-1/2-inch or 2-inch NPT inlet and outlet
- 1/4-inch NPT vent connection
- Adjustable leg assembly




\*Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.

## How To Order

Build an ordering code as shown in the example.

	Housing	Options
<b>Example :</b>	<b>NCO8-30 - 2P - * - 150 - C - B - PB - NSF</b>	
<b>MODEL</b>		
NCO8 (#1, #2 bag & 500 cartridge)		
NLCO8 (#12 bag)		
NCO8135 (700 cartridge)		
NCO8135 convertible		
<b>BASKET SIZE</b>		
15-inch (NCO only) = 15		
30-inch (NCO or NLCO) = 30		
NCO8135 = No Symbol		
<b>PIPE SIZE</b>		
1-1/2-inch female NPT = 1-1/2P		
2-inch female NPT = 2P		
<b>OUTLET STYLE</b>		
Side/Bottom Unistyle (NCO or NLCO) = *		
Bottom = 1		
<b>PRESSURE RATING</b>		
150 psi = 150		
<b>HOUSING MATERIAL</b>		
Carbon steel = C		
304 Stainless steel = S		
<b>COVER SEAL</b>		
Buna N = B		
Ethylene propylene = E		
Viton® Fluoroelastomer = V		
<b>BASKET TYPE</b>		
Filter bag basket (NCO or NLCO) = PB		
700 Cartridge (NCO8135) = 700		
Convertible (NCO8135) <sup>4</sup> = 700PB		
<b>NSF</b>		
NSF 61 listed = NSF		

1. Filter bags are specified separately.
2. Basket material is compatible with housing.
3. Weight (approximately): 70 lbs.
4. Accepts 700 Series cartridge as well as filter bag



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.


## **R Model 8-125 psi Bag Filters**

Low cost filter housings for flow rates to 100 gpm\*

These high-capacity bag filters are very low in cost and offer large dirt holding capacity. These housings are made from carbon steel or stainless steel. They use a clamp cover that is easily removed, reducing time spent on bag change-out. The O-ring seal on the cover ensures a seal. This housing also utilizes our Unistyle design offering the option of a side or bottom outlet. There is a 2-inch outlet on the side with a 2-inch plugged drain at the bottom of the housing. The outlet can easily be changed to the bottom by merely moving the plug from the drain to the side outlet.

### **Features**

- Permanently piped housings are opened without special tools
- Quick opening cover
- Carbon or stainless steel housings
- Adjustable-height tripod legs
- O-ring seals: Buna N, EPR and Viton®
- 125-psi rated housing
- Basket material is compatible with housing
- Uses standard number 2 size bags and baskets
- Bag/Basket surface area is 4.4 square feet
- 2-inch NPT ports



\* Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.

## **R** How To Order


### Low Pressure Model 8 Housing

Build an ordering code as shown in the example

	Housing	Options
<b>Example:</b>	<b>830 - 2P - * - 125 - C - B - PB</b>	
<b>REDUCED-PRESSURE MODEL 8</b>	= 815	
	= 830	
<b>PIPE SIZE</b>		
2-inch female NPT	= 2P	
<b>OUTLET STYLE</b>		
Side/Bottom Unistyle= *		
<b>PRESSURE RATING</b>		
125 psi	= 125	
<b>HOUSING MATERIAL</b>		
Carbon steel	= C	
304 Stainless steel	= S	
<b>COVER SEAL</b>		
Buna N	= B	
Ethylene propylene	= E	
Viton® Fluoroelastomer	= V	
<b>BASKET TYPE</b>		
Filter bag basket	= PB	

1. Filter bags are specified separately. See page 150.

### Dimensions (IN)



Dimensions	
Model	A
815	21.1
830	35.9

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



## **R Aluminum Housings**

Spark Free, Heavy Duty Housings!

Economical aluminum AL Series housings for commercial, industrial and process applications. Aluminum can be used in place of carbon steel, stainless steel or plastic in many applications with superior results. It is especially effective in water and water based applications such as machine tool coolants and cooling towers. Also ideal for diesel, oils, and fuels, as well as many others.

### FEATURES

- 3/4" through 3" pipes sizes
- NPT connections
- Light weight lid with handle
- O-ring sealed
- Max temp. 250°F
- Pressure ratings to 300 PSI
- Strainer baskets optional
- 5 outlet styles
- Stainless steel filter bag baskets
- Tripod legs

Housing	Bag Size	Sq. Area	Maximum Flow	
			GPM	M <sup>3</sup> /H
Model 50	3	0.5	20	4
	4	1.0	40	8
Model 66	7	1.5	60	12
	8	2.0	80	16
	9	3.0	120	24
Model 80	1	2.0	80	16
	2	4.5	180	36

### PRESSURE DROP DATA

Chart shows clean pressure drop of housing with basket.

Viscosity CPS								
1 (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
1.0	1.3	1.5	1.7	1.9	2.1	2.3	2.5	2.8

## STRAINERS OR BAG FILTERS

### High-Capacity Strainer Baskets




All housings are available with perforated or mesh lined cleanable strainer baskets in place of filter bag baskets. These baskets can be perforated or mesh lined, with handle.


### High-Capacity Filter Bags



Filter bag sizes are industry standard sizes, and are offered in polyester, polypropylene and nylon materials in micron ratings of 1 to 1000. Filter bags are ordered separately.



# **R Dimensions** Approximate in Inches



Model 50				Size 3			Size 4			Size 3			Size 4		
Dia.	Pipe Size NPT	A		B	C	D	B	C	D	B	C	D	B	C	D
		IN.	MM	INCHES			INCHES			MM			MM		
5.0 IN.  127. MM	0.75	3.0	76.	12.0	11.9	6.0	18.0	17.9	12.0	304.	302.	152.	457.	454.	304.
	1.00	3.0	76.	12.4	12.2		18.4	18.2		314.	309.		467.	462.	
	1.25	4.3	109.	12.8	12.8		18.8	18.8		325.	325.		477.	477.	
	1.50	4.3	109.	13.2	12.8		19.2	18.8		335.	325.		487.	477.	
	2.00	4.8	121.	13.8	13.3		19.8	19.3		350.	337.		502.	490.	

Model 66				Size 7			Size 8			Size 9			Size 7			Size 8			Size 9		
Dia.	Pipe Size NPT	A		B	C	D	B	C	D	B	C	D	B	C	D	B	C	D	B	C	D
		IN.	MM	INCHES			INCHES			INCHES			MM			MM			MM		
6.625 IN.  168. MM	0.75	3.0	76.2	19.9	19.9	13.5	24.4	24.4	18.0	33.9	33.9	27.5	505.	505.	342.	619.	619.	457.	861.	861.	698.
	1.00	3.0	76.2	20.3	20.2		24.8	24.7		34.3	34.2		505.	513.		629.	627.		871.	868.	
	1.25	4.3	109.	20.8	20.6		25.3	25.1		34.8	34.6		528.	523.		642.	637.		883.	878.	
	1.50	4.3	109.	21.1	20.8		25.6	25.3		35.1	34.8		535.	528.		650.	642.		891.	883.	
	2.00	4.8	121.	21.7	21.3		26.2	25.8		35.7	35.3		551.	541.		665.	655.		906.	896.	
	3.00	6.3	160.	23.0	22.5		27.5	27.0		37.0	36.5		584.	571.		698.	685.		939.	927.	

Model 80				Size 1			Size 2			Size 1			Size 2		
Dia.	Pipe Size NPT	A		B	C	D	B	C	D	B	C	D	B	C	D
		IN.	MM	INCHES			INCHES			MM			MM		
8.0 IN.  203 MM	0.75	3.0	76.2	19.9	19.9	13.0	33.9	33.9	27.0	505.	505.	330.	861.	861.	685.
	1.00	3.0	76.2	20.3	20.2		34.3	34.2		515.	513.		871.	868.	
	1.25	4.3	109.	20.8	20.6		34.8	34.8		528.	523.		883.	883.	
	1.50	4.3	109.	21.1	20.8		35.1	34.8		535.	528.		891.	883.	
	2.00	4.8	121.	21.7	21.3		35.7	35.3		551.	541.		906.	896.	
	3.00	6.3	160.	23.1	22.5		37.1	36.5		586.	571.		924.	927.	

Dimensions are reference only and not to be used for hard plumbing. Consult factory for certified drawings.



## How To Order

Build an ordering code as shown in the example

OPTIONAL

EXAMPLE: **66 - 18 - 2P - 4 - 150 - AL - B - PB - CL**

<p><b>MODEL NUMBER:</b>          Model 50 = <b>50</b>          Model 66 = <b>66</b>          Model 80 = <b>80</b></p> <p><b>HOUSING SIZE</b>  <b>Model 50 only:</b>          Size 3 -6" long basket = <b>6</b>          Size 4 -12" long basket = <b>12</b>  <b>Model 66 only:</b>          Size 7 -14" long basket = <b>12</b>          Size 8 -18" long basket = <b>18</b>          Size 9 -28" long basket = <b>30</b>  <b>Model 80 only:</b>          Size 1 -14" long basket = <b>15</b>          Size 2 -28" long basket = <b>30</b></p> <p><b>INLET &amp; OUTLET SIZE</b>  <b>All Models:</b> NPT Connections          3/4" = <b>3/4P</b>          1" = <b>1P</b>          1-1/4" = <b>1-1/4P</b>          1-1/2" = <b>1-1/2P</b>          2" = <b>2P</b>  <b>Model 66 and 80 only:</b>          3" = <b>3.0P</b></p> <p><b>OUTLET STYLE</b>          Bottom = <b>1</b>          Side High 180 = <b>2</b>          Side Low 180 = <b>3</b>          Same Side High = <b>4</b>          Same Side Low = <b>D</b></p>	<p><b>TRIPOD LEG ASSEMBLY</b>  <b>CL</b> = Carbon Steel Legs  <b>SL</b> = Stainless Steel Legs  <b>NL</b> = No Legs</p> <p><b>BASKET TYPE</b>  <b>PB</b> = Perforated bag, 9/64" perforations  <b>P (*)</b> = Strainer basket, perforated metal                <b>*P1/16", P3/32", P1/8", P9/64", P1/4"</b>  <b>M (*)</b> = Filter bag basket, perforated, mesh lined                <b>*M20, M30, M40, M50, M60, M70, M100, M150, M200</b></p> <p><b>COVER GASKET</b>  <b>B</b> = Buna N  <b>E</b> = Ethylene Propylene  <b>V</b> = Viton Fluoroelastomer</p> <p><b>HOUSING MATERIAL</b>  <b>AL</b> = Aluminum</p> <p><b>PRESSURE RATING</b>  <b>300</b> = <b>Model 50 only:</b> 300 psi  <b>150</b> = <b>Model 66 only:</b> 150 psi  <b>125</b> = <b>Model 80 only:</b> 125 psi</p>
--	---





## Heat Transfer Fluid Filtration

300°F to 700°F

Heat transfer fluids are used for the indirect heating of processes by circulating the fluid between hot oil boilers, molds, tanks, extruders, and reactor vessels. The fluids are subjected to temperatures ranging from 300-700°F. These fluids can become contaminated from system construction, millscale, and oxidization by-products resulting in the formation of sludge. This contamination can cause operational problems such as pump shaft seal leakage, valve stem wear, plugging of heat exchangers and flow passages. Rosedale's HT Line of filters can solve your thermal fluid contamination problems. Particle removal is offered via glass fiber or stainless steel cartridges and wire cloth lined baskets. The filter vessels are offered in a variety of pipe sizes with flows to several hundred gallons per minute. The filter cartridges are accessed through an easily opened lid and can quickly be serviced. Duplex and multiplex arrangements are available for uninterrupted operation.

### Features

- ANSI class 150 design
- Temperature ratings of 285 PSI @ 100°F to 85 PSI @ 700°F
- Housings available in carbon steel, 304, and 316 stainless steel
- Covers blind fig



		STYLE 1							STYLE 2				STYLE 3					
Model No.	Pipe Size	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
HT8-30	2	8.62	7.5	57.4	50.4	12.0	68.0	38.4	49.5	42.5	34.5	60.1	49.5	42.5	4.5	5.0	60.1	38.0

				STYLE 1					STYLE 2					
Model No.	Pipe Size	A	B	C	D	E	F	G	H	I	J	K	L	M
HT86-30	3/4	8.62	7.5	54.4	38.3	12.0	65.0	26.3	44.5	28.5	4.5	5.0	55.1	24.0
	1								44.9	28.8			55.5	24.3
	1-1/4								45.2	29.1			55.8	24.6
	1-1/2								45.6	29.6			56.2	25.1
	2								46.3	30.3			56.9	25.8
	3	8.0	48.4	32.4	5.3	7.3	59.1	27.1						

		Standard					Low Profile				
Model No.	Pipe Size	A	B	C	D	E	F	G	H	I	J
HT18-30	2	18.0	11.1	4.50	42.9	54.4	14.0	15.0	8.0	39.7	51.3
	3		12.9	5.25	45.3	56.9	15.0	17.0	9.0	40.7	52.3
	4		14.6	6.0	47.7	59.2	N/A	N/A	N/A	N/A	N/A

		Standard						Low Profile				
Model No.	Pipe Size	A	B	C	D	E	F	G	H	I	J	K
HT1825-30	2	18.0	13.0	12.0	39.6	55.1	66.7	4.5	31.6	47.1	58.6	5.5
	3							5.3	33.8	49.3	60.8	7.3
	4							6.0	36.0	51.5	63.0	9.0

		Standard						Low Profile				
Model No.	Pipe Size	A	B	C	D	E	F	G	H	I	J	K
HT2447-30	2	24.0	16.0	12.0	41.1	56.6	68.5	4.5	33.1	48.6	60.5	5.5
	3							5.3	35.3	50.8	62.7	7.3
	4							6.0	37.5	53.0	64.9	9.0
	6							7.0	41.4	56.9	68.8	12.5

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



## How To Order Housings

Build an ordering code as shown in the example.

### Example :

**HT8-30-3F-2-85-S-F-M-50-BJ-C**

#### MODEL

Single Basket = **HT8-30**  
 Multiple Basket (3) = **HT\*18-30**  
 Multiple Basket (6) = **HT\*24-30**  
 Multiple Cartridge (6) = **HT86-30**  
 Multiple Cartridge (25) = **HT\*1825-30**  
 Multiple Cartridge (47) = **HT\*2447-30**

\*HTLP for low profile

#### PIPE SIZE

150 class ANSI flange  
 1-inch = **1F**  
 2-inch = **2F**  
 3-inch = **3F**  
 4-inch = **4F**  
 6-inch = **6F**

#### OUTLET STYLE

Side / Bottom = **1**  
 Side / Side = **2**

#### PRESSURE RATING

85 PSI @ 700°F = **85**

#### HOUSING MATERIAL

Carbon steel = **C**  
 Stainless steel = **S**  
 316 Stainless steel = **S316**

#### COVER SEAL

Flexitalic = **F**

#### BASKET TYPE

Strainer basket, perforated, mesh lined = **M**

#### BASKET, MEDIA SIZE

Mesh sizes  
**20, 30, 40, 50, 60, 70, 80, 100, 150, 200**

#### CARTRIDGE

Double Open End = **DOE**  
 Single Open End (NPT) = **SOE**

#### CARTRIDGE SEALING METHOD

V Post and Spring Seal = **VP**  
 Threaded Post = **TP**

#### STEAM JACKET

Body Jacket = **BJ**  
 Full Jacket = **FJ**

#### ASME CODE STAMP

ASME Code Stamp = **C**

## Heat Transfer Media

300°F to 700°F

### Models 8-30, 18-30, and 24-30

Holds 1 to 6 stainless steel baskets, or wire cloth lined baskets, or glass fiber-wound elements.

### Models 86-30, 1825-30, and 2447-30

Holds 6 to 47 stainless steel cartridges, or wire cloth lined baskets, or glass fiber-wound elements



## How To Order

Build an ordering code as shown in the example.

### Example :

**G - 10 - A - 30 - S**

#### FILTER MATERIAL

Fiber Glass = **G**

#### MICRON RATING

150 class ANSI flange  
 0.5 micron = **0.5**  
 1 micron = **1**  
 3 micron = **3**  
 5 micron = **5**  
 10 micron = **10**  
 20 micron = **20**  
 30 micron = **30**  
 50 micron = **50**  
 75 micron = **75**  
 100 micron = **100**

#### DIAMETER

2-1/2 inch = **A**

#### CARTRIDGE LENGTH

30 inches = **30**

#### CORE

316 Stainless Steel = **S**

## High-Pressure Filtration

Bag or Cartridge Housings  
740/1440 PSIG

Rosedale High-Pressure filter housings are the ideal way to meet your needs for oil and gas systems.

The bolted closure system assures a positive seal during operation, and changout is with the davit arm assembly.

The versatile Rosedale system allows you to use filter bags for coarse filtering, or high surface area pleated cartridges for heavy solids loading applications. Inside-out flow design contains solids inside the bag or cartridge, and prevents downstream contamination. The horizontal configuration can use 40" or 60" long cartridges.

### Features

- ANSI class 600 design
- Housings available in carbon steel, 304, and 316 stainless steel
- Horizontal or vertical mounting
- ASME code stamp

### Industries

- Chemical
- Plastics
- Rubber
- Petrochemical,
- Pharmaceutical
- Pulp and Paper
- Fiber
- Food Industries


### Applications

- Bulk Oil Handling
- Process Liquids



## Dimensions

Approximate in Inches



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## How To Order Housings

Build an ordering code as shown in the example.

**Example :**

**H - 8-30 - 3F - 2 - 1440 - C - F - R - C**

### CONFIGURATION

Vertical = **No Symbol**

Horizontal = **H**

### MODEL

#2 Filter Bag = **8-30**

40" High Flow Cartridge = **8-40**

60" High Flow Cartridge = **8-60**

### PIPE SIZE

150 class ANSI flange

1-inch = **1F**

2-inch = **2F**

3-inch = **3F**

4-inch = **4F**

6-inch = **6F**

### OUTLET STYLE

Side / Bottom = **1**

Side / Side = **2**

### ASME CODE STAMP

**C** = ASME Code Stamp

### MEDIA TYPE

**R** = 7.20 Rosedale

**S** = 6.32 HF

**B** = Filter bag

### COVER SEAL

**F** = Flexitalic

### HOUSING MATERIAL

**C** = Carbon steel

**S** = Stainless steel

**S316** = 316 Stainless steel

### PRESSURE RATING

**740** = 740 PSIG @ 100°F

**1440** = 1440 PSIG @ 100°F

## **R Model 82 Dual Capacity Bag Filter And Basket Strainer**

Extra capacity at higher flow rates!

Rosedale dual capacity housings can serve as either basket strainers or bag filters. Covers are easily removed, without tools, and the basket or bag is quickly and easily cleaned or replaced. Rosedale's bag-sized pleated cartridges will provide even greater dirt-holding capacity (see page 150).

**Low price, greater dirt holding capacity, and higher flow rates make the Model 82 a very cost-efficient choice!**

### **Features**

- Low pressure drops
- Permanently-piped housings
- Covers are O-ring sealed
- Carbon steel or stainless steel (304 or 316) housings
- Housings are electropolished to resist adhesion of dirt or scale
- Adjustable-height legs
- For flow rates to 440 gpm
- ASME code stamp available
- Large-area, heavy-duty baskets
- Dual stage straining/filtering

### **Options**

- Higher pressure ratings
- Extra-length legs
- Heat jacketing
- Liquid displacers for easier servicing

### **Basket Data**

(each basket, two baskets total)

Depth inches (nominal)	Diameter (inches)	Surface Area (sq. ft.)	Bag Size No.
15	6.7	2.3	1
30	6.7	4.4	2



### **Viscosity Factors**

CPS NUMBER

$1/(H_2O)$	50	100	200	400	600	800	1000	2000
.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80


## How To Order

Build an ordering code as shown in the example


Housing		Options	
<b>Example:</b>	<b>82- 30- 4F- 1 -150- C - B - S - BM- 200 -D - C</b>		
MODEL 82	= <b>82</b>		
<b>HOUSING SIZE</b>			
15 inch	= <b>15</b>		
30 inch	= <b>30</b>		
<b>PIPE SIZE, NPT &amp; FLANGED</b>			
2-in. 150 or 300-lb ANSI flange*	= <b>2F</b>		
3-in. 150 or 300-lb ANSI flange*	= <b>3F</b>		
4-in. 150 or 300-lb ANSI flange*	= <b>4F</b>		
6-in. 150 or 300-lb ANSI flange*	= <b>6F</b>		
*Dependent on required pressure rating			
<b>OUTLET STYLE</b>			
Side	= <b>1</b>		
<b>PRESSURE RATING<sup>1</sup></b>			
150 psi (flanged)	= <b>150</b>		
300 psi (flanged)	= <b>300</b>		
<b>HOUSING MATERIAL</b>			
Carbon steel	= <b>C</b>		
304 stainless steel	= <b>S</b>		
316 stainless steel	= <b>S316</b>		
<b>COVER SEAL</b>			
Buna N	= <b>B</b>		
Ethylene Propylene	= <b>E</b>		
Viton® Fluoroelastomer	= <b>V</b>		
Teflon® Encapsulated Viton®	= <b>TEV</b>		
Teflon® (solid white) (6 Bolt Cover)	= <b>TSW</b>		
<b>BASKET SEAL</b>			
Seal (required)	= <b>S</b>		
<b>BASKET TYPE</b>			
Filter bag basket <sup>2</sup>	= <b>PB</b>		
Strainer basket	= <b>P</b>		
Filter bag basket, mesh lined <sup>2</sup>	= <b>BM</b>		
Strainer basket, mesh lined	= <b>M</b>		
Filter bag basket, heavy wire mesh	= <b>HWM</b>		
<b>BASKET, MEDIA SIZE</b> , no symbol if type B basket was selected			
Type P perforation diameters 1/4, 3/16, 9/64, 3/32, 1/16			
Type M and BM mesh sizes 20, 30, 40, 50, 60, 70, 80, 100, 150, 200 = <b>200</b>			
<b>DISPLACER</b>			
Displacer	= <b>D</b>		
<b>ASME CODE STAMP</b>			
Code	= <b>C</b>		

1. Higher pressures are available, consult factory.  
 2. Filter bags are specified separately. See pages 150.  
 3. Flanges provided with the housing match the pressure rating of the vessel.  
 Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges.

## Dimensions (IN)



Pipe Size	2	3	4	6
<b>A</b>	6-5/8	7-1/2	7-1/2	9
<b>B</b>	2-7/8	3-3/4	3-3/4	5-1/4
<b>C</b> (15 in)	14-1/2	14-1/2	14-1/2	14-1/2
(30 in)	29-1/2	29-1/2	29-1/2	29-1/2
<b>D</b> (15 in)	21-3/16	22-3/32	22-3/32	23-9/16
(30 in)	36-3/16	37-3/32	37-3/32	38-9/16
<b>E</b>	8	8	9	9
<b>F</b>	16	16	18	18
<b>G</b>	28-9/16	28-9/16	30-9/16	30-9/16
<b>H</b>	4-1/2	5-1/2	6-1/2	8



\* Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



## **R The All Plastic PVDF/ Polypro Model 8 Bag Filter Housing**

Excellent for use in pure, ultra-pure, and corrosive applications

Rosedale's Generation II filter housings incorporate a unique one piece, seamless body that handles flows to 100 gpm. It is rated to 100 psi at 150°F, and offers excellent resistance to corrosion. In addition Rosedale has added new features:

### **Features**

- All molded construction
- 2-inch flat face flange connections
- Unistyle piping configuration (side and/or bottom outlet)
- Accepts all number 2 sized bags or 500 Series Cartridges (down to 0.5μ absolute)
- Wide selection of cover o-ring materials
- External cover and pressure threads with plug
- Hold down assembly

### **Options**

- Cover vent and drain valve
- Duplex and multiplex arrangements available
- Leg assembly (stainless steel)
- Pressure differential instrumentation
- Convertible 700 Series Cartridge (see page 181)
- Also available in PVDF

### **Design Details**

An easy to remove cover and basket make bag change-out quick, clean and simple. No special tools are needed, and the filter is back in service in a matter of minutes. The cover threads are external, and have no contact with the process fluids to prevent product accumulation. For extra strength the cover features buttress-style threads. The housing is complete with a cover vent, drain and gage port connections. The gauge connections

allow for the use of Rosedale differential pressure indicating equipment that assist in determining bag change-out. This can be accomplished by utilizing our pressure gauges, switches options. Its versatile unistyle design, side or bottom outlet, makes piping easy in any arrangement.

### **Construction**

This durable, corrosion resistant design is constructed from special polymer compounds. The Polypro housing is molded of reinforced chemically coupled polypropylene homopolymer. The addition of a UV stabilizer makes it suitable for outdoor use.



Plastic model base shown above. Also available for the Platinum 700 Series cartridge - See page 181.

## How To Order

Build an ordering code as shown in the example

Generation II Polypro housings are designed to accept all number 2 size elements, including our standard bags, bag-sized pleated cartridges, Surfaceplus, and the absolute-rated Platinum 500 series. The elements are rated from 0.5 micron absolute (99.98% efficiency or  $\beta 5000$ ) to 800 micron nominal. See page 150 for media selection.


	Housing	Option
<b>Example:</b>	<b>CR8 - 30 - 2F - *- 100 - P - B - C</b>	
<b>MODEL NO.</b> Corrosive Resistant Model 8 = <b>CR8</b>		
<b>HOUSING SIZE</b> 30 inch = <b>30</b>		
<b>PIPE SIZE (Flange)</b> 2-inch Flat Face Class 150 = <b>2F</b>		
<b>OUTLET STYLE</b> Side/Bottom Unistyle = <b>*</b>		
<b>PRESSURE RATING</b> 100 psi = <b>100</b>		
<b>HOUSING MATERIAL</b> Polypropylene = <b>P</b> PVDF = <b>K</b>		
<b>COVER SEAL</b> Buna N = <b>B</b> Ethylene Propylene = <b>E</b> Viton = <b>V</b> Teflon Encapsulated Viton = <b>TEV</b>		
Convertible (700 Cartridge Adapter) = <b>C</b>		

**Note:** Filter bags are specified separately. See page 150.

## Technical Specifications


<b>Element Size:</b>	No. 2 Size Elements
<b>Piping Connections:</b>	2" ANSI B16.5 FF Flange
<b>Housing Material :</b>	Glass-reinforced polypropylene with UV stabilizer or PVDF
<b>Basket Material:</b>	Natural polypropylene or PVDF
<b>Recommended Change Out:</b>	15 PSID
<b>Pressure Rating:</b>	100 psi @ 150°F
<b>Shipping Weight:</b>	50lb (approx.)

## Dimensions (IN)



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## Temperature vs. Pressure



**NOTE:** Not for use in conditions under 40°

## **R Model OT Bag Filter Housing**

Guarantees a 360° positive seal  
for flows to 100 gpm\*

### **Performance**

The Model OT filter provides optimum filtration performance when combined with our high capacity filter bags. Our unique design ensures a 360-degree positive seal and media compression, eliminating the potential for bypass. Unfiltered liquid and debris does not accumulate above the filter bag and contaminate the clean fluid area during change-out. Fluid passes through the bag from inside to outside.

The Rosedale Model OT filter ensures an even flow into the filter bag where contaminate is contained for easy disposal.

### **Construction**

The Model OT housing is a durable, high capacity filter with an uncompromising welded construction to meet ASME Section VIII Code requirements. The cover is hinged and fastened with swing bolts for quick access and easy bag change-out. They have a high quality electropolished finish to resist adhesion of dirt and scale, making routine maintenance fast and simple.

Model OT filters are available in two sizes with flanged or threaded connections. Customize with several options, including gauges and switches. A wide range of filter bags or cartridges (rated 0.5μ absolute to 100μ nominal) with various surface areas can be utilized in this housing.




### **Features**


- Accepts all major competitive brands of bags
- Permanently piped housings are opened without special tools
- Carbon or stainless steel housings
- Covers are O-ring sealed
- All sealing surfaces are blancher ground
- O-ring seals: Buna N, EPR, Viton® and Teflon®
- 150 psi rated housing
- ASME Code Stamp available
- Uses standard #1, #2 or 500 series PL cartridges
- 1/4-inch NPT gauge ports and vent connection
- 1/2-inch NPT drain connection
- Adjustable-height tripod leg assembly

## Dimensions (IN)




### Outlet Styles - 2" Pipe



### Outlet Styles - 3" Pipe



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



\*Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.

## How To Order


Build an ordering code as shown in the example.

	Housing	Options
<b>Example :</b>	<b>OT8-30-2P-3-150-C-B-M-200-C</b>	
<b>MODEL</b>		
<b>OT8</b>		
<b>BASKET SIZE</b>		
15-inch	=15	
30-inch	=30	
<b>PIPE SIZE</b>		
2-inch female NPT	=2P	
2-inch 150 class ANSI flange	=2F	
<b>OUTLET STYLE</b>		
Bottom	=1	
Side	=2	
Bottom elbow	=3	
Side out, same side (low profile)	=4	
<b>PRESSURE RATING</b>		
150 psi	=150	
<b>HOUSING MATERIAL</b>		
Carbon steel	=C	
304 Stainless steel	=S	
316 Stainless steel	=S316	
<b>COVER SEAL</b>		
Buna N	=B	
Ethylene propylene	=E	
Viton® Fluoroelastomer	=V	
Teflon Encapsulated Viton	=TEV	
<b>BASKET TYPE</b>		
Filter bag basket, 9/64 perforations <sup>1</sup>	=PB	
Strainer basket, perforated metal	=P	
Filter bag basket, perforated, mesh lined <sup>1</sup>	=BM	
Strainer basket, perforated, mesh lined	=M	
Filter bag basket, heavy wire mesh <sup>1</sup>	=HWM	
<b>BASKET, MEDIA SIZE-No symbol if type B basket was selected</b>		
Perforation diameters (for type P baskets)		
1/4, 3/16, 9/64, 3/32, 1/16		
Mesh sizes (for type M and BM baskets)		
20, 30, 40, 50, 60, 70, 80, 100, 150, 200		
<b>ASME CODE STAMP</b>		
Code	=C	

1. Filter bags are specified separately.  
See page 150.

2. Weight (approximately): 100 lbs.

## **Multi-Bag Filter Standard Features**



### **Typical Multi-basket Strainer and Multi-bag Filter Housing**

Unfiltered fluid enters the bottom of the housing and flows into the open area under the dome of the cover. Flow is distributed uniformly through the bags or baskets, where they can be removed easily and completely.



## Multi-Basket Strainers and Multi-Bag Filters

These multi-basket strainers and bag filters offer a wide range of flow capacities and contaminant-holding capabilities. They contain from 2 to 23 baskets.

To serve as a strainer, a unit is ordered with perforated stainless steel baskets (mesh-lined if desired). When ordered as a filter, it's fitted with perforated stainless steel baskets designed to hold disposable or cleanable filter bags. Accepts industry-standard #1 and #2 size filter bags, or 500 series pleated cartridges (see page 150).

The standard pressure rating for all models is 150 psi. All housings can be supplied with an ASME code stamp, if required.

### Features

- NSF 61 listed
- Multiple housing styles available (standard, quick access, low profile, hinged)
- Permanently piped housings are opened without tools and without disturbing the piping
- Machined cover gasket groove provides positive O-ring sealing
- Carbon steel, 304 or 316 stainless steel construction housings
- Large-area, 30 inch deep, heavy-duty, 9/64 inch perforated baskets
- Easy to clean
- Low pressure drop
- Four cover seal materials: Buna N, Ethylene Propylene, Viton®, and Teflon®
- Pressure rating 150 psi
- Flanged connections for 2 through 12 inch pipe
- Vent, drain and gage connections

### Options

- ASME code stamp
- Higher pressure ratings
- Corrosion allowances
- Steam jackets
- Special connection locations



- Bag hold down assembly (standard on QII design)
- Inner baskets for dual-stage straining or filtering
- Cleanable wire mesh lined or perforated strainer baskets
- Special alloy materials
- Hydraulic cover lifting assembly
- Sanitary fittings
- Differential pressure indicators



Certified to  
NSF/ANSI 61

### Duplex Systems

All multi-basket models described here are also available as duplex systems. Two units come piped together with valves to permit continuous use of either unit while servicing the other. One lever actuates all valves simultaneously or it can be ordered for automatic service. See page 82.

## **R Choose Housing Style**

Designed to suit your requirements

The versatility of Rosedale Products provides a choice of several different designs.

- **Standard Housing Design (STD)** is durable and economic. It includes a davit arm and handwheel to facilitate cover removal. It is our most versatile housing design offering a variety of options, including our low profile design.

- **Spring Access Cover Design (HLP)** opens and closes without effort. Simply loosen the swing bolts and lift the cover up to open. An automatic cover stop is provided. See page 46 for details.

- **Quick Access Cover (QII)** features a unique counter weight design that makes opening, closing, and change-out, fast, easy, and simple. This will significantly reduce change-out time and lower operating costs. The QAC is rated to 150 PSI and constructed to meet ASME code requirements. Built-in safety features ensure that the cover cannot be opened unless the internal pressure is first released. The QII is offered with our low profile design making bags more accessible and easy to remove.

- **Low Profile Design (SLP) Housings** are compact and space saving, allowing for ease of bag change-out. Standard operating height is reduced, resulting in a safe design by eliminating platforms and ladders. The SLP is manufactured in any housing version, including our standard davit arm cover, QAC design, and spring assisted hinged cover.



Standard Davit Arm



Spring Access Cover



QII Quick Access Cover



Low Profile Design

## **R Choose Baskets That Strain or Filter**

Whatever your needs dictate


Strainer baskets are cleanable, reusable.

A seal is supplied on any strainer basket. It forms a seal between basket and housing to prevent dirty fluid bypass. Choose between various perforation sizes or wire mesh. Strainer baskets have flat, non-perforated bottoms and contain heavy-duty handles.


Filter bag baskets hold disposable filter bags.

Filter bags have an interference fit between the bags top rim and the housing causing a positive seal to prevent fluid bypass. Filter bag baskets have flat perforated bottoms.

Filter bags are available in a wide variety of felt, micro-fiber, monofilament and multifilament mesh materials. They are detailed completely on pages 150.



Model 24 with Strainer Baskets



Model 24 shown with PL Series Cartridge

**DUAL-STAGE**— Dual-stage action will increase strainer or filter life and reduce servicing needs. This straining/filtering action can be achieved by ordering a second, inner basket. It is supported on the top flange of the outer basket. Both baskets can be utilized as strainers (with or without wire mesh linings), filter bag baskets, or a combination of strainer and bag basket.



### **Basket Data**

Surface area of each 30 in. basket: 4.4 sq. ft.

Volume of each 30 in. basket: 0.6 cu. ft.

### **Basket Construction**

For cleanable strainer baskets, choose from the following perforation diameters: 1/4, 3/16, 9/64, 3/32, or 1/16 inch (for other not shown consult factory).

Any perforated basket can also be ordered lined with wire mesh. Stainless steel wire is used in mesh sizes 20, 30, 40, 50, 60, 70, 80, 100, 150, or 200.

Filter bag baskets, have standard 9/64 inch diameter perforations that are 51% open area. A wire mesh can also be utilized with bag baskets for two advantages:

1. Fiber migration is minimized.
2. In the unlikely event of bag rupture, the wire mesh better contains the contaminant.

Q II



**SAFETY VALVE  
MECHANISM**



**COUNTER  
BALANCED COVER**



**ELEMENT/BAG  
RETAINING DEVICE**





**HANDWHEEL  
OPERATION OF  
TURNBUCKLE  
MECHANISM**





MODEL NUMBER & Dim. A	Pipe Sizes B	Leg Bolt Circle Dia.	Standard					Weight, lb (Approx)	Low Profile				
			C	D	E	F	G		H	I	J	K	L
16	2	14.0	10.9	40.1	57.1	4.50	10.5	400	37.9	54.9	8.00	15.0	13.0
	3			42.5	59.5	5.25	12.3	425	38.3	55.3	9.00	17.0	14.0
	4			44.9	61.9	6.00	14.0	450	N/A	N/A	N/A	N/A	N/A
18	2	16.0	11.9	40.5	58.0	4.50	11.1	450	39.6	58.5	8.00	15.0	14.0
	3			42.9	60.4	5.25	12.9	475	40.0	58.9	9.00	17.0	15.0
	4			45.3	62.8	6.00	14.6	500	N/A	N/A	N/A	N/A	N/A
22	2	20.0	14.0	41.4	60.0	4.50	11.9	485	39.5	58.0	8.00	15.0	16.0
	3			43.9	62.4	5.25	13.7	500	40.0	58.5	9.00	17.0	17.0
	4			46.2	64.7	6.00	15.4	515	39.5	58.0	9.00	19.0	18.0
	6			50.4	69.0	7.00	18.9	560	N/A	N/A	N/A	N/A	N/A
24	2	22.0	15.0	41.7	60.7	4.50	13.1	675	41.2	61.6	8.00	15.0	17.0
	3			44.1	63.1	5.25	14.8	700	41.6	62.0	9.00	17.0	18.0
	4			46.5	65.5	6.00	16.6	725	41.1	61.5	9.00	19.0	19.0
	6			50.7	69.7	7.00	20.1	750	N/A	N/A	N/A	N/A	N/A
30	2	28.0	18.0	42.8	63.3	4.50	15.2	635	41.3	61.9	8.00	15.0	20.5
	3			45.2	65.7	5.25	17.0	650	41.8	62.4	9.00	17.0	21.0
	4			47.6	68.1	6.00	18.7	665	41.3	61.9	9.00	19.0	22.5
	6			51.9	72.4	7.00	22.2	705	41.2	61.8	10.0	17.0	23.0
	8			56.4	76.8	8.25	25.7	850	N/A	N/A	N/A	N/A	N/A
36	3	34.0	21.0	46.4	68.4	5.25	18.8	840	43.3	64.5	9.00	17.0	24.0
	4			48.8	70.8	6.00	20.6	860	43.2	64.5	9.50	19.0	25.0
	6			53.1	75.1	7.00	24.1	870	43.2	64.4	10.5	17.0	26.0
	8			57.6	79.6	8.25	27.6	1010	43.2	64.4	11.5	17.0	27.0
	10			62.1	84.1	9.50	30.6	1150	N/A	N/A	N/A	N/A	N/A
42	4	40.0	24.0	50.0	73.5	6.00	22.6	1840	45.9	70.7	9.50	19.0	28.0
	6			54.3	77.8	7.00	26.1	1870	45.9	70.6	10.5	17.0	28.0
	8			58.8	82.3	8.25	29.6	1960	45.9	70.6	11.5	17.0	29.5
	10			63.3	86.8	9.50	32.6	2070	45.8	70.5	12.5	17.0	30.0
48	12			68.0	91.5	11.0	36.1	2200	N/A	N/A	N/A	N/A	N/A
	4	46.0	27.0	51.0	76.0	6.00	24.8	2015	46.5	71.5	9.50	19.0	32.0
	6			55.4	80.4	7.00	28.3	2075	46.4	71.4	10.5	17.0	32.0
	8			60.0	85.0	8.25	31.8	2200	46.4	71.4	11.5	17.0	32.5
	10			64.4	89.4	9.50	34.8	2350	46.4	71.4	12.5	17.0	33.0
	12			69.2	94.2	11.0	38.3	2530	N/A	N/A	N/A	N/A	N/A

## Dimensions (IN)

(30-inch deep basket)



**Standard**




**Low Profile**

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

QII Low Profile									
MODEL NUMBER & Dim. A	Leg Bolt Circle Dia.	Pipe Size	A	B	C	D	E	F	G
16 & 18	16.0	18.0	2	40.0	53.2	8.00	15.0	14.0	35.5
			3	40.4	53.6	9.00	17.0	15.0	
22	22.0	24.0	2	41.5	56.2	8.00	15.0	16.0	35.5
			3	41.9	56.6	9.00	17.0	17.0	
			4	41.4	56.1	9.00	19.0	18.0	
24	22.0	24.0	2	41.5	56.2	8.00	15.0	17.0	38.5
			3	41.9	56.6	9.00	17.0	18.0	
			4	41.4	56.1	9.00	19.0	19.0	
30	28.0	30.0	2	43.0	59.2	8.00	15.0	20.5	41.5
			3	43.4	59.6	9.00	17.0	21.0	
			4	42.9	59.1	9.00	19.0	22.5	
			6	42.9	59.1	10.00	17.0	23.0	
36	34.0	36.0	3	44.9	62.6	9.00	17.0	24.0	44.5
			4	44.9	62.6	9.50	19.0	25.0	
			6	44.9	62.6	10.5	17.0	29.5	
			8	44.9	62.6	11.5	17.0	27.0	
42	40.0	42.0	4	46.4	65.6	9.5	19.0	28.0	47.5
			6	46.4	65.6	10.5	17.0	28.0	
			8	46.4	65.6	11.5	17.0	29.5	
			10	46.3	65.5	12.5	17.0	30.0	
48	46.0	48.0	4	47.9	68.6	9.5	19.0	32.0	50.5
			6	47.9	68.6	10.5	17.0	32.0	
			8	47.9	68.6	11.5	17.0	32.5	
			10	47.8	68.5	12.5	17.0	33.0	

## Dimensions (IN)



## Model Selection (For all housings)

Model No.	Number of Baskets	Straining, Filtering Area, ft <sup>2</sup>	Nominal Flow Rate (gpm)**	Inlet/Outlet Size (in)
16	2	8.8	200	2,3,4*
18	3	13.2	300	2,3,4*
22	4	17.6	400	2,3,4,6*
24	6	26.4	600	2,3,4,6*
30	8	35.2	800	2,3,4,6,8*
36	12	52.8	1200	2,3,4,6,8,10*
42	17	74.8	1700	2,3,4,6,8,10,12*
48	23	101.2	2300	2,3,4,6,8,10,12*

\* Not available on SLP, HLP, and QII styles.

\*\* Nominal flow rate is based on water @ 1 psi  $\Delta P$ .  
A lower fluid velocity is best for optimum filtering effectiveness (under 10 ft/sec is recommended).

## Pressure Drop Data

Basket strainers and bag filters are usually selected so that the pressure drop does not exceed 2 psi, when they are clean. Higher pressure drops may be tolerated when contaminant loading is low.


### Determining housing pressure drop:

The pressure drops shown on the graph are reliable for all multi-basket housings, including strainer baskets or bag filter (perforated only or mesh lined). The pressure drop of any housing is governed by the size of the inlet and outlet, not the vessel itself.

1. Using the desired pipe size and approximate flow rate, determine the basic pressure drop from the graph.
2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table.
3. You now have the pressure drop for a clean multi-basket unit. If bag filters are employed, you must add the pressure drop they incur to get a true pressure drop for the assembly.

**Note:** Filter bags are specified separately.

See page 150.



Recommended flow rates are based on housing only. Fluid viscosity, filter bag used, and expected dirt load should be considered when sizing a filter.

## Viscosity Factors

CPS NUMBER								
1 (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80





## How To Order

Build an ordering code as shown in the example

Example: SLP-24-30-4F -1-150-C- B -S -M-20- C- 2P 1/16	
Housings	Options
<b>HOUSING STYLE</b> Standard (std) = <b>No Symbol</b> Standard Low Profile = <b>SLP</b> Quick Access Cover = <b>Q</b>	<b>OPTIONAL INNER BASKET</b> <b>OPTIONAL INNER BASKET, MEDIA SIZE</b> Perforation diameters (for type 2P baskets) <b>1/4, 3/16, 9/64, 3/32, 1/16</b> Mesh sizes (for type 2M & 2BM baskets) <b>20, 30, 40, 50, 60, 70, 80, 100, 150, or 200</b> <b>OPTIONAL INNER BASKET, TYPE</b> <b>2B</b> = Filter bag basket, 9/64 perforations <b>2P</b> = Strainer basket, perforated metal <b>2BM</b> = Filter basket, mesh lined <b>2M</b> = Strainer basket, perforated, mesh lined <b>ASME CODE STAMP</b> <b>C</b> = Code <b>NSF</b> = NSF 61 listed <b>BASKET, MEDIA SIZE</b> <b>No symbol if type PB basket was selected</b> Perforation diameters (for type P baskets) <b>1/4, 3/16, 9/64, 3/32, 1/16</b> Mesh sizes (for type M & BM baskets) <b>20, 30, 40, 50, 60, 70, 80, 100, 150, or 200</b> <b>BASKET, TYPE</b> <b>PB</b> = Filter bag basket, 9/64 perforations <b>P</b> = Strainer basket, perforated metal <b>BM</b> = Filter bag basket, perforated, mesh lined <b>M</b> = Strainer basket, perforated, mesh lined <b>HWM</b> = Filter bag basket, heavy wire mesh
<b>MODEL NO.</b> 16 = <b>16</b> 30 = <b>30</b> 18 = <b>18</b> 36 = <b>36</b> 22 = <b>22</b> 42 = <b>42</b> 24 = <b>24</b> 48 = <b>48</b>	
<b>BASKET DEPTH</b> 15-in. = <b>15</b> 30-in. (std) = <b>30</b>	
<b>PIPE SIZE (FLANGED<sup>1</sup>)</b> 2-in. (Std, SLP, HLP 16-48 / QII 18 & 24) = <b>2F</b> 3-in. (Std, SLP, HLP 16-48 / QII 18 & 24) = <b>3F</b> 4-in. (Std 16-48 / SLP, HLP 22-48 / QII 24) = <b>4F</b> 6-in. (Std 22-48 / SLP, HLP 30-48) = <b>6F</b> 8-in. (Std 30-48 / SLP, HLP 36-48) = <b>8F</b> 10-in. (Std 36-48 / SLP, HLP 42 & 48) = <b>10F</b> 12-in. (Std 42, 48) = <b>12F</b>	
<b>OUTLET STYLE</b> In-line, bottom (std) = <b>1</b> Side inlet/outlet (SLP, HLP, QII) = <b>2</b> Side inlet/outlet, same side (SLP, HLP, QII) = <b>4</b>	
<b>PRESSURE RATING<sup>2</sup></b> 150 psi (flanged) = <b>150</b>	
<b>HOUSING MATERIAL</b> Carbon steel = <b>C</b> 304 stainless steel = <b>S</b> 316 stainless steel = <b>S316</b>	
<b>* COVER SEAL</b> Buna N (N/A on Q housing) = <b>B</b> Ethylene Propylene (N/A on Q housing) = <b>E</b> Viton® = <b>V</b> Teflon® Encapsulated Viton® (N/A on Q housing) = <b>TEV</b> Teflon® (solid white) (N/A on Q housing) = <b>TSW</b>	
<b>BASKET SEAL</b> No seal = <b>N</b> Seal (only on strainer housings) = <b>S</b>	

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. Other styles and classes available. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.

2. Higher pressure ratings available. Consult factory.

**\*Note: Because of its unique Quick Access Cover, the Q (QII) housing style is available only with a Viton cover seal.**

## **R HLP Series Multi-Basket Strainers and Multi-Bag Filters with Spring-Access Cover**

These multi-basket strainers and bag filters offer a wide range of flow capacities and contaminant-holding capabilities. They contain from 2 to 23 baskets/bags. Larger units that hold more baskets/bags are available, consult Rosedale.

- Low Profile Design Housings are compact and space saving, allowing for ease of bag change-out. Standard operating height is reduced, eliminating platforms and ladders.
- Spring Assisted Hinged Cover opens and closes without effort. Simply loosen the swing bolts and lift the cover up to open. An automatic cover stop is provided.
- The units meet ASME code requirements for 150 PSI ratings. Rosedale is an ISO 9000 facility.



Certified to  
NSF/ANSI 61

### **Features**


- Permanently piped housings are opened without disturbing the piping
- Machined cover seal groove provides positive sealing
- Carbon steel, 304 or 316 stainless steel construction housings (wetted parts)
- Large-area, 30-inch deep, heavy-duty, 9/64-inch perforated baskets
- Easy to clean
- Low pressure drop
- Three cover seal materials: Buna N, Ethylene Propylene, and Viton®
- Pressure rating 150 psi
- Flanged connections for 2 through 8-inch pipe
- Vent, drain and gage connections
- Bag hold down assembly

### **Options**

- ASME code stamp
- Special connection locations
- Inner baskets for dual-stage straining or filtering
- Cleanable wire mesh lined or perforated strainer baskets
- Special alloy materials
- Sanitary fittings
- Bag or cartridge design
- Differential pressure indicators
- Safety pressure release
- Steam jackets (body jacket only)



## Dimensions



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## How To Order

Build an ordering code as shown in the example

**Example: HLP18-30-4F-2- 150-C- B- S- M-20-C**

### MODEL NO.

18 = **HLP18** (3-Bag Unit)  
24 = **HLP24** (6-Bag Unit)  
36 = **HLP36** (12-Bag Unit)

### BASKET DEPTH

15-in. = **15**  
30-in. (std) = **30**

### PIPE SIZE FLANGED<sup>1</sup>

2-in. (All Models) = **2F**  
3-in. (All Models) = **3F**  
4-in. (Model 24/36) = **4F**  
6-in. (Model 36) = **6F**  
8-in. (Model 36) = **8F**

### OUTLET STYLE

Side inlet/outlet = **2**  
Side inlet/outlet (same side) = **4**

### PRESSURE RATING<sup>2</sup>

150 psi (flanged) = **150**

### HOUSING MATERIAL

Carbon steel = **C**  
304 stainless steel = **S**  
316 stainless steel = **S316**

### ASME CODE STAMP

**C** = Code  
**NSF** = NSF 61 listed

### BASKET, MEDIA SIZE No symbol if type B basket was selected

Perforation diameters (for type P baskets)

**1/4, 3/16, 9/64, 3/32, 1/16**

Mesh sizes (for type M & BM baskets)

**20, 30, 40, 50, 60, 70, 80, 100, 150, or 200**

### BASKET, TYPE

**PB** = Filter bag basket, 9/64 perforations  
**P** = Strainer basket, perforated metal  
**BM** = Filter bag basket, perforated, mesh lined  
**M** = Strainer basket, perforated, mesh lined  
**HWM** = Filter bag basket, heavy wire mesh

### BASKET SEAL

**N** = No seal  
**S** = Seal (only on strainer housings)

### COVER SEAL

**B** = Buna N  
**E** = Ethylene Propylene  
**V** = Viton®

1. Flanges provided with the housing match the pressure rating of the vessel.

2. Housings rated 150 psi have 150 class flanges.



Other styles and classes available.

ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.

## **Rosedale High Flow Filtration Systems**

- From 1 to 31 elements per filter housing
- Beta 5000 (99.98% efficiency) rated for consistent product quality
- Operator-friendly cartridge and housing system
- High flow performance in a convenient design
- Horizontal mounting configuration

Model 18340



DPU Series Cartridge

## High Flow Housings

These housings are available in standard and custom configurations to suit your specific needs. All housings are designed, manufactured, tested, and code stamped in accordance with ASME Section VIII, Division 1.

They are available in a variety of sizes to accommodate from 1 to 31 filter cartridges in 40-inch and 60-inch lengths and two popular styles. You can select from the "High Flow" basic size 6.32-inch (152.4 mm) seal diameter or "Trade Size" #2, 7.20-inch (182.9 mm).

Larger housings are available upon request. The horizontal style maximizes ease of operation and change-out, while reducing the systems footprint.

### Features

Horizontal mounting configuration


Hinged cover for easy element change-outs

Standard pressure / temperature ratings to 300 psig and 250 °F


Available in Carbon Steel, 304, or 316 Stainless Steel

40" and 60" element lengths

ASME Code design



Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.



Dimensions - Approximate in Inches

Dia. A	Element Length	B	C	D	No. of Elements
8	40	66.9	52.3	7.5	1
	60	86.9			
18	40	75	57.0	13	3/4
	60	95			
24	40	79.5	60.0	16	7
	60	99.5			
30	40	85	63.0	19	10/12
	60	105			
36	40	95.5	66.0	22	13/19
	60	115			
42	40	100	69.0	28	18/24
	60	120			
48	40	104	72.0	32	18/24
	60	124			

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.





# High Flow Elements

40" Length / 60" Length



Removal Ratings (microns)  
0.5, 1, 5, 10, 20, 40, 70  
@ Beta 5000 (99.8% efficiency)

Maximum Operating  
Temperature (°F / °C) 160 / 71


Maximum Differential  
Pressure 50 psid @ 68°F  
(3.4 bar @ 20°C)

Recommended Change-out  
Differential Pressure  
35 psid @ 68°F  
(2.4 bar @ 20°C)

Depending on application,  
systems can be used with  
40" or 60" bags or cartridges.  
Bag restrainer expands  
bag fully during filtration.




## TYPICAL ROSEDALE HIGH FLOW SYSTEM




**Rosedale System**  
7 Cartridges / 24" Diameter Housing

## REPLACES



**Competitive System**  
125 Cartridges / 36" Diameter Housing  
2000 GPM SYSTEM (7571 LPM)





## How To Order Housing

Build an ordering code as shown in the example

**Example: H - 183 - 60 - 4F - 1 - 150 - S - E - S - C**

### HOUSING= H

#### R CARTRIDGE (No. of Elements)

Model 8	=	<b>8 (1)</b>
Model 18	=	<b>18 (3)</b>
Model 24	=	<b>24 (7)</b>
Model 30	=	<b>30 (10)</b>
Model 36	=	<b>36 (13)</b>
Model 42	=	<b>42 (18)</b>
Model 48	=	<b>48 (24)</b>

#### S CARTRIDGE (No. of Elements)

Model 8	=	<b>8 (1)</b>
Model 18	=	<b>18 (4)</b>
Model 24	=	<b>24 (7)</b>
Model 30	=	<b>30 (12)</b>
Model 36	=	<b>36 (19)</b>
Model 42	=	<b>42 (22)</b>
Model 48	=	<b>48 (31)</b>

#### ELEMENT LENGTH

40 Inch	=	<b>40</b>
60 Inch	=	<b>60</b>

#### PIPE SIZE, FLANGED

Model 8	=	<b>2F or 3F</b>
Model 8, 18	=	<b>4F</b>
Model 18, 24	=	<b>6F</b>
Model 24, 30	=	<b>8F</b>
Model 30, 36	=	<b>10F</b>
Model 36	=	<b>12F</b>
Model 42	=	<b>12F or 14F</b>

### ASME CODE OPTION

**C** = ASME Code Stamp

### CARTRIDGE STYLE

**R** = 7.20 Rosedale  
**S** = 6.32 HF

### GASKET MATERIAL

**V** = Fluorocarbon  
**E** = EPR  
**B** = Buna N

### HOUSING MATERIAL


**C** = Carbon Steel  
**S** = 304 Stainless Steel  
**S316** = 316 Stainless Steel

### PRESSURE RATING

**150** = 150 psi  
**300** = 300 psi

### OUTLET STYLE

**1** = Bottom  
**2** = Side  
**3** = Bottom Elbow



## How To Order Element

Build an ordering code as shown in the example

**Example: DP-605-P60-1-V**

### Rosedale High Flow

7.2-Inch Diameter = **DP**

### High Flow

6.32-Inch diameter = **DPU**

### MICRON RATING @ Beta 5000

0.5 Micron	=	<b>600*</b>
2 Micron	=	<b>601*</b>
5 Micron	=	<b>603</b>
10 Micron	=	<b>605</b>
20 Micron	=	<b>607</b>
40 Micron	=	<b>608</b>
70 Micron	=	<b>609</b>

\*Requires Caps 1 or P

### SEAL MATERIAL

**EPR** = No Symbol  
**V** = Viton®  
**B** = Buna  
**SA** = Santoprene

### CAP STYLE

**F** = Flare Cap (No seal required, DP Only)  
**1** = O-ring Cap (7.32 Dia. DP Only)  
**P** = O-ring Cap (6.32 Dia. DPU Only)

### LENGTH

**40** = 40.5"  
**60** = 60.5"

### MATERIAL

**P** = Polypropylene  
**G** = Glass  
**R** = Polyester

## **R** **Rosedale Model HSS300 and HSS750** Single Cartridge Housings for Liquids

The Rosedale Model HSS single element filter housing is an all stainless steel unit ideal for general industrial service. It features a ring-nut closure (HSS 300) or bolt closure (HSS750) for easy access to the head and cartridge sump.

- The HSS is available in 10", 20", 30", or 40" cartridge models.
- HSS300 units are rated for 300 PSI service at 200°F.
- HSS750 units are rated for 750 PSI service at 200°F.

Flow rates to 40 GPM are acceptable depending on cartridge selection. Buna-N gaskets are standard, while other materials are available.

### **Standard Features**

- Simple closure for quick cartridge change outs
- In line fittings for easy installation
- Knife edge seal at both cartridge ends to eliminate by-pass
- Housings accept double-open-end cartridges



**MODEL HSS300**




**MODEL HSS750**




For detailed information about filter cartridges, see pages 184-203.

Dimensions (IN)

MODEL HSS300



MODEL HSS750



Model	PSI	A	B
HSS300-M101	300 PSI	13-9/16	12-3/4
HSS300-M102		23-9/16	22-3/4
HSS300-M103		33-9/16	32-3/4
HSS300-M104		43-9/16	42-3/4
HSS750-M101	750 PSI	13	12-1/8
HSS750-M102		23	22-1/8
HSS750-M103		33	32-1/8
HSS750-M104		43	42-1/8



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## Standard Design Specifications

Model	Qty. (Length) of Cartridges	Flow Rate GPM*	Max Ctg Diameter	Approx. Ship Weight	Box Size
M101	1 (10")	7	2 3/4" OD	10 lbs	4x5x16
M102	1 (20")	14	2 3/4" OD	12 lbs	4x5x25
M103	1 (30")	21	2 3/4" OD	14 lbs	4x5x36
M104	1 (40")	28	2 3/4" OD	16 lbs	4x5x47

Based on 7gpm per 10" length with a 25 micron wound cartridge at 2PSID clean and a viscosity of 1 cps.

\*Flow rates are guide lines only. Actual flow rates are based on fluid, viscosity, cartridge type, micron ratings and other factors.



## How To Order

Build an ordering code as shown in the example

**Example:** **HSS300 - M101 - SS304 - 1.0 - V**

### MODEL

HSS300 Cartridge  
Filter

= **HSS300**

HSS750 Cartridge  
Filter

= **HSS750**

### CARTRIDGE LENGTH

10" = **M101**

20" = **M102**

30" = **M103**

40" = **M104**

### GASKET

**Blank** = Buna-N

**E** = EPR

**V** = Viton

### INLET/OUTLET

**3/4** = 3/4" NPT

**1.0** = 1" NPT

**1-1/4** = 1-1/4" NPT

### MATERIAL

**SS304** = 304 stainless steel

## **R Model 7180 Series Hydraulic Lube-Oil Filter**

Designed for use with 718 and 736 style filter cartridges.  
Flows to 100 GPM.

The 7180 series Hydraulic lube filters are ideal for your oil reclamation and maintenance operations.

The 7180 series housings incorporate an eyenut cover that is easily removed, reducing time spent on cartridge change-out. The side-in/side-out piping arrangement is available in 1", 1-1/2", and 2" NPT connection sizes. Housings are electropolished creating a smooth, easy-to-clean surface.

The 7180 series accepts single 718 or 736 style filter cartridges, and are rated at 1 $\mu$  absolute to 100 $\mu$  nominal. They seal on the housing's elevated pedestal and are retained by a threaded post and cap assembly.

Keep your filtration process cost effective without sacrificing quality.

### **Applications**


- Bulk Oil Handling
- Coolants
- Cutting Oils
- Fuels
- Hydraulic Oils
- Lubrication Oils
- Process Liquids
- Quench Oils
- Rolling Mill Oils
- Solvents

### **Features**

- Permanently piped housings are opened without special tools
- Carbon steel housings or 304 and 316 stainless steel
- Covers are O-ring sealed
- 150 psi rated housing
- 1", 1-1/2", or 2" NPT inlet and outlet
- 1/4" NPT vent connection



**DUPLEX MODEL D8-7182**



\*Based on housing only. Fluid viscosity, filter bag used, and expected dirt loading should be considered when sizing a filter.

## How To Order

Build an ordering code as shown in the example.

**Example :**      **8-7181 - 2P - 2 - 150 - C - V - C**

### MODEL

**8-7181** (single element)

**8-7182** (double element)

**D8-7181** (duplex single element)

**D8-7182** (duplex double element)

### PIPE SIZE

1-inch female NPT = **1P**

1-1/2-inch female NPT = **1-1/2P**

2-inch female NPT = **2P**

### OUTLET STYLE

Side / Side = **2**

### PRESSURE RATING

100 psi = **150**

### HOUSING MATERIAL

Carbon steel = **C**

Stainless steel = **S**

316 Stainless steel = **S316**

### COVER SEAL

Buna N = **B**





Ethylene propylene = **E**

Viton® Fluoroelastomer = **V**

### ASME CODE STAMP

ASME Code Stamp = **C**

Weight (approximately): 70 lbs. (Model 8-7181)



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



## **R 718 and 736 Filter Cartridges**

For Use With the 7180 Housing.  
Flows to 100 GPM.

The Rosedale 718 and 736 style filter cartridges, are rated at  $1\mu$   $\beta$ 1000 to  $100\mu$  nominal.

### **Specifications**

**Filtration Ratings:**

95% at 1, 5, 10, 20, and  $30\mu$ m

**Filter Media:**

Phenolic Impregnated Cellulose

**Perforated Sleeve & Core, End Caps:**

ETP Steel

**Adhesive:**

Thermosetting PVC

**End Seals:**

Buna-N Gasket Standard

**Recommended Operating Conditions:**

Maximum Temperature: 250°F (121°C)

Change-Out  $\Delta P$ : 25 PSID (1.7 BAR)

Maximum Flow Rate:

718 Series: 50 GPM

736 Series: 100 GPM

**Size:**

718: 6" OD x 18.1" Long

736: 6" OD x 36.1" Long

(ID is 2-5/8" or 2-1/8")

**Shipping Weight:**

718: 20 lb (6 per carton)

736: 40 lb (6 per carton)



**Liquid Particle Retention Ratings ( $\mu$ m)  
at Removal Efficiencies Of:**

Cartridge	$\beta=1000$ 99.9%	$\beta=75$ 98.7%	$\beta=20$ 95%
1	12	3	1
5	25	18	5
10	40	25	10
20	50	40	20
30	85	60	40




## How To Order


Build an ordering code as shown in the example.

### Flow vs Differential Pressure


#### 718: 1/2 to 1 Microns



#### 718: 5 to 10 Microns



#### 718: 20 to 100 Microns



#### Example :

**718 - 10 - 8 - V - None**

#### MODEL

18.1" x 6.25" = **718**

36.1" x 6.25" = **736**

#### MICRON RATING

**1, 5, 10, 20, 30**

#### INSIDE DIAMETER

2-5/8 Inch

= **None**

2-1/8 Inch

= **8**

#### COVER SEAL

Buna N

= **None**

Cork

= **C**

Vellumoid

= **V**


#### PERFORATED SLEEVE & CORE

ETP Steel

= **None**

No Sleeve & Core

= **N**



## Cartridge Filter Housings

These cartridge filters offer a wide range of flow capacities and contaminant holding capabilities. The housings can accommodate from 1 to 205 cartridges around. All housings can be supplied with an ASME code stamp, if required.

### Standard Features



- Low pressure drop
- Permanently piped housings are opened without special tools and without disturbing the piping
- Machined cover gasket groove provides positive O-ring sealing
- Easy to clean
- In-line inlet and outlet
- Stainless steel internals

### Standard Options

- 2 outlet styles
- Carbon steel, 304 or 316 stainless steel housings
- ASME code stamp
- O-ring seals: Buna N, EPR, Viton®, Teflon®
- Accommodates 10, 20, 30 or 40-inch cartridges
- Flanged connections for 3/4 through 12-inch pipe
- V posts or threaded center posts
- Units accept DOE or 222 style cartridges

### How They Work

Unfiltered fluid enters the housing and is distributed evenly around the cartridges, from outside to inside. Solids are collected on the outside for easy removal. The filtered fluid then exits through the outlet pipe.



Center: Models 4, 6 and 8  
Bottom Right: Models 12 thru 48

## Cartridge Requirements

The following table gives the number of cartridges needed for each housing model.

Model Number and Diameter	Cartridge Lengths	Number of Cartridges	Equivalent 10-inch lengths	Available Pipe Sizes
Model 4	10-inch	1	1	3/4, 1, 1-1/4, 1-1/2, 2
	20-inch	1	2	
	30-inch	1	3	
	40-inch	1	4	
Model 6	20-inch	3	6	3/4, 1, 1-1/4, 1-1/2, 2, 3
	30-inch	3	9	
	40-inch	3	12	
Model 8	20-inch	6	12	3/4, 1, 1-1/4, 1-1/2, 2, 3
	30-inch	6	18	
	40-inch	6	24	
Model 12	20-inch	12	24	2,3,4
	30-inch	12	36	
	40-inch	12	48	
Model 16	20-inch	20	40	2,3,4
	30-inch	20	60	
	40-inch	20	80	
Model 18	20-inch	27	54	2,3,4
	30-inch	27	81	
	40-inch	27	108	
Model 22	20-inch	40	80	3,4,6
	30-inch	40	120	
	40-inch	40	160	
Model 24	20-inch	52	104	3,4,6
	30-inch	52	156	
	40-inch	52	208	
Model 30	20-inch	82	164	4,6,8
	30-inch	82	246	
	40-inch	82	328	
Model 36	20-inch	116	232	6,8,10
	30-inch	116	348	
	40-inch	116	464	
Model 42	20-inch	158	316	8,10,12
	30-inch	158	474	
	40-inch	158	632	
Model 48	20-inch	205	410	8,10,12
	30-inch	205	615	
	40-inch	205	820	


### Determining Housing Pressure Drop Only

The pressure drops shown on the graph are reliable for all cartridge housings. The pressure drop of any housing is governed by the size of the inlet and outlet, not the vessel itself.

1. Using desired pipe size and approximate flow rate, determine the basic pressure drop from the graph.
2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table.
3. You now have the pressure drop for an empty cartridge housing.
4. The user selected cartridge pressure drop must then be added to the housing pressure.
5. To calculate pressure drop through cartridges, see page 192.

### Viscosity Factors


	CPS NUMBER							
1 (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80



\*Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.



## Dimensions for Models 4, 6, and 8 (IN)



Model No.	Pipe Size	A	B	C	D	E	F	H	I	J
<b>4110</b>	3/4	6.0	5.0	3.5	20.0	18.6	18.9	11.8	1.9	4.0
	1	6.0	5.0	3.5	20.0	18.8	19.3	11.8	2.5	4.0
	1-1/4	6.0	5.0	3.5	20.0	18.8	19.7	11.8	2.9	4.0
	1-1/2	6.0	5.0	3.5	20.0	18.8	20.1	11.8	3.3	4.0
	2	6.0	5.0	3.5	20.0	18.7	20.8	11.8	4.0	5.0
<b>4120</b>	3/4	11.0	5.0	3.5	30.0	28.6	28.9	21.8	1.9	4.0
	1	11.0	5.0	3.5	30.0	28.8	29.3	21.8	2.5	4.0
	1-1/4	11.0	5.0	3.5	30.0	28.8	29.7	21.8	2.9	4.0
	1-1/2	11.0	5.0	3.5	30.0	28.8	30.1	21.8	3.3	4.0
	2	11.0	5.0	3.5	30.0	28.7	30.8	21.8	4.0	5.0
<b>4130</b>	3/4	16.0	5.0	3.5	40.0	38.6	38.9	31.8	1.9	4.0
	1	16.0	5.0	3.5	40.0	38.8	39.3	31.8	2.5	4.0
	1-1/4	16.0	5.0	3.5	40.0	38.8	39.7	31.8	2.9	4.0
	1-1/2	16.0	5.0	3.5	40.0	38.8	40.1	31.8	3.3	4.0
	2	16.0	5.0	3.5	40.0	38.7	40.8	31.8	4.0	5.0
<b>4140</b>	3/4	21.0	5.0	3.5	50.0	48.6	48.9	41.8	1.9	4.0
	1	21.0	5.0	3.5	50.0	48.8	49.3	41.8	2.5	4.0
	1-1/4	21.0	5.0	3.5	50.0	48.8	49.7	41.8	2.9	4.0
	1-1/2	21.0	5.0	3.5	50.0	48.8	50.1	41.8	3.3	4.0
	2	21.0	5.0	3.5	50.0	48.7	50.8	41.8	4.0	5.0

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.




**Dimensions for Models 4, 6, and 8 (IN) Cont.**

Model No.	Pipe Size	A	B	C	D	E	F	H	I	J
<b>6310</b>	3/4	6.0	6.0	4.0	21.0	18.7	18.9	11.8	1.9	5.0
	1	6.0	6.0	4.3	21.0	18.8	19.3	11.8	2.5	5.0
	1-1/4	6.0	6.0	4.3	21.0	18.8	19.7	11.8	2.9	5.0
	1-1/2	6.0	6.0	4.3	21.0	18.8	20.1	11.8	3.3	5.0
	2	6.0	6.0	4.3	21.88	18.8	20.8	11.8	4.0	5.0
	3	6.0	6.0	4.3	21.88	19.1	22.1	11.8	6.1	7.3
<b>6320</b>	3/4	11.0	6.0	4.0	31.0	28.7	28.9	21.8	1.9	5.0
	1	11.0	6.0	4.3	31.0	28.8	29.3	21.8	2.5	5.0
	1-1/4	11.0	6.0	4.3	31.0	28.8	29.7	21.8	2.9	5.0
	1-1/2	11.0	6.0	4.3	31.0	28.8	30.1	21.8	3.3	5.0
	2	11.0	6.0	4.3	31.88	28.7	30.8	21.8	4.0	5.0
	3	11.0	6.0	4.3	31.88	29.1	32.1	21.8	6.1	7.3
<b>6330</b>	3/4	16.0	6.0	4.0	41.0	38.7	38.9	31.8	1.9	5.0
	1	16.0	6.0	4.3	41.0	38.8	39.3	31.8	2.5	5.0
	1-1/4	16.0	6.0	4.3	41.0	38.8	39.7	31.8	2.9	5.0
	1-1/2	16.0	6.0	4.3	41.0	38.8	40.1	31.8	3.3	5.0
	2	16.0	6.0	4.3	41.88	38.8	40.8	31.8	4.0	5.0
	3	16.0	6.0	4.3	41.88	39.1	42.1	31.8	6.1	7.3
<b>6340</b>	3/4	21.0	6.0	4.0	51.0	48.7	48.9	41.8	1.9	5.0
	1	21.0	6.0	4.3	51.0	48.8	49.3	41.8	2.5	5.0
	1-1/4	21.0	6.0	4.3	51.0	48.8	49.7	41.8	2.9	5.0
	1-1/2	21.0	6.0	4.3	51.0	48.8	50.1	41.8	3.3	5.0
	2	21.0	6.0	4.3	51.88	48.8	50.8	41.8	4.0	5.0
	3	21.0	6.0	4.3	51.88	49.1	52.1	41.8	6.1	7.3
<b>8620</b>	3/4	11.0	7.5	5.3	32.1	29.7	30.1	21.8	1.9	5.0
	1	11.0	7.5	5.3	32.1	29.8	30.4	21.8	2.5	5.0
	1-1/4	11.0	7.5	5.3	32.1	29.8	30.7	21.8	2.9	5.0
	1-1/2	11.0	7.5	5.6	32.1	29.8	30.1	21.8	3.3	5.0
	2	11.0	7.5	5.8	32.1	29.8	31.8	21.8	4.0	5.0
	3	11.0	7.5	6.8	32.4	30.3	33.2	21.8	6.1	7.3
<b>8630</b>	3/4	16.0	7.5	5.3	42.1	39.7	40.1	31.8	1.9	5.0
	1	16.0	7.5	5.3	42.1	39.8	40.4	31.8	2.5	5.0
	1-1/4	16.0	7.5	5.3	42.1	39.8	40.7	31.8	2.9	5.0
	1-1/2	16.0	7.5	5.6	42.1	39.8	40.1	31.8	3.3	5.0
	2	16.0	7.5	5.8	42.1	39.8	41.8	31.8	4.0	5.0
	3	16.0	7.5	6.8	42.4	40.3	43.2	31.8	6.1	7.3
<b>8640</b>	3/4	21.0	7.5	5.3	52.1	49.7	50.1	41.8	1.9	5.0
	1	21.0	7.5	5.3	52.1	49.8	50.4	41.8	2.5	5.0
	1-1/4	21.0	7.5	5.3	52.1	49.8	50.7	41.8	2.9	5.0
	1-1/2	21.0	7.5	5.6	52.1	49.8	50.1	41.8	3.3	5.0
	2	21.0	7.5	5.8	52.1	49.8	51.8	41.8	4.0	5.0
	3	21.0	7.5	6.8	52.4	50.3	53.2	41.8	6.1	7.3




## **R** Dimensions for Models 12-24 (IN)

STYLE 1



STYLE 2



Model No.	No. of Cart.	Cart. Length	Pipe Size	STYLE 1					STYLE 2							Empty Weight (lbs)	Total Volume (cu. ft.)
				A	B	C	D	E	B	C	D	F	G	H	I		
12	12	20	2	12.0	59.1	43.1	33.1	12.0	50.6	34.6	24.6	4.5	5.5	9.3	10.0	370	2.2
			3						52.9	36.9	26.9	5.3	7.3			385	
			4						55.1	39.1	29.1	6.0	9.0			410	
		30	2	12.0	69.1	53.1	38.1	12.0	60.6	44.6	29.6	4.5	5.5	9.3	10.0	395	2.9
			3						62.9	46.9	31.9	5.3	7.3			410	
			4						65.1	49.1	34.1	6.0	9.0			425	
		40	2	12.0	79.1	63.1	43.1	12.0	70.6	54.6	34.6	4.5	5.5	9.3	10.0	420	3.7
			3						72.9	56.9	36.9	5.3	7.3			435	
			4						75.1	59.1	39.1	6.0	9.0			455	
16	20	20	2	16.0	61.1	44.1	34.1	12.0	52.6	35.6	25.6	4.5	5.5	10.9	12.0	450	3.6
			3						54.9	37.9	27.9	5.3	7.3			465	
			4						57.1	40.1	30.1	6.0	9.0			480	
		30	2	16.0	71.1	54.1	39.1	12.0	62.6	45.6	30.6	4.5	5.5	10.9	12.0	475	4.8
			3						64.9	47.9	32.9	5.3	7.3			495	
			4						67.1	50.1	35.1	6.0	9.0			510	
		40	2	16.0	81.1	64.1	44.1	12.0	72.6	55.6	35.6	4.5	5.5	10.9	12.0	505	5.9
			3						74.9	57.9	37.9	5.3	7.3			520	
			4						77.1	60.1	40.1	6.0	9.0			540	

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.


**Dimensions for Models 12-24 (IN) Cont.**

Model No.	No. of Cart.	Cart. Length	Pipe Size	STYLE 1					STYLE 2							Empty Weight (lbs)	Total Volume (cu. ft.)
				A	B	C	D	E	B	C	D	F	G	H	I		
18	27	20	2	18.0	62.1	44.6	34.6	12.0	53.6	36.1	26.1	4.5	5.5	11.9	13.0	480	4.7
			3						55.9	38.4	28.4	5.3	7.3			500	
			4						58.1	40.6	30.6	6.0	9.0			515	
		30	2	18.0	72.1	54.6	39.6	12.0	63.6	46.1	31.1	4.5	5.5	11.9	13.0	515	6.1
			3						65.9	48.4	33.4	5.3	7.3			530	
			4						68.1	50.6	35.6	6.0	9.0			550	
		40	2	18.0	82.1	64.6	44.6	12.0	73.6	56.1	36.1	4.5	5.5	11.9	13.0	550	7.6
			3						75.9	58.4	38.4	5.3	7.3			565	
			4						78.1	60.6	40.6	6.0	9.0			580	
22	40	20	2	22.0	64.1	45.6	35.6	12.0	55.6	37.1	27.1	4.5	5.5	13.9	15.0	615	7.3
			3						57.9	39.4	29.4	5.3	7.3			630	
			4						60.1	41.6	31.6	6.0	9.0			645	
		30	2	22.0	74.1	55.6	40.6	12.0	65.6	47.1	32.1	4.5	5.5	13.9	15.0	655	9.5
			3						67.9	49.4	34.4	5.3	7.3			670	
			4						70.1	51.6	36.6	6.0	9.0			690	
		40	2	22.0	84.1	65.6	45.6	12.0	75.6	57.1	37.1	4.5	5.5	13.9	15.0	695	11.7
			3						77.9	59.4	39.4	5.3	7.3			710	
			4						80.1	61.6	41.6	6.0	9.0			730	
24	52	20	2	24.0	65.1	46.1	36.1	12.0	56.6	37.6	27.6	4.5	5.5	14.9	16.0	665	8.8
			3						58.9	39.9	29.9	5.3	7.3			680	
			4						61.1	42.1	32.1	6.0	9.0			700	
		30	2	24.0	75.1	56.1	41.1	12.0	66.6	47.6	32.6	4.5	5.5	14.9	16.0	710	11.4
			3						68.9	49.9	34.9	5.3	7.3			725	
			4						71.1	52.1	37.1	6.0	9.0			740	
		40	2	24.0	85.1	66.1	46.1	12.0	76.6	57.6	37.6	4.5	5.5	14.9	16.0	750	14.0
			3						78.9	59.9	39.9	5.3	7.3			770	
			4						81.1	62.1	42.1	6.0	9.0			785	
		6	2	24.0	85.1	66.1	46.1	12.0	85.1	66.1	46.1	7.0	12.5			830	
			3														
			4														



## Dimensions for Models 30-48 (IN)

Model No.	No. of Cart.	Cart. Length	Pipe Size	STYLE 1					STYLE 2							Empty Weight (lbs)	Total Volume (cu. ft.)
				A	B	C	D	E	B	C	D	F	G	H	I		
30	82	20	2	30.0	68.1	47.6	37.6	12.0	59.6	39.1	29.1	4.5	5.5	17.9	19.0	955	14.5
			3						61.9	41.4	31.4	5.3	7.3			970	
			4						64.1	43.6	33.6	6.0	9.0			990	
			6						68.1	47.6	37.6	7.0	12.5			1035	
			8						72.4	51.9	41.9	8.3	16.0			1100	
		30	2	30.0	78.1	57.6	42.6	12.0	69.6	49.1	34.1	4.5	5.5	17.9	19.0	1030	18.6
			3						71.9	51.4	36.4	5.3	7.3			1045	
			4						74.1	53.6	38.6	6.0	9.0			1060	
			6						78.1	57.6	42.6	7.0	12.5			1110	
			8						82.4	61.9	46.9	8.3	16.0			1170	
		40	2	30.0	88.1	67.6	47.6	12.0	79.6	59.1	39.1	4.5	5.5	17.9	19.0	1100	22.7
			3						81.9	61.4	41.4	5.3	7.3			1120	
			4						84.1	63.6	43.6	6.0	9.0			1135	
			6						88.1	67.6	47.6	7.0	12.5			1180	
			8						92.4	71.9	51.9	8.3	16.0			1245	
36	116	20	2	36.0	71.1	49.1	39.1	12.0	62.6	40.6	30.6	4.5	5.5	20.9	22.0	1315	22.0
			3						64.9	42.9	32.9	5.3	7.3			1330	
			4						67.1	45.1	35.1	6.0	9.0			1350	
			6						71.1	49.1	39.1	7.0	12.5			1395	
			8						75.4	53.4	43.4	8.3	16.0			1460	
			10						79.6	57.6	47.6	9.5	19.0			1570	
		30	2	36.0	81.1	59.1	44.1	12.0	72.6	50.6	35.6	4.5	5.5	20.9	22.0	1425	27.9
			3						74.9	52.9	37.9	5.3	7.3			1440	
			4						77.1	55.1	40.1	6.0	9.0			1460	
			6						81.1	59.1	44.1	7.0	12.5			1505	
			8						85.4	63.4	48.4	8.3	16.0			1570	
			10						89.6	67.6	52.6	9.5	19.0			1680	
		40	2	36.0	91.1	69.1	49.1	12.0	82.6	60.6	40.6	4.5	5.5	20.9	22.0	1535	33.8
			3						84.9	62.9	42.9	5.3	7.3			1550	
			4						87.1	65.1	45.1	6.0	9.0			1570	
			6						91.1	69.1	49.1	7.0	12.5			1615	
			8						95.4	73.4	53.4	8.3	16.0			1680	
			10						99.6	77.6	57.6	9.5	19.0			1790	
42	158	20	2	42.0	74.1	50.6	40.6	12.0	65.6	42.1	32.1	4.5	5.5	23.9	25.0	2030	31.6
			3						67.9	44.4	34.4	5.3	7.3			2045	
			4						70.1	46.6	36.6	6.0	9.0			2060	
			6						74.1	50.6	40.6	7.0	12.5			2110	


**Dimensions for Models 30-48 (IN) Cont.**

Model No.	No. of Cart.	Cart. Length	Pipe Size	STYLE 1					STYLE 2							Empty Weight (lbs)	Total Volume (cu. ft.)
				A	B	C	D	E	B	C	D	F	G	H	I		
			8						78.4	54.9	44.9	8.3	16.0			2170	
			10						82.6	59.1	49.1	9.5	19.0			2280	
			12						87.1	63.6	53.6	11.0	22.5			2415	
	30	2		42.0	84.1	60.6	45.6	12.0	75.6	52.1	37.1	4.5	5.5	23.9	25.0	2160	39.6
		3							77.9	54.4	39.4	5.3	7.3			2175	
		4							80.1	56.6	41.6	6.0	9.0			2195	
		6							84.1	60.6	45.6	7.0	12.5			2240	
		8							88.4	64.9	49.9	8.3	16.0			2305	
		10							92.6	69.1	54.1	9.5	19.0			2415	
		12							97.1	73.6	58.6	11.0	22.5			2550	
	40	2		42.0	94.1	70.6	50.6	12.0	85.6	62.1	42.1	4.5	5.5	23.9	25.0	2285	47.6
		3							87.9	64.4	44.4	5.3	7.3			2300	
		4							90.1	66.6	46.6	6.0	9.0			2320	
		6							94.1	70.6	50.6	7.0	12.5			2360	
		8							98.4	74.9	54.9	8.3	16.0			2430	
		10							102.6	79.1	59.1	9.5	19.0			2535	
		12							107.1	83.6	63.6	11.0	22.5			2670	
48	205	20	2	48.0	77.1	52.1	42.1	12.0	68.6	44.1	34.1	4.5	5.5	26.9	28.0	2510	43.2
			3						70.9	46.4	36.4	5.3	7.3			2520	
			4						73.1	48.6	38.6	6.0	9.0			2540	
			6						77.1	52.6	42.6	7.0	12.5			2585	
			8						81.4	56.9	46.9	8.3	16.0			2650	
			10						85.6	61.1	51.1	9.5	19.0			2760	
			12						90.1	65.6	55.6	11.0	22.5			2895	
	30	2		48.0	87.1	62.1	47.1	12.0	78.6	54.1	39.1	4.5	5.5	26.9	28.0	2655	53.7
		3							80.9	56.4	41.4	5.3	7.3			2670	
		4							83.1	58.6	43.6	6.0	9.0			2685	
		6							87.1	62.6	47.6	7.0	12.5			2730	
		8							91.4	66.9	51.9	8.3	16.0			2800	
		10							95.6	71.1	56.1	9.5	19.0			2905	
		12							100.1	75.6	60.6	11.0	22.5			3040	
	40	2		48.0	97.1	72.1	52.1	12.0	88.6	64.1	44.1	4.5	5.5	26.9	28.0	2800	64.1
		3							90.9	66.4	46.4	5.3	7.3			2815	
		4							93.1	68.6	48.6	6.0	9.0			2830	
		6							97.1	72.6	52.6	7.0	12.5			2880	
		8							101.4	76.9	56.9	8.3	16.0			2945	
		10							105.6	81.1	61.1	9.5	19.0			3050	
		12							110.1	85.6	65.6	11.0	22.5			3180	



## How To Order

Build an ordering code as shown in the example.  
Each available only on the model sizes highlighted  
in the colored blocks preceding its description

Key To Blocks:				
4	6	8	12	= Model 4
4	6	8	12	= Model 6
4	6	8	12	= Model 8
4	6	8	12	= Model 12 etc.

**Example:** **HOUSING** **OPTION**  
**245230- 4F-1-150-S-B-DOE-VP-C**

**MODEL NO.**  
= 4  
= 6  
= 8  
= 12  
= 16  
= 18  
= 22  
= 24  
= 30  
= 36  
= 42  
= 48

**NUMBER OF CARTRIDGES<sup>4</sup>**  
(Around) Cartridges  
= 1  
= 3  
= 6  
= 12  
= 20  
= 27  
= 40  
= 52  
= 82  
= 116  
= 158  
= 205

**CARTRIDGE LENGTH<sup>4</sup>**  
10-in. = 10  
20-in. = 20  
30-in. = 30  
40-in. = 40

**PIPE SIZE NPT (female)**  
3/4-in. = 3/4P  
1-in. = 1P  
1-1/4-in. = 1-1/4P  
1-1/2-in. = 1-1/2P  
2-in. = 2P  
3-in. = 3P

**FLANGED<sup>1</sup>**  
3/4-in. = 3/4F  
1-in. = 1F  
1-1/4-in. = 1-1/4F  
1-1/2-in. = 1-1/2F  
2-in. = 2F  
3-in. = 3F  
4-in. = 4F  
6-in. = 6F  
8-in. = 8F  
10-in. = 10F  
12-in. = 12F

**ASME CODE STAMP**  
C = Code

**CARTRIDGE SEALING METHOD**  
VP = V Post and Spring Seal  
TP = Threaded Post  
For other styles, consult factory

**CARTRIDGE DESIGN<sup>4</sup>**  
DOE = Double-Open End  
SOE = Single-Open End  
222 = Double O-Ring  
226 = Bayonet Lock (Pall)

**COVER SEAL**  
B = Buna N  
E = Ethylene Propylene  
V = Viton®  
TEV = Teflon® Encapsulated Viton®  
TSW = Teflon® (solid white)

**HOUSING MATERIAL<sup>2</sup>**  
C = Carbon Steel  
S = 304 Stainless Steel  
S316 = 316 Stainless Steel

**PRESSURE RATING<sup>3</sup>**  
150 = 150 psi (NPT or flanged)  
300 = 300 psi (NPT or flanged)

**PIPING STYLE<sup>2</sup>**  
1 = Side Inlet, Bottom Outlet  
2 = In-line, Inlet-high, Outlet-low

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. Other styles and classes are available. ANSI B1.6.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.  
2. Consult factory for special options.  
3. Higher pressure ratings available. Consult factory.  
4. Filter cartridges are sold separately. See page 150.

**Pressure Drop Data**  
Cartridge filters are usually selected so that the clean pressure drop does not exceed 2 psi. Higher pressure drops may be tolerated when contaminant loading is low. The user must determine the appropriate cartridge for the application, and note the flow rate ΔP per cartridge as suggested by the media manufacturer.

**Viscosity Factors**

	CPS NUMBER							
1 (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80


## **R** Cartridge Filters

Rugged, low-cost cartridge design  
for flow rates to 100 gpm\*

These cartridge-filter housings are rugged and low in cost. They hold five cartridges, in 10-inch, 20-inch, 30-inch, or 40-inch lengths, using industry standard designs (222, SOE, or DOE). The unique, "quick-opening" clamp design uses a standard O-ring.

### Standard Features

- Low pressure drop
- Permanently piped housings are opened without disturbing the piping or requiring tools
- Quick-opening, clamp-type cover
- Carbon or stainless steel housings
- Adjustable-height tripod legs
- Holds 5 cartridge elements
- Accommodates cartridge elements in four lengths: 10", 20", 30", 40"
- 125-psi rated housing
- 3/4-inch clean-dirty/gage ports
- 2-inch female NPT ports
- V posts or threaded-center posts
- Standard hardware V-post and spring seals are 316 stainless steel.
- O-ring seals: Buna N, EPR, Viton®



\*Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.





## **R** How To Order


### Reduced Pressure Model 8 Cartridge Housing

Build an ordering code as shown in the example

	Housing	Options
<b>Example:</b>	<b>8520 - 2P - 1 - 125 - S - B - 222</b>	
<b>REDUCED PRESSURE MODEL 8 CARTRIDGE HOUSING</b> = 8		
<b>NUMBER OF CARTRIDGES</b> 5 = 5		
<b>CARTRIDGE LENGTH</b> 10 inch = 10 20 inch = 20 30 inch = 30 40 inch = 40		
<b>PIPE SIZE</b> 2-inch female NPT = 2P		
<b>OUTLET STYLE</b> Bottom = 1		
<b>PRESSURE RATING</b> 125 PSI = 125		
<b>HOUSING MATERIAL</b> Carbon Steel = C 304 Stainless Steel = S		
<b>COVER SEAL</b> Buna N = B Ethylene Propylene = E Viton® Fluorelastomer = V		
<b>CARTRIDGE DESIGN</b> 222 = 222 Single-open End = SOE Double-open End = DOE		

1. Filter cartridges are specified separately.  
See page 150.
2. Comes with V-Posts and spring seals.

### Dimensions (IN)



Cart. Length	A	B
10	6	14-13/16
20	11	19-13/16
30	16	24-13/16
40	21	29-13/16

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## **R Platinum 700 Cartridge Filter Housings**

Ultra high capacity filter eliminates maintenance by providing high dirt removal

These new cartridge housings are designed to end the high cost of cartridge change-out. They are offered in three Model 8 styles (LCO, Polypropylene, and Standard Model 8) and Multi-cartridge housings.

### **Standard Features**

- From 1 to 29 cartridges
- Multi-cartridge units are offered in the low profile design, for quick and easy cartridge removal
- Horizontal or vertical mount
- Housings available in carbon steel, 304 or 316 stainless steel and polypropylene
- Pressure ratings in 100, 125, and 150 psi
- ASME code stamp available on selected models
- Flanged or threaded connection sizes from 2-inch through 10-inch
- Covers are o-ring sealed and easy to remove
- Leg assembly (excludes CR8)
- Clean and dirty/gage port connections
- O-ring seals: Buna, Ethylene Propylene, Viton®, and Teflon® Encapsulated Viton®

A single 700 Series cartridge unit will out perform 40 standard wound or 10 pleated cartridges, reducing maintenance. A decrease in cartridge use, reduces labor, inventory, worker exposure and disposal costs. A single cartridge holds as much as 20 pounds of contaminant and flows to 100 gallons per minute. The labor-intensive v-posts and spring seals are eliminated and cartridges are easily removed, requiring no special tools. Elements are approximately 6.25-inch diameter and 35-inch length.



For more detailed design information about the 700 Series cartridge element see page 181.



# Single Cartridge Platinum 700 Filter Housing

## How To Order

Build an ordering code as shown in the example

**Example: CR8135 - 2F - 1- 150 - P - B - 700 - C**

### MODEL NUMBER

Low Pressure, 1 Element = **LCO8135**

Poly-Pro, 1 Element = **CR8135**

Model 8, 1 Element = **NCO8135 or 8135**

### PIPE SIZE, FLANGED

CR8, Flat Face class 150 = **2F**

RCO, LCO8, female NPT = **2P**

Model 8, RF class 150, or FNPT = **2F or 2P**

### OUTLET STYLE

Side In/Bottom Out = **1**

Side In/Side Out = **2**

### PRESSURE RATING

Low pressure = **125 psi**

Poly Pro = **100 psi**

Model 8 = **150 psi**

### HOUSING MATERIAL

Carbon Steel = **C**

304 Stainless Steel = **S**

316 Stainless Steel = **S316**

Polypropylene (CR8 only) = **P**

### COVER GASKET

Buna = **B**

Ethylene Propylene = **E**

Viton® Fluorelastomer = **V**


Teflon® Encapsulate Viton® = **TEV**

### ELEMENT SERIES

ASME CODE OPTION


ASME Code Stamp (8135 only) = **C**

NSF 61 listed (8135 only) = **NSF**




## Dimensions (IN)


### LCO8135



### CR8135



### 8135



## Viscosity Factors

	CPS NUMBER							
1 (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80

\*Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## Multiple Cartridge Platinum 700 Filter Housing





### How To Order

Build an ordering code as shown in the example


<b>Example:</b>	<b>SLP-18435 - 3F - 1- 150 - S - B - 700 - C</b>
<b>HOUSING STYLE</b>	
Standard Low Profile = <b>SLP</b>	
Horizontal Mount = <b>HM</b>	
<b>MODEL NUMBER</b>	
Model 18, 4 Elements = <b>18435</b>	
Model 24, 7 Elements = <b>24735</b>	
Model 36, 18 Elements = <b>361835</b>	
Model 42, 21 Elements = <b>422135</b>	
Model 48, 29 Elements = <b>482935</b>	
<b>PIPE SIZE, FLANGED</b>	
Model 18 = <b>2F or 3F</b>	
Model 24 = <b>3F or 4F</b>	
Model 36 = <b>4F, 6F or 8F</b>	
Model 42 = <b>8F, 10F or 12F</b>	
Model 48 = <b>8F, 10F or 12F</b>	
<b>OUTLET STYLE</b>	
Side In/Bottom Out = <b>1</b>	
Side In/Side Out = <b>2</b>	
<b>PRESSURE RATING</b>	
150 PSI = <b>150</b>	
<b>HOUSING MATERIAL</b>	
Carbon Steel = <b>C</b>	
304 Stainless Steel = <b>S</b>	
316 Stainless Steel = <b>S316</b>	
<b>COVER GASKET</b>	
Buna = <b>B</b>	
Ethylene Propylene = <b>E</b>	
Viton® Fluorelastomer = <b>V</b>	
Teflon Encapsulate Viton® = <b>TEV</b>	
<b>ELEMENT SERIES</b>	
= <b>700</b>	
<b>ASME CODE OPTION</b>	
ASME Code Stamp = <b>C</b>	
NSF 61 listed = <b>NSF</b>	

### Dimensions (IN)



\*Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



MODEL NO. & Dim. A	Pipe Sizes B	Leg Bolt Circle Dia.	C	D	E	F	G
<b>18</b>	2	16.0	22.2	49.4	68.2	8.00	14.0
	3		21.6	49.8	68.7	9.00	14.0
<b>24</b>	3	22.0	23.1	51.3	71.7	9.00	18.0
	4		22.6	50.8	71.2	9.00	19.0
<b>36</b>	4	34.0	27.4	55.9	77.7	9.50	25.0
	6		26.3	55.9	77.6	10.5	26.0
	8		25.3	55.9	77.6	11.5	27.0
<b>42</b>	10	40	36.0	60.0	92.0	10.0	34.0
<b>48</b>	12	42	38.5	62.0	98.0	12.0	38.0

## **The Platinum 900 and 2040 Cartridge Filter Housings**

Ultra high capacity filtration system provides maximum dirt holding capacity—eliminating maintenance

End the high cost of element change-out with the Platinum 900 and 2040 cartridge filter system. Imagine changing a filter element only once or twice a year, instead of changing several cartridges on a weekly or daily basis!

### **Standard Features**

- Housings available in carbon steel, 304 or 316 stainless steel.
- Pressure rating 150 psi
- Clean and dirty/gauge port connections
- O-ring seals: Buna, Ethylene Propylene and Viton®
- Covers are o-ring sealed and easy to remove
- ASME code stamp (optional)
- Flange connection sizes from 3-inch through 10-inch
- Cable-hoist assembly for quick and easy removal of element is standard on Model 18 (optional on other models)

A single cartridge system has the life of hundreds of standard wound or 50 pleated cartridges. This reduces maintenance and cartridge use, labor, inventory, worker exposure, and disposal costs.


Flow rates and contaminant holding capacities vary depending on micron size. A single cartridge element can hold up to 400 pounds of contaminant and flows to 600 gallons per minute. Elements are 13- or 20-inch diameter and 40-inches long.

The 900 Series filter housings contain one, three, four, seven, or eight cartridges. The 2040 Series is available a single cartridge.

By using the cable-hoist assembly change-out is completed in minutes. The element shipping container allows for easy handling and disposal.



Extra large cartridges hold more contaminate.



\* Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.

### **Viscosity Factors**

CPS NUMBER								
I (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80

For more detailed design information and how to order the 900 and 2040 Series cartridge element see page 182.



## How To Order

Build an ordering code as shown in the example

**Example:** **SLP - 18140 - 4F - 1- 150 - S - B - 900 - C**

### HOUSING STYLE

Standard Low Profile = **SLP**

### MODEL NUMBER

Model 18, 1 Element = **18140**

Model 22, 1 Element = **22140**

Model 30, 3 Elements = **30340**

Model 36, 4 Elements = **36440**

Model 42, 7 Elements = **42740**

Model 48, 8 Elements = **48840**

### PIPE SIZE, FLANGED

Model 18 = **2F or 3F**

Model 30 = **4F or 6F**

Model 36 = **6F or 8F**

Model 42 = **8F or 10F**

Model 48 = **8F or 10F**

### OUTLET STYLE

Side In/Side Out = **1**

### PRESSURE RATING

150 PSI = **150**

### HOUSING MATERIAL

304 Stainless Steel = **S**

Carbon Steel = **C**

316 Stainless Steel = **S316**

### COVER GASKET

Buna = **B**

Ethylene Propylene = **E**

Viton® Fluorelastomer = **V**

Teflon® Encapsulated Viton® = **TEV**

**ELEMENT SERIES** = **900**




= **2040** (22140 element only)

### ASME CODE OPTION

ASME Code Stamp = **C**

MODEL NUMBER & Dim. A	Pipe Sizes B	Leg Bolt Circle Dia.	C	D	E	F	G	H
<b>18</b>	2	16.0	22.2	53.4	72.2	8.0	14.0	101.8
	3		21.6	53.8	72.7	9.0	15.0	102.3
<b>22</b>	4	14.6	24.0	58.9	76.9	6.0	17.25	107.6
<b>30</b>	4	28.0	29.9	56.2	76.6	9.0	22.5	
	6		28.8	56.2	76.6	10.0	23.0	
<b>36</b>	6	34.0	28.7	57.7	79.5	10.5	26.0	
	8		27.3	57.7	79.5	11.5	27.0	
<b>42</b>	8	40.0	26.3	60.0	83.3	11.5	29.5	
	10		25.2	59.9	83.2	12.5	30.0	
<b>48</b>	8	46.0	29.2	61.2	86.7	11.5	32.5	
	10		28.1	61.1	86.6	12.5	33.0	

## Dimensions (IN)



Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.



## **R** Rosedale Fabricated Basket Strainers

Standard or Custom Design

Rosedale Fabricated Strainers are available in standard designs as shown, or can be custom designed and manufactured to fit your specific requirements. The standard strainer is designed and built in accordance with ASME Code Section VIII, Division 1. Available code designs include ANSI B 31.4, ANSI B 31.3, and ANSI B 31.8. Standard housing material is carbon steel, 304 stainless steel, or 316 stainless steel.


Rosedale Fabricated Strainers can be supplied in ANSI flange ratings. We have the design capabilities and manufacturing facilities to handle your straining requirements to 50 microns. Rosedale Fabricated Strainers are available in pipe sizes from 2" to 24".

For assistance designing a strainer to fit your application, please contact us.



**ABOVE: Model RBS Pipeline Strainer and basket**


**BELOW: Model BS Industrial Strainer with optional legs**




## INDEX

### F A B R I C A T E D   B A S K E T   S T R A I N E R S

#### MODEL RBS



#### MODEL BS



Model*	Line Size (Max.)	Dimensions (Inches)						Basket Surface Area (Sq. In.)	Basket Open Area (Sq. In.)	Open Area Ratio*	Volume Gallon
		A	B	C	D	E	Drain				
<b>4</b>	2	4 1/2	17	16	9	7	1	44	17.6	524%	0.20
<b>6</b>	3	6 5/8	20	20	11	9	1	99	39.6	536%	0.60
<b>8</b>	4	8 5/8	23	24	14	10	1 1/2	207	82.8	650%	1.25
<b>10</b>	6	10 3/4	26	29	17	12	1 1/2	330	132	457%	3.00
<b>12</b>	8	12 3/4	30	35	21	14	1 1/2	509	204	408%	4.50
<b>14</b>	10	16	34	42	25	17	1 1/2	792	317	402%	8.50
<b>16</b>	10	18	37	46	28	18	2	1034	414	366%	13.00
<b>18</b>	12	18	37	53	33	20	2	1232	493	358%	15.00
<b>22</b>	14	22	37	54	35	20	2	1528	611	400%	19.00
<b>24</b>	16	24	44	60	36	24	2	1885	754	413%	32.00
<b>30</b>	18	30	45	65	39	26	2	2073	829	355%	70.00
<b>36</b>	20	36	48	71	45	26	2	2512	1005	345%	110.0
<b>42</b>	24	42	56	95	64	31	2	4310	1724	406%	220.0
<b>48</b>	24	48	62	97	66	31	2	6781	2712	600%	260.0

\* Based on Standard Basket perforated 1/8" diameter holes on 3/16" centers.

\*\* Davit included on models 10-48.

Dimensions are reference only and should not be used for hard plumbing. Consult factory for certified drawings.

## How To Order

Build an ordering code as shown in the example

### Example:

**RBS - 12 - 6F - 150 - C - F - 80 - C**

#### SERIES

Pipeline = **RBS**  
Industrial = **BS**

#### MODEL (Max. Line Size)

4	(3)	= <b>4</b>
6	(4)	= <b>6</b>
8	(6)	= <b>8</b>
10	(8)	= <b>10</b>
12	(8)	= <b>12</b>
14	(10)	= <b>14</b>
16	(10)	= <b>16</b>
18	(12)	= <b>18</b>
22	(14)	= <b>22</b>
24	(16)	= <b>24</b>
30	(18)	= <b>30</b>
36	(20)	= <b>36</b>
42	(24)	= <b>42</b>
48	(24)	= <b>48</b>

#### PIPE SIZE, Flanged

**2F, 3F, 4F, 6F, 8F, 10F, 12F,  
14F, 16F, 18F, 20F, 24F**

#### FLANGE CLASS

**Series RPS: 150, 300, 600**

Flange/Class rating @ 100°F.

**Series BS: 150, 300**

Flange/Class rating @ 100°F.

#### ASME CODE STAMP

**C** = ASME Code Stamp

#### BASKET, MEDIA SIZE

Perforation diameters

**1/4, 3/16, 9/64, 3/32, 1/16**

Mesh sizes

**20, 30, 40, 50, 60, 70,  
80, 100, 150, 200**

#### COVER SEAL

**F** = Flexitalic (RBS Only)

**B** = Buna

**E** = Ethylene Propylene

**V** = Viton® Fluorelastomer

#### HOUSING MATERIAL

**C** = Carbon steel

**S** = 304 Stainless steel

**S316** = 316 Stainless steel

**Legs are Optional** depending on size of unit and application.

**Basket Removal Cable Hoist** is available as an option.

Please consult factory.



Model BS with basket removal cable hoist assembly.

## **R Duplex Bag Filters And Basket Strainers**

Trouble free, continuous operation

Duplex filters permit continuous operation, reducing overall operating costs. Flow can be switched back and forth between two filter vessels, allowing one side to be serviced while the other is in use.

The Rosedale duplex, using a single multi-ported valve operating system, is a better solution, and offers many benefits:

- Four separate valves are used all operated simultaneously by a single lever.
- Valves use the standard butterfly design, known for their effective seal, low pressure drop, and low cost.
- Any of the valves can be serviced individually, without need to disturb the other valves or piping. Replacements are readily available.
- Valves are soft-seated to provide bubble-tight closure.
- A variety of valve seal materials is available for use with a number of hard-to-handle fluids.
- Pressure drop is minimized because the flow path has the equivalent of only four elbows instead of the usual six.
- Mechanical stops assure that the valves are completely open or closed.
- A single-valve pressure balancing vent system is furnished to ease movement of the lever and to fill the just serviced vessel before use.
- Vents in filter covers and drain ports in filter housing speed evacuation and filling.
- Remotely operated power actuators and automatic power actuation (triggered by pressure differential sensing) are offered. Air or electric actuation is best if such power is available.





## Construction Materials

Available in carbon steel, 304 stainless steel, or 316 stainless steel.

Internal valve parts other than seals are 316 stainless steel.

Four different materials can be ordered for all seals involved.

All baskets and mesh linings are made of stainless steel. 304 stainless will be supplied with carbon and 304 housings, 316 stainless with 316 housings.

## Choosing a Basket Strainer or Bag Filter

Choose between straining a fluid (removing particles down to 74 micron size) and filtering it (removing particles down to 1 micron).

## Pressure Drop Data

Basket strainers and bag filters are usually selected so that the pressure drop does not exceed 2 psi, when they are clean. Higher pressure drops may be tolerated, when contaminant loading is low.

The pressure drop data are accurate for all housings with strainer or filter bag baskets. When filter bags are added, total pressure drop becomes the sum of the pressure drop as determined by the steps below plus the pressure drop through the bag as defined on pages 80-81.

### Follow these easy steps:

1. Using the desired pipe size and approximate flow rate, determine the basic pressure drop from the appropriate graph.
2. Multiply the pressure drop obtained in step 1 by the viscosity correction factor found in the accompanying table. This is the adjusted (clean) pressure drop for all baskets without filter bags.

**Note:** Filter bags are specified separately. See page 150.



	Viscosity, cps								
	1 (H <sub>2</sub> O)	50	100	200	400	600	800	1000	2000
All unlined baskets	.65	.85	1.00	1.10	1.20	1.40	1.50	1.60	1.80
40-mesh lined	.73	.95	1.20	1.40	1.50	1.80	1.90	2.00	2.30
60-mesh lined	.77	1.00	1.30	1.60	1.70	2.10	2.20	2.30	2.80
80-mesh lined	.93	1.20	1.50	1.90	2.10	2.40	2.60	2.80	3.50
100-mesh lined	1.00	1.30	1.60	2.20	2.40	2.70	3.00	3.30	4.40
200-mesh lined	1.30	1.70	2.10	3.00	3.40	3.80	4.40	5.00	6.80

## Selecting A Size

These descriptions and flow charts can aid in size selection. Capacities given are for each of the two vessels in any duplex system.

### Model 4—For flow rates to 50 gpm\*

- Pipe sizes 1, 2, or 3 inch, flanged
- Basket depth: 12 inches (nominal)

#### Basket Data

Depth (nominal, inches)	Diameter (inches)	Surface Area	Volume (cu. in.)
12	3.9	1.0	130

### Model 6—For flow rates to 100 gpm\*

- Delivers 3.4 square feet of basket or bag surface without need for ASME code construction.
- Can be fitted to hold cartridge filter elements
- Pipe sizes 1, 2, 3, or 4 inches (flanged).
- Two basket depths: 18, or 30 inches (nominal)

#### Basket Data




Depth (nominal, inches)	Diameter (inches)	Surface Area	Volume (cu. in.)
18	5	2.0	350
30	5	3.4	630

### Model 8—For flow rates to 220 gpm\*

- Can be fitted to hold cartridge filter elements
- Pipe sizes 2, 3, or 4 inch, flanged.
- Two basket depths: 15 or 30 inches (nominal)

#### Basket Data

Depth (nominal, inches)	Diameter (inches)	Surface Area	Volume (cu. in.)
15	6.7	2.3	500
30	6.7	4.4	1000







\*Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.



## Single-Basket Models (IN)

Model	Flange Size	A				B	B1 (Model 82 only)	C	D	F	G	H	I	J (Model 82 only)
		Basket Depths												
		12	15	18	30									
4	1	18				29.5		9	15	14	19	22.25	7.0	
	2	18				29.5		9	15	14	19	22.25	7.0	
	3	22.125				31.75		11	17	14	19	24.25	7.0	
6	1			25.75	37.75	34.75		9	15	18	20.5	24.25	10.0	
	2			25.75	37.75	34.75		9	15	18	20.5	24.25	10.0	
	3			27.75	39.625	37		11	17	18	20.5	26.25	10.0	
	4			27.625	39.625	41.5		13	18	18	20.5	31	10.0	
8	1		23.75		38.75	44.75	45.75	9	15	22	21.3	32.25	11.6	28.6
	2		23.75		38.75	44.75	45.75	9	15	22	21.3	32.25	11.6	28.6
	3		25.625		40.625	47	48	11	17	22	21.3	34.5	11.6	30.6
	4		25.625		40.625	49.5	50.5	13	18	22	21.3	37	11.6	30.6

The inlets and outlets on all duplex systems come standard in a horizontal configuration (facing opposite directions). The option of arranging the inlet and outlet is available in three positions, 90° apart. The system is designed with flanged tees, allowing the orientation to be changed in the field.



Duplex Models 4, 6, and 8

Duplex Model 82

## **R Duplex Bag Filters With Automatic Sequencing**

Continuous, uninterrupted operation is provided by these automatic duplex filters

When the filter bags on one side get to the point of requiring change-out, the incoming flow is automatically diverted to the clean filter bags on the other side. Maintenance personnel are alerted to the need to change the dirty filters so that the system will be ready for the next cycle.

### **Typical step-by-step operation**

1. As the filter bags in vessel A become so loaded with particulate that the differential pressure increases to a selected level, a switch actuates an air-operated valve in the loop pipe. This diverts a small flow of fluid to fill vessel B. After enough time to equalize the pressure in the two vessels, the four main valves are actuated by an air cylinder.
2. The duplex valve system shifts four valves at once, closing the inlet and outlet on vessel A and opening the two on vessel B.

An indicator light (and remote signal, if desired) shows that vessel B is now being utilized. Another light shows that the shift from one vessel to the other has occurred, and that filter bags need to be replaced. An electrical interlock prevents another shift cycle until the dirty filter bags have been replaced and the operator has pushed a reset button.

3. With the interlock released, the system is ready to cycle whenever the pressure differential again indicates the necessity.

### **Availability**

The automatic duplex valve system can be ordered on any Rosedale filter vessel. The standard multi-bag filter models are shown in the table.

The main inlet and outlet connections can be positioned to accommodate any flow direction within reason.

Systems are shipped assembled, ready for use, often on dollies or skids to assist putting them in place.


<b>Rosedale Model No. *</b>	<b>Number of bags</b>	<b>Nominal flow rate, gpm</b>
16	2	400
18	3	600
22	4	800
24	6	1200
30	8	1600
36	12	2000
42	17	3500
48	23	4500

\* Model number also indicates vessel diameter in inches.




### Models 16 through 48 – For flow rates to 4600 gpm

- Contain from 2 to 23 baskets
- Pipe sizes 2 through 12 inches, flanged
- Two basket depths: 15 or 30 inches (nominal) both 6.7 inches in diameter



### Multi-Basket Models (IN)



The inlets and outlets on all duplex systems come standard in a horizontal configuration (facing opposite directions). The option of arranging the inlet and outlet is available in three positions, 90° apart. The system is designed with flanged tees, allowing the orientation to be changed in the field.

Model Number	Number of Baskets	Basket Depth (nom.)	Surface Area (sq. ft.)	Flow Rate* (gpm)
16	2	30	8.8	400
18	3	30	13.2	600
22	4	30	17.6	800
24	6	30	26.4	1200
30	8	30	35.2	1600
36	12	30	52.8	2400
42	17	30	74.8	3400
48	23	30	101.2	4600

\*Based on housing only. Fluid viscosity, filter cartridge used, and expected dirt loading should be considered when sizing a filter.

Model (Dia.) A	Inlet/Outlet B	C	D	E	F	G	H
16	2	40.1	57.1	4.5	40.3	65.3	25.3
	3	42.5	59.5	5.3	42.5	67.5	30.3
	4	44.9	61.9	6.0	45.0	70.0	35.0
18	2	40.5	58.0	4.5	42.3	69.3	26.4
	3	42.9	60.4	5.3	44.5	71.5	31.4
	4	45.3	62.8	6.0	47.0	74.0	36.3
22	2	41.4	60.0	4.5	46.3	77.3	24.9
	3	43.9	62.4	5.3	48.5	79.5	28.4
	4	46.2	64.7	6.0	51.0	82.0	31.8
	6	50.4	69.0	7.0	54.3	85.3	37.8
24	2	41.7	60.7	4.5	50.3	83.3	24.1
	3	44.1	63.1	5.3	52.5	85.5	28.8
	4	46.5	65.5	6.0	55.0	88.0	34.1
	6	50.7	69.7	7.0	58.3	91.3	40.1
30	2	42.8	63.3	4.5	56.3	95.3	28.4
	3	45.2	65.7	5.3	58.5	97.5	30.4
	4	47.6	68.1	6.0	61.0	100.0	32.4
	6	51.9	72.4	7.0	64.3	103.3	44.4
	8	56.4	76.8	8.3	67.0	106.0	49.4
36	3	46.4	68.4	5.3	64.5	109.5	34.1
	4	48.8	70.8	6.0	67.0	112.0	36.1
	6	53.1	75.1	7.0	70.3	115.3	39.1
	8	57.6	79.6	8.3	73.0	118.0	41.1
	10	62.1	84.1	9.5	77.0	122.0	60.1
42	4	50.0	73.5	6.0	73.0	124.0	40.1
	6	54.3	77.8	7.0	76.3	127.3	43.1
	8	58.8	82.3	8.3	79.0	130.0	45.1
	10	63.3	86.8	9.5	83.0	134.0	49.1
	12	68.0	91.5	11.0	86.0	137.0	69.1
48	4	51.0	76.0	6.0	79.0	136.0	44.5
	6	55.4	80.4	7.0	82.3	139.3	47.5
	8	60.0	85.0	8.3	85.0	142.0	49.5
	10	64.4	89.4	9.5	89.0	146.0	53.5
	12	69.2	94.2	11.0	92.0	149.0	55.5



## How To Order

Build an ordering code as shown in the example.

Housing		Options		OPTIONAL INNER BASKET	AUTOMATIC DUPLEX CONTROL OPTIONS
<b>Example:</b>	<b>D16 -30- 4F-1-150-C-B-S-M-200-DPG-D-C- 2M-50- EP</b>				
<b>MODEL</b> Duplex Style = <b>D</b> Automatic Duplex = <b>AD</b>					
<b>MODEL NO.</b> 4 = <b>4</b> 6 = <b>6</b> 8 = <b>8</b> 16 = <b>16</b> 18 = <b>18</b> 22 = <b>22</b> 24 = <b>24</b> 30 = <b>30</b> 36 = <b>36</b> 42 = <b>42</b> 48 = <b>48</b> 82 = <b>82</b>					
<b>BASKET DEPTH</b> 12-in. = <b>12</b> 15-in. = <b>15</b> 18-in. = <b>18</b> 30-in. = <b>30</b>					
<b>CONNECTION SIZES, FLANGED<sup>1</sup></b> 1-in. (Models 4 thru 48) = <b>1F</b> 2-in. (Models 4 thru 48) = <b>2F</b> 3-in. (Models 4 thru 48) = <b>3F</b> 4-in. (Models 6 thru 48) = <b>4F</b> 6-in. (Models 22 thru 48) = <b>6F</b> 8-in. (Models 30 thru 48) = <b>8F</b> 10-in. (Models 36 and 48) = <b>10F</b> 12-in. (Models 42 and 48) = <b>12F</b>					
<b>OUTLET STYLE</b> Standard = <b>1</b>					
<b>PRESSURE RATINGS<sup>2</sup></b> 150psi (flanged) = <b>150</b>					
<b>CONSTRUCTION MATERIAL</b> Carbon steel = <b>C</b> 304 stainless steel = <b>S</b> 316 stainless steel = <b>S316</b>					
<b>COVER SEAL</b> Buna N = <b>B</b> Ethylene Propylene = <b>E</b> Viton® = <b>V</b> Teflon® Encapsulated Viton® = <b>TEV</b> Teflon® (solid white) = <b>TSW</b>					
<b>BASKET SEAL</b> No Seal (never on Model 4, 6, or multi-bag filters) = <b>N</b> Seal wanted (always on Model 8 bag filters) = <b>S</b>					
					<b>AUTOMATIC DUPLEX CONTROL OPTIONS</b> <b>EP</b> = Electric controller/Pneumatic actuators <b>EE</b> = Electric controller/Electric actuators <b>PP</b> = Pneumatic controller/Pneumatic actuators <b>JB</b> = Junction Box  <b>OPTIONAL INNER BASKET, MEDIA SIZE. No symbol if type 2B basket was selected</b> Perforation diameters (for type 2P baskets) <b>1/4, 3/16, 9/64, 3/32, 1/16</b> Mesh sizes (for type 2M and 2BM baskets) <b>20, 30, 40, 50, 60, 70, 80, 100, 150, 200</b>  <b>OPTIONAL INNER BASKET TYPE</b> <b>2PB</b> = Filter bag basket, 9/64 perforations <sup>3</sup> <b>2P</b> = Strainer basket, perforated metal <b>2BM</b> = Filter bag basket, perforated, mesh lined <sup>3</sup> <b>2M</b> = Strainer basket, perforated, mesh lined  <b>ASME CODE STAMP</b> <b>C</b> = Code Stamp  <b>DISPLACER</b> <b>D</b> = Displacer  <b>DIFFERENTIAL PRESSURE GAUGE</b> <b>DPG</b> = Gauge System <b>DPS</b> = Switch  <b>BASKET, MEDIA SIZE</b> <b>No symbol if type B basket was selected</b> Perforation diameters (for type P baskets) <b>1/4, 3/16, 9/64, 3/32, 1/16</b> Mesh sizes (for type M and BM baskets) <b>20, 30, 40, 50, 60, 70, 80, 100, 150, 200</b>  <b>BASKET TYPE</b> <b>PB</b> = Filter bag basket, 9/64 perforations <sup>3</sup> <b>P</b> = Strainer basket, perforated metal <b>BM</b> = Filter bag basket, perforated, mesh lined <sup>3</sup> <b>M</b> = Strainer basket, heavywire mesh <sup>3</sup>

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME housings.
2. Higher pressure ratings available. Consult factory.
3. Filter bags are ordered separately. See page 150.

## **R Automatic Backwashing Filtration System**

There are many advantages to our Automatic Backwashing Systems.

- Reduces process/system downtime
- Reduces operator exposure
- Reduces maintenance cost
- Reduces waste fluid
- Reduces filter element disposal and replacement cost
- Increases productivity

Self-cleaning filters represent the ideal situation and provide the most productive and labor free solution. Rosedale Products' ABW is unique because our patented technology backwashes with the lowest volume of liquid. This is achieved by using air to create the shear velocity needed to effectively clean the filter with the clean liquid inside each housing chamber.

### **Flexible and Versatile**

Flow rates to several thousand GPM can be easily accommodated. To meet space requirements various configurations are available. Micron ratings from 2 microns are possible in sintered porous metal, wedge wire, and nylon filter bags. Continuous flow is maintained by taking one station off line while the rest continue operating.

### **Single vs Dual Stations**

On systems with flow rates less than 400 GPM our standard is "single station" systems which means each housing is a station. Larger systems use a "dual station" approach which has two housings per station. The two housings share a common manifold which allows a reduction in valves and, during backwash, two housings at a time (1 Dual Station) go off-line for cleaning.



### **Applications**

The ABW is being used in many industries throughout the USA as well as overseas in such places as Argentina, Taiwan, Chile and Venezuela.

**Industries served include:** Automotive - Steel - Petroleum - Chemical - Pharmaceutical - Electronics - Nuclear Power - Superfund Sites - Groundwater & Soil Remediation - Commercial Laundries - Entertainment - Food - Mining - Detergents - Paper

**Applications include:** Cooling Towers - Coolants - Membrane Protection - Sulfuric and other Acids - Harvesting Steroids - Oil Reclamation - Potable & DI Water - Bottling Plants - Food Processing - Recycling - Decorative Ponds

### **Turnkey Systems**


Our systems have included air compressors, pumps, power distribution boxes, motor starters, climate controlled enclosures, heat trace and air dryers, all skid mounted and ready for installation.






## How It Works

Fluid is introduced through the bottom of the filter housing. It is then forced through a filter element where the contaminant is captured on the outside surface of the filter. The clean fluid exits through the outlet. A controller monitors the differential pressure across the filter. When enough contaminant collects on the element and the differential pressure reaches a pre-selected point ( $\Delta P$ ), the backwash sequence is initiated. The backwash is accomplished by automatically shocking the filter with air and forcing the dirty fluid through the waste outlet. There is no introduction of additional fluids to contaminate the process, and the volume of liquid discharged is held to a minimum, reducing disposal costs. When the backwash operation is completed, the system returns on-line, the controller resets itself, and the whole process begins again.



## Media Characteristics

This information is intended to be used as a general guideline. Since some characteristics are very similar from one media to the next, you should choose the media whose advantages best fit your particular filtration requirements. Consult Rosedale for assistance in selecting the proper media for your application.




**Wedge Wire (W/W)** or slotted, is the most durable of all backwashable media. They are strictly limited to .001" slot or 25 micron as the lowest retention rating. Wedge wire is particularly suited for critical low maintenance applications. As a result of their construction, they are used in many instances where manual cleaning is necessary but might damage other types of media.

MICRON RATING	OPENING (INCH)	% OF OPEN AREA
25	.001	2.1
50	.002	4.2
75	.003	6.1
150	.006	11.5
250	.010	18.0
350	.014	23.0



**Poroplate®** filter media is made from layers of stainless steel wire cloth diffusion-bonded together to form a rigid porous metal laminate structure. Poroplate filter media is corrosion resistant, cleanable, and can withstand high temperature applications up to 800°F. Micron ratings from 2 to 150 are available.

MICRON RATING	NOMINAL RATING	ABSOLUTE RATING
10	2μ	10μ
25	10μ	20μ
50	20μ	40μ
75	40μ	70μ
100	100μ	100μ
150	150μ	150μ



**Nylon** monofilament provides exceptional backwash efficiency. It exhibits a wide range of retention ratings. Nylon media should be considered for the filtration ranges of 25-75 microns. Filter bags have a defined cycle life.

MICRON RATING	% OF OPEN AREA
75	43
50	36
25	33



# How To Order

Build an ordering code as shown in the example

**Example:** **ABW 8-30-D-2F-1-4-S-150-S-E-B-B-25-E-C**

**AUTO BACKWASHING FILTER**

**MODEL NUMBER**  
8 = 8

**BASKET DEPTH**  
30-inch (std.) = 30

**STATION TYPE**  
Single = S  
Dual = D

**VALVE SIZE**  
2-inch 150 class ANSI flange = 2F  
3-inch 150 class ANSI flange = 3F  
4-inch 150 class ANSI flange = 4F

**NUMBER OF STATIONS**  
One = 1  
Two = 2  
Three = 3  
Four = 4  
Five = 5  
Six = 6  
Seven = 7  
Eight = 8  
Nine = 9  
Ten = 10

**HEADER PIPE SIZE**  
2-inch = 2  
3-inch = 3  
4-inch = 4  
6-inch = 6  
8-inch = 8  
10-inch = 10  
12-inch = 12

**ASME CODE STAMP**  
C = Code

**CONTROL SYSTEM**  
E = Electric

**MICRON RATING**  
10 = 10    100 = 100  
25 = 25    150 = 150  
50 = 50    250 = 250  
75 = 75    350 = 350

**MEDIA**  
WW = Wedge wire  
PS = Sintered  
B = Bag style

**VALVE SEATS**  
B = Buna-N  
M = Ethylene propylene  
T = Teflon®  
V = Viton®

**COVER SEAL**  
B = Buna N  
E = Ethylene Propylene  
V = Viton® Fluoroelastomer  
TEV = Teflon® Encapsulated Viton®  
TSW = Teflon® (solid white)

**HOUSING MATERIAL**  
C = Carbon Steel  
S = 304 Stainless Steel  
S316 = 316 Stainless Steel


**PRESSURE RATING**  
150 = 150 psi (NPT or flanged)

**HEADER PIPE STYLE**  
S = Single sided  
D = Double sided

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges.  
ANSI B1 6.5 Pressure-Temperature rating tables determine flange class for ASME housings.

2. Higher pressure ratings available. Consult factory.

3. Filter bags are ordered separately. See page 150.



## Stations and Headers

Rosedale offers both single and double-sided headers to conform to space restrictions. Header pipes have connections on one or on both sides. Each housing is separately controlled, increasing capacity while maintaining a high-level of control. A station has one set of controls, while accepting either one filter housing per station (a single station), or two housings per station (a dual station). Capacity is again increased, but the number of controls are minimized. By minimizing those controls, great savings are realized. For example, everything else being equal, a single-sided header with three dual-stations accommodates the same six housings and flow as a double-sided header with six single-single stations. However, there are three less controls on the dual-station unit, greatly reducing costs, perhaps as much as \$15,000.

## **Multiplex Filters and Strainers From Rosedale Products**

These high-capacity filters and strainers require no flow interruption for servicing

- For use with filter bags for filtering to as fine as one micron, or with perforated strainer baskets
- From 2 to 10 Model 8 housings are mounted in parallel to inlet and outlet manifolds
- Each unit has inlet and outlet valves, gage ports, and a drain port, to permit servicing one at a time
- These are completely packaged free-standing systems in carbon steel and stainless steel

See page 12 for more details on the Model 8 housings used.




**Standard Model 8 Triplex**



**Special Multi-Bag Multiplex**

### **Dimensions (IN)**



No. of Units	A	B	Inlet-Outlet Header Size	Valve Size	C	D	E
2	40	30	3	2	14.9	45.9	5.5
3	45	15	3	3	15.1	46.4	5.5
4	60	30	3	4	N/A	N/A	N/A
5	75	45	4	2	15.7	46.7	6.0
6	90	60	4	3	15.8	47.1	6.0
7	105	75	4	4	17.2	48.7	6.0
8	120	90	5	2	16.7	47.7	7.1
9	135	105	5	3	16.8	48.1	7.1
10	150	120	6	4	18.2	49.7	7.1
			8	2	17.9	48.9	8.1
			8	3	18.1	49.4	8.1
			8	4	19.4	50.9	8.1

Build an ordering code as shown in the example



## **R Solids/Liquids Separators**

### In-Line Separators for Industrial Applications

Use our centrifugal-action separator to remove grit, sand, metal chips, fines, and other solids from liquids. Perfect for use as a pre-filter to extend the life of fine filtration systems. These units require little or no maintenance, as there are no moving parts to wear out, or filter media to replace. The unit only requires a simple purging, eliminating downtime. For flows from 6 gpm and retention ratings to 50 micron.

#### How it works:

Fluid enters the pressure vessel tangentially at high velocity. A centrifugal action is created, which forces the solids to separate and enter the sump, while the clean liquid exits up through the standpipe. The solids collect in the sump, and can easily be purged. The operation is so simple, it can be set to automatically purge on a timed interval.



#### Features

- Low constant pressure drops
- Piped housings
- Carbon steel or stainless steel (304 or 316) construction for housings
- All housings are electropolished to resist adhesion of dirt and scale
- ASME code stamp available
- Pipe sizes 3/8 through 10-inch (larger sizes also available)


#### Options

- Different outlet connections
- Special materials

#### Typical Applications



- Cooling towers
- Process water
- Food processing
- Chemical processing
- Well water
- Pulp & paper mills
- Mining operations
- Steel mills
- Petrochemical industry
- Power plants
- Protection of spray nozzles and other small orifices
- Chip removal from cutting coolants
- Car and vehicle wash systems
- Paint spray booths
- Heat exchangers
- Spray nozzle protection
- Industrial laundries
- Solids recovery
- Parts washing systems
- Pump protection
- Domestic Water
- Recirculating cooling water
- Sprinkler systems
- Quench water
- Pre-filter for seawater

FLOW RANGE – GPM					
Model No.	Pipe Size (inch)	5 PSID	10 PSID	Inlet/Outlet	Drain Size (inch)
SEP-6	3/8	3	6	NPT	1
SEP-11	1/2	7	11	NPT	1
SEP-25	3/4	15	25	NPT	1
SEP-35	1	30	40	NPT	1
SEP-75	1-1/4	55	75	NPT	1
SEP-80	1-1/2	60	80	NPT	1
SEP-130	2	90	130	NPT	1
SEP-140	2-1/2	96	140	NPT	1
SEP-275	3	200	275	NPT or Flanged	1
SEP-553	4	425	553	Flanged	2
SEP-1265	6	985	1265	Flanged	2
SEP-2210	8	1715	2210	Flanged	2
SEP-3410	10	2640	3410	Flanged	2



#### Specific Gravity of Various Materials

Material	Specific Gravity	Material	Specific Gravity
Aluminum	2.7	Graphite	2.3
Ashes (Coal)	2.0	Iron	7.8
Brass	9.0	Lead	11.3
Bronze/Copper	8.9	Limestone	2.8
Carbon/Concrete/Lava	1.8-2.5	Manganese	7.4
Coal (Anthracite)	1.3-1.9	Nickel	8.9
Earth (Silt/Soil)	1.2-2.0	Sand/Silica/Shale	2.6-2.8
Glass (Crystal)	3.0	Steel	7.8
Granite/Gravel	2.5-3.0	Tin Ore	6.4-7.0



#### Separator Sizing:

Separators are generally sized so that there is at least a 5 PSID pressure drop across the unit. Separation efficiency increases as pressure drop increases. We've shown flow ranges for each unit based on 5 and 10 PSID. Choose a unit based on a flow/efficiency balance.

## Installation

The Separator should be installed in a near vertical position. The unit should be supported by means other than the inlet/outlet piping. First, connect the outlet of the unit to the outlet piping. Then install any supports, such as U-bolts or legs. Next, connect the inlet piping to the inlet. Test for leaks and separation. The unit is now ready for operation.

## Purging and Maintenance


Separators must be purged regularly. If they are not, the separated solids will accumulate and overflow the collection area, affecting performance and contaminating effluent.

You can manually, automatically, or continuously purge the collection area of the separator. Manual purging requires that the operator open a simple valve and empty the contents. Automatic purging can be done many different ways, but the simplest is setting a timer to open and close the valve, purging the contaminant on a regular basis. Continuous purging simply requires leaving a manual valve partially open at all time, letting the contaminant leak out at a controlled rate. For best results, all purging should be done while the separator is in operation. Avoid purging “uphill” which will result in buildup and clogging, affecting performance and operation.

Simple rules of maintenance include checking the purge valve regularly for clogging, scale, and buildup. If the unit is installed in an area where the ambient temperature is below freezing, the collection area and all purge piping should be kept from freezing while operating. If left in idle state under freezing conditions, the entire unit must be drained of liquid, and the collection area must be purged of solids.

## Dimensions (IN)

Model	A	B	C	D	E
<b>SEP-6</b>	3.0	14.8	4.5	1.9	.6
<b>SEP-11</b>	3.0	14.8	4.5	1.9	.6
<b>SEP-25</b>	4.5	17.2	8.6	3.5	1.1
<b>SEP-35</b>	4.5	23.6	8.6	3.5	1.1
<b>SEP-75</b>	4.5	23.5	8.6	4.5	1.4
<b>SEP-80</b>	4.5	23.5	8.6	4.5	1.3
<b>SEP-130</b> (2")	4.8	22.6	8.6	6.6	2.1
<b>SEP-140</b> (2.5")	6	22.6	8.6	6.6	1.9
<b>SEP-275</b>	6.6	25.2	10.7	8.6	2.6
<b>SEP-553</b>	13.	45.2	18.0	12.7	4.1
<b>SEP-1265</b>	16.4	58.0	24.0	16.0	4.7
<b>SEP-2210</b>	21.0	67.2	24.0	16.0	4.7
<b>SEP-3410</b>	21.7	105.6	42.0	30.0	8.0







## How To Order

Build an ordering code as shown in the example

EXAMPLE: <b>SEP-275-3P-150-C-C-APV</b>		Options
<b>MODEL NO. AND FLOW RATE</b>		<b>OPTION</b>
6 GPM = <b>SEP-6</b>		<b>APV</b> = Optional APV Automatic
11 GPM = <b>SEP-11</b>		<b>P</b> = Manual purge valve
25 GPM = <b>SEP-25</b>		Leave blank for no purge valve
35 GPM = <b>SEP-35</b>		
75 GPM = <b>SEP-75</b>		<b>ASME CODE STAMP</b>
80 GPM = <b>SEP-80</b>		<b>C</b> = Code
130 GPM = <b>SEP-130</b>		
140 GPM = <b>SEP-140</b>		<b>HOUSING MATERIAL</b>
275 GPM = <b>SEP-275</b>		<b>C</b> = Carbon Steel
553 GPM = <b>SEP-553</b>		<b>S</b> = 304 Stainless Steel
1265 GPM = <b>SEP-1265</b>		<b>S316</b> = 316 Stainless Steel
2210 GPM = <b>SEP-2210</b>		
3410 GPM = <b>SEP-3410</b>		<b>PRESSURE RATING<sup>2</sup></b>
		<b>150</b> = 150 PSI (NPT or Flanged)
<b>PIPE SIZE, NPT, FLANGED<sup>1</sup></b>		
3/8-inch NPT = <b>3/8P</b> (SEP Model 6)		
1/2-inch NPT = <b>1/2P</b> (SEP Model 11)		
3/4-inch NPT = <b>3/4P</b> (SEP Model 25)		
1-inch NPT = <b>1P</b> (SEP Model 35)		
1-1/4-inch NPT = <b>1-1/4P</b> (SEP Model 75)		
1-1/2-inch NPT = <b>1-1/2P</b> (SEP Model 80)		
2-inch NPT = <b>2P</b> (SEP Model 130)		
2-1/2-inch NPT = <b>2-1/2P</b> (SEP Model 140)		
3-inch NPT = <b>3P</b> (SEP Model 275)		
3-inch Flanged = <b>3F</b> (SEP Model 275)		
4-inch Flanged = <b>4F</b> (SEP Model 553)		
6-inch Flanged = <b>6F</b> (SEP Model 1265)		
8-inch Flanged = <b>8F</b> (SEP Model 2210)		
10-inch Flanged = <b>10F</b> (SEP Model 3410)		

**NOTE:**

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.
2. Higher pressure ratings are available. Consult factory.



**THE  
INDICATING  
FILTER**  


## **Model 4-8 Indicating Bag Filters**

Intelligent, mechanically actuated, Indicating Filters. Filters that tell the whole story.

These filters will let you know when your filter bag needs attention. This allows you to maximize the efficiency of your operations and reduce system downtime by changing filters only when they really need it. You'll save time, money and effort, because you'll use each bag to its maximum capacity, since change-out will be based on the remaining life of the bag, not on someone's best guess.


### **New Features**

- Integral Differential Pressure Indicator (non-clogging)
- Electric Micro Switch included - 3-wire or 4-wire
- Electric Switch has dual actuation (one for **requires attention soon** and one for **requires immediate attention**)
- Optional explosion-proof Pneumatic Switch
- Optional Digital Model available

### **Features**

- Low pressure drops
- Permanently piped housings are opened without disturbing the piping or requiring tools
- Covers are O-ring sealed
- Carbon or stainless (304 or 316) steel housings
- Housings are electropolished to resist adhesion of dirt and scale
- Large-area, heavy-duty baskets
- O-ring seals: Buna N, EPR, Viton® fluorelastomer, and Teflon® fluorocarbon resin
- Two pressure ratings-150 and 300 psi
- Indicating device is mechanical, no tubes or orifices to clog






Most differential pressure indicators use a piston connected through a small hole in the side of the filter. This hole could clog, or the piston could easily be blocked or restricted. Rosedale's piston is much larger in diameter and surface area, requiring a greater blockage to restrict it, and since it is inside the housing, there is no outside hole to clog. It produces a cleaner, more accurate and reliable unit, providing excellent performance and value.

	Standard	Rosedale Model 4
Piston Diameter	.38	4.38
(F=P X A) Force Exerted @ 15 psi	1.65 lbs. of force	225.00 lbs. of force



### As Amount Of Trapped Dirt Increases, Pressure Drop Increases, And The Remaining Life Of The Filter Decreases

That's right, as the pressure drop across your filter increases, additional dirt-holding capacity decreases. As the chart illustrates, at a 5 psi drop in pressure, over 90 percent of the filter's dirt-holding capacity has been reached. When the pressure drop has increased to 10 psid, it has reached 95 percent of its total dirt-holding capacity. For each additional 5 psi pressure drop, the amount of extra dirt retained decreases dramatically. As a matter of fact, pressure drops greater than 15 psi retain no appreciable amount of additional dirt. Our line of indicating filters automatically and intelligently sense these pressure differences, and will indicate when the optimum time to change the filter element in your system, saving you time, money and effort.





## How To Order

Build an ordering code as shown in the example.


	Housing	Options
<b>Example:</b>	<b>IND - 4 12 - 1P - 1 - 300 - C - B - BM - 200</b>	
<b>MODEL NO.</b> IND-4 = <b>4</b>		
<b>HOUSING SIZE</b> 12 inch = <b>12</b>		
<b>PIPE SIZE, NPT &amp; FLANGED</b> 3/4-inch, female NPT = <b>3/4P</b> 1-inch, female NPT = <b>1P</b> 3/4-inch, 150 class ANSI flange = <b>3/4F</b> 1-inch, 150 class ANSI flange = <b>1F</b> 1-1/4-inch 150 class ANSI flange = <b>1-1/4F</b> 1-1/2-inch, 150 class ANSI flange = <b>1-1/2F</b> 2-inch, 150 class ANSI flange = <b>2F</b>		
<b>OUTLET STYLE</b> Bottom = <b>1</b> Side = <b>2</b> Bottom Elbow = <b>3</b>		
<b>PRESSURE RATING<sup>1</sup></b> 150 psi (NPT or flanged) = <b>150</b> 200 psi (NPT Only) = <b>200</b> 300 psi (NPT or flanged) = <b>300</b>		
<b>HOUSING MATERIAL</b> Carbon steel = <b>C</b> 304 Stainless steel = <b>S</b> 316 Stainless steel = <b>S316</b>		
		<b>BASKET MEDIA SIZE</b> No symbol if type B basket was selected Perforation diameters (for type P baskets) 1/4, 3/16, 9/64, 3/32, 1/16 <b>Mesh sizes</b> (for type M and BM baskets) 20, 30, 40, 50, 60, 70, 80, 100, 150, 200  <b>BASKET TYPE<sup>2</sup></b> <b>PB</b> = Filter bag basket, 9/64 perforations <b>P</b> = Strainer basket, perforated metal <b>BM</b> = Filter bag basket, perforated, mesh-lined <b>M</b> = Strainer basket, perforated, mesh-lined <b>HWM</b> = Filter bag basket, heavy wire mesh  <b>COVER SEAL</b> <b>B</b> = Buna N <b>E</b> = Ethylene Propylene <b>V</b> = Viton® Fluoroelastomer <b>TEV</b> = Teflon® Encapsulated Viton® <b>TSW</b> = Teflon® (solid white)

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. ANSI B16.5 Pressure Temperature rating tables determine flange class for ASME code housings. Consult factory.
2. Higher pressure ratings available. Consult factory.
3. Filter bags are specified separately. See page 150.

### Dimensions (IN)

Model	Pipe Size	A	B	C	D	E
4-12	3/4	15.5	17.4	15.8	4.0	2.0
	1	15.7	17.4	16.2	4.0	2.5
	1-1/4	15.7	18.0	16.6	4.0	2.9
	1-1/2	15.6	18.0	16.9	4.0	3.3
	2	15.6	18.0	17.6	5.0	4.0

### Dimensions (IN)





## How To Order

Build an ordering code as shown in the example.

**Example:**      **Housing**      **Options**  
**IND - 8 30 - 2P - 1 - 150 - C - B - BM - 200**

**MODEL NO.**

IND-8 = **8**

**HOUSING SIZE**

30 inch = **30**

**PIPE SIZE, NPT & FLANGED<sup>1</sup>**

2-inch, female NPT = **2P**

3-inch, female NPT = **3P**

2-inch, 150 class ANSI flange = **2F**

3-inch, 150 class ANSI flange = **3F**

**OUTLET STYLE**

Bottom = **1**

Side = **2**

Bottom Elbow = **3**

**PRESSURE RATING<sup>2</sup>**

150 psi (NPT or flanged) = **150**

300 psi (NPT or flanged) = **300**

**HOUSING MATERIAL**

Carbon steel = **C**

304 Stainless steel = **S**

316 Stainless steel = **S316**

**BASKET MEDIA SIZE**

No symbol if type B basket was selected

Perforation diameters (for type P baskets) 1/4, 3/16, 9/64, 3/32, 1/16

**Mesh sizes** (for type M and BM baskets) 20, 30, 40, 50, 60, 70, 80, 100, 150, 200

**BASKET TYPE<sup>3</sup>**

**PB** = Filter bag basket, 9/64 perforations

**P** = Strainer basket, perforated metal

**BM** = Filter bag basket, perforated, mesh-lined

**M** = Strainer basket, perforated, mesh-lined

**HWM** = Filter bag basket, heavy wire mesh

**COVER SEAL**

**B** = Buna N

**E** = Ethylene Propylene

**V** = Viton® Fluoroelastomer

**TEV** = Teflon® Encapsulated Viton®


**TSW** = Teflon® (solid white)

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. ANSI B16.5 Pressure Temperature rating tables determine flange class for ASME code housings. Consult factory.
2. Higher pressure ratings available. Consult factory.
3. Filter bags are specified separately. See page 150.

### Dimensions (IN)

Model	Pipe Size	A	B	C	D	E	F	G
8-30	2	5.9	7.5	35.8	38.1	37.8	5.0	4.06
	3	6.7	7.5	36.3	38.4	39.2	7.25	6.12
	4	6.8	8.6	36.3	38.9	40.6	9.0	7.75

### Dimensions (IN)



## **R Convertible Filter Housings Use Either Bags or Cartridges**

You can switch from one to the other instantly

The emergence of new, more effective filter bag materials has challenged the popular filter cartridge. Filter bags are now an attractive, economical alternative to cartridges in many applications. Bags cost less, are easier to install and remove, and require less room in storage and disposal.

The convertible filter housings from Rosedale offer you the ability to use filter bags in place of cartridges without burning your bridges behind you. You can always change back to cartridges, for whatever reason.

### **Features**


- Permanently piped housings—no repiping necessary for change-over
- Covers are O-ring sealed
- Designed for standard double open-end type cartridges. Can also be supplied adapted to other cartridge-end configurations
- Carbon steel, 304 or 316 stainless steel construction for housing
- All housings are electropolished to resist adhesion of dirt and scale
- ASME code stamp is available
- Adjustable-height legs are included
- V-post spring seal for both options are in 316 stainless steel

### **Options**

- Filter bag hold-down devices
- Sanitary construction
- Different outlet connection
- Higher pressure ratings
- Extra-length legs
- Heat jacketing
- Duplex units

### **Flow Rates**


Rosedale's convertible filter housings are offered in two diameters to hold 3 and 5 cartridges, respectively. The 3-cartridge housings are nominally rated at 70 gpm\*. The 5-cartridge Series housings are nominally rated at 100 gpm\*. These ratings are governed by the restrictive openings in the cartridge support plate. They do not take into account the pressure drops imposed by the bags or cartridges used.



Pictured is a Model 6330. It can hold three 30-in. long cartridges (shown inserted) or a filter bag and support basket (at left). The two 3/4-in. ports at the bottom of the housing are 1) a dirty liquid drain (upper port), and 2) a clean liquid drain (lower port). The dirty liquid drain need not be used when filter bags are employed; if bags are properly removed, no dirt washes off downstream. (The use of a liquid displacer makes this easier to do.)

\*30-inch cartridge

## Dimensions (IN)



## Dimensions (IN)

Model	Pipe Size	A	A1	B	C	D	E	F	G	H	I	J
<b>6320</b>	1	6.3	2.5	4.3	6.0	26.3	28.5	21.0	26.8	4.6	22.8	5.0
	1-1/4	6.3	2.5	4.3	6.0	26.3	28.5	21.0	27.2	4.6	22.8	5.0
	1-1/2	6.3	2.5	4.3	6.0	26.3	28.5	21.0	27.6	4.6	22.8	5.0
	2	7.1	3.4	4.3	6.0	25.4	28.5	19.5	27.4	5.8	22.8	5.0
	3	7.1	3.4	4.3	6.0	25.6	28.5	19.0	28.7	5.8	22.8	7.3
<b>6330</b>	1	6.3	2.5	4.3	6.0	36.3	38.5	31.0	36.8	4.6	32.8	5.0
	1-1/4	6.3	2.5	4.3	6.0	36.3	38.5	31.0	37.2	4.6	32.8	5.0
	1-1/2	6.3	2.5	4.3	6.0	36.3	38.5	31.0	37.6	4.6	32.8	5.0
	2	7.1	3.4	4.3	6.0	35.4	38.5	29.5	37.4	5.8	32.8	5.0
	3	7.1	3.4	4.3	6.0	35.8	38.5	29.0	38.7	5.8	32.8	7.3
<b>8520</b>	3/4	7.75	4.0	5.3	7.5	30.0	32.3	30.3	4.8	25.8	5.0	1.9
	1	7.75	4.0	5.3	7.5	30.0	32.3	30.6	4.8	25.8	5.0	2.5
	1-1/4	7.75	4.0	5.3	7.5	30.0	32.3	31.0	4.8	25.8	5.0	2.9
	1-1/2	7.75	4.0	5.6	7.5	30.0	32.3	31.4	4.8	25.8	5.0	3.3
	2	7.75	4.0	5.88	7.5	30.0	32.3	32.1	4.8	25.8	5.0	4.0
	3	7.75	4.0	6.7	7.5	30.6	31.8	33.5	6.5	25.8	7.3	6.1
<b>8530</b>	3/4	7.75	4.0	5.3	7.5	42.3	42.3	40.3	4.8	35.8	5.0	1.9
	1	7.75	4.0	5.3	7.5	42.3	42.3	40.6	4.8	35.8	5.0	2.5
	1-1/4	7.75	4.0	5.3	7.5	42.3	42.3	41.0	4.8	35.8	5.0	2.9
	1-1/2	7.75	4.0	5.6	7.5	42.3	42.3	41.4	4.8	35.8	5.0	3.3
	2	7.75	4.0	5.88	7.5	42.3	42.3	42.1	4.8	35.8	5.0	4.0
	3	7.75	4.0	6.7	7.5	41.8	41.6	43.5	6.5	35.8	7.3	6.1

## How To Order

Build an ordering code as shown in the example.

Each option is available only on the model series indicated in the colored blocks preceding its description.

### Key To Blocks

**6** = Series 6300  
**8** = Series 8500

**Example:** **6330 -1P-1-150 - C - B - N - BM 200-D-C**

#### HOUSING SIZE/CAPACITY

- 6** Three 20-in. cartridges or one 5.6-in. dia. x 21-in. bag = **6320**
- 6** Three 30-in. cartridges or one 5.6-in. dia. x 32-in. bag = **6330**
- 8** Five 20-in. cartridges or one 7-in. dia. x 16.5-in. bag = **8520**
- 8** Five 30-in. cartridges or one 7-in. dia. x 32-in. bag = **8530**

#### PIPE SIZE, NPT & FLANGED<sup>1</sup>

- 6** **8** 3/4-in. female NPT = **3/4P**
- 6** **8** 1-in. female NPT = **1P**
- 6** **8** 1-1/4-in. female NPT = **1-1/4P**
- 6** **8** 1-1/2-in. female NPT = **1-1/2P**
- 6** **8** 2-in. female NPT = **2P**
- 6** **8** 3-in. female NPT = **3P**
- 6** **8** 3/4-in. 150 class ANSI flange = **3/4F**
- 6** **8** 1-in. 150 class ANSI flange = **1F**
- 6** **8** 1-1/4-in. 150 class ANSI flange = **1-1/4F**
- 6** **8** 1-1/2-in. 150 class ANSI flange = **1-1/2F**
- 6** **8** 2-in. 150 class ANSI flange = **2F**
- 6** **8** 3-in. 150 class ANSI flange = **3F**

#### OUTLET STYLE

- 6** **8** Bottom = **1**
- 6** **8** Bottom elbow = **3**

#### PRESSURE RATING<sup>2</sup>

- 8** 150 psi (NPT and flanged) = **150**
- 6** 300 psi (NPT and flanged) = **300**

#### HOUSING MATERIAL

- 6** **8** Carbon steel = **C**
- 6** **8** 304 stainless steel = **S**
- 6** **8** S316 stainless steel = **S316**

#### ASME CODE STAMP

- 6** **8** **C** = Code

#### DISPLACER<sup>3</sup>

- 6** **8** **D** = Displacer

#### BASKET MEDIA SIZE

No symbol if type B basket was selected

- 6** **8** Perforations diameters (for type P baskets)  
**1/4, 3/16, 9/64, 3/32, 1/16**
- 6** **8** Mesh sizes (for type M and BM baskets)  
**20, 30, 40, 50, 60, 80, 100, 150, 200**

#### FILTER BAG BASKET<sup>4</sup>

- 6** **8** **PB** = Filter bag basket, 9/64 perforations<sup>4</sup>
- 6** **8** **P** = Strainer basket, perforated metal
- 6** **8** **BM** = Filter bag basket, perforated, mesh lined<sup>4</sup>
- 6** **8** **M** = Strainer basket, perforated, mesh lined
- 6** **8** **HWM** = Filter bag basket, heavy wire mesh<sup>4</sup>

#### BASKET SEAL

- 6** **N** = None (Series 6300)
- 8** **S** = Seal (Series 8500)

#### COVER SEAL

- 6** **8** **B** = Buna N
- 6** **8** **E** = Ethylene Propylene
- 6** **8** **V** = Viton<sup>®</sup>
- 6** **8** **TEV** = Teflon<sup>®</sup> Encapsulated Viton<sup>®</sup>
- 6** **8** **TSW** = Teflon<sup>®</sup> (solid white)

**Note:** All housings include a full set of spring caps and springs, and knife-edge cups.

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. ANSI B16.5 Pressure/Temperature Rating Tables determine flange class for ASME code housings. Consult factory.
2. Higher pressure ratings available. Consult factory.
3. Displacers only usable with filter bag baskets.
4. Filter bags are specified separately. See page 150.

## **Manual Backwashing System**

Manually-controlled system minimizes operator exposure and backwash fluid - ideal for hazardous environments!

### **Rosedale Products' Manually-Controlled Backwashing Filter:**

- Minimizes backwash fluid
- Increases productivity
- Reduces process/system downtime
- Reduces maintenance costs
- Reduces labor costs
- Reduces filter element disposal and replacement costs
- Reduces operator exposure

Our backwashing filter uses standard 30 inch filter bags and baskets, providing over 600 square inches of filter surface area. The unit can be cycled through hundreds of backwashes before change-out is required. When pressure drop across the system is too great, indicated by the standard pressure gages, the system is easily cycled through the backwash operation. Operation is simple, first closing the valves for the inlet and outlet, then opening the valve for the backwash outlet, which can be piped to a separate, safe location. Once that has been accomplished, simply depress the lever that shocks the system with factory air, causing the fluid in the housing to exit through the backwash outlet, removing the contaminant from the element at the same time. When the element is clean, usually in 30 seconds or so, simply return the three valves to their original positions to resume filtering.

### **Standard Features**

- No-spill cover
- Permanently piped housings are opened without disturbing piping or requiring special tools
- Low-pressure drop
- Adjustable-height tripod legs
- 150 psi rated housing
- Pressure indicators for monitoring system efficiency

### **Standard Options**

- Carbon or stainless steel housings
- Gaskets of Buna-N, Ethylene Propylene, Viton®, or Teflon®
- Valve Seats of Buna-N, Ethylene Propylene, Viton®, or Teflon®
- 150 psi ASME code stamp
- Air eliminator



Manually-controlled backwashing filter housing

## How To Order

Build an ordering code as shown in the example

**Example:**

**MBW 8 - 30 - 2P - 150 - S - B - B - C**

**BACKWASHING FILTER** = **MBW**

**MODEL NUMBER** = **8**

**BASKET DEPTH**  
30-inch (std.) = **30**

**PIPE SIZE, NPT & FLANGED**  
2-inch, female NPT (std) = **2P**  
3-inch female NPT = **3P**  
4-inch female NPT = **4P**  
2-inch 150 class ANSI flange = **2F**  
3-inch 150 class ANSI flange = **3F**  
4-inch 150 class ANSI flange = **4F**

**PRESSURE RATING**  
150 psi (NPT and flanged) = **150**

**Options**

**ASME CODE STAMP**  
**C** = Code stamp


**VALVE SEATS**  
**B** = Buna-N  
**M** = Ethylene propylene  
**T** = Teflon®  
**V** = Viton®

**COVER SEAL**  
**B** = Buna-N  
**E** = Ethylene propylene  
**V** = Viton® Fluoroelastomer  
**TEV** = Teflon® Encapsulated Viton®  
**TSW** = Teflon® (solid white)

**HOUSING MATERIAL**  
**C** = Carbon Steel  
**S** = 304 Stainless Steel  
**S316** = Stainless Steel

**NOTES:**

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME housings.
2. Higher pressure ratings available. Consult factory.
3. Filter bags are ordered separately. See page 150.



## How It Works

Fluid is introduced through the bottom of the filter housing. It is then forced through a filter element consisting of a bag rigidly contained between inner and outer baskets. The contaminant is captured on the outside surface of the outer basket and filter bag, while the clean fluid exits through the upper outlet. When the operator determines the unit needs to be backwashed, all valve positions are reversed, and the system is shocked by the introduction of factory air, causing the fluid in the vessel to exit through the backwash outlet, cleaning the element at the same time. To resume operations, just return the valves to their original positions.



## **R** Portable Filtration System

The Perfect choice for batch processing, or filtering from tanks or drums

This cart-mounted filter system has a diaphragm pump, pneumatic components and valves. The housing itself uses a standard size 12 bag. The clamp cover is easily removed and helps to reduce the time spent cleaning or replacing the bag. Rosedale's superior side-entry design does not allow contaminant by pass around the filter bag nor fluid to impinge the filter bag. It also prevents the spills and messes caused when opening. So for efficient, clean filtration, Rosedale is your choice.

### **Features**


- Quick-opening covers that do not require special tools
- Carbon or stainless steel housings
- Large area bag and basket for greater dirt-holding capacity
- O-ring seals: Buna N, EPR, and Viton®
- 125 psi-rated housing
- Basket material is compatible with housing
- Uses standard number 12 size bags with surface area of 5.6 square feet.
- 1-inch NPT ports
- Air-operated, double-diaphragm pump
- Poly-Pro pump (optional)
- Cart has built-in drip pan and 9" air-filled tires
- Compressed air filter/regulator
- 10-foot inlet/outlet hoses with quick-disconnect couplings
- 25 gpm flow rate
- Four wheel cart optional



## How To Order

Build an ordering code as shown in the example.

<b>EXAMPLE:</b>		<b>PLC8 - 30 - 1P - 125 - C - B - PB</b>	
<b>PORTABLE LCO8</b>	= <b>PLC8</b>		<b>BASKET TYPE</b>
			<b>PB</b> = Filter Bag Basket
<b>HOUSING SIZE</b>	= <b>30</b>		<b>COVER SEAL</b>
			<b>B</b> = Buna N
<b>PIPE SIZE</b>			<b>E</b> = Ethylene Propylene
1-inch female NPT	= <b>1P</b>		<b>V</b> = Viton® Fluorelastomer
<b>PRESSURE RATING</b>			<b>HOUSING MATERIAL</b>
125 PSI	= <b>125</b>		<b>C</b> = Carbon Steel with aluminum pump
			<b>S</b> = 306 Stainless with stainless steel pump




## **R Portable Filter Cart For Coolants and Metalworking Fluids**


Rugged, Versatile,  
and On the Move ...

This versatile portable filter cart (PFC), is easily movable from machine to machine, holding tank to reservoir, or drum to tank. These two wheel hand truck systems provide a means for pre-filtering and transferring fluids. They are most effective controlling particulate problems before they cause damage to critical production equipment. Rosedale's PFCs' high-flow, industrial quality centrifugal pumps transfer fluids quickly and economically.

### **Applications**

Portable filter systems can be used with coolants and other fluids with viscosities of 300 ssu or less that are compatible with aluminum and steel. Most new fluids are unfit for use in hydraulic and lube systems. Contamination enters the fluid during processing, mixing, handling and storage. Solid particulate may be present in unacceptable levels. Portable filter carts are the ideal means of pre-filtering and transferring these fluids. With a 1/2 horsepower motor and bag filter housing, this two wheel hand truck system is used for fluids with viscosities of 300 ssu or less.





#### 1" Self-Priming Centrifugal Pump Specs

GPH of Water at Total Feet of Head*					Max. Head	
10ft.	20ft.	30ft.	40ft.	50ft.	Ft.	PSI
2280	1920	1440	900	360	57	25

(\*) Flow rate based on 1" pipe; flow rate and pressure will decrease with smaller pipe and/or base.

#### Portable Filter Cart – Ordering Code Example:

	Housing			Options		
Pre-Selected Example Code:	<b>PFC8</b>	<b>30</b>	<b>1P</b>	<b>125</b>	<b>C</b>	<b>B PB</b>
Model No. =	PFC8					
Housing Size	30 inch = 30					
Pipe Size	1 inch female NPT = 1P					
Pressure Rating	125 psi = 125					
Housing Material	Carbon Steel = C					
Cover Seal	Buna N = B					
Basket Type	30 inch = PB					

#### Model 8 Suggested Bags — General Uses

	PE	5	P	12	S
Fiber Rating					
Felt, Polyester =	PE				
Micron Rating (grade)*					
General Use =	5, 25				
Fine =	BB-12				
Very Fine =	BB-10				
Ultra Fine =	BB-1				
Bag Finish					
None =		P			
Bag Size and Dimensions					
8-3/8 x 32 =		12			
Bag Style					
Carbon Steel Plated Ring =		S			

**R Filter Selection By Applications**

Page



Portable LCO Cart .....105

Portable Coolant Filter Cart .....107

Coolant Filter Selection Guide .....110

Water Filter Selection Guide .....117

Sorbent Containment Systems .....127

Mini-Bag Filter.....130

Vibrating Filter .....131

Giardia Filtration System.....133

Coalescer Filter System .....143

Filter and Bulk Media Tanks .....148

## Coolant Filter Selection Guide

For low pressure machine tool coolant applications

Rosedale Filtration Products has installed a wide variety of systems throughout the metalworking and manufacturing industries. Our high quality industrial filters prevent metal chips, fines and other debris from contaminating cutting oils and coolants. Our pre-selected systems include the housing, appropriate seals and a filter bag.


### General Requirements and Measurements

There are important factors that enter into specifying the level of coolant cleanliness that will improve the finish and extend tool life. Variables that affect coolants include: full or partial filtration, single pass or recirculating flow, dirt loading, pressure drop through all components of the filter systems, coolant temperature, flow rate, system pressure, and the presence of tramp oil.

This filtration guide is intended to provide general information about industry specifications. Use the data to compare and evaluate your specific application.

### Typical Applications

Our schematics illustrate how Rosedale filters can be easily installed in any coolant circuit. The versatile Rosedale filters can be used in all metalworking machines, including milling, boring, broaching, grinding, drilling, turning, etc.



### Methodology

Charts, schematics and other information provided or referred to throughout this guide are intended as examples only. "Nominal" filter ratings are used and monthly throughputs are calculated to include the sizing of filter elements to provide a 30 day minimum life expectancy based on a typical dirt load ingress.

Rosedale offers the widest range of filters and filter bags, including oil-adsorbing, high temperature, high-capacity bags, high-efficiency liquid filter bags, and Beta Bag® filter bags. The term Beta Ratio or Beta Rating refers to the number of particles upstream divided by the number of particles downstream in a given size. For example, if there are 100 five micron particles upstream and 50 five micron particles downstream of the filter bag, then the Beta Rating for this filter in the five micron size is 100/50, or 2. In other words, the filter bag is said to have a Beta 5 of 2. The efficiency is 50% in the five micron range.

<b>Recommended Clarity Levels Of Filtered Coolant</b> Filtered coolant shall meet or exceed the following average clarity levels.	Average Particle Size	Concentration: PPM
<b>Ultra Fine:</b> Honing, micro-sizing, lapping, and polishing	larger than 8 microns	<b>less than 10 microns</b> 5 PPM to 10 PPM
	between 1 to 8 microns	25 PPM to 50 PPM
<b>Very Fine:</b> Grinding, gun-drilling, gun-reaming (with tool diameters of 0.125 inch or less)	larger than 8 microns	<b>less than 15 micron</b> 10 PPM to 15 PPM
	between 1 to 8 microns	50 PPM to 100 PPM
<b>Fine:</b> Tapping, milling, lathe, hobbing, drilling, boring, general machining	larger than 8 microns	<b>less than 20 micron</b> 15 PPM to 30 PPM
	between 1 to 8 microns	100 PPM to 200 PPM



## Single-Bag Filters


**Model 4 Coolant Filter**

For Flows to 5 gpm

Flows can be higher. These flows are selected to optimize dirt holding capacity.

(For more detail information and other specifications concerning the Model 4, please see page 4 or contact a Rosedale representative.)

These rugged and reliable bag filters are tailored to high-capacity applications yet are relatively low in cost, making these durable filtration devices one of the best values on the market. Choose from among the pre-selected ordering codes listed below for filter flows to 5 gpm with a 200 psi rated housing.



**MODEL 4 SUGGESTED BAG**  
**PE 5 P 4 S**

**FIBER RATING**Felt, polyester = **PE****MICRON RATING (grade)**General Use = **5, 25**Fine = **BB-12**Very Fine = **BB-10**Ultra Fine = **BB-1****BAG FINISH**None = **P****BAG SIZE AND DIMENSIONS**4-1/8 x 14 = **4****BAG STYLE**Carbon steel plated ring = **S****Technical Specifications**

<b>Bag Size:</b>	Any Standard Size 4 Bag
<b>Drain connection:</b>	1" NPT
<b>Piping connections:</b>	1" NPT
<b>Construction material:</b>	Carbon steel
<b>Pressure rating:</b>	200 psi
<b>Weight:</b>	20 lbs
<b>Surface Area:</b>	1 Ft <sup>2</sup>

**Note:** If your application requires options other than those listed, please turn to page 4.

## Single-Bag Filters

**Model 8 Coolant Filter**



For Flows to 25 gpm

Flows can be higher. These flows are selected to optimize dirt holding capacity.

(For more detail information and other specifications concerning the LCO Model 8, please see page 17 or contact a Rosedale representative.)

These rugged and reliable bag filters are tailored to high-capacity applications yet are relatively low in cost, making these durable filtration devices one of the best values on the market. Choose from among the pre-selected ordering codes listed below for filter flows to 25 gpm with a 125 psi rated housing.

See page 178 for extra long life coolant filter cartridges.


**MODEL 8 SUGGESTED BAG****Technical Specifications**

<b>Bag Size:</b>	Any Standard Size 12 bag
<b>Drain connection:</b>	2" NPT
<b>Piping connections:</b>	2" NPT
<b>Construction Material:</b>	Carbon steel
<b>Pressure rating:</b>	125 psi
<b>Weight:</b>	70 lb
<b>Surface Area:</b>	5.6 Ft. <sup>2</sup>

**Note:** If your application requires options other than those listed, please turn to page 17.

## Features

### Typical Single-Bag Filter Housing



## Benefits

### Ease of Maintenance

- Easy to change
- No messy cartridges
- Dirt left in bag/no wash off
- Quick change over

### Performance

- Inherently simple, yet state-of-the-art
- Highly efficient
- Three major components (housing, bag and basket) do all the work

### Service

- Easy to maintain
- No caps, spring seals, gaskets or adapters involved during change-out

## Multi-Bag Filters

These multi-bag filters offer the widest range of flow capacities and contaminant holding capabilities. With anywhere from 2–23 perforated stainless-steel baskets specially fitted to hold disposable or cleanable filter bags, these high-capacity multi-bag filtration devices are extremely versatile. Bag sizes meet industry-wide standards: conventional 3-inch baskets take bag size 2 while optional 15-inch basket take bag size 1. The standard pressure rating for all models is 150 psi and all housing units can be supplied with a ASME code stamp, if required.

Choose from among the pre-selected ordering codes listed below. If you need assistance determining the size or type of product that suits your application, call a Rosedale representative today for assistance and information.



## Benefits

### Ease of Maintenance

- Easy to change
- No messy cartridges
- Dirt left in bag/no wash off
- Quick change over

### Performance

- Inherently simple
- Three major components (housing, bag and basket) do all the work

### Service

- Easy to maintain
- No caps, spring seals, gaskets or adapters involved during change-out



## Model Selection (30-inch deep baskets)

Model No. (and diameter in inches)	Number of Baskets	Straining, Filtering Area (ft <sup>2</sup> )	Standard Pipe Sizes Avail. (in.)	Suggested Flow Rate <sup>3</sup> (gpm)
16	2	8.8	2	50
18	3	13.2	2	75
22	4	17.6	2,3	100
24	6	26.4	3	150
30	8	35.2	4	200
36	12	52.8	4	300
42	17	74.8	6	425
48	23	101.2	6	575

### Coolant Filter: **24 - 30 - 4F - 1 - 150 - C - B - N - PB**

**MODEL NO.** (See Above)  
Diameter (inches) = **Model No.**

**BASKET DEPTH**  
30 inch (std.) = **30**

**PIPE SIZE** (Flanged)  
2 in. (models 16, 18) = **2F**  
3 in. (models 16, 18, 22, 24) = **3F**  
4 in. (models 16, 18, 22, 24, 30) = **4F**  
6 in. (models 22, 24, 30, 36) = **6F**  
8 in. (models 30, 36, 42, 48) = **8F**  
10 in. (models 36, 42, 48) = **10F**  
12 in. (models 42, 48) = **12F**

**OUTLET STYLE**  
In-line, bottom (std.) = **1**

**PRESSURE RATING**  
150 psi = **150**

**BASKET TYPE**  
**PB** = Filter bag basket

**BASKET SEAL**  
**N** = No seal

**COVER SEAL**  
**B** = Buna N

**HOUSING MATERIAL**  
**C** = Carbon Steel

#### MODEL 8 SUGGESTED BAG PE 5 P 2 S

##### FIBER & MICRON RATINGS

Felt, polyester = **PE**  
Microns: 5, 25

**BAG FINISH**  
None = **P**

**BAG SIZE AND  
DIMENSIONS**


7-1/16 x 32 = **2**

##### BAG STYLE

Carbon steel plated ring = **S**

## Features

### Typical Multi-Bag Filter Housing





## Water Filter Selection Guide

Rosedale has installed many housings for filtering industrial water applications in industries as diverse as automotive, steel, metal fabrication, and paper processing, among many others.

### The Generation II All Plastic Model 8 Bag Filter

(For more information on the Generation II, see page 33)

Rosedale's Generation II model 8-sized polypropylene bag filters are made in a one-piece, seamless body that offers excellent resistance to corrosion. It is rated to 100 psi @ 150°F and flows to 100 gpm, choose the pre-selected ordering code listed below.

Pre-Selected Corrosive Resistant Model 8 Ordering Code

Example:		Housing	Option
		<b>CR8135 - 30 - 2F - * - 100 - P - B</b>	
<b>Model No.</b>			
Corrosive Resistant Model 8 = <b>CR8135</b>			
<b>Housing Size</b>			
30 inch = <b>30</b>			
<b>Pipe Size (Flange)</b>			
2-inch Flat Face class 150 = <b>2F</b>			
<b>Outlet Style</b>			
Side/Bottom Unistyle = <b>*</b>			
<b>Pressure Rating</b>			
100 psi = <b>100</b>			
<b>Housing Material</b>			
Polypropylene = <b>P</b>			
PVDF = <b>K</b>			
<b>Cover Gasket</b>			
Buna N = <b>B</b>			
Ethylene Propylene = <b>E</b>			
Viton® = <b>V</b>			
Teflon® Encapsulated Viton® = <b>TEV</b>			



Plastic model base shown above. For more information on filter elements see page 150.

## **R Model 8 Filter Housing With Quick Opening Clamp Cover**

(For more information on the Model 8-125, see page 21)

These high-capacity bag filters are rugged and low in cost. The Quick Opening Clamp Cover is quick and easy to remove. The housing is rated at 125 psi and flows to 100 gpm, choose the pre-selected ordering code listed below.

For more information on filter bags, see page 150.

Pre-Selected Model 8 Filter Housing with Quick Opening Clamp Cover

<b>Example:</b>		<b>Housing</b>		<b>Options</b>	
		<b>815 - 2P - * - 125 - S - B - PB</b>			
<b>Model 815</b>					
<b>830</b>					
<b>Pipe Size</b>					
2-inch female NPT = <b>2P</b>					
<b>Outlet Style</b>					
Side/Bottom Unistyle = <b>*</b>					
<b>Pressure Rating</b>					
125 psi = <b>125</b>					
<b>Housing Material</b>					
Stainless Steel = <b>S</b>					
<b>Cover Seal</b>					
Buna N = <b>B</b>					
<b>Basket Type</b>					
Filter bag basket = <b>PB</b>					




## **R Extra High Capacity Multi-Bag Filters**

(For more information on the Multi-Bag Filters, see page 39)

These multi-bag filters offer a wide range of flow capacities and contaminant holding capabilities. They contain from 2 to 23 baskets, all the same size. They are fitted with perforated stainless steel baskets designed to hold disposable or cleanable filter bags. Industry standard size bags are used: the standard 30-inch baskets take bag size 2, and optional 15-inch baskets take size 1. The standard pressure rating for all models is 150 psi. All housings can be supplied with a ASME code stamp, if required. For filter flows to 2300 gpm with a 150 psi rated housing, use the pre-selected ordering code listed on the next page.

### Typical Application

#### D.I. Water System Schematic



### Water Flow Rates with 10m Filter Bags

Model	GPM
16	200
18	300
22	400
24	600
30	800
36	1200
42	1700
48	2300



## Pre-Selected Multi-Bag


Filters Ordering Code

### Model Selection (30-inch deep baskets)

Model No. (and dia. in inches)	Number of baskets	Straining, filtering area, ft <sup>2</sup>	Standard pipe sizes available, in.	Nominal flow rate, gpm
16	2	8.8	2, 3, 4	200
18	3	13.2	2, 3, 4	300
22	4	17.6	3, 4, 6	400
24	6	26.4	3, 4, 6	600
30	8	35.2	4, 6, 8	800
36	12	52.8	6, 8, 10	1200
42	17	74.8	8, 10, 12	1700
48	23	101.2	8, 10, 12	2300

Pre-selected Multi-Bag  
Filters Ordering Code

### Typical Application



### Example: 24 - 30 - 4F - 1 - 150 - S - E - N - PB - N

#### MODEL NO.

16 = **16** 30 = **30**  
 18 = **18** 36 = **36**  
 22 = **22** 42 = **42**  
 24 = **24** 48 = **48**

#### BASKET DEPTH

30-in. (std) = **30**

#### PIPE SIZE (FLANGED<sup>1</sup>)

2-in. (Models 16, 18, 22, 24) = **2F**  
 3-in. (Models 16, 18, 22, 24, 30, 36) = **3F**  
 4-in. (Models 16, 18, 22, 24, 30, 36) = **4F**  
 6-in. (Models 22, 24, 30, 36) = **6F**  
 8-in. (Models 30, 36, 42, 48) = **8F**  
 10-in. (Models 36, 42, 48) = **10F**  
 12-in. (Model 42, 48) = **12F**

#### OUTLET STYLE

In-line, bottom (std) = **1**

#### ASME CODE STAMP

**N** = No Symbol  
**C** = Code

#### BASKET, TYPE

**PB** = Filter bag basket,  
 9/64 perforations

#### BASKET SEAL

**N** = No seal

#### COVER SEAL

**E** = Ethylene Propylene

#### HOUSING MATERIAL

**S** = 304 stainless steel

#### PRESSURE RATING<sup>2</sup>

**150** = 150 psi (flanged)

1. Flanges provided with the housing match the pressure rating of the vessel. Housings rated 150 psi have 150 class flanges. Housings rated 300 psi have 300 class flanges. Other styles and classes available. ANSI B16.5 Pressure-Temperature rating tables determine flange class for ASME code housings. Consult factory.

2. Higher pressure ratings available. Consult factory.

3. Filter bags are specified separately. See page 150.

## **R Sanitary Service – Bag Filters for Fine Filtration**

New multilayer, polyester and polypropylene felt filter bags make possible filtration to 1 micron

Rosedale sanitary service filters conform to USDA/3A dairy standards with housings of polished 316 stainless steel. They're rated for 200 psi pressure and have quick-release clamp-type covers. Outlets and inlets have sanitary flange connections. All internal surfaces can be visually inspected (and easily cleaned in place).

The great economy of these filters is in their use of filter bags instead of the more costly filter cartridges. Made of a new filtering media, they carry nominal retention ratings of 1, 10 and 12 microns. They have been evaluated by the Multi-Pass Test Method (OSU-F2). See page 159 for complete information. (Other bags, including some made of monofilament meshes rated as fine as 10 microns, are also available.)

The contaminant-carrying capacity of these bags is equal to that of cartridges of the same flow capacity. Because the filter bags are supported by perforated stainless steel baskets, there is no filter collapse, flow fatigue, or filter end-load problems. Bags are removed more easily than cartridges, and bags hold the contaminant inside, not outside where it can wash off into the system during replacement. Some filter bags can be safely used at temperatures to 325°F.

Applications for these filters include dairy, beverage, vegetable oils, and other foods and pharmaceuticals. They also make excellent pre-filters upstream of ultra-fine cartridge and membrane filters removing bacteria, etc.



<b>PRESSURE RATINGS</b>	<b>Maximum Pressure @ 70°F</b>	<b>Maximum Pressure @ 250°F</b>
Model 4	200 PSI	125 PSI
Model 8	100 PSI	50 PSI



## How To Order

Build an ordering code as shown in this example

	Housing	Option
<b>Example:</b>	<b>SAN - 4-12 - 1-1/2 - T</b>	
<b>SANITARY BAG FILTER:</b>		
<b>SAN</b>		
<b>HOUSING SIZE</b>		
Model 4	= <b>4-12</b>	
Model 8	= <b>8-30</b>	
<b>CONNECTION SIZE</b>		
1-in.	= <b>1</b>	
1-1/2-in	= <b>1-1/2</b>	
2-in.	= <b>2</b>	
3-in.	= <b>3</b>	
<b>COVER GASKET</b>		
Buna N	= <b>B</b>	
Viton®	= <b>V</b>	
Teflon®	= <b>T</b>	


Order filter bags separately.  
See page 150.

## Construction

Housings are of 316 stainless steel, polished inside and out (unless ordered otherwise). The bags are supported by stainless steel baskets that provide 50% open area and lift out easily. The housing is then completely open with all surfaces visible and cleanable.

The filter bags have stainless steel rings sewn in their openings. Their close fit inside the housing effectively seals against bypass of liquid. They have cloth handles to assist in removal.

## Dimensions (IN)



## Dimensions (IN)

Model	Connection Size	A	B	C	D
4	1	4.5	15.5	2	5
	1.5	4.5	15.5	2	5
	2	4.5	15.5	2	5
	2.5	4.5	16.0	2.5	6
	3	4.5	16.0	2.5	6
8	1	8.6	38.0	3.6	7.1
	1.5	8.6	38.0	3.6	7.1
	2	8.6	38.0	3.6	7.1
	3	8.6	38.0	3.6	8.1



## T-Type Sanitary Cartridge-Housing


For fine filtration

Rosedale's sanitary service filters for sterile filtration are constructed with housings of electropolished 316 stainless steel. This "T" type sanitary housing is rated for 150 psi pressure and has a quick-release clamp closure which is safe for compressed gas applications. Outlets and inlets have sanitary flange connections. All internal surfaces can be visually inspected and easily cleaned in place. The housing uses an industry standard 222 or 226 style cartridge.

Applications for this sanitary filter housing include dairy, food and beverage processing, sterile filtration for pharmaceuticals, and sterile air/gas filtration. They are also excellent pre-filters used upstream of membrane filters.

### Construction

Housings are all welded construction with all wetted parts of 316 stainless steel. All welded attachments are 300 series stainless steel. The materials and manufacturing process exceed industry standards for sterile filtration. See pages 193-202 for sanitary use filter cartridges.




## How To Order

Build an ordering code as shown in this example.

	Housing	Options
<b>SANITARY CARTRIDGE FILTER</b>	<b>SAN-T-1- 150-T-222 -20-H</b>	
<b>PIPING STYLE</b>		
<b>CONNECTION SIZE</b>		
1-in = <b>1</b>		
<b>PRESSURE</b>		
150 psi = <b>150</b>		
<b>O-RING MATERIAL</b>		
Teflon® = <b>T</b>		
<b>CARTRIDGE STYLE</b>		
Style 222 = <b>222</b>		
Style 226 = <b>226</b>		
<b>CARTRIDGE LENGTH</b>		
10-inch = <b>10</b>		
20-inch = <b>20</b>		
30-inch = <b>30</b>		
<b>OPTIONAL</b>		
Housing stand = <b>H</b>		
No options = <b>No Symbol</b>		

**Note:** Order cartridges separately. See page 150.



## In-Line Sanitary Cartridge Housing

Rosedale in-line sanitary cartridge housings are constructed of electropolished 316 stainless steel for sterile filtration. They are rated for 150 psi pressure and have a quick-release, clamp-type closure. A recessed filter connection reduces hold-up volume and ensures a proper O-ring seal.

The in-line design features a sanitary purge valve that ensures proper venting for complete filter wetting. There's also a sanitary drain valve ensuring proper liquid drainage during venting applications. This sanitary filter housing uses an industry standard 222 or 226 style cartridge.




Sanitary USDA/3A Standards

Applications for this housing include sterile venting, sterile air/gas filtration, food and beverage processing, and sanitary applications requiring high purity, non-reactive surfaces. They are also excellent pre-filters used upstream of membrane filters.

### Construction

Housings are all welded construction with all wetted parts of 316 stainless steel. All welded attachments are 300 series stainless steel. The materials and manufacturing process exceed industry standards for sterile filtration. A cast clamp closure connects the shell to the base assembly.



## How To Order

Build an ordering code as shown in this example

**Housing** **Options**  
**SAN-IL-1-150-T-222-10**

**SANITARY CARTRIDGE FILTER**

**PIPING STYLE**

**CONNECTION SIZE**  
1-in = **1**


**PRESSURE**  
150 psi = **150**

**O-RING MATERIAL**  
Teflon® = **T**

**CARTRIDGE STYLE**  
Style 222 = **222**  
Style 226 = **226**

**CARTRIDGE LENGTH**  
10-inch = **10**  
20-inch = **20**  
30-inch = **30**

**Note:** Order cartridges separately. See page 150.



## **R** **Rosedale Bulk Loading Filters**

Know your liquid products are clean upon delivery - and be able to prove it! For flow rates to 50 gpm

Here is a way to ensure that the liquid chemicals or petroleum products you put into bulk containers - from drums to tanks cars - are as clean as they should be.

This final filter uses low-cost filter bags with dirt retention capabilities as fine as one micron. The filter attaches to the end of your loading pipe or hose, so it's the last thing your product touches before being loaded. It will stop any contaminant that has escaped your regular filtering system.

The filter can be attached to your line by a standard quick-connect coupler for easy removal. The cover is held closed by an easy-operating clamp - no tools required. It acts to hold the bag down in proper position, also. The filter bag can be quickly removed after loading for inspection. This will indicate your system filtration condition, and the bag can also serve as proof of the cleanliness of the product delivered. (Just send the bag along with the shipment.)

### **Description**

The filter is of welded construction, in carbon or 304 stainless steel. It weighs approximately nine pounds. The filter bag basket is of perforated 304 stainless steel.

It uses standard-sized filter bags, #3 or #4. We offer them in many materials and micron ratings. If filter bags aren't desired, you can order units with strainer baskets, in a wide range of perforation hole sizes and with wire cloth linings as fine as 200 mesh.



## How To Order


Build an ordering code for the filter and the filter bags as shown in these examples

	Housing	Options
<b>EXAMPLE</b>	<b>BL- 412- CL/PT-2-1-200-S - B-N-B-D</b>	
<b>BULK LOADING</b>		
<b>SIZE</b>		
6 inch = <b>46</b>		
12 inch = <b>412</b>		
<b>INLET/OUTLET</b>		
(Cam-locking quick coupler = CL, female NPT = PT)		
	<b>CL/PT</b>	
	<b>CL/CL</b>	
	<b>PT/CL</b>	
	<b>PT/PT</b>	
<b>CONNECTION SIZE</b>		
1-1/2 inch = <b>1-1/2</b>		
2 inch = <b>2</b>		
3 inch = <b>3</b>		
<b>OUTLET STYLE</b>		
<b>PRESSURE RATING</b>		
200 psi (clamp cover) (Std.) = <b>200</b>		
300 psi (eyenut cover) = <b>300</b>		
<b>HOUSING MATERIAL</b>		
Carbon steel = <b>C</b>		
304 stainless steel = <b>S</b>		
<b>COVER GASKET</b>		
Buna N = <b>B</b>		
Ethylene Propylene = <b>E</b>		
Viton® Fluoroelastomer = <b>V</b>		
Teflon® Fluorocarbon = <b>T</b>		
<b>BASKET SEAL</b>		
No seal (Std.) = <b>N</b>		
Seal (basket strainers only) = <b>S</b>		
<b>BASKET TYPE</b>		
For filter bag, 9/64 perforations (Std.) = <b>B</b>		
For straining, perforated metal = <b>P</b>		
For filter bag, perf., mesh-lined = <b>BM</b>		
For straining, perf., mesh-lined = <b>M</b>		
<b>DISPLACER</b>		
Displacer = <b>D</b>		
<b>BASKET MEDIA SIZE</b>		
Type B basket, <b>no symbol</b> (Std.)		
Type P basket, perf. diameters		
<b>1/4, 3/16, 9/64, 3/32, 1/16</b>		
Type M & BM baskets, mesh size		
<b>20, 30, 40, 50, 60, 70, 80, 100, 150, 200</b>		

**Note:** Order filter bags separately. See page 150.

### Model 4—For flow rates to 50 gpm

- Pipe sizes 3/4 thru 2-inch, NPT or flanged
- Two basket depths: 6 or 12 inches (nominal)
- Three pressure ratings: 200 psi (with clamp cover) and 300 or 500 psi (with eyenut cover)
- ASME code stamp available



## **R Sorbent Containment Systems**

- Treatment vessels
- Carbon-holding baskets
- Activated carbon packs

**Treatment Vessels** are standard Rosedale strainer/filter housings, available in carbon steel, and 304 or 316 stainless steel. They are made in many sizes. Single-basket models are pressure rated from 75 to 500 psi, with pipe connections from 3/4-in.-NPT to 4-in.-flange. Multi-basket models can hold from 2 to 23 baskets and are pressure rated at 150 psi. Pipe sizes are from 2 to 12 inches (flanged).

**Sorbent-Holding Baskets** are made in two styles: the RS, for recirculating systems, passes liquid (horizontally) through a shallow bed (approximately 2-1/2 inches deep); the SP, for single-pass systems, has a deep (vertical) bed (approximately 29 inches deep).

Baskets are made entirely of 304 stainless steel, and are of high quality construction. They are easily recharged with sorbents such as activated carbon. Turning the large lifting handle opens a cover so that they can be emptied and refilled. The particles are retained by 100-mesh wire screening.

These baskets can also be filled with materials other than activated carbon. Other processing media might include deionizing resin beads, silica gels, alumina, green sand, and odorizing agents.

**Activated Carbon Packs** are pre-measured amounts of 20 x 50-mesh-size activated carbon, packaged to protect against moisture. A universal grade of carbon is used, offering good flow rates.



An SP-style basket being put into a Rosedale Model 8-30 vessel. An RS-style basket is in the foreground.

## **Designing An Optimum System**

While carbon granules can act as a filtering media to remove solid particulate from a liquid, it is far more economical to pre-filter liquids entering a carbon adsorption vessel to avoid impeding the adsorption process. It is also recommended that a second filter be placed downstream of the carbon unit to catch any carbon particles that might be flushed out by the fluid stream. Rosedale bag filters are excellent in these roles.




A combination carbon adsorption and downstream filtering unit can be ordered. Available in the larger single-basket and all multi-basket vessels, it positions the carbon-

holding basket inside a larger filter bag-holding basket. A variety of filter bag media is offered.


### RS Style For Recirculating Systems

Flow enters from the top, into a perforated cylinder around, which is packed activated carbon. Flow moves radially through the carbon and exits through the side wall, which is perforated and lined with 100-mesh screen.



### SP Style For Single-Pass (1-Time) Processing

Flow enters from the top through a perforated cover and into the activated carbon bed. Flow moves down through the carbon and exits through the bottom plate, which is perforated and lined with 100-mesh screen.



Activated carbon is a "black magic" material that removes molecules of organic pollutants from various liquids by physical adsorption. (It does not act by chemical bonding.) It is a surface attraction, and the fine porous carbon particles have an incredibly large surface area. (Used carbon can be reactivated by oxidizing the adsorbed contaminant.)

Uses of carbon adsorption include:

1. Purification of sugar syrups, liqueurs, glycerine, pharmaceuticals, etc.
2. Treatment of water to remove chlorine and odor, and improve color and taste.
3. Purification of process effluents, per EPA requirements.
4. Drying, degumming, and decolorization of fuel and lubricants, organic solvents, vegetable oil, and animal fats.





## Treatment Vessels

Any of Rosedale's standard single or multi-bag housings can be used as the treatment vessel. See pages 4-225, 31-47, 78-84, 88-89, 100-103.

## Activated Carbon Packs

Order carbon packs by using the basket order number (as shown below) plus the suffix 'CP'.

### Example:

To order a replacement pack of carbon in an amount sufficient to fill an O-730-RS basket, order number O-730-RS-CP

## Ordering Information

Carbon-Holding Baskets				Carbon-Holding Baskets			
Flow Rate (gpm)	Carbon Capacity (cu.in.)	To fit vessel (Model No.)	Basket Order No.	Flow Rate (gpm)	Carbon Capacity (cu.in.)	To fit vessel (Model No.)	Basket Order No.
<b>RS-style (for recirculating systems)</b>				<b>SP-Style (for single pass systems)</b>			
2.5	66	4-6	O-46-RSB-6671	1.25	70	4-6	O-46-SPB-6673
5.0	130	4-12	O-412-RSB-6675	2.5	140	4-12	O-412-SPB-6677
4.0	197	6-12	O-612-RSB-4359	4.0	235	6-12	O-612-SPB-4367
10.0	296	6-18	O-618-RSB-4361	5.0	353	6-18	O-618-SPB-4365
15.0	494	6-30	O-630-RSB-4363	7.5	589	6-30	O-630-SPB-5046
15.0	484	8-15	O-715-RSB-1538	5.0	494	8-15	O-715-SPB-1537
20.0	963	8-30	O-730-RSB-8119	10.0	1020	8-30	O-730-SPB-8432
<b>To fit Model 8 vessels with backup filter bag baskets</b>				<b>To fit Model 8 vessels with backup filter bag baskets</b>			
	249	8-15	I-715-RSB-1617		285	8-15	I-715-SPB-1615
	574	8-30	I-730-RSB-1625		658	8-30	I-730-SPB-7669
<b>To fit multi-basket vessels</b>				<b>To fit multi-basket vessels</b>			
15.0*	484	15-in.nom.	O-915-RS	5.0*	494	15-in.nom.	O-915-SP
20.0*	963	30-in.nom.	O-930-RSB-1534	10.0*	1020	30-in.nom.	O-930-SPB-1215
<b>To fit multi-basket vessels with backup filter bag baskets</b>				<b>To fit multi-basket vessels with backup filter bag baskets</b>			
	249	15-in.nom.	I-915-RS		285	15-in.nom.	I-915-SP
	574	30-in.nom.	I-930-RS		658	30-in.nom.	I-930-SP

\*Flow rate is per basket: Multiply by number of baskets in vessel.

## **An All-Stainless Steel Mini-Bag Filter For 3000 psi Service**

Ideal for spray nozzle protection

Here's the best answer yet to the need for a small yet rugged final filter for liquids at pressures to 3000 psi. The filter contains a stainless wire mesh "bag" with a 14 square inch area. It can be thrown away when dirty, or cleaned and reused. Flow is from the inside to the outside of the element; contaminant stays trapped inside. The straight through design has no elbows, turns or internal pockets to create pressure drops or collect sediment, and they're easy to flush out.



The mini-bag filter is very easy to service too. Just spin the knurled collar loose, push the housing out of line a bit, remove the element, slip a new or clean one in, and you're back in business. The seal is a special, Teflon-encapsulated Viton O-ring. It can be tightened by turning the knurled collar, usually by hand.

### Specifications

- Pressure rating: 3000 psi
- Differential pressure rating: 25 psi
- Port sizes: 3/8 inch NPT
- Micron retention ratings (absolute): 25, 50, 75, 100, 125 and 150

## How To Order

Order filter housings separately:  
Model No. MF-1

Order element bags separately, according to micron retention desired:

25 micron (absolute),	Part No. MB-25
50 micron (absolute),	Part No. MB-50
75 micron (absolute),	Part No. MB-75
100 micron (absolute),	Part No. MB-100
125 micron (absolute),	Part No. MB-125
150 micron (absolute),	Part No. MB-150


**NOTE:** A model with 2 collars, to be removed from rigid piping, is also available.

**Flow Capacities** (gpm)  
at 2 psi (.14 bar) pressure drop

Viscosity (SSU/cSt)	Element Micron Rating			
	150	75	50	25
100/20.5	6	6	6	6
250/55	6	6	5.3	4
1000/250	4.5	4	3.1	2
1500/325	3.5	3.5	2.3	1.5



### Dimensions (IN)



## **The Vibrating Filter**

High-frequency sieving action prevents rapid filter loading

### **The Rosedale Vibrating Filter**

prevents filter cake from forming on the element surface. As in sieving, the screen through which the product passes is rapidly agitated. This prevents the building up of even smaller particles on larger ones stopped at the screen. By keeping over-sized material bouncing off the screen, the smaller particles can reach the screen and pass through. This sieving-type filter is ideal for paints, medicines, paper coatings, foods, or any product containing desirable solids that can be classified by size.



Clean, unlubricated plant air at 25 to 60 psi is supplied to this 3/8-in NPT port

Outlet for purged material

Air Outlet (To Silencer)

FLUID INLET

Seal

Air Hoses

Vibrating Motor

FLUID OUTLET

Unlike standard sieving, the vibrating filter works in a closed, pressurized system that greatly increases throughput. The high-frequency vibration also serves to delump agglomerated material.

The vibrating filter contains a perforated stainless steel basket lined with either stainless wedgewire or wire cloth. An air-driven vibrating motor at the bottom causes the basket to vibrate. The vibration rate is changed by varying the air pressure. Higher pressures produce higher frequencies. The basket is isolated from the housing, so very little vibration is transmitted to housing and piping.

### **Cleaning The Filter**

- Release system pressure, and close inlet and outlet valves. Turn off the air to the vibrating motor.
- Loosen the eye nuts enough to swing rod ends free of the cover. Open the drain valve at the outlet to remove the remaining clean fluid.
- Remove cover-vibrator-basket assembly straight-up for the housing. (Contaminated fluid will now drain from the housing.)
- The easiest method for cleaning the unit is to run the vibrator while the basket is immersed in solvent. If this isn't effective, the basket must be removed and cleaned by hand.
- Separate the filter basket by removing the cotter pin, castle nut and lock washer. If the basket doesn't break free, tap the top of the basket lightly. If that fails, tap the stem down on a wood board to break the basket loose.
- Use brushes, solvents, compressed air, or other suitable means to remove the contaminant from the wire cloth or wedgewire element. Be careful not to damage the basket with sharp instruments.

## How To Order

Build an ordering code as shown in this example

	Housing	Options
<b>Example:</b>	<b>VF- 4- 12- 3/4P- 1 -300- S -T -T- 100WW</b>	
<b>VIBRATING FILTER</b>		
<b>MODEL</b>		
<b>SIZE</b>		
<b>PIPE SIZE &amp; CONNECTION</b>		
3/4-in. female NPT	= <b>3/4P</b>	
1-in. female NPT	= <b>1P</b>	
1-1/2-in. female NPT	= <b>1-1/2P</b>	
2-in. female NPT	= <b>2P</b>	
1-in. 150 class ANSI flange	= <b>1F</b>	
1-1/2-in. 150 class ANSI flange	= <b>1-1/2F</b>	
2-in. 150 class ANSI flange	= <b>2F</b>	
<b>OUTLET STYLE</b>		
Bottom = <b>1</b>		
Side = <b>2</b>		
<b>PRESSURE RATING</b>		
<b>HOUSING MATERIAL</b>		
<b>COVER SEAL</b>		
<b>BASKET SEAL</b>		
<b>BASKET ELEMENT</b>		
50-micron wedgewire	= <b>50WW</b>	
75-micron wedgewire	= <b>75WW</b>	
100-micron wedgewire	= <b>100WW</b>	
125-micron wedgewire	= <b>125WW</b>	
150-micron wedgewire	= <b>150WW</b>	
25-micron wire cloth	= <b>25</b>	
50-micron wire cloth	= <b>50</b>	
75-micron wire cloth	= <b>75</b>	
100-micron wire cloth	= <b>100</b>	
125-micron wire cloth	= <b>125</b>	
150-micron wire cloth	= <b>150</b>	

## Specifications


- Unlubricated plant air: 20 psi
- Maximum flow: 20 gpm
- Maximum pressure: 300 psi
- Maximum pressure drop: 50 psi
- Pressure drop (clean): 2 psi
- Air Consumption: 2 SCFM

## Element


Wedgewire baskets are available in micron ratings ranging from 50 to 150 (25 microns equal .001 in.). Wire used has a strong wedge-shaped cross-section. Wire cloth-lined baskets are available with micron openings from 25 to 150. Wire cloth has a much higher percent of open area than wedgewire. A given flow passes through with less pressure drop.

## Materials

Housings and metal internals are 304 stainless steel. Air hoses are nylon with nickel-plated steel fittings. Seals are Teflon.



## Dimensions (IN)



# Single Stage Giardia Cryptosporidium Removal

## Municipal Drinking Water Filters

### THE HOUSING

#### **The Rosedale Model 8302P or Model NCO8135**

#### Stainless Steel Housings

The Model 8302P and NCO8135 high-capacity filters offer an exceptional value in Giardia Cryptosporidium Removal applications. The system is approved for use in Colorado and Oregon and has met all the EPA LT2 guidelines.

Each housing provides large containment capacity combined with a rugged design rated to 150 psi. It incorporates an eyenut cover that is easily removed, reducing time spent on cartridge change-out.

#### Features

- NSF 61 listed
- Low pressure drops
- Permanently piped housings
- Covers are O-ring sealed
- 304 stainless steel construction
- All housings are electropolished to resist adhesion of dirt and scale
- Adjustable-height legs, standard
- ASME code stamp available



Certified to  
NSF/ANSI 61



Model 8302P



TYPICAL CREDITS	Pathogen log <sub>10</sub> Removal Credit			Filter Loading Rate (gpm/bag)	Max. Pressure Differential (psi)
	Virus	Giardia	Cryptosporidium		
Filter Bag: PS-740-PPP-356	0	3	2 Log	20	30



## THE ELEMENT

### **R PS-740-PPP-356 Filter Cartridge**

Maximize dirt-holding capacity and meet LT2 requirements

PS-740-PPP-356 elements are manufactured in a unique "Y" pleat arrangement that optimizes physical size and maximizes effective surface area. The large surface area provides a low fluid flux rate maximizing dirt containment.


The element fits into the Rosedale NCO8135 housing or can retrofit 8302P housings with an adaptor basket. The end caps are heat sealed for high efficiency performance. The o-ring seal insures sealing and eliminates bypass.

### Features

- 100 sq. ft. of surface area maximum
- 11 lbs. (approx.) of dirt carrying capacity
- 2 log cryptosporidium credit
- Flow rates to 10 gpm
- 6.25-inch diameter and 35-inch length
- Fits into standard Rosedale Model NCO8135 and 8302P
- Double o-ring seals
- NSF 61 listed



Certified to  
NSF/ANSI 61



Cutaway of 740 Cartridge. The "Y" pleat maximizes effective surface area.



### Retrofit Current Sites

Existing installations using the Rosedale 8302P and PS-520-PPP-241 or GLR-PO-825-2 can easily convert to a single housing by installing the PS 740 adaptor basket.

This is accomplished by replacing the perforated filter basket with the adaptor. The solid side basket accepts the new PS 740 cartridge and directs the flow through the unit.





# Dual Stage Giardia Cryptosporidium Removal

## THE HOUSING

**R** Rosedale has developed an effective water filtration system that meets the SWTR and protocols for most states. This system offers a dual-stage design that filters out larger contaminants before filtering out micro-organisms.

**The system** consists of two high-quality Rosedale **Model 8 housings** (pressure vessels), placed in series.

**The first stage** is fitted with a **PS-520-PPP-241** bag/cartridge.

**The second stage** is Rosedale's **GLR-PO-825-2** bag/cartridge.

This provides a 2 LOG cryptosporidium credit when used in tandem. The optimum flow rate for the system described is 13 gallons per minute (GPM).

Rosedale manufactures filtration systems for larger applications, that can filter water up to 500 GPM. Multiple designs are available to meet your needs.



**STAGE 1**  
**Pre Filter**  
**PS-520-PPP-241**

**STAGE 2**  
**Final Filter**  
**GLR-PO-825-P2**

TYPICAL CREDITS	Pathogen log <sub>10</sub> Removal Credit			Filter Loading Rate (gpm/bag)	Maximum Pressure Differential (psi)
	Virus	Giardia	Cryptosporidium		
Filter Bag Prefilter: GD-PO-523-2	0	2	1	10 (w/ prefilter)	10
Final Filter: GLR-PO-825-2				3 (w/o prefilter)	
Prefilter: PS-520-PPP-241	0	2	2	13 (Must be operated w/ both filters in series)	PS-520-PPP-241: ΔP = 20
Final Filter: GLR-PO-825-2					GLR-PO-825-2: ΔP = 2.5



Filter Housings  
and Cartridges are  
NSF 61 Listed



**Pre-Filter**

## THE ELEMENTS



### Pre-filter (Optional)

All graded-density bags are constructed of nine-layers of polypropylene micro fibers and standard fibers that are variably calendered. Heavy-duty handles are sewn and turned inside out to avoid leakage and enhance their pressure capacities.



**GLR-PO-825-2**

### Final Filter (2 Choices)

**1**—The Rosedale GLR-PO-825-2 element has 26 layers of high-efficiency polypropylene micro fiber material, encased in a rigid support cage. The initial layers are pre-filtration levels, while the next several layers filter the cyst pathogen itself. The final barriers prevent any material from migrating into the effluent. All GLR units have a specially designed gasket to assure a bypass-proof seal. All seams and joints are heat sealed to prevent leakage. The inside-out flow design traps contaminants on the inside, reducing the possibility of downstream contamination during changeout and simplifying the service process. NSF 61 listed.



**PS-520-PPP-241**

**2**—The PS-520-PPP-241 filters are manufactured in a "Y" pleat arrangement that optimizes physical size and maximizes effective surface area. The large surface area provides a low fluid flux rate maximizing dirt containment. This means element life is extended. NSF 61 listed.


Rosedale Products' Cyst Reduction system provides easy installation, operation, and maintenance for a cost-effective solution to water treatment not previously realized by high-cost conventional systems.

## How To Order Single Stage Systems

Build an ordering code as shown in the examples.

### Housings

<b>Example :</b>	<b>NCO8135 - 2P - * - 150 - S - EDPM - E-700</b>
<b>MODEL</b>	
<b>8302P</b>	
<b>NCO8135</b>	
<b>PIPE SIZE</b>	
2-inch female NPT	= <b>2P</b>
<b>OUTLET STYLE</b>	
Side/Bottom Unistyle	= <b>*</b>
Bottom	= <b>1</b>
<b>PRESSURE RATING</b>	
150 psi	= <b>150</b>
<b>HOUSING MATERIAL</b>	
304 Stainless steel	= <b>S</b>
<b>COVER SEAL</b>	
Ethylene propylene	= <b>EDPM</b>
<b>SERIES</b>	
<b>E-700</b>	



The system is approved for use in Oregon and has met all the LT2 guidelines.

### Cartridges

	<b>PS - 740 - PPP - 356</b>
<b>PLATINUM SERIES</b>	= <b>PS</b>
<b>MICRON RATING</b>	
0.5 Micron	= <b>740</b>
<b>FILTER MEDIA</b>	
Polypropylene	= <b>PPP</b>
<b>LENGTH &amp; SEAL</b>	
Length (35" OAL)	= <b>356</b>
Seal-6 (BUNA)	



### Adaptor Basket

	<b>PS-740 Adaptor Basket</b>
<b>ADAPTOR BASKET</b>	



## How To Order Dual Stage Systems

Build an ordering code as shown in the examples.

### Housings

#### CYST REDUCTION FILTER SYSTEM (Housings)

	Housing	Options	Bags
<b>Example:</b>	<b>GFS - 8 - 30 - 2P - 2 - 150 - S - E - S - PB - B</b>		
<b>GIARDIA / CRYPTOSPORIDIUM FILTRATION SYSTEM = GFS</b>			
<b>MODEL NO.</b> Model 8 = <b>8</b>			
<b>BASKET DEPTH</b> 30 inch = <b>30</b>			
<b>PIPE SIZE NPT AND FLANGED</b> 2-in. female NPT = <b>2 P</b> 2-in. ANSI flange = <b>2 F</b>			
<b>OUTLET STYLE</b> Bottom = <b>1</b> Side = <b>2</b> Bottom = <b>3</b>			
<b>PRESSURE RATING</b> 150 psi (flanged) = <b>150</b>			
<b>HOUSING MATERIAL</b> 304 Stainless steel = <b>S</b>			
<b>COVER SEAL</b> Ethylene Propylene (NSF) = <b>E</b>			
<b>BASKET SEAL</b> Seal Required = <b>S</b>			
<b>BASKET TYPE</b> Filter Bag Basket = <b>PB</b>			
<b>FILTER ELEMENTS</b> 1 GDP05232 and 1 GLRPO825P2 = <b>B</b>			

#### Typical 2-Stage System — Included Components

- 5** 2-inch butterfly valve (hand actuated) used for isolation and drainage
- 1** 0-60 psid differential pressure gauge (stage 1) rolling diaphragm
- 1** 0-30 psid differential pressure gauge with switch, NEMA 4 enclosure (stage 2) rolling diaphragm
- 2** 1/4 inch vent valve (ball valve)

Two stage systems are approved in Alaska, California, Washington, Oregon, Vermont, Maine, and Minnesota. Meets the SWTR and protocols for most states.

### Elements

#### PRE-FILTER


##### Graded-Density Filter Bags

Part Number = **GD-PO-523-2**

#### FINAL FILTER

##### Cyst Reduction Cartridge

- 1. Part Number = **GLR-PO-825-2**  
NSF61
- 2. Part Number = **PS-520-PPP-241**  
Pleated, Longer Life,  
U-Cup Seal,  
NSF61



## **R** **Platinum 520** **ABSOLUTE-RATED** **Bag-Sized Cartridges** Maximum dirt-holding capacity


### Features

- 50 sq. ft. of surface area
- 8 lbs. (approx.) of dirt carrying capacity
- Rated 0.5 micron, 2 LOG cryptosporidium credit when used in tandem with the Rosedale GLR-PO-825-P2
- Flow rates to 20 gpm
- 6.25-inch diameter and 24-inch length
- Fits into standard Rosedale Model 8, and Multi-cartridge housings
- NSF 61 listed

These elements are manufactured in a unique "Y" pleat arrangement that optimizes its physical size and maximizes effective surface area. A low fluid flux rate maximizes dirt containment. This means element life is extended.


### Design Details

The element fits into Rosedale standard size 2 baskets and functions similar to a bag (dirt is caught inside). The end caps are heat sealed for high efficiency performance. The o-ring seal insures sealing and eliminates bypass.






## Dirt Holding Capacity (Platinum Series)



## Flow Rate Vs. $\Delta P$



## How To Order

Build an ordering code as shown in the example.

### 500 Series

Example: **PS - 520 - PPP - 241**

**PLATINUM SERIES** = **PS**

**MICRON RATING**

0.5 Micron

= **520**

**FILTER MEDIA**

Polypropylene

= **PPP**

**LENGTH & SEAL**


Length (24" OAL)

Seal-1 (EPR Seal)

= **241**



Certified to  
NSF/ANSI 61





## TYPICAL SYSTEM SPECIFICATIONS

10 GPM System Consists of 2 ROSEDALE 8-30-2P Bag/Cartridge Filters connected in series with isolation valves and instrumented with differential pressure gages.

Model Number GFS-8-30-2P-2-150-S-FG-B-PB-DPS

### Stage 1 Description - Pre Filter

Rosedale Model 8-30-2P Bag/Cartridge Filter - Quantity 1  
Design Pressure 150 PSIG @ 400°F  
2" ANSI 150# Flanged Connections  
1" NPT Drain  
1/4" NPT Vent and Gage Connections  
304 Stainless Steel Construction  
Swing Bolt Cover  
Accepts 1 Standard #2 Size Filter Bag or Cartridge  
5V-2787 Hold Down Devices  
Pressure Differential Switch  
Gasket - EPR NSF 61

### Stage 2 Description - Final Filter

Rosedale Model 8 Bag/Cartridge Filter - Quantity 1  
Design Pressure 150 PSIG @ 400°F  
2" ANSI 150# Flanged Connections  
1" NPT Drain  
1/4" NPT Vent and Gage Connections  
304 Stainless Steel Construction  
Swing Bolt Cover  
Accepts 1 Final Giardia Cartridges  
5V-2787 Hold Down Device  
Pressure Differential Switch  
NSF 61

### One Complete Set of Filter Media

#### Rosedale GLR 825 Series Cartridge Giardia/Cryptosporidium Reduction Final Filter

#GLR-PO-825-2  
2 LOG Giardia Credit Efficiency  
Polypropylene Construction  
26 Layers Wrapped Depth Element  
Integral "V" Seal

#### Rosedale PS 520 Series Cartridge Giardia/Cryptosporidium Reduction Pre Filter

#PS-520-PPP-241  
2 LOG Cryptosporidium Credit in Concert with Above  
Polypropylene Construction  
3 Layers Pleated Element  
Integral "V" Seal

### Optional

#### Rosedale Model 8-30-2P Bag Filter

GFS-8-30-2P-2-150-S-FG-S-PB-HD5V-2787

#### with Filter Bag

GD-PO-523-2

Tested in series at the USDA Forest Service facility in San Dimas, CA.

Pre Filter: PS-520-PPP-241

Post Filter: GLR-PO-825-2

95th Percentile	Log Reduction		
	2-5 um	5-15 um	2+ um
First Filter Set	2.01	2.26	2.06
Second Filter Set	3.06	3.44	3.17
Third Filter Set	3.21	3.38	3.25

**FINAL FILTER Filtration Unit - Design Information**

Item Description	Information
<b>Model Number</b> .....	GRL-PO-825-2
<b>Filter and System Information</b>	
Type of Filtration Unit .....	Cartridge / Bag
Filter Material Description .....	Polypropylene
Absolute/Nominal Pore Size, Lower Cutoff Particle Size.....	0.5 Microns
Final Filter Life Expectancy.....	At the accumulation of approximately 1.2 lbs solids
Number of Filtration Units/Banks.....	2
Vessels .....	2
Filter Connections.....	2" NPT or Flange
<b>Testing Results</b>	
NSF, ETV, Other 3rd Party Verification Testing? .....	NSF 61, State of California
NSF Standard 61, FDA, Certification .....	Yes
Pilot Study Data?.....	Yes
<b>Removal Efficiency and Credits</b>	
Treatment Log Removal Credits.....	2.0-Log Giardia and Cryptosporidium
Targeted Removal Efficiency .....	99%
Targeted Turbidity .....	0.1 NTU
<b>Flow rate, Pressure, Etc.</b>	
Flux Rate (gsfd) .....	13-20 GPM per (2) Stage System
Filter Surface Area.....	4.4 ft <sup>2</sup> Final / 50 ft <sup>2</sup> Prefilter
Peak Flow Rate (GPM) .....	20 GPM
Continuous Flow Rate (GPM).....	13 GPM
Minimum, Maximum Inlet Pressure .....	10 PSI Min. / 150 PSI Max.
Differential Pressures - Operating, Maximum, Setpoints/Alarms.....	Maximum ΔP, 15 PSID Post 30 PSID Prefilter
<b>Raw Water Quality</b>	
Pre-Sediment/Pre-Treatment (screening, oxidation, cartridge/bag filters, dechlorination).....	Yes
Colloidal Particles: Pretreatment requirements or reduction of filter life .....	Yes
Source Water Limitations.....	High NTU >5
pH Limitations.....	No
Inorganics/Organics (Fe, Mn) Fouling Problems .....	Possibly
Water Temperature Range, Any Flow Rate Impacts? .....	No
Pre-Chlorination/Oxidation -Incompatibility with Filter? pH <10? .....	No
<b>Design Considerations</b>	
Process Flow Description .....	2-Stage Filter Unit
Raw Water Flow Meter, Rate Control .....	As Requested
Redundancy of Critical Components -Valves, Air Supply, Computers, PLC? .....	As Requested
Protection from Water Hammer .....	Needed
Pressure Gages for Pressure Drop Across Filter .....	Yes
Replacement Parts .....	Elements, Gaskets
O & M Manual.....	Yes

**PRE FILTER Filtration Unit - Design Information**

Item Description	Information
Type of Units.....	Bag Filters
NSF Standard 61 Certification.....	Yes

## Coalescer Filter Systems

### Rosedale Single-Cartridge or Multi-Cartridge Housings


Rosedale Coalescer Filter Systems provide cost effective high efficiency liquid coalescence of gas streams.

The introduction of proprietary interception, coalescence, and drainage layers pleated in conjunction with a high efficiency micro-fiber media ensures separation of sub-micron liquid aerosols from gas streams while minimizing fluid carry-over.

Available in Model 4, 6, and 8 housings which hold 1 cartridge, and multi-cartridge housings which hold from 1 to 30 cartridges.

#### FEATURES AND BENEFITS

- Provides high efficiency removal of unwanted liquid contaminants
- Available in both 99.98% and 99.0% efficiency ratings
- High surface area providing low pressure drop
- Cartridges designed to upgrade existing vessels or to be specified in new installations
- Standard version and amine compatible version available
- Buna and Viton® gaskets used as standard sealing elastomers (other materials available)





### GENERAL HOUSING SPECIFICATIONS

Rosedale standard coalescer housings are available to accept 28", 40", and 60" cartridges. Larger multi-cartridge housings are also available.

- Model 4, 6, and 8 housings hold 1 cartridge
- Multi-cartridge housings hold from 1 to 30 cartridges
- Available in vertical or horizontal configurations
- Permanently piped housings
- Covers are bolted flange or QOC
- Carbon steel, or stainless steel (304 or 316) construction for housings
- All housings are electropolished to resist adhesion of dirt and scale
- ANSI class 150, 300, 600, 900, or 1500

### GENERAL CARTRIDGE SPECIFICATIONS


- 15 psi maximum pressure differential rating
- 5 to 9 pH range
- 150°–160°F maximum operating temperature
- Aluminum center tube
- Buna-N gaskets
- Aluminum end caps are standard on 6" diameter open end cartridges
- All 6" diameter cartridge end caps are bonded directly to the media with high strength epoxy or urethane
- 4" diameter cartridge end caps are molded polyester resin or injection molded

### HOW COALESCER CARTRIDGES WORK


Tiny droplets of water contact and adhere to strands of fiberglass. Flow pushes the droplets along the strand until they reach an intersection of strands where they combine with other droplets (coalesce) into large drops.

These large drops are then carried to the outside surface of the cartridge. Having a higher specific gravity than the hydrocarbon fluid, they release and settle to the bottom of the vessel. The larger the drops, the faster and more efficiently they fall out. In general, particle removal efficiency increases with coalescing efficiency.

This is accomplished by employing a tighter, finer filtration media. Flow direction is from inside to outside of the cartridge. This minimizes surface velocity and helps prevent the water drops from breaking up and being carried downstream.







### COMMON APPLICATIONS

- Amine plant feed gas and treated gas
- Suction and discharge of compressors
- Fuel gas purification
- Refine natural gas
- Remove water from shop air

### COMMON LIQUID CONTAMINANTS

- Compressor lubrication oils, water, hydrocarbon condensates. Amines. Glycols. Solvents, Completion Fluids, Brine, and other liquid phase contaminants

## **Coalescer Filter Systems**

TEL 800-821-5373 OR 734-665-8201

FAX 734-665-2214

fiilters@rosedaleproducts.com

www.rosedaleproducts.com

**Application Type** (or what needs to be protected)

PLEASE SUPPLY INFORMATION BELOW:

Date \_\_\_\_\_

Contact \_\_\_\_\_

Company \_\_\_\_\_

Phone \_\_\_\_\_

Email \_\_\_\_\_

Gas specific gravity \_\_\_\_\_

Gas Composition \_\_\_\_\_

Gas viscosity \_\_\_\_\_

Gas type \_\_\_\_\_

Flow \_\_\_\_\_


Pressure \_\_\_\_\_

Temperature \_\_\_\_\_

Required Codes \_\_\_\_\_

Special requirements \_\_\_\_\_

Expected contaminants to remove \_\_\_\_\_





## How To Order

Please provide the following information to build a Coalescer Filter System

- Operating pressure range
- Operating temperature range
- Gas molecule weight, or specific gravity
- Type of liquid contaminant
- Liquid density or specific gravity
- Amount of liquid load
- Design pressure
- Corrosion allowance requirements
- Special design requirements



## How To Order Cartridges

Build an ordering code as shown in the example

### Example:

**28 - 0.1**

#### ELEMENT SIZE

Outside Diameter 2.75"

Inside Diameter 1.50"

Length 30" = **28**

Outside Diameter 4.50"

Inside Diameter 3.25"

Length 36" = **40**

Outside Diameter 6.00"

Inside Diameter 4.00"

Length 40" = **60**

#### MICRON RATING

0.1 Micron 99.98% Efficiency = **0.1**

0.3 Micron 99.98% Efficiency = **0.3**

0.1 Micron 99% Efficiency = **0.1A**

0.3 Micron 99% Efficiency = **0.3A**



## **R Filter and Bulk Media Tanks —**

Rosedale manufactures standard or custom large vessels up to 10 feet in diameter. They are designed to meet all applicable codes and tested to assure they meet the highest standards. The Tank Quotation Request form on the next page lists many of the available features. For more options and information, please contact Rosedale.

### **Manufacturing Capabilities**

- Plant Management
- Engineering/Drafting
- Quality Control
- Safety, Inspection and Training
- Warehouse, Shipping and Handling
- Vessel Fabrication
- Skid and Manifold Fabrication
- Internals Fabrication
- Pipe Spool Fabrication
- Fitting and Welding
- Sandblasting and Coating
- Complete Production Assemblies

#### **TYPICAL APPLICABLE CODES**

- ASME Section VIII, Division I and II, Pressure
- DNV
- Bureau of Veritas

#### **VESSELS**

- API Production Equipment Specs
- AWS D1.1
- ASME B31.3
- NACE



#### **PRESSURE TESTING**

- Hydrostatic (PSI) 2500

#### **NON-DESTRUCTIVE EXAMINATION**


- Radiography (RT)
- Magnetic Particle (MT)
- Liquid Penetrant (LT)
- Ultrasonic (UT)

#### **MAXIMUM TANK SIZE**

- Diameter 10 Feet
- Thickness 2.75 Inch
- Weight 20 Ton

#### **WELDING PROCESS**

- Shielded Metal Arc
- Gas Metal Arc
- Gas Tungsten Arc
- Submerged Arc
- Flux Cored Arc
- STT Welding



## Tank Quotation Request

Requested from: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 City / State / Zip: \_\_\_\_\_  
 Phone: \_\_\_\_\_ Fax: \_\_\_\_\_  
 E-mail: \_\_\_\_\_

### Rosedale Products, Inc.

3730 W. Liberty Road  
 Ann Arbor, MI 48103  
 Tel 800-821-5373 or  
 734-665-8201  
 Fax 734-665-2214



### TANK DATA

Reference (item/project): \_\_\_\_\_

Quote Qty: \_\_\_\_\_

Tank Size (any **two** are required)

Diameter: \_\_\_\_\_

Straight Side: \_\_\_\_\_

End to End: \_\_\_\_\_

Volume (gal. or cu-ft.): \_\_\_\_\_

Type of Top

☐ Dish

☐ Cone

☐ Flat

☐ Open

Type of Bottom

☐ Dish

☐ Cone

☐ Flat

Tank Supports

☐ legs

☐ skirtbase

☐ mounting lugs

☐ saddles

☐ none

Tank Alignment

☐ Vertical

☐ Horizontal

Tank Material

(wetted parts)

☐ Carbon Steel

☐ 304 Stainless

☐ 304L Stainless

☐ 316 Stainless

☐ 316L Stainless

External Attachments Material

(non-wetted parts)

☐ Carbon Steel

☐ 304 Stainless

☐ 316 Stainless

ASME Code?

☐ Yes

☐ No

Thickness

☐ Per ASME Code

☐ Per Mfg. Standard

Other Spec'd: \_\_\_\_\_

Design Pressure: \_\_\_\_\_ PSI

Design Temp: \_\_\_\_\_ °F

Threaded NPT Connections

(anywhere into tank)

NPT Size	Quantity
1/4"	_____
1/2"	_____
3/4"	_____
1"	_____
1-1/2"	_____
2"	_____
3"	_____

Flanged Nozzle Connections

(anywhere into tank)

Flange Size	Quantity	Flange Size	Quantity
1"	_____	10"	_____
1-1/2"	_____	12"	_____
2"	_____	14"	_____
3"	_____	16"	_____
4"	_____	18"	_____
6"	_____	20"	_____
8"	_____	24"	_____

Manway Access Openings

Type	Quantity
12" x 16"	_____
20" w/ Blind	_____
24" w/ Blind	_____
20" Hinged w/ swing-bolts	_____
24" Hinged w/ swing-bolts	_____

Exterior Surface Finish ☐ as welded ☐ prime painted ☐ primed + enamel paint ☐ other - (describe below)

### For Jacketed Vessels

Jacketed Area

☐ Sideshell

☐ Bottom

☐ Both

Type of Jacket

☐ Dimpled

☐ Double-Wall

☐ 3" half-pipe

Jacket Material

☐ Carbon Steel

☐ 304 Stainless

☐ 304L Stainless

☐ 316 Stainless

☐ 316L Stainless

Jacket Flanged Connections

Flange Size Quantity

1" \_\_\_\_\_

1-1/2" \_\_\_\_\_

2" \_\_\_\_\_

3" \_\_\_\_\_

Jacket NPT Connections

NPT Size Quantity

1/2" \_\_\_\_\_

3/4" \_\_\_\_\_

1" \_\_\_\_\_

1-1/2" \_\_\_\_\_

2" \_\_\_\_\_

Jacket Design Pressure: \_\_\_\_\_ PSI

Jacket Design Temp: \_\_\_\_\_ °F

ASME Jacket?

☐ Yes ☐ No

Jacket Insulation Support Rings?

☐ Yes ☐ No



## Rosedale Filter Media Index

			Page
	<b>Filter Performance Guide</b> Determine the filter performance you require.	Micron, Efficiency, Beta Rating Guide	152
	<b>Standard Bags</b> High-capacity filter bags with ratings to 1 micron are available in a wide range of sizes and materials for general use. Special-purpose bags for high-temperature service are also available.	Rosedale Top Standard Felt Standard Mesh Standard OA Standard Teflon® Standard Nomex Polypropylene Top	Economy 1-100 Micron 50-800 Micron Oil Adsorbent High Temperature 1-110 Micron
	<b>Beta Bags</b> Meets the more exacting requirements of fine process filtration and hydraulic and lubricating fluid filtration. Rated by the multi-pass method of filter performance evaluation, allowing direct comparison between Beta Bags and cartridges.	Excellent for Oil and Gas, Hydraulic and Lubrication Industries	8-47 Microns at 98.7 Efficiency
	<b>Beta Bags</b> Meets the more exacting requirements of fine process filtration and hydraulic and lubricating fluid filtration. Rated by the multi-pass method of filter performance evaluation, allowing direct comparison between Beta Bags and cartridges.		
	<b>Graded Density Bags</b> (Membrane Prefilters) Great dirt-carrying capacity is combined with fine filtration efficiency. Excellent prefilters in applications previously requiring cartridges, cutting costs.	Graded Density	1-19 Microns
	<b>X-Tend</b> Rosedale offers the X-TEND filter bag as a balance between increased efficiency and capacity versus cost.	Twice the Size of Standard Bag, Fits Standard Housing	Increase Efficiency
	<b>Vertical Pleated Bag</b> Outperforms standard bags at a similar price	Increases surface area by 50%	Longer Run Times
	<b>The OA Oil Removal Bag</b> All Polypropylene Filter Bag is the perfect answer for removing trace oil and grease from an industrial stream of aqueous-based fluids.	Ideal as a Pre-Filter	Remove from 2 to 16 lb of Oil
	<b>Series OE</b> (Oil/Water Separation Cartridge) The OE cartridges can be used as stand-alone oil water separators, or to enhance or protect other systems.	Oil / Water Separation	Environmental Applications
	<b>High Flow Elements</b> Designed specifically for use with our High Flow Housing Systems. Elements in 40-inch and 60-inch lengths.	1 to 31 Elements in Our High Flow Housings	Up to 400 GPM Per Element
	<b>Surfacem maxx</b> High-performance cartridge provides up to 12 times more dirt-holding capacity	Solvents, Acids, Chemicals, Water Hydrocarbons,	20 Square Feet of Surface Area

			Page
	<b>Bag-Sized Pleated Cartridges</b> Combines the advantages of bags with the best features of cartridges. Like bags, contaminant is trapped inside. Pleated construction packs more surface area in less cubic space.	Pleated Bag Sized  1-110 Microns	174
	<b>Disposable Pleated Cartridges</b> Easily installed in our housings, providing TEN TIMES the surface as standard filter bags.	Disposable Pleated Cartridges  Low Cost High Capacity Filtration	178
	<b>Platinum Series</b> Our line of Platinum absolute-rated filter cartridges offer maximum dirt holding capacity. Micron retention ratings to 0.5 at 99.98%.	Platinum 500 Platinum 700 Platinum 900 Platinum 2040	180
	<b>Stainless Steel Filter Elements</b> These stainless steel cartridge elements overcome the temperature and compatibility limitations of fabric or synthetic fiber cartridges.	Standard Stainless Steel  Rated 5-840 Microns	184
	<b>Poroplate® Filter Elements</b> Sintered Stainless Steel filter elements provide longer life and superior filtration results.	Longer Life, High Dirt-Holding Capacity, Easy Cleaning  3-150 Microns	186
	<b>Pleated Cartridges</b> These cartridges each have pleated, fixed pore media to maximize surface area, prevent particle unloading, and fiber migration. Media include: cellulose, fiberglass, polyester, and polypropylene.	Absolute Pleated Standard Size  Rated to 0.5 Microns	188
	<b>Wound Cartridge</b> Cartridges come in a wide range of materials, lengths, and micron retention ratings. Materials include cotton, acrylics, nylon, and polypropylene.	Standard Wound  All Purpose	190
	<b>Membrane</b> The high flow rates achieved by our cartridges make them an ideal source for varied systems.	GSC-FSC-PS-ES-WS-  General Service-Food, Beverage-Pharmaceutical-Electronics-Water Service-	193
	<b>Baskets</b> Bag filter baskets and basket strainers for a wide range of filter housings.	Cleanable Baskets-Cone Baskets-Replacement Baskets-  Equal or Exceed OEM Specs	203
	<b>Giardia Cryptosporidium Removal</b> Water filtration systems that meet protocols for most states.	NSF 61 Listed, LT2 Compliant	133

## Beta Rating

Use this chart to determine the filter performance you require.

The Product Groups are listed on the left, Micron Sizes are in red, with corresponding Efficiency (blue), and Beta Rating along the top (green).

	EFFICIENCY % BETA RATING	PAGE NO.
<b>PLATINUM 500</b>	PS-520 PS-521 PS-523 PS-525 PS-527 PS-528 PS-529	160
<b>PLATINUM 700/ 40" HIGH FLOW</b>	PS-740 PS-741 PS-743 PS-745 PS-747 PS-748 PS-749	160
<b>PLATINUM 900</b>	PS-940 PS-941 PS-943 PS-945 PS-947 PS-948 PS-949	162
<b>PLEATED HI-E</b>	PL-PEMF/POMF-1 PL-PEMF/POMF-3 PL-PEMF/POMF-8 PL-PEMF/POMF-19	173
<b>PLEATED STANDARD</b>	PL-PE/PO-35 (1 nom.) PL-PE/PO-48 (5 nom.) PL-PE/PO-55 (10 nom.) PL-PE/PO-70 (25 nom.) PL-PE/PO-90 (50 nom.)	157
<b>VERTICAL PLEATED</b>		155
<b>HI-E</b>	PEMF/POMF-1 PEMF/POMF-3 PEMF/POMF-8 PEMF/POMF-19	173
<b>STANDARD</b>	PE/PO-1 PE/PO-5 PE/PO-10 PE/PO-25 PE/PO-50	146
<b>GRADED DENSITY</b>	GD-523 GD-525 GD-527 GD-529	149
<b>BETA</b>	BB-1 BB-10 BB-12	146
<b>GIARDIA</b>	PS-520-PPP-241 GLR-825 PS-740-PPP-356	126
<b>SURFACEMAXX</b>	PLJRPE-10-2	



# INDEX

## F I L T E R P E R F O R M A N C E G U I D E

	30 1.5	50 2	66 3	80 5	90 10	95 20	98 50	98.7 75	98.75 80	99 100	99.8 500	99.9 1000	99.95 2000	99.98 5000	99.99 10000	ELEMENT AREA FT <sup>2</sup>	FLOW RATE GPM*	DIRT HOLDING CAP. (lbs)
										0.25 0.9 1.6 2 9 18 40		<0.5 1.4 2 6.5 17 30 60		0.5 2 5 10 20 40 70		85	30 ↕ 50	8 8 8 10 10 12 12
										0.25 0.9 1.6 2 9 18 40		<0.5 1.4 2 6.5 17 30 60		0.5 2 5 10 20 40 70		120	50 ↕ 100	12 15 15 17 18 20 20
										0.25 0.9 1.6 2 9 18 40		<0.5 1.4 2 6.5 17 30 60		0.5 2 5 10 20 40 70		600	200 ↕ 400	55 75 75 85 90 100 100
					1	1 3 8 19				2 5 19 25					10	25	35 ↕ 100	1.5 3 5 6
						35 48 55 70 90										25	50 ↕ 150	7.5 8 9 10 11
																10F <sup>2</sup>	50	.75
					1	1 3 8 19				2 5 19 25					10	4.4 SINGLE LAYER	20 ↕ 50	0.2 0.25 0.35 0.75
	10 40		20	30	30	35 48 55 70 90	40									4.4 SINGLE LAYER	50 ↕ 110	.25 .30 .35 .40 .50
						1 3 8 19				2 5 19 25		20	30		40	4.4 SINGLE LAYER	20 ↕ 50	0.6 0.65 1.25 2
		1 10 12			3	4 16 37		8 20 47	10							4.4 SINGLE LAYER	20 ↕ 50	0.15 0.35 0.6
													3			4.4 TWENTY SIX LAYER	10	0.5
							10		20	30						20F <sup>2</sup>	50	2.8

\*Per No. 2 size

\*\*Based on water and nominal flow rate

## **R** **FILTER BAG** **Design Details**

### Standard Filter Bag Types

**MOLDED ROSEDALE TOP BAGS** are stocked with polypropylene tops in sizes 1, 2, 3, 4, 8 & 9.

**RING TOP BAGS** are stocked in sizes 1, 2, 3, 4, 8, 9 & 12 with galvanized steel, rings.

**HANDLES** are standard on all bags.

**ALL STANDARD STOCK BAGS** have sewn construction.

### **FILTER BAG FINISH**

Felt filter bags are supplied with a glazed finish to reduce fiber migration. Mesh filter bags are supplied with a plain finish as woven.

Microfiber filter bags have spunbonded covers to prevent fiber migration.

### **CONSTRUCTION**

Standard filter bags are typically manufactured with a metal ring, either galvanized carbon steel or stainless steel, sewn in the top of the filter bag. Woven fabric handles are also sewn.


Another design incorporates a molded plastic top. These tops typically are polypropylene or polyester with molded lifting handles. Various types of tops are available to fit specific manufacturers' housings.

### **All Welded Construction**

All seams and the collar are sonically welded, enhancing filtration quality, eliminating leaks and bypass that may have occurred with sewn seams.



Bag With Metal  
Ring Top



Bag With Molded  
Rosedale Top

Nominal Micron Rating- 50%	High Efficiency Micron Rating- 95%
1	35
5	48
10	55
25	65
50	70
100	110
200	200

### **Felt Filter Bag Micron Rating**

For years filter bag manufacturers have used nominal ratings, i.e., about 50% efficiency for polyester and polypropylene felt filter bags. The table gives the micron ratings at about 95% efficiency.

## Filter Bag Pressure Drop

The graphs give the clean pressure drop through a number 2 size bag for water, 1 CPS @ 68°F

To determine the pressure drop caused by the filter bag, follow these steps:

**Step 1** Select the type of bag, micron rating and flow rate, determine the pressure drop for water, 1 cps @ 68°F, for a size #2 bag.



**Step 2** Correct for bag size from the Bag Size Correction table at the right if the bag size is different than a #2 size.

**Step 3** If the viscosity of the liquid is greater than 1 cps (water@ 68°F), multiply the result from step 2 by the proper correction factor from the Viscosity Correction table at the right.

The value obtained in Step 3 is the clean pressure drop caused by the filter bag.

### SUMMARY

For new applications, the clean pressure drop of the system, housing and bag should be 2.0 PSI or less. The lower the value is, the more contaminant a bag will hold. For applications with low dirt loading, this value can go to 3.0 PSI or more. Consult the factory for recommendations when the clean pressure drop of the system exceeds 3.0 PSI.





**Bag Size Correction**

Bag Size	Dia. x Length	Multiply By
1	7.2 x 16	2.25
2	7.2 x 32	1.0
3	4.3 x 8	9.0
4	4.3 x 14	4.5
8	5.7 x 21	2.25
9	5.7 x 37	1.50

**Viscosity Correction**

Viscosity CPS	Correction Factor
50	4.5
100	8.3
200	16.6
400	27.7
800	50.0
1000	56.2
1500	77.2
2000	113.6
4000	161.0
6000	250.0
8000	325.0
10,000	430.0


Construction	Fiber	Available Micron Ratings																			
		1	2.5	5	10	20	25	30	40	50	75	100	150	200	250	300	400	600	800	1000	1500
Felts	Polyester																				
	Polypropylene																				
Multifilament Meshes	Polyester																				
Monofilament Meshes	Nylon																				
High-Efficiency Microfiber	Polypropylene																				
Oil Removal	Polypropylene																				

Size	Diameter (Inches)	Length (Inches)	Area Ft <sup>2</sup>	Metal Ring Type	Available In Sizes	Molded Rosedale Type	Available In Sizes
1	7.2	16	2.0	Fits Housings Brands: Rosedale Krystil Strainrite Micron Technologies Filtration Systems Parker "G" Style Eaton Filtration Others		Fits Housings Brands: Rosedale Strainrite Micron Technologies	
2	7.2	32	4.5				
3	4.3	8	0.5				
4	4.3	14	1.0				
5	6.1	20	2.8				
7	5.7	15	1.5				
8	5.7	32	2.0				
9	5.7	32	3.0				
12	8.4	34	5.5				
X01	5	20	2.0				

### MOLDED ROSEDALE TOPS - RPO STYLE

Filter bags with molded Rosedale tops require no filter bag hold down devices. As the differential pressure in the application increases, the integrity of the seal improves. Polypropylene tops are standard with polyester optional for temperatures over 200°F, or for chemical capatibility.

**THE MOLDED ROSEDALE TOP OFFERS THE BEST BAG-TO-HOUSING SEAL IN TODAY'S MARKETPLACE, IN ADDITION TO BEING THE EASIEST TO INSTALL AND REMOVE.**



FILTER BAG WITH MOLDED ROSEDALE TOP JUST PRIOR TO INSTALLATION IN BASKET HOLDER

FILTER BAG WITH MOLDED ROSEDALE TOP INSTALLED IN HOUSING

	<p><b>FELT</b> filter bag materials are made from synthetic fibers in polypropylene or polyester. The proper combination of fiber diameters, weights and thickness results in an economical depth type filter media. Polypropylene and polyester bags are supplied with a glazed finish to reduce fiber migration. These bags have a nominal micron rating. Filter efficiency is about 50%.</p>	<p>Depth Felt Filter Media Traps Dirt Particles</p>
	<p><b>MULTIFILAMENT MESH</b> materials are offered in polyester and are woven from threads made of small fibers twisted together. Bags made of this material are low cost and considered disposable. They have lower efficiencies than the monofilament mesh. Filter efficiencies are about 80%.</p>	
	<p><b>MONOFILAMENT MESH</b> is offered in nylon and is a woven material. Each thread is a single filament. The openings are square. They have excellent strength and are considered to be cleanable. Filter efficiency is 90% or more.</p>	<ul style="list-style-type: none"> <li>Operates on the principle of surface filtration</li> <li>Wide range of micron ratings</li> <li>Reusable or disposable</li> <li>Non-fiber releasing</li> <li>Good efficiencies</li> <li>High contaminant quantities under correct conditions</li> </ul>
	<p><b>MICROFIBER</b> filter bags provide high efficiency and high contaminant holding capacity at low ratings. Bags are available in polypropylene. Filter efficiency is 95% or more.</p> <p>MICROFIBER polypropylene filter bags also can remove oil from water and other liquids. Optimized designs are called "OIL REMOVAL BAGS".</p>	



## OTHER BAG TYPES AND DESIGNS

**500 SERIES 3M TYPE** multiple layer filter bags with microfiber filter layers and felt prefilter layers. Up to 5 layers of felt. See page 162.

**DOUBLE & TRIPLE LAYER** felt bags where the micron rating of the layers are designed to optimize service life.

**SPECIAL SIZE & DESIGN** bags are available in all materials and most micron ratings.

**OIL REMOVAL BAGS** require a special design to obtain to result in the largest surface area of fibers in a bag for maximum oil removal capacity. These are standard in micron ratings of 10 and 25. See page 166.

## FILTER BAG HOLD-DOWNS

Adjustable filter bag hold-downs for Size #1 and #2 bags are available for side entry housings manufactured by:

Filter Specialists, Inc. / Micron Technologies / Krystil Klear / Strainrite / Other Side Entry Brands

Available in polypropylene, they provide additional positive filter bag hold-down capabilities for critical applications where necessary. It is suitable for ring top bags and bags with molded plastic tops. It is necessary for many bags with molded tops and ring bags if the bag manufacturer improperly designs and manufactures them.

A FILTER BAG HOLD-DOWN IS NOT REQUIRED WHEN USING FILTER BAGS WITH MOLDED ROSEDALE TOPS.

See page 215.

## How To Order Build an ordering code as shown in the example

**Example: PE - 25 - G - 2 - RPO - WE**

### MATERIALS & MICRON RATING

Beta (Polyester) = **BB**

Microns = **1, 10, 12**

Polyester Felt = **PE**

Microns = **1, 5, 10, 25, 50, 100, 200**

Polypropylene Felt = **PO**

Microns = **1, 5, 10, 25, 50, 100**

Polyester Multifilament Mesh = **PEM**

Microns = **75, 100, 150, 200, 250, 300, 400, 600, 800**

Nylon Monofilament Mesh = **NMO**

Microns = **5, 10, 25, 50, 75, 100, 150, 200, 250, 300, 400, 600, 800**

Polypropylene Microfiber = **POMF**

Microns = **1, 3, 8, 19**

Polyester Microfiber = **PEMF**

Microns = **1, 3, 8, 19**

Oil Removal = **OA**

Microns = **10, 25**

### BAG CONSTRUCTION

**WE** = Welded Construction  
(Not available on POMF or PEMF)

**No Symbol** = Sewn (BB)

### BAG STYLES

**S** = Galvanized Carbon Steel Ring

**S-SS** = 304 Stainless Steel Ring

**RPO** = Molded Polypropylene Rosedale Top

**RPE** = Molded Polyester Rosedale Top

### BAG SIZES (Inches)

	Dia.	x	Length
<b>1</b>	= 7.2	x	16
<b>2</b>	= 7.2	x	32
<b>3</b>	= 4.3	x	8
<b>4</b>	= 4.3	x	12
<b>7</b>	= 5.7	x	15
<b>8</b>	= 5.7	x	21
<b>9</b>	= 5.7	x	32
<b>12</b>	= 8.4	x	34

### BAG FINISH

**G** = Felt - Glazed or Singed  
(Standard with RPO and RPE top)

**P** = Plain Finish

## **R** Rosedale Beta Bag® Filters

Filter bags for fine filtration requirements

After years of supplying filter bag products to the process industries, Rosedale has developed a new filter bag that meets even more exacting requirements, extending their use to finer process filtration and to hydraulic and lubricating fluid filtration. Rosedale Beta Bag® filter bags are made of a unique multilayer polyester felt, encased in spun-bonded nylon to prevent possible migration of bag material into the fluid stream. They're rated by the multi-pass method of filter performance evaluation, so that direct comparison can be made between Beta Bag® filters and cartridges of rigid construction using cellulose or synthetic elements, pleated or non-pleated. They compare very well:

- Because disposable Rosedale Beta Bags® are fitted into and supported by perforated-metal baskets, you need not be concerned with filter collapse, flow fatigue, or filter end-load problems.
- Beta Bags® can be installed and removed from their housings in a fraction of the time required to service rigid cellulose or synthetic element cartridge filters.
- Beta Bags® cost less than cylindrical filter cartridges, and they fold flat for more compact storage.
- Polyester/nylon bag materials are more resistant to the chemical additives in today's hydraulic and lubricant fluids (especially the high water base fluids), as well as the chemicals in Table IV.
- Prevention of possible media migration is assured by the spun nylon cover.

**EXCELLENT FOR USE IN THE PROCESS, OIL AND GAS, HYDRAULIC AND LUBRICATION INDUSTRIES**



### **The Multi-Pass Test Method For Evaluating Filter Element Performance** (OSU-F2, ISO 4572, ANSI B93.31-1973, NFPA T3.10.8.8-1973)

In this test procedure ACFTD (AC Fine Test Dust) is put into a reservoir ahead of a test filter. The test dust is comprised of many particle sizes (see Table II).

During the test, the flow rate through the filter is held constant, and test dust is added continuously. Contaminant not stopped by the filter is recirculated (hence the term "multi-pass").

At predetermined pressure drops across the filter, fluid samples are taken upstream and downstream of the filter. Using automatic particle counters (per ANSI B93.28-1973), the samples are analyzed for the number of particles per milliliter greater than a selected size. These counts are used to calculate "Beta ratios". **A Beta ratio is an accurate indication of how the filter performs throughout the life of the filter. The Beta ratio is an average filtration rating.**

A typical Beta ratio is expressed as B (Beta) 10 (particle size) = 16 (ratio), or  $B_{10} = 16$  to 1 reduction of dirt at selected micron rating. Table I gives the Beta ratios for the three Beta Bag® micron-rated bag materials.

Table I

### Rosedale Beta Bag® Beta Ratios


Multi-pass tests are at 20 gpm flow, with terminal pressure drop of 15 psi. Standard sewn bags were tested, in standard housings.

Beta Bag® Micron Rating (nominal)	Mean ACFTD retention size Equals 50% filter efficiency (nominal rating)	Effective ACFTD retention size Equals 95% filter efficiency	Maximum ACFTD retention size Equals 98.7% filter efficiency (absolute rating)
BB-1	$B_1 = 2$ (1 um nominal)	$B_4 = 20$ (4 um)	$B_8 = 75$ (8 um absolute)
BB-10	$B_{10} = 2$ (10 um nominal)	$B_{16} = 20$ (16 um)	$B_{20} = 75$ (20 um absolute)
BB-12	$B_{12} = 2$ (12 um nominal)	$B_{37} = 20$ (37 um)	$B_{47} = 75$ (47 um absolute)

Table II

### ACFTD Composition

Range of Particle sizes (micrometers)	Distribution by weight (percent)
0-5	39
5-10	18
10-20	16
20-40	18
40-80	9



### Selecting A Rosedale Beta Bag®

1. Determine the micron rating needed. For hydraulic fluids, the BB-1-rated bags should be considered for high-pressure circuits, the BB-10 for common service, and the BB-12 for low-pressure service. For process liquids, the BB-1 rated bags are recommended for use as pre-filters for membrane filters. Automotive clear coatings are being successfully filtered with BB-10 and BB-12 rated bags.
2. The Pressure Drop Versus Flow Chart shows specific flow rates achieved through various sizes of Beta Bags® using 32 (water) and 80 SSU viscosity liquids. Pressure drops can be read directly for these viscosity levels.
3. If your liquid viscosity level is higher than 80 SSU, you can use a correction factor to determine what your pressure drop will actually be.
4. Using Table III find your actual SSU level and multiply the pressure drop of interest to you by the correction factor shown. You can interpolate easily since the relationship is linear. For example, a viscosity of 280 SSU would have a correction factor of 3.5.
5. Example: A clean BB-1 rated No. 8 size Beta Bag® at 20 gpm will impose a pressure drop of 2.7 psi (with 80 SSU liquid). For use with 320 SSU oil, the pressure drop will be 2.7 times 4 (the correction factor), or 10.8 psi.

Table III

SSU	Viscosity CPS	Correction Factor
80	15	1
160	35	2
240	55	3
320	70	4
400	90	5

Table IV

**Compatibility With**

Bag Materials (Fiber)	Organic Solvents	Animal Vegetable & Petro Oils	Micro-organisms	Alkalies	Organic Acids	Oxidizing Agents	Mineral Acids	Temperature Limitations (max. deg F)
Polyester Nylon	Excellent Excellent	Excellent Excellent	Excellent Excellent	Good Good	Good Fair	Good Poor	Good Poor	325 325

**Design Details**

All Beta Bags® have a metal retaining ring sewn in their openings. Standard ring material is carbon steel, with a 316 stainless steel optional. They hold the bag in place and prevent fluid bypassing the element.

Heavy-duty handles, sewn to the reinforced bag lip, are a standard feature. They make bag removal faster and easier.

**How To Order**

Build an ordering code as shown in this example

**Example: BB - 10 - 2 - SS**

**BETA BAG®**

**MICRON RATING** (nominal)  
 1 micron = **1**  
 10 micron = **10**  
 12 micron = **12**

**BAG SIZE** (dimensions in inches)  
**Dia. X Length Symbol**  
 7-1/16 x 16-1/2 = **1**  
 7-1/16 x 32 = **2**  
 4-1/8 x 8 = **3**  
 4-1/8 x 14 = **4**  
 5-5/8 x 15 = **7**  
 5-5/8 x 21 = **8**  
 5-5/8 x 32 = **9**  
 8-3/8 x 32 = **12**

**OPTIONS**  
 Carbon steel ring = **No Symbol**  
 Stainless steel ring = **SS**



## Graded Density

Depth filtration for enhanced clarity-  
For filtration to 1.0 micron

Rosedale's Graded Density (GD) Fat Bags® bags have approximately four times the dirt holding capacity of standard bags at equivalent filtration levels. These bags have 9 layers of material, each with 4.4 sq. ft. of surface area. GD bags are easier to install and remove, require less room in storage and disposal, and prevent the contaminant wash off downstream associated with cartridges.

They produce excellent results when used as a pre-filter for membrane filtration. They will retain a large quantity of contaminant that will unnecessarily clog the membrane. The bags are available in either all polyester or all polypropylene construction. **Polyester should be used** where oil adsorption is not desirable or where higher temperatures are required.

### Filtration Level

These bags have been tested by an independent laboratory to determine the filtration efficiency of the media used in each of the filter bags. The efficiencies for polyester and polypropylene are identical.

Model Number	523	525	527	529
EFFICIENCY	MICRON RATING			
95.0%	1.0	3.0	8.0	19.0
99.0%	2.0	5.0	19.0	25.0

The test was conducted using AC Fine Test Dirt interfaced into clean water at 20 GPM.

### Dirt Carrying Capacity

Tests that were conducted using a size 2 bag and AC fine test dirt at 20 GPM, show dirt holding capacities for the following filtration ratings (at 20 psi).

Micron Rating (95%)	Model	Dirt Holding Capacity (in grams)
1.0	523	267
3.0	525	296
8.0	527	573
19.0	529	870


Pressure drop at 50 gpm flow (water) and specified micron rating using a Rosedale Model 8 (8-30) filter.

### Design Details

Graded Density Bags have a 304 stainless steel retaining ring sewn in their opening. Heavy-duty handles, sewn to the reinforced bag lip, are a standard feature. They make bag removal faster and easier.

The bags are sewn, then turned inside out to avoid leakage through the threads. They are also made with sewn, fully-shaped bottoms to enhance the pressure capacities of the bags.

There are two sizes available. Size 1 is 7 inches by 16 inches. Size 2 is 7 inches by 32 inches.



### How To Order

Build an ordering code as shown in this example

<b>Example:</b>	<b>GD - PO - 523 - 1 - RPO</b>
<b>GRADED DENSITY = GD</b>	
<b>FIBER</b>	
Polyester = <b>PE</b>	
Polypropylene = <b>PO</b>	
<b>MICRON RATINGS (95%)</b>	
1.0 Micron = <b>523</b>	
3.0 Microns = <b>525</b>	
8.0 Microns = <b>527</b>	
19.0 Microns = <b>529</b>	
<b>BAG SIZE (nominal in inches)</b>	
Dia. x Length	Symbol
7-1/16 x 16 = <b>1</b>	
7-1/16 x 32 = <b>2</b>	
<b>ROSEDALE TOP BAG STYLES</b>	
Polypropylene = <b>RPO</b>	
Polyester = <b>RPE</b>	



## **R X-TEND Filter Bags Offer Additional Surface Area for Increased Filtration Efficiency**

### **Sonically Welded Seams and Integral Plastic Collar Further Increase Efficiency**

Rosedale offers the new X-TEND filter bag as a balance between increased efficiency and capacity versus cost. It offers about twice the surface area of a standard bag. The integral hard plastic collar makes installation and disposal easier, as there is no metal to worry about. These bags do require the use of a special cone basket. It supports the inner layer, ensuring the full surface area is utilized, maintaining optimum filtration.

As an added feature, all seams and the collar are sonically welded, greatly enhancing filtration quality, reducing or eliminating leaks and bypass that may have occurred with sewn seams. The X-TEND bag is about twice the length of a standard bag, and you simply tuck the bottom of the bag back up into the main cylinder of the element. When the bottom of the bag reaches the neck of the collar, the bag should now be the size of a standard bag, and fit most housings.



### **Filtration Level**

These bags have been tested by an independent laboratory to determine the filtration efficiency of the media used in each of the filter bags. The efficiencies for polyester and polypropylene are identical.

Efficiency	Micron Rating										
95%	1	3	8	19	35	48	55	65	70	90	110



### Design Details

These bags have a plastic collar sonically welded into their opening. This collar has integral handles as a standard feature. They make removal faster and easier.

The standard felt finish is glazed. The micro fiber bags are sonically welded, then turned inside out, increasing the protection against leakage through the seam.

These bags are available in standard bag sizes.



## How To Order

Build an ordering code as shown in the example

### Example:

**XTND - PE - 35 - 2 - CB**

X-Tend Bag

= **XTND**

### FIBER

Polyester Felt

= **PE**

Polypropylene Felt = **PO**

### MICRON RATING (95% efficiency)

35.0 Micron

= **35**

48.0 Micron

= **48**

55.0 Micron

= **55**

65.0 Micron

= **65**

70.0 Micron

= **70**

90.0 Micron

= **90**

110.0 Micron

= **110**

### CONE BASKET

**CB** = Cone Basket

**No Symbol** = No Basket

### BAG SIZE

(nominal in inches, final assembled size)

Dia x Length

**2** = 7-1/16 x 32

## **Vertical Pleated Bag**

Increases surface area by 50%

With proprietary advances in pleat profile and rigidity, graded density material, and utilized surface area, our vertical pleated bag outperforms standard bags at a similar price.

### Features

- Fits all standard #1 and #2 size bag housings
- Protects final filter media from premature blinding, and increases filter life
- Fewer filter change outs reduces cost
- Reduced filter bag disposal cost
- Longer, uninterrupted processing/run times

### Applications

- Glycols
- Adhesives
- Inks
- Amine
- Paints/Coatings
- Beverages
- Plating Solutions
- Coolants
- Resins
- Cutting Fluids
- Petro-Chemicals
- Cooling Towers
- Down Well Injection
- Fine Chemicals



## **How To Order** Build an ordering code as shown in the example

**Example: PE - 5 - P2 - RPO - IP**

<b>MATERIALS &amp; MICRON RATING</b> Polyester Felt = <b>PE</b> Microns = <b>5</b> Polypropylene Felt = <b>PO</b> Microns = <b>1,5,10,25,50,100</b>		<b>INNER PLEAT</b> <b>IP</b> = Inner Pleat	
<b>BAG SIZE</b> <b>Dia. x Length</b> 7 x 16 = <b>P1</b> 7 x 30.5 = <b>P2</b>		<b>BAG STYLES</b> <b>RPO</b> = Rosedale Top <b>S</b> = Stainless Steel Snap Ring	

## **R The OA All Polypropylene Oil Removal Filter Bag**

**The perfect answer for removing trace oil and grease from an industrial stream of aqueous-based fluids**


Bag can be designed to remove from 2 to 161b. of oil by increasing layers or adding strips which add to the surface area and increase efficiency, structural strength, and filter life.

OA Bags are designed with a cover for the prevention of fiber migration and include reinforced lift handles to facilitate its removal. If waste storage is a problem, the OA Bag can be completely disposed of by Incineration.

The Ideal oil removal system is the OA bag as a pre-filter and a high-efficiency bag as the final polish filter.

### **Features**

- Micron rated and able to remove oil from aqueous based fluids.
- Standard with reinforced handles for easy removal.
- Maximum oil absorption with minimum pressure drop.



**R** **How To Order** Build an ordering code as shown in the example

**Example: OA - 20 - 7 - S - OTS**


**ALL POLYPROPYLENE OIL REMOVAL FILTER BAG = OA**

**MICRON RATING**  
10 Micron = **10**  
20 Micron = **20**

**BAG SIZES (Inches)**  
**Dia. x Length**  
7.2 x 16 = **1**  
7.2 x 32 = **2**  
4.3 x 8 = **3**  
4.3 x 21 = **4**  
5.7 x 15 = **7**  
5.7 x 21 = **8**  
5.7 x 32 = **9**  
8.4 x 34 = **12**

**OPTION**  
**OTS** = Oil-Thirsty® Strips

**BAG STYLES**  
**PO** = Polypropylene Ring  
**RPO** = Molded Polypropylene Rosedale Top  
**S** = Carbon Steel Ring  
**SS** = Stainless Steel Ring



## **Series OE Oil/Water Separation Cartridge**

Oil Eliminator cartridges utilize media that can economically reduce hydrocarbon contamination in aqueous solutions. Our radial flow designs provide the largest possible surface area, reducing the media bed depth. The OE Series is capable of removing very high concentrations of free oil, dispersed oil, as well as surfactant based emulsions, and dissolved hydrocarbons to non-detectable levels.

These cartridges can be used as stand-alone oil water separators, or to enhance or protect other systems.

### 3 Styles

#### **The Oil Eliminator OE™**

Our top performing OE cartridge capable of breaking the IMO 107(49) surfactant based emulsion in a single pass. The special patented non swelling organic clay allows the cartridge to be filled with 100% active oil absorbing media, providing greater oil holding capacity.

#### **The ECO™**

The ECO is our GREEN cartridge, made using a uniquely processed post consumer recycled media. The ECO has the ability to remove soluble oils from water in a single pass. It can be used alone or following our standard Oil Eliminator™ cartridge to bring the effluent down to non-detect levels. US patent pending No. 13/051,872

#### **The Oil Eliminator NF™**

The OENF cartridge uses a combination of adsorbing media and nano-technology to remove high concentrations of free and oil emulsions. This high area, pleated cartridges can provide particle removal of 0.2 u @ 99.9% efficiency. The OENF's adsorptive characteristics remove negatively charged particles such as bacteria, organic contaminants, heavy metals such as copper, iron, lead, and tin. US patent pending No. 12/582,684



### Specifications

#### **Materials of Construction:**

Absorbent: ..... Polypropylene & Proprietary Medias

Support Construction: ..... 100% Polypropylene

Seal Material: ..... Buna-N

Maximum Recommended Operating Conditions:

Temperature: ..... 150°F (65°C)

Pressure D/P: ..... 75 psid (5 bar)

Maximum Flow Rate:

Series 250: ..... 1 gpm per 10"

Series 450: ..... 5 gpm per 10"

Series 650: ..... 20 gpm  
(recommended flow < 50% of max.)

Change Out Pressure Drop: ..... 35 psid (2.4 bar)

#### **Approximate Oil Capacity Removal (10" Length):**

OE 250 ..... 160-200 ml

OE 450 ..... 500 ml

OE 650 ..... 3 l



## How To Order

Build an ordering code as shown in the example

### Features

- Meet governmental regulations
- Reduced maintenance due to fouling
- Can be incinerated
- Minimal pressure drop
- Withstands harsh environments
- Industry standard sizes and end caps
- Operating temperature to 65°C
- Withstands high Dp up to 5 bar
- Typically removes better than 99% in a single pass

### Applications

- Commercial bilge and ballast water
- Post oil/water separator polishing
- Oil field produced water
- Pipeline maintenance activities
- Hydraulic tramp oil removal
- Parts washing and plating baths
- Compressor condensates
- Boiler blow down
- Membrane pretreatment
- GAC pretreatment
- Pump sump discharge

#### SERIES 250



#### Example: 250-OE-2-10-A-1

##### SERIES 250

The Oil Eliminator = **OE**  
 The Oil Eliminator ECO = **ECO**  
 The Oil Eliminator NPM = **NF**

##### Diameter

2.75" = **2**

##### Length

9.875" = **10**

20.0" = **20**

30.0" = **30**

40.0" = **40**

##### End Cap

**1** = Double Open Ended

**2** = Single Open Ended  
 (222 O-ring / Flat Top)

##### Core

**A** = Standard

**S** = Special

#### SERIES 450



#### Example: 450-OE-2-10-A-1

##### SERIES 450

The Oil Eliminator = **OE**  
 The Oil Eliminator ECO = **ECO**  
 The Oil Eliminator NPM = **NF**

##### Diameter

4.50" = **4**

##### Length

9.875" = **10**

20.0" = **20**

##### End Cap

**1** = Double Open Ended

##### Core

**A** = Standard

#### SERIES 650



#### Example: 650-OE-2-10-A-1

##### SERIES 650

The Oil Eliminator = **OE**  
 The Oil Eliminator ECO = **ECO**  
 The Oil Eliminator NPM = **NF**

##### Diameter

6.50" = **6**

##### Length

27.50" = **27**

31.0" = **30**

##### End Cap

**3** = Single Open Ended  
 (226 O-ring / Handle Top)

##### Core

**A** = Standard

## Rosedale High Flow Elements

Designed specifically for use with our High Flow Housing Systems

The housings are available in a variety of sizes to accommodate from 1 to 31 filter elements in 40-inch and 60-inch lengths.

- Flow rates up to 400 gpm per element
- Removal Ratings (microns) 0.5, 1, 5, 10, 20, 40, 70 @ Beta 500 (99.8% efficiency)
- Maximum Operating Temperature 160 °F (71 °C)
- Maximum Differential Pressure 50 psid @ 68°F (3.4 bar @ 20°C)
- Recommended Change-out Differential Pressure 35 psid @ 68°F (2.4 bar @ 20°C)
- Bag restrainer expands bag fully during filtration.




Model 18


## The High Flow Housings

High Flow housings can accommodate from 1 to 31 filter elements. Larger housings are available upon request. The horizontal style maximizes ease of operation, while minimizing the system's footprint.

- Horizontal mounting configuration
- Hinged cover for easy element change-outs
- Standard pressure / temperature ratings to 300 psig and 250 °F
- Available in Carbon Steel, 304, or 316 Stainless Steel
- 40" and 60" element lengths
- ASME Code design




**TYPICAL ROSEDALE HIGH FLOW SYSTEM**



**Rosedale System**

7 Cartridges / 24" Diameter Housing

**REPLACES**



**Competitive System**

125 Cartridges / 36" Diameter Housing  
2000 GPM SYSTEM (7571 LPM)




DPU O-Ring Seal

See page 48  
for High Flow  
Housings


## Rosedale High Flow Filtration Systems

- Flow rates up to 400 gpm per element
- Absolute-rated for consistent product quality
- Operator-friendly cartridge and housing system
- Horizontal mounting configuration


### Dirt Holding Capacity



### Flow Rate



### Efficiency



## How To Order Element

Build an ordering code as shown in the example

### Example: DP-605-P60-1-V

#### Rosedale High Flow

7.2-Inch Diameter = **DP**

#### High Flow

6.32-Inch diameter = **DPU**

#### MICRON RATING @ Beta 5000

0.5 Micron = **600\***

2 Micron = **601\***

5 Micron = **603**

10 Micron = **605**

20 Micron = **607**

40 Micron = **608**

70 Micron = **609**

\*Requires Caps 1 or P

#### SEAL MATERIAL

**EPR** = No Symbol

**V** = Viton®

**B** = Buna

**SA** = Santoprene

#### CAP STYLE

**F** = Flare Cap (No seal required, DP Only)

**1** = O-ring Cap (7.32 Dia. DP Only)

**P** = O-ring Cap (6.32 Dia. DPU Only)

#### LENGTH

**40** = 40.5"

**60** = 60.5"

#### MATERIAL

**P** = Polypropylene

**G** = Glass

**R** = Polyester

## **R** **NEW SurfaceMaxx Series Bag-Sized Cartridges**

High-performance cartridge provides up to 12 times more dirt-holding capacity

The new Rosedale filter cartridge traps contaminants inside, preventing "WASHOFF" when removing spent or dirty cartridges. They provide larger surface areas and greater dirt holding capacities than standard bags. They are the ideal solution when frequent servicing of filters is a problem.

### **Construction**

Rosedale bag-sized pleated cartridges are unique. Twenty square feet of high efficiency polyester material pleated in a supported construction. This ensures flow cannot be pinched off. It also greatly strengthens the overall integrity of the element. The top sealing ring and cartridge bottom are made of polyester.

### **Applications**


Fluid processing: Solvents, acids, chemicals, hydrocarbons, water and other fluids used in refinery, chemical and petrochemical processing.

### **Features**

- Available in standard bag size 2
- Low pressure drop



### **Add Area**





## Product Specifications

Filter Composition- 100% Polyester

Surface Area: 20 ft<sup>2</sup>

Nominal Size: 7"D x 26"L (178 x 660 mm)

Recommended change out differential pressure: 15 PSID



## How To Order

Build an ordering code as shown in the example

### Example:

#### MODEL

Polyester element

= **PLJRPE**

#### MICRON RETENTION LEVEL

10 Micron

= **10**

### PLJRPE - 10 - 2

#### CARTRIDGE SIZE/LENGTH

**2** = Standard Bag Size



## **R** PL Series Bag-Sized Cartridges

Absolute-rated units  
provide up to 12 times more  
dirt-holding capacity

Rosedale has combined the best features of filter bags and cartridges into one single unit. Like bags, these bag-sized pleated cartridges are easy to handle and trap contaminant inside, preventing "WASH OFF" when removing spent or dirty cartridges. Like cartridge elements, they provide larger surface areas and greater dirt-holding capacities than standard bags. They are the ideal solution when frequent servicing of filters is a problem.


### Construction

Rosedale bag-sized pleated cartridges are unique. Twenty-five\* square feet of high efficiency material is sandwiched between two flow-enhancing, coarse-mesh screens, and then pleated in a supported construction. This supported pleat construction ensures flow cannot be pinched off. It also greatly strengthens the overall integrity of the element. The seams in these units are ultrasonically welded, not sewn, to prevent leakage or contamination bypass. The top sealing ring and cartridge bottom, made of solid molded polypropylene, are sonically welded to the pleated cylinder.


### Features

- Eleven micron retention ratings from 1 to 110 at 95% efficiency, are available
- Three different top sealing ring designs - one to fit your needs
- Available in standard bag sizes 1 and 2, to fit housings 8-15 and 8-30
- Low pressure drop

\*For Size 2 cartridge, Size 1 cartridge has 13 square feet of material.




R1 Design - Flared  
RPO Rosedale Top (standard)






## Supported Medium Means No Breakthrough


### A. Section of Supported Filter Element



### B. Unsupported Element Section



Cyclic flow, cyclic pressures, and increasing  $\Delta P$  as the element loads with dirt cause unsupported medium to crack through and become a "non-filter."



Schematic showing single-pass efficiency test

## Materials

These elements use our unique high-efficiency microfiber material. Polyester or polypropylene microfibers and standard fibers are variably calendered to produce a single layer of our high-efficiency microfiber felt. This unique construction provides filtration to 1 micron at 95% efficiency. A real rating for the real world, consistently giving the same level or performance from batch to batch.

## Greater Capacity Means Longer Life

### FILTRATION LEVEL

These elements have been tested using the Single-Pass Efficiency Test (see diagram) using water and AC Fine Test Dust. Water is passed through an initial pre-filter (at 0.45  $\mu$ ), after which contaminant is injected into the water line. An automatic particle counter analyzes the number of particles per milliliter greater than a selected size, before the water enters the filter. The water then passes through the test filter, and the effluent is analyzed for the number of those same-size particles. The number of particles removed provides the efficiency rating. For example, if after the single pass, 95 percent of the particles are removed, then the filter is 95 percent efficient at the specified micron rating.

### FILTRATION EFFICIENCY

Using the single pass efficiency test, we've determined the following efficiency ratings for our pleated cartridges. Real ratings are consistently accurate and reliable, time and time again.

# MICROFIBER GRADES

Model Number	PL-PEMF-1.0 PL-POMF-1.0	PL-PEMF-3.0 PL-POMF-3.0	PL-PEMF-8.0 PL-POMF-8.0	PL-PEMF-19.0 PL-POMF-19.0
EFFICIENCY	MICRON RATING			
95%	<b>1</b>	<b>3.0</b>	<b>8.0</b>	<b>19.0</b>
99%	<b>2</b>	<b>5.0</b>	<b>19.0</b>	<b>25.0</b>

# RECOMMENDED MAXIMUM FLOW RATE (GPM / ELEMENT) AT 1.0 PSID

Element Size	Model Number		Viscosity
	PL-PEMF 1-19 PL-POMF 1-19	PL-PE 35-110 PL-PO 35-110	
P1	50 GPM	75 GPM	1 CST
P2	100 GPM	150 GPM	1 CST

# STANDARD FIBER GRADES

Model Number	PL-PE-35.0 PL-PO-35.0	PL-PE-48.0 PL-PO-48.0	PL-PE-55.0 PL-PO-55.0	PL-PE-65.0 PL-PO-65.0	PL-PE-70.0 PL-PO-70.0	PL-PE-90.0 PL-PO-90.0	PL-PE-110.0 PL-PO-110.0
EFFICIENCY	MICRON RATING						
95%	<b>35.0</b>	<b>48.0</b>	<b>55.0</b>	<b>65.0</b>	<b>70.0</b>	<b>90.0</b>	<b>110.0</b>

If fluids with viscosities greater than 1 CST are used, divide the flow by the correction factor obtained below.

If your viscosity is not listed, choose the next highest viscosity from the chart and use that correction factor.

Fluid Viscosity		Correction Factor
SSU	CPS	
80	15	1.2
160	35	2
240	55	3
320	70	4
400	90	5
480	110	6
560	130	7
640	150	8
720	180	9
800	260	10

For example, to filter a fluid having a viscosity of 55 cps using a PL-PEMF P2 element the equation is as follows:

$$\text{Corrected Flow Rate} = \frac{\text{Max Flow Rate}}{\text{Correction Factor}} = \frac{100}{3} = 33 \text{ GPM}$$



## How To Order

Build an ordering code as shown in the example

**Example: PL - R1 - PEMF - 1 - P1**

**BAG-SIZED PLEATED CARTRIDGE = PL**

### TOP SEALING RING DESIGN

Flared Polypropylene (P1 - P2)

Solid Polypropylene (P3 - P9)

= R1

= R2

### HIGH EFFICIENCY MATERIAL

High-Efficiency Microfiber Polyester

High-Efficiency Microfiber Polypropylene

High-Efficiency Standard Polyester

High-Efficiency Standard Polypropylene

= PEMF

= POMF

= PE

= PO

### BAG SIZE

Symbol Dia. x Length

P1 = 7-1/16 x 11-1/8

P2 = 7-1/16 x 24

P3 = 4-1/8 x 5-1/16

P4 = 4-1/8 x 11-1/16

P7 = 5-5/8 x 10-3/4

P8 = 5-5/8 x 16-1/8

P9 = 5-5/8 x 26-3/4

### MICRON RATING

(95% efficiency)

1 = 1.0 Micron

3 = 3.0 Micron

8 = 8.0 Micron

19 = 19.0 Micron

Microfiber  
Only- PEMF  
and POMF

35 = 35.0 Micron

48 = 48.0 Micron

55 = 55.0 Micron

65 = 65.0 Micron

70 = 70.0 Micron

90 = 90.0 Micron

110 = 110.0 Micron

Standard  
Felt Only-  
PE and PO

### CHEMICAL COMPATIBILITIES

EXCELLENT

GOOD

#### Bag Materials (Fiber)


Polyester Polypropylene

	Polyester	Polypropylene
Organic Solvents	EXCELLENT	EXCELLENT
Animal Vegetable & Petro Oils	EXCELLENT	EXCELLENT
Micro-organisms	EXCELLENT	EXCELLENT
Alkalies	GOOD	EXCELLENT
Organic Acids	GOOD	EXCELLENT
Oxidizing Agents	GOOD	GOOD
Mineral Acids	GOOD	GOOD

Temperature Limitations, 225°F.

**Note:** For more complete information on chemical compatibilities, refer to our web site.

### DIRT HOLDING CAPACITY



## **R Low-Cost, High-Capacity Disposable Bag-Sized Pleated Cartridges**

For Models 8, LCO, NCO, and  
Multi-Bag Filters

These new elements from Rosedale are easily installed in our standard housings. The PLRICU cellulose filter provides 10 TIMES the surface area of standard filter bags, and the PLRIPF polyester felt provides 6 TIMES the area. Also available; a pleated element insert and a self contained cartridge/basket combination. These low cost dirt gluttons provide superb capacity with filtration performance as high as 99% efficiency.

### **Features**


- Available with or without metal cage
- Seals in a standard strainer basket
- Over 50 square feet of surface area
- Beta 100 (99%) Retention Levels
- Longer Element Life provides improved system efficiency

### **Benefits**

- Fewer Change-outs required
- Less Downtime
- Improved quality due to improved retention ratings
- Lower Maintenance and Labor Costs
- Reduced Operator Exposure
- Recyclable with no metal (optional)

### **Ideal for Coolants**

PLRICU- Cellulose Filter







### **General Use**

PLRIPF- Polyester Felt



Recyclable styles with no  
metal pleated cartridge





Model PB - Basket style pleated cartridge with metal cage

## How To Order

Build an ordering code as shown in the example

### Example:

**PLRICU - 10 - 2**

#### MODEL

Cellulose element only style  
pleated cartridge = **PLRICU**

Polyester felt element only style  
pleated cartridge = **PLRIPF**

Basket style pleated  
cartridge = **PB**

#### MICRON RETENTION LEVEL

**PLRICU:** 10 Micron = **10**  
20 Micron = **20**  
30 Micron = **30**

**PLRIPF:** 5 Micron = **5**  
25 Micron = **25**  
100 Micron = **100**

#### CARTRIDGE SIZE/LENGTH

Standard Bag Size 1 (N/A PLRIPF) = **1**  
Standard Bag Size 2 = **2**  
Standard Bag Size 4 = **4**  
Standard Bag Size 8 = **8**  
Standard Bag Size 12 = **12**


## **R** **Platinum Series ABSOLUTE-RATED Bag-Sized Cartridges** Maximum dirt-holding capacity

These absolute-rated filter cartridges offer maximum dirt holding capacity coupled with micron retention ratings to 0.5 at 99.98% efficiency.

These elements are manufactured in a unique "Y" pleat arrangement that optimizes its physical size and maximizes effective surface area. A low fluid flux rate maximizes dirt containment. This means element life is extended and productivity is increased, resulting in fewer cartridge change-outs, less labor, and lower replacement costs.


### **Design Details**

This design uses only the highest quality materials and most advanced manufacturing processes. The end caps are heat sealed for high efficiency performance. The o-ring seal insures sealing and eliminates bypass.



The "Y" pleat maximizes effective surface area.

### **Rosedale BETA Curves**



The Beta Ratio ( $\beta$ ) at a given particle size can be correlated to the filter efficiency at that particle size according to the following formula:

$$\text{Filter Efficiency (\%)} = \left[ \frac{(\beta - 1)}{\beta} \right] \times 100\%$$

Beta Ratio ( $\beta$ )	100	1000	5000
Filter Efficiency (%)	99.00	99.90	99.98


Each filter element will have a different Beta Ratio for every specified particle size. The determination of a variety of Beta values for the same filter provides a filter efficiency profile commonly referred to as a Beta Curve.



## **Platinum 500**



- 68 sq. ft. of surface area maximum
- 12 lbs. (approx.) of dirt carrying capacity
- Rated 0.5 micron to 70 micron @  $\beta 5000$  or 99.98% efficiency
- Flow rates to 50 gpm.
- 6.25-inch diameter and 24-inch length
- Fits into Rosedale Model 8-30, Multiple-bag housings, Polypropylene, and Multi-cartridge housings

**Flow Rate Vs.  $\Delta P$**



**Dirt Holding Capacity**


12 (Platinum Series #2 bag)





## **Platinum 700**

- 100 sq. ft. of surface area maximum
- 20 lbs. (approx.) of dirt carrying capacity
- Rated 0.5 micron to 70 micron @  $\beta 5000$  or 99.98% efficiency
- Flow rates to 100 gpm.
- 6.25-inch diameter and 35-inch length
- Fits into Rosedale Model 8135, Polypropylene, and Multi-cartridge housings

**Flow Rate Vs.  $\Delta P$**



**Dirt Holding Capacity**




See Platinum Filter Housings on page 70





## **R Platinum 900**

- 400 sq. ft. of surface area maximum
- 100 lbs. (approx.) of dirt carrying capacity
- Rated 0.5 micron to 70 micron @  $\beta 5000$  or 99.98% efficiency
- Flow rates to 400 gpm
- 13-inch diameter and 40-inch length
- Rosedale housings can hold multiple cartridge elements

**Flow Rate Vs.  $\Delta P$**




**Dirt Holding Capacity**





## **Platinum 2040**

- 1150 sq. ft. of surface area maximum
- 250 lbs. (approx.) of dirt carrying capacity
- Rated 0.5 micron to 70 micron @  $\beta 5000$  or 99.98% efficiency
- Flow rates to 600 gpm
- 20-inch diameter and 40-inch length
- Rosedale housings can hold 1 element

**Flow Rate Vs.  $\Delta P$**




**Dirt Holding Capacity**



## **How To Order** Build an ordering code as shown in the example

**Example: PS - 520 - P241**

<p><b>PLATINUM SERIES = PS</b></p> <p><b>MICRON RATING</b> <b>Series 500 (99.98%)</b></p> <p>*0.5 Micron = <b>520</b></p> <p>*2 Micron = <b>521</b></p> <p>5 Micron = <b>523</b></p> <p>10 Micron = <b>525</b></p> <p>20 Micron = <b>527</b></p> <p>40 Micron = <b>528</b></p> <p>70 Micron = <b>529</b></p> <p><b>Series 700 @ Beta 5000</b></p> <p>*0.5 Micron = <b>740</b></p> <p>*2 Micron = <b>741</b></p> <p>5 Micron = <b>743</b></p> <p>10 Micron = <b>745</b></p> <p>20 Micron = <b>747</b></p> <p>40 Micron = <b>748</b></p> <p>70 Micron = <b>749</b></p> <p><b>Series 900 @ Beta 5000</b></p> <p>*0.5 Micron = <b>940</b></p> <p>*2 Micron = <b>941</b></p> <p>5 Micron = <b>943</b></p> <p>10 Micron = <b>945</b></p> <p>20 Micron = <b>947</b></p> <p>40 Micron = <b>948</b></p> <p>70 Micron = <b>949</b></p> <p><b>Series 2040 @ Beta 5000</b></p> <p>*0.5 Micron = <b>2040</b></p> <p>*2 Micron = <b>2041</b></p> <p>5 Micron = <b>2043</b></p> <p>10 Micron = <b>2045</b></p> <p>20 Micron = <b>2047</b></p> <p>40 Micron = <b>2048</b></p> <p>70 Micron = <b>2049</b></p>	<p><b>LENGTH</b> <b>Series 500</b> <b>241</b> = Length (24" OAL)</p> <p><b>Series 700</b> <b>356</b> = Length (35" OAL) Seal-6 (EPR 226 O-Ring)</p> <p><b>Series 900 and 2040</b> <b>405</b> = Length-40" Seal-5 (235 EPR O-Ring)</p> <p><b>FILTER MEDIA</b></p> <p><b>P</b> = Polypropylene</p> <p><b>G</b> = Glass</p> <p><b>R</b> = Polyester</p> <p><b>C</b> = Cellulose</p> <div style="text-align: center;">  <p><b>STANDARD 61 LISTED</b></p> <p><small>**520 and 700 Series</small></p> </div>
--	--

\*0.5 and 2.0 micron ratings are not available in polyester or cellulose.

\*\*Use with Model 8 or Multi-Bag Housings




## **R Stainless Steel Filter Cartridges**

Overcome the temperature and compatibility limitations of fabric or synthetic fiber cartridges by replacing them with these stainless steel wire cloth elements. They're good up to 500°F instead of the usual 250°F, and they are unaffected by most caustic fluids.

Made entirely of 304 or 316 stainless steel, they are cleanable and reusable, and can withstand differential pressures up to 60 psi. (500 psid units are also available.) You can choose particle retention ratings as fine as 5 microns. (For nomograph see page 192).

Element surfaces can be plain cylindrical, or pleated to increase surface area. Pleated units rated 100 microns or finer have an underlying support layer of coarser mesh to prevent pleat collapse. Fabrication is by welding and crimping; no silver brazing or epoxy bonding is used.

A "bubble pointing" test can be done to certify that no openings larger than the specified pore size exist in product joints or seams. Ask for more information about this.



Rosedale seals are specially shaped to hold in place mechanically, like a grommet. There's little chance they will be dislodged and lost in handling. They are made in different thicknesses to provide seven different standard overall element lengths.

### **STANDARD END CONFIGURATIONS**

Double-open end, with grommet-type seals

Single-open end, with female NPT connection

Single-open end, with 222 O-rings


Single-open end, with grommet-type seals

Single-open end, with male NPT connection



Build an ordering code as shown in this example

### Dimensions (IN)



Pleat protectors prevent accidental denting of pleat forms that reduce filter area. Made of stainless steel with 1/4-in. dia. perforations, they are held in place by bending tabs at the top and bottom. When ordering give nominal length (10, 20, or 30 inches) and material (304 or 316 stainless steel).

## **R POROPLATE® Filter Elements**

Superior Filtration and Longer Life

The Poroplate line of Sintered Stainless Steel filter elements provide longer life and superior filtration results. They utilize multiple layers of woven wire mesh, sintered into a robust high-strength media. This media is then formed into a filter element, and welded to provide strength and stability. The resulting element traps contaminant on the outside or up-stream surface. The inner or down-stream layers (flow is from outside in) have an open pore construction to facilitate high flow rates and excellent backflushing. During the Backwash Cycle, virtually all contaminant is removed from the element, and is then ready for reuse.

These Poroplate filter elements meet demanding application requirements in many industries, such as Chemical Processing, Industrial Gas Flow, Polymer Production, Food & Beverage Processing, and in Power Generation. The longer life, higher dirt-holding capacity, and easy cleaning and reuse through backflushing, make these elements ideal in applications where reduced operator exposure is desired or required.

They are available in micron retention ratings from 3 to 150. The elements use industry standard sizes of 2-3/8 inch diameter in 10-inch, 20-inch, 30-inch and 40-inch lengths. Stainless 316L is standard, but other steels may be custom ordered, consult factory.




### **Features**

- No media migration
- 316L Stainless Steel construction
- Resists corrosion
- Easily cleaned/backflushed
- Longer life
- Reduced labor
- Reduced operator exposure
- Reduced disposal costs
- Custom sizes, designs and construction

Note: Poroplate is a registered trademark of Purolator




Downstream Support Layers provide reduced differential pressure through open flow channels, as well as higher flow rates and longer filtration cycles. These layers greatly encourage backflushing, keeping the element on line longer.




Protective Guard Layer  
Filter mesh for precise particle size control  
Flow distribution layer

Two coarse support layers for strength and rigidity



These elements are sintered at over 1100°C in a controlled atmosphere furnace. This process fuses metal molecules of the different layers at contact points into a new, completely integrated structure.

#### END CONFIGURATIONS



## How To Order

Build an ordering code as shown in this example

#### Example:

**PPP 10 5 S316 NPT**

#### SERIES

Poroplate Sintered  
Stainless Steel Element

= **PPP**

#### CARTRIDGE LENGTH

10 inch  
20 inch  
30 inch  
40 inch

= **10**  
= **20**  
= **30**  
= **40**

#### MICRON RATING

3  
5  
10  
20  
40  
70  
100  
150

= **3**  
= **5**  
= **10**  
= **20**  
= **40**  
= **70**  
= **100**  
= **150**

#### END CONFIGURATION

**DOE** = Double Open End  
**1NPT** = 1" NPT with Hex Nut  
**222** = 222 Twin O-Ring  
**226** = 226 O-Ring with locking tabs

#### ELEMENT MATERIAL

**S316** = 316 Stainless Steel

## **R** **Rosedale's Absolute Pleated Cartridges**

High efficiency cartridges—  
Long service life

Rosedale filter cartridges provide efficient solids removal in liquid systems where series filtration is not required. Absolute Ratings range from 0.5 to 70 microns.

Each cartridge has pleated, fixed pore media to maximize surface area, prevent particle unloading, and fiber migration. Media selections include cellulose, fiberglass, polyester, and polypropylene.

The wide variety of media, filter sizes, and end cap configurations provide customers with the preferred cartridge for their specific application.

Superior construction materials and quality control techniques ensure that our filter cartridges will provide quality filtration, even in harsh operating conditions.





## How To Order

Build an ordering code as shown in the example

**Example:** **AB - 10 - P - 2 - 1**

**ABSOLUTE SERIES** = **AB**

**MICRON RATING**  
(@ Beta 5000)

0.5 Micron = **0.5**  
 2 Micron = **2**  
 5 Micron = **5**  
 10 Micron = **10**  
 20 Micron = **20**  
 40 Micron = **40**  
 70 Micron = **70**

**FILTER MEDIA**

Polypropylene = **P**  
 Glass = **G**  
 Polyester = **R**  
 Cellulose = **C**


**CARTRIDGE LENGTH**

29.75 = **2**  
 40 = **4**  
 20 = **9**

**END CAP**

Doe = **1**  
 222 O-ring = **2**  
 Soe = **3**

### Rosedale Beta Curves




The Beta Ratio ( $\beta$ ) at a given particle size can be correlated to the filter efficiency at that particle size according to the following formula:

$$\text{Filter Efficiency (\%)} = \left[ \frac{\beta - 1}{\beta} \right] \times 100\%$$

Beta Ratio ( $\beta$ )	100	1000	5000
Filter Efficiency (%)	99.00	99.90	99.98

Each filter element will have a different Beta Ratio for every specified particle size. The determination of a variety of Beta values for the same filter provides a filter efficiency profile commonly referred to as a Beta Curve.

### Flow Rate Vs. $\Delta P$



Flow rate is per single 10-inch element. For other liquid's, multiply the  $\Delta P$  by the fluid's viscosity in centipoise. For longer cartridges, divide the  $\Delta P$  by the number of 10-inch equivalents.

## **R Wound Cartridge Elements**

All-purpose elements have high dirt-holding capacity

Rosedale continuous-wound cartridge elements come in a wide range of materials, lengths, and micron retention ratings. A highly innovative single-core design is used, eliminating the "joints" common in other manufacturers' elements at 10" intervals. Materials of these elements include cotton, nylon, glass, and polypropylene. Their lengths range from 9-3/4 inches to 40 inches, fitting most cartridge housings in the field. Micron retention ratings are from 200 down to 0.5 microns. These elements offer true depth filtration, higher efficiency, lower pressure drop, and greater solids holding capacity than standard elements and competitive prices.

A full range of center core materials are offered to meet specific filtration requirements. Extended core materials are also available upon request.

The center core covering, for reducing fiber migration, is compatible with and equivalent in ratings to the micron rating of the filter element. The inside diameter of all cartridges is 1 inch and the outside diameter is 2-1/2 inches.





# How To Order

Build an ordering code as shown in this example

**Example:**

**C - 10 - A - 20 - S - 02**

**FILTER MATERIAL**

Bleached-White Cotton = **C**

Glass = **G**

Nylon = **N**

Polypropylene = **P**

**MICRON RATING**

200.0 micron = **200**

100.0 micron = **100**

75.0 micron = **75**

50.0 micron = **50**

30.0 micron = **30**

20.0 micron = **20**

10.0 micron = **10**

5.0 micron = **5**

3.0 micron = **3**

1.0 micron = **1**

0.5 micron = **0.5**

**OUTSIDE DIAMETER** (in inches)

2-1/2 = **A**

**OPTION**

**EXTENDED CORE**

**No Symbol** = No Extended Core

**02** = 316 stainless steel

**03** = Polypropylene

**CENTER CORE MATERIAL**

**S** = 316 stainless steel

**P** = Polypropylene

**CARTRIDGE LENGTH,**  
(nominal, in inches)

**40** = 40

**39** = 39

**30** = 30

**29.25** = 29.25

**20** = 20

**19.5** = 19.5

**10** = 10


**9.75** = 9.75

**Note:** For nomograph, see the following page.

# R Pressure Drop vs. Flow Rate

## Non-Aqueous Liquid ▼ Instructions:


1. Draw a line from the desired micron rating **1** through specified pressure drop **2**, and extend to index line **3**.
2. From viscosity **4**, draw a line through the previous intersection on the index line, continuing to intersect flow line. This is flow for one 10" element.



## Water at 68° ▼

### Instructions:

This is a direct reading.  
Connect the particle size **1**, with either pressure drop **2**, or flow **3**, to find the third quantity.



Media Symbols	PO	C	NC	N	G	SS
	Polypropylene	Bleached cotton	Natural cotton	Nylon	Fiber gins	Stainless steel

## **R** **Rosedale Water Service Membrane Cartridges**


Cost effective units for DI Water applications

WS Series Membrane Cartridges are designed to meet the special needs of the electronics and high purity chemical industries. These cartridges are resistant to most acids and bases and capable of handling strong sanitization agents. The high flow rates achieved by our cartridges make them an ideal source for central DI water systems. They also handle elevated process temperatures in compatible fluids.

### **Flow Rate**

The following table represents typical water flow at one psid (69 mbar) across a single 10 inch cartridge element. The test fluid is water at ambient temperature. Extrapolation for housings with multiple elements or higher pressure drops is acceptable. However, as flow increases, the pressure drop attributed to the housing itself will become evident.

**WS Series Flow Rate**



Shown with Spear Guide



## How To Order

Build an ordering code as shown in the example

### Example:

**WSMC - 10 - PES - 2 - V - N - 2**

#### MODEL

Water Service Membrane Cartridge = **WSMC**

#### PORE SIZE

0.03µm = **03**  
0.10µm = **10**  
0.22µm = **20**  
0.45µm = **40**  
0.65µm = **60**

#### MEMBRANE MEDIA

Polyethersulfone = **PES**

#### CARTRIDGE LENGTH

10 inches (25.4 cm) = **1**  
20 inches (50.8 cm) = **2**  
30 inches (76.2 cm) = **3**  
40 inches (101.6 cm) = **4**

#### O-RINGS

EPDM = **E**  
Viton = **V**  
Buna N = **B**  
Teflon = **T**

#### 316 STAINLESS STEEL RING

Ring = **R**  
No Ring = **N**

#### END CAP

Flat Gasket, DOE = **0**  
222, SOE, O-Ring = **2**  
020 O-Ring = **3**  
222 O-Ring with Spear = **4**  
226 O-Ring with Spear = **5**

### Dimensions

**Length:** 10 to 40 inches  
(25.4 to 101.6 cm) nominal  
**OD:** 2.75 inches (7.0 cm) nominal

### Maximum Differential Pressure

**Forward:** 50 psi (3.4 bar) at 20° C  
**Reverse:** 40 psi (2.7 bar) at 20° C

### Construction Materials

**Filtration Media:** Polyethersulfone  
**Media Support:** Polypropylene  
**End Caps:** Polypropylene  
**Center Core:** Polypropylene  
**Outer Support Cage:** Polypropylene  
**O-Ring Material:** EPDM, Viton, Buna N, Teflon, Ethylene Propylene

### Sanitization/Sterilization


#### Chemical Sanitization:

Industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

### Integrity Test Specifications

(per ten inch length, water wetted membrane)

PORE SIZE	AIR DIFFUSION RATE		
	≤cc/min	@ psi	mbar
0.03µm	30	60	4137
0.05µm	30	56	3860
0.10µm	30	48	3307
0.22µm	30	35	2412
0.45µm	30	20	1378
0.65µm	30	15	1044



## **Rosedale Pharmaceutical Service Membrane Cartridges**

Cost effective units for Pharmaceutical Industry applications

PS Series Membrane Cartridges are designed to be used as sterilizing grade cartridges for the pharmaceutical industry. The PS Series Membrane is optimized for retention, so additional layers are not necessary. Ideal for use in Sterile Fill applications and SVPs and bio products. Polyethersulfone is particularly suited for filtration of products whose constituents, such as preservatives, can adsorb to the media. Also works well with valuable protein solutions such as vaccines and other biological substances.

### **Flow Rate**


The following table represents typical water flow at one psid (69 mbar) across a single 10 inch cartridge element.

The test fluid is water at ambient temperature. Extrapolation for housings with multiple elements or higher pressure drops is acceptable. However, as flow increases, the pressure drop attributed to the housing itself will become evident.



Spear Guide

### **FS Series Flow Rate**



## How To Order

Build an ordering code as shown in the example

**Example:** **PSMC - 10 - PES - 2 - V - N - 2**

### MODEL

Pharmaceutical Service  
Membrane Cartridge = **PSMC**

### PORE SIZE

0.03µm = **03**  
0.10µm = **10**  
0.22µm = **20**  
0.45µm = **40**  
0.65µm = **60**

### MEMBRANE MEDIA

Polyethersulfone = **PES**

### CARTRIDGE LENGTH

10 inches (25.4 cm) = **1**  
20 inches (50.8 cm) = **2**  
30 inches (76.2 cm) = **3**  
40 inches (101.6 cm) = **4**

### O-RINGS

EPDM = **E**  
Viton = **V**  
Buna N = **B**  
Teflon = **T**

### 316 STAINLESS STEEL RING

Ring = **R**  
No Ring = **N**

### END CAP

Flat Gasket, DOE = **0**  
222, SOE, O-Ring = **2**  
020 O-Ring = **3**  
222 O-Ring with Spear = **4**  
226 O-Ring with Spear = **5**

### Dimensions

**Length:** 10 to 40 inches  
(25.4 to 101.6 cm) nominal  
**OD:** 2.75 inches (7.0 cm) nominal

### Maximum Differential Pressure

**Forward:** 50 psi (3.4 bar) at 20° C  
**Reverse:** 40 psi (2.7 bar) at 20° C

### Construction Materials

**Filtration Media:** Polyethersulfone  
**Media Support:** Polypropylene  
**End Caps:** Polypropylene  
**Center Core:** Polypropylene  
**Outer Support Cage:** Polypropylene  
**O-Ring Material:** EPDM, Viton,  
Buna N, Teflon, Ethylene Propylene

### Sanitization/Sterilization

**Filtered Hot Water:** 90°  
**Autoclave:**  
127° C, 30 minute multiple cycles  
**In-Line Steam:**  
135° C, 30 minute multiple cycles


### Chemical Sanitization:

Industry standard concentrations of  
hydrogen peroxide, peracetic acid,  
sodium hypochlorite and other selected  
chemicals.

### Integrity Test Specifications

(per ten inch length, water wetted membrane)

PORE SIZE	AIR DIFFUSION RATE		
	≤cc/min @	psi	mbar
0.03µm	15	60	4137
0.10µm	15	48	3307
0.22µm	15	35	2412
0.45µm	15	20	1378
0.65µm	15	15	1044



## **Rosedale General Service Membrane Filter Cartridges**



Cost effective units for industrial applications

GS Series Membrane Cartridges are designed for general industrial service where the need for cost effective filtration is a must. These cartridges utilize a pleated membrane design, incorporating the maximum amount of media that can be used in a cartridge. These units, manufactured for general industrial use, are manufactured to the same high standards as our special application cartridges. Pore sizes start at 0.03  $\mu\text{m}$  with a polyethersulfone membrane.

### **Flow Rate**

The following table represents typical water flow at one psid (69 mbar) across a single 10 inch cartridge element. The test fluid is water at ambient temperature. Extrapolation for housings with multiple elements or higher pressure drops is acceptable. However, as flow increases, the pressure drop attributed to the housing itself will become evident.

**GS Series Flow Rate**



## How To Order

Build an ordering code as shown in the example

**Example:** **GSMC - 10 - PES - 2 - V - N - 2**

### MODEL

General Service Membrane Cartridge = **GSMC**

### PORE SIZE

0.03µm = **03**  
 0.10µm = **10**  
 0.22µm = **20**  
 0.45µm = **40**  
 0.65µm = **60**

### MEMBRANE MEDIA

Polyethersulfone = **PES**

### CARTRIDGE LENGTH

10 inches (25.4 cm) = **1**  
 20 inches (50.8 cm) = **2**  
 30 inches (76.2 cm) = **3**  
 40 inches (101.6 cm) = **4**

### O-RINGS

EPDM = **E**  
 Viton = **V**  
 Buna N = **B**  
 Teflon = **T**

### 316 STAINLESS STEEL RING

Ring = **R**  
 No Ring = **N**

### END CAP

Flat Gasket, DOE = **0**  
 222, SOE, O-Ring = **2**  
 020 O-Ring = **3**  
 222 O-Ring with Spear = **4**  
 226 O-Ring with Spear = **5**

## Dimensions

**Length:** 10 to 40 inches  
 (25.4 to 101.6 cm) nominal  
**OD:** 2.75 inches (7.0 cm) nominal

## Maximum Differential Pressure

**Forward:** 50 psi (3.4 bar) at 20° C  
**Reverse:** 40 psi (2.7 bar) at 20° C

## Construction Materials

**Filtration Media:** Polyethersulfone  
**Media Support:** Polypropylene  
**End Caps:** Polypropylene  
**Center Core:** Polypropylene  
**Outer Support Cage:** Polypropylene  
**O-Ring Material:** EPDM, Viton, Buna N, Teflon, Ethylene Propylene

## Sanitization/Sterilization

**Filtered Hot Water:** 90°


## Chemical Sanitization:

Industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

## Integrity Test Specifications

(per ten inch length, water wetted membrane)

PORE SIZE	AIR DIFFUSION RATE		
	≤cc/min	@ psi	mbar
0.03µm	55	60	4137
0.10µm	55	48	3307
0.22µm	55	35	2412
0.45µm	55	20	1378
0.65µm	55	15	1044





## **Rosedale Food, Wine and Beverage Service Membrane Cartridges**


Cost effective units for food applications

FS Series Membrane Cartridges are designed to comply with all FDA rules and regulations for the food industry. The properties of Polyethersulfone make it an excellent choice for use with fermented beverages. Cartridges are designed to provide maximum throughput, while easily sanitized or cleaned.

### **Flow Rate**

The following table represents typical water flow at one psid (69 mbar) across a single 10 inch cartridge element. The test fluid is water at ambient temperature. Extrapolation for housings with multiple elements or higher pressure drops is acceptable. However, as flow increases, the pressure drop attributed to the housing itself will become evident.

**FS Series Flow Rate**



## How To Order

Build an ordering code as shown in the example

**Example:** **FSMC - 10 - PES - 2 - V - N - 2**

### MODEL

Food and Beverage Service  
Membrane Cartridge = **FSMC**

### PORE SIZE

0.03µm = **03**  
0.10µm = **10**  
0.22µm = **20**  
0.45µm = **40**  
0.65µm = **60**

### MEMBRANE MEDIA

Polyethersulfone = **PES**

### CARTRIDGE LENGTH

10 inches (25.4 cm) = **1**  
20 inches (50.8 cm) = **2**  
30 inches (76.2 cm) = **3**  
40 inches (101.6 cm) = **4**

### O-RINGS

EPDM = **E**  
Viton = **V**  
Buna N = **B**  
Teflon = **T**

### 316 STAINLESS STEEL RING

Ring = **R**  
No Ring = **N**

### END CAP

Flat Gasket, DOE = **0**  
222, SOE, O-Ring = **2**  
020 O-Ring = **3**  
222 O-Ring with Spear = **4**  
226 O-Ring with Spear = **5**

## Dimensions

**Length:** 10 to 40 inches  
(25.4 to 101.6 cm) nominal  
**OD:** 2.75 inches (7.0 cm) nominal

## Maximum Differential Pressure

**Forward:** 50 psi (3.4 bar) at 20° C  
**Reverse:** 40 psi (2.7 bar) at 20° C

## Construction Materials

**Filtration Media:** Polyethersulfone  
**Media Support:** Polypropylene  
**End Caps:** Polypropylene  
**Center Core:** Polypropylene  
**Outer Support Cage:** Polypropylene  
**O-Ring Material:** EPDM, Viton,  
Buna N, Teflon, Ethylene Propylene

## Sanitization/Sterilization

**Filtered Hot Water:** 90°

### Autoclave:

127° C, 30 minute multiple cycles

### In-Line Steam:

135° C, 30 minute multiple cycles


### Chemical Sanitization:

Industry standard concentrations of  
hydrogen peroxide, peracetic acid,  
sodium hypochlorite and other selected  
chemicals.

## Integrity Test Specifications

(per ten inch length, water wetted membrane)

PORE SIZE	AIR DIFFUSION RATE		
	≤cc/min @	psi	mbar
0.03µm	30	60	4137
0.10µm	30	48	3307
0.22µm	30	35	2412
0.45µm	30	20	1378
0.65µm	30	15	1044



## **Rosedale Electronics Service Membrane Cartridges**


Cost effective units for Electronics Industry applications

ES Series Membrane Cartridges are designed to meet the special needs of the electronics and high purity chemical industries. The high flow rates achieved by our cartridges make them an ideal source for central DI water systems. They also handle elevated process temperatures in compatible fluids.

### **Flow Rate**

The following table represents typical water flow at one psid (69 mbar) across a single 10 inch cartridge element. The test fluid is water at ambient temperature. Extrapolation for housings with multiple elements or higher pressure drops is acceptable. However, as flow increases, the pressure drop attributed to the housing itself will become evident.

**ES Series Flow Rate**





## How To Order

Build an ordering code as shown in the example

**Example:** **ESMC - 10 - PES - 2 - V - N - 2**

### MODEL

Electronics Service  
Membrane Cartridge = **ESMC**

### PORE SIZE

0.03µm = **03**  
0.10µm = **10**  
0.22µm = **20**  
0.45µm = **40**  
0.65µm = **60**

### MEMBRANE MEDIA

Polyethersulfone = **PES**

### CARTRIDGE LENGTH

10 inches (25.4 cm) = **1**  
20 inches (50.8 cm) = **2**  
30 inches (76.2 cm) = **3**  
40 inches (101.6 cm) = **4**

### O-RINGS

EPDM = **E**  
Viton = **V**  
Buna N = **B**  
Teflon = **T**

### 316 STAINLESS STEEL RING

Ring = **R**  
No Ring = **N**

### END CAP

Flat Gasket, DOE = **0**  
222, SOE, O-Ring = **2**  
020 O-Ring = **3**  
222 O-Ring with Spear = **4**  
226 O-Ring with Spear = **5**

## Dimensions

**Length:** 10 to 40 inches  
(25.4 to 101.6 cm) nominal  
**OD:** 2.75 inches (7.0 cm) nominal

## Maximum Differential Pressure

**Forward:** 50 psi (3.4 bar) at 20° C  
**Reverse:** 40 psi (2.7 bar) at 20° C

## Construction Materials

**Filtration Media:** Polyethersulfone  
**Media Support:** Polypropylene  
**End Caps:** Polypropylene  
**Center Core:** Polypropylene  
**Outer Support Cage:** Polypropylene  
**O-Ring Material:** EPDM, Viton, Buna N, Teflon, Ethylene Propylene


## Sanitization/Sterilization

**Chemical Sanitization:**  
Industry standard concentrations of hydrogen peroxide, peracetic acid, sodium hypochlorite and other selected chemicals.

## Integrity Test Specifications

(per ten inch length, water wetted membrane)

PORE SIZE	AIR DIFFUSION RATE		
	≤cc/min	@ psi	mbar
0.03µm	30	60	4137
0.10µm	30	48	3307
0.22µm	30	35	2412
0.45µm	30	20	1378
0.65µm	30	15	1044





## Introduction

In many applications, baskets are a good alternative to replace filter bags or other media. Basket design varies greatly depending on the application.

CONTENTS	PAGE
MEDIA CHARACTERISTICS	203
ROSEDALE CLEANABLE BASKETS	204
ROSEDALE REPLACEMENT BASKETS	206
TURN BAG HOUSING INTO CARTRIDGE FILTER	208
INNER BASKETS AND BAGS	210



FOR MORE INFORMATION GO TO [www.rosedaleproducts.com/baskets.pdf](http://www.rosedaleproducts.com/baskets.pdf) or scan here:

## Media Characteristics

This information is intended to be used as a general guideline. Since some characteristics are very similar from one media to the next, you should choose the media whose advantages best fit your particular filtration requirements. Consult Rosedale for assistance in selecting the proper media for your application.



**Wedge Wire (W/W)** or slotted, is the most durable of all backwashable media. They are strictly limited to .001" slot or 25 micron as the lowest retention rating. Wedge wire is particularly suited for critical low maintenance applications. As a result of their construction, they are used in many instances where manual cleaning is necessary but might damage other types of media.

MICRON RATING	OPENING (INCH)	% OF OPEN AREA
25	.001	2.1
50	.002	4.2
75	.003	6.1
150	.006	11.5
250	.010	18.0
350	.014	23.0



**Poroplate®** filter media is made from layers of stainless steel wire cloth diffusion-bonded together to form a rigid porous metal laminate structure. Poroplate filter media is corrosion resistant, cleanable, and can withstand high temperature applications up to 800°F. Micron ratings from 2 to 150 are available.

MICRON RATING	NOMINAL RATING	ABSOLUTE RATING
10	2μ	10μ
25	10μ	20μ
50	20μ	40μ
75	40μ	70μ
100	100μ	100μ
150	150μ	150μ



## **Rosedale Cleanable Baskets**

Replaces bag filters with multiple layers of stainless steel wire-woven cloth, diffusion bonded together for increased strength, corrosion resistance, and long life.


One piece construction for ease in handling, no need for a perforated basket for support, no need for a bag for filtration, basket becomes the filter media.

Sized to replace #1 or #2 bag filters and perforated strainer baskets.

### **FEATURES**

- All 316 stainless steel construction
- 6 micron ratings
- 10-150 micron absolute
- TIG welded construction for long life
- Easily cleaned
- Additional end ring configurations to fit other liquid bag housings
- Custom applications available

See next page for How to Order.



Made from layers of stainless steel wire cloth, diffusion-bonded to form a rigid porous metal laminate structure.



## **Cone Baskets**

Cone baskets are valuable when a large filtering area is needed in a small space. They are available as a basket within a basket, or a bag within a basket.

Cone baskets are widely used for filtration of solid particles in pharmaceutical, chemical, and food industries.

Please contact Rosedale for ordering information.





## How To Order

Build an ordering code as shown in the example

### EXAMPLE:

**PPB - 2 - ROS - SB - 40**

#### MODEL NO.

Cleanable Basket = **PPB**

#### SIZE

6.5" Dia. x 13.04/13.38" = **1**

6.5" Dia. x 24.85/25.19" = **2**

Length varies depending on end fitting

#### HOUSING MFG.

Rosedale

= **ROS**

American Felt & Filter

= **AFF**

Filter Specialists

= **FSI**

GAF

= **GAF**

Hayward

= **HAY**

Krystil Klear

= **KK**

Loeffler

= **LOF**

Nowata

= **NOW**

Parker

= **PAR**

Plenty

= **PLE**

Purolator Facet

= **PFI**

Ronnington-Petter

= **RPA**

UF Strainrite

= **UFS**

#### PRESSURE

NOMINAL      ABSOLUTE

**10** = 2μ      10μ

**20** = 10μ      20μ

**40** = 20μ      40μ

**70** = 40μ      70μ

**100** = 100μ      100μ

**150** = 150μ      150μ

#### FEATURES

**SB** = Swing Bolt

**BC** = Band Clamp Cover

**1B** = Single Bag Housing  
(Other Mfg.)\*

**MB** = Multi Bag Housing\*

\*Provide manufacturer's housing  
model number

## **R** Rosedale Replacement Baskets

Rosedale manufactures replacement bag filter baskets and basket strainers for a wide range of filter housings made by:

American Felt & Filter  
Cuno  
Commercial Filters  
Eaton  
Filter Specialists (FSI)  
Filtration Systems  
GAF  
Ronningen-Petter  
Strainrite  
Oakland  
Plenty

We offer replacements for all current models, and any that have been discontinued by the original manufacturer.

These replacement baskets are made to specifications that equal, or exceed the original manufacturers specifications.

### **Basket Construction**

**STAINLESS STEEL:** Standard material is 304 stainless steel. 316 stainless steel is available as an option.

### **Basket Media Selection**

**PERFORATED STRAINER AND BAG FILTER BASKETS:** For cleanable basket strainers, choose from the following perforation diameters: 1/4, 3/16, 9/64, or 1/16 inch. For filter bag baskets: standard 9/64-inch diameter perforations with 51 percent open area are supplied.



Perforated



With wire mesh lining

**PERFORATED WITH WIRE MESH LINING STRAINER AND FILTER BAG BASKETS:** Stainless steel wire is used in mesh sizes 30, 60, 100, 150, or 200. When used as a bag filter basket, the following advantages are realized:

- Fiber migration is minimized.
- In the unlikely event of bag rupture, the wire mesh contains the contaminant.
- Bag material cannot become "lodged" in the perforations due to extreme pressure differential.
- Flow characteristics are enhanced when using monofilament bags.



#### **Model CF**

Replaces Commercial Filter baskets SB11, SB12



#### **Model CU**

Replaces Cuno baskets 7PC1, 7PC2



#### **Model RP**

Replaces Ronningen-Petter baskets 224, 324, 424, 152



#### **Model AFF/GAF**

Replaces American Felt & Filter/GAF baskets 112, 122, AMS R, AMC R, NCX, RBX 1L, RBX 2L

# How To Order

Build an ordering code as shown in the example.

**EXAMPLE:** **FS1 - BM30 - S316**

**BASKET MODEL NUMBER**

Filter Specialists, Inc. = **FSR/FS/FSP**

American Felt & Filter = **AFF**

GAF = **GAF**

Strainrite = **STR**

Ronningen-Petter = **RP**

Filtration Systems = **FF**

Cuno = **CU**

Commercial Filters = **CF**

Oakland = **OA**

Plenty = **PL**

**BASKET SIZE** (approx., inches)

OD (nominal)	Length (nominal)	
7	15	= <b>1</b>
7	30	= <b>2</b>
4	6	= <b>3</b>
4	12	= <b>4</b>

**BASKET TYPE**

Perforated filter bag basket = **B**

Perforated strainer basket = **P**

Mesh lined perforated filter bag basket = **BM**

Mesh lined strainer basket = **M**

Heavy wire mesh filter bag basket = **HWM**

**BASKET MEDIA SIZE**

Perforation diameters (for P type baskets)\*

**1/4, 3/16, 9/64, 1/16**

Mesh sizes (for BM and M baskets)

**30, 60, 100, 150, or 200**

**OPTIONS**

304 stainless steel construction = **S**


All 316 stainless steel construction = **S316**

\*Additional options available. Consult factory.

Rosedale can manufacture any basket to your specifications.

Send us a drawing, or just a simple sketch as shown, and we'll submit a quote for your review.

- A = Basket diameter
- B = Basket height
- C = Bail height
- D = Outside diameter of rim




## Basket Designs

Standard filter bag baskets have rounded perforated bottoms.

Mesh lined bag baskets have round solid bottoms.

Strainer baskets have flat non-perforated bottoms.



**Model STR**  
Replaces Strainrite baskets  
UF1-90, UF1-180



**Model FF**  
Replaces Filtration Systems  
baskets 112, 122



**Model FSR**



**Model FS**

**Model FSR or FS**  
Replaces all Filter  
Specialists baskets

## **R Turn Bag Housings Into Cartridge Filters!**

Basket holds cartridges inside a bag housing!

Rosedale's bag filter converter can be quickly converted to a cartridge filter. Simply put, there are applications that call for a bag filter and others that call for a cartridge filter. Until now, it wasn't very easy to change between the two.

If it becomes necessary to change from bags to cartridges – install the Rosedale Converter Basket.

- Remove the original basket
- Install the new converter basket
- Load the cartridges
- Unique design prevents clean side contamination by removing basket from housing before removing cartridges from converter

You now have a cartridge filter able to utilize any standard cartridge.

Baskets fit standard models 4-12, 8-15, and 8-30 housings. Construction materials are either 304 stainless or 316 stainless steel.



◀ Flow is introduced from above and circulates around cartridges. Fluid flows through cartridge walls, leaving contaminant on media, and "clean" fluid exits through bottom outlet.



## How To Order

Build an ordering code as shown in the example below

### EXAMPLE:

BC1 - S

BASKET CONVERTER = BC

BASKET SIZE (IN INCHES, NOMINAL)

OD Length

6.5 10 = 1  
6.5 20 = 2  
4 10 = 4

### CONSTRUCTION MATERIALS

304 Stainless Steel = S  
316 Stainless Steel = S316



### Dimensions




Housing Size & Cartridge Capacity	Model Code	OD*	Length*
<b>Model 4</b> 1 cartridge	BC4	4	10
<b>Model 8</b> 3 cartridges	BC1	6.5	10
	BC2	6.5	20

\*Nominal in inches

See pages 190-191 for more information on Wound Cartridges and Stainless Steel filter cartridges.

## **R Inner Baskets and Bags**

Model 8 and any of the multi-basket or multi-bag units can be fitted with smaller, inner basket strainers or bag filters, through which the in-coming fluid flows first, giving two-stage cleaning action. Inner baskets and bags are offered in the same construction materials and ratings as those of the primary outer elements.



## **R Custom Manufacturing Solutions**

We can build anything from simple modifications on standard housings, to customer specified skid-mounted filtration systems. These can incorporate filters, strainers, separators, controllers, sensors, and automated operations.

Rosedale has a long history of innovative filtration designs. They are as simple as our Model 4 Housing or as complex as our multi-station Automatic Backwashing Filtration Systems. Using our expertise, we work with our clients to manufacture systems that meet their needs. Some of our standard models started out as solutions to a client's need, such as the duplex and multiplex filters or convertible housings.





In this section, you'll see several examples of filters and filtration systems that show what we can do for you.

These systems incorporate any number of filtration solutions including:

- Basket strainers
- Bag filters
- Cartridge filters
- Solids/liquids separators
- Single layer bags
- Multilayer bags
- Bag sized cartridges
- Wound cartridges
- Membrane cartridges
- Stainless steel cartridges
- "Smart" controls
- Differential pressure sensors



- Pumps and motors
- Controllers
- Skid or cart mounting
- Pit mounting
- Gangways for access

Application specific components:

- Oxygen concentrators,
- Heated jacketing
- Internal coatings

We also take your specific flow requirements into account, ensuring that the system we design will not restrict your process. For more information, contact Rosedale to get started today.





## Special Configuration Skid Packages



### Filter For Natural Gas Use

Filter CNG between supply and compressor for improved product quality and longer compressor life. Removes impurities and particulate matter for longer compressor life.



### Special Options And Accessories

For improved filtration! Rosedale offers answers to your specific needs with a wide range of options and accessories. If your specific needs are not represented here, please call us. We will discuss how we can solve your problems.



## **R** Rosedale Accessories



### **Heated Jacketing For Resins, etc.**

All Rosedale filter housings can be fitted with heated jacketing for improved filtration of resins, adhesive coatings, and viscous materials. The entire vessel can be enclosed by the jacketing, including the inlet and outlet nozzles. The unit is rated to 600°F, requiring metallic seals (included). The housing is electropolished to prevent product buildup, maintaining clean inside walls.




### **Bag Hold Down Assemblies**

Hold down assemblies can be supplied with any Rosedale filter housing.



### **Internal Coatings**

Special coatings can be internally applied to any of Rosedale's housings, meeting your special requirements. These coatings include epoxy, with other coatings available. Call Rosedale for more information or product compatibility.




### **Bag Restrainer**

This restrainer expands the bag fully during filtration, insuring that it doesn't fold over on to itself, reducing the amount of material used in filtration. It can also be used in conjunction with the liquid displacer, easing its installation.



## Differential Pressure Indicators

All Rosedale filter housings can be fitted with pressure indicators that tell the operator when the element needs servicing. This improves the process quality, reduces system downtime and maximizes efficiency of plant operations. A variety of options are available including standard liquid-filled gauges, differential pressure gauges, differential pressure switches, or a combination switch and gauge. Recommended change-out of most elements is 15 psid.



## Liquid Displacers

Rosedale filter housing models 4, 6, and 8, as well as our convertible filter housings, can be supplied with a liquid displacer attached to the cover. When in use, the displacer (a sealed 304 stainless steel cylinder) fits inside the basket strainer or bag filter, displacing liquid that would otherwise fill the inner space. When the cover and attached displacer are removed, the level of the liquid within the basket strainer or bag filter drops resulting in less product loss, and fast easy changes.

# Technical Manual

	PAGE
Viscosity Guide	218
Application Guide	219
Vessel Data	220
Basket Data	221
Cartridge Sealing Options	222
Filtration Ranges	223
ISO 4406 Code	225
Velocity vs. Flow	227
Pipe Flow Rate	228
Flow Conversion	229
Air to Liquid Flow Equivalents	230
Viscosity vs. Temperature	231
Enclosure Types	234
Conductor I.D.	236
Pipe Pressure Loss	237
Orifice Pressure Drop	238
Pressure Conversion	239
Temperature Data	240
Pressure Indicator	242
Pipe Properties	243
Hardness-Tensile Strength	244
ASME / Radiography	245
Glossary	246
Chemical Resistance Guide	256

## CONVERSION FACTORS

Suspended  
Solid Conversions

PPM	%	lbs./1000 gal.
10,000	1.0000	80.0
8,000	.8000	70.0
6,000	.6000	50.0
4,000	.4000	35.0
2,000	.2000	15.0
1,000	.1000	9.0
800	.0800	6.5
600	.0600	5.5
400	.0400	3.5
200	.0200	1.75
100	.0100	.85
80	.0080	.65
60	.0060	.50
40	.0040	.35
20	.0020	.175
10	.0010	.08
8	.0008	.065
6	.0006	.055
4	.0004	.035
2	.0002	.0175
1	.0001	.0003

Viscosity  
Equivalents

SSU (Saybolt Seconds Universal)	CPS (Centi- poise)
30	1
50	5
100	20
200	40
300	65
400	85
500	105
600	130
700	150
800	175
900	195
1000	210
2000	425
3000	625
4000	860
5000	1050
6000	1300
7000	1500
8000	1700
9000	1960
10,000	1250

MESH	MICRON	INCHES
4	5205	0.2030
8	2487	0.0970
10	1923	0.0750
14	1307	0.0510
18	1000	0.0394
20	840	0.0331
25	710	0.0280
30	590	0.0232
35	500	0.0197
40	520	0.0165
45	350	0.0138
50	297	0.0117
60	250	0.0098
70	210	0.0083
80	177	0.0070
100	149	0.0059
120	125	0.0049
140	105	0.0041
170	88	0.0035
200	74	0.0029
230	62	0.0024
270	53	0.0021
325	44	0.0017
400	37	0.0015
550	25	0.0009
800	15	0.0006
1250	10	0.0004
—	5	0.0002

MULTIPLY	BY	TO OBTAIN
Atmospheres	14.7	psi
Barrels of Oil	42.0	gallons (U.S.)
Centimeters	.03281	feet
Centimeters	.3937	inches
Centipoise	.01	poises
Centistoke	.01	stokes
Cubic centimeters	.06102	cubic inches
Cubic centimeters	.0002642	gallons (liq.)
Cubic feet	7.4805	gallons (liq.)
Cubic feet	.1728	cubic inches
Cubic feet/min.	7.4805	g.p.m.
Cubic inches	.004329	gallons
Cubic inches	16.387	cubic cm.
Cubic inches	.0005787	cubic feet
Cubic meters	264.17	gallons (liq.)
Cubic metes	35.31	cubic feet
Feet	30.48006	centimeters
Feet	.3048006	meters
Feet of water	.4335	psi
Feet of water	.8826	inches of Hg.
Feet/min	.01136	miles per hour
Feet/second	.681818	miles per hour
Gallons	3,785.43	cubic cm.
Gallons	231	cubic inches
Gallons	.83268	gallons (imp.)
Gallons	.13368	cubic feet
Gallons/min.	.13368	cu. ft./min
Inches	.0254	meters
Inches of Hg.	1.133	feet of water
Inches of Hg.	.491	psi
Kilograms	2.2046	pounds (avdp.)
Kilogram/sq. cm.	14.2233	psi
Kilograms/sq. mm	1,422.33	psi
Liters	.264178	gallons
Meters	3.2808	feet
Poise	100.0	centipoise
Pounds water	.11985	gallons
PSI	2.036	inches of Hg.
PSI	2.31	feet of water
Square inches	6.4516	sq. cm.



## APPLICATIONS FOR LIQUID BAG HOUSINGS

Filter Recirculating Water  
 Keep Spray Nozzles Open  
 Protect Catalyst Beds  
 Protect Instruments  
 Remove DE Filter Carryover  
 Remove Precipitated Solids  
 Remove Undispersed Solids  
 Remove Particles from Coatings  
 Clean Electrolytic Solutions  
 Remove Oversize Particles from Slurries  
 Filter Condensate  
 Filter Bottle and Can Wash Water  
 Filter Poultry and Meat Wash Water  
 Remove Char Particles  
 Filter Cooling Tower Water  
 Filter Waste Oil for Reuse  
 Protect Chiller and Air Conditioners  
 Protect Reverse Osmosis Systems  
 Filter Broiler Feed Water  
 Filter Pump Seal Water  
 Protect Glue Applicators  
 Filter Scrubber Water  
 Remove Plastic Fines from Water  
 Remove Pulp from Juices

## INDUSTRIES

### CHEMICAL

Acetic Acid  
 Brine  
 Calcium Carbonate  
 Cooling Tower Water  
 Ethylene Glycol  
 Herbicides  
 Hydrochloric Acid  
 Latices  
 Pellitizer Water  
 Polymers  
 Resins  
 Sulphuric Acid

### FOOD

Peanut Butter  
 Corn Syrup  
 Lard  
 Dextrose  
 Chocolates  
 Jelly  
 Juices  
 Milk Sugar  
 Edible Oils  
 Soybean Concentrate  
 City and Well Water  
 Tea Liquor  
 Extracts

### PAPER

Clay Slurry  
 Pigmented Coatings  
 Fresh Water  
 White Water  
 Decker Shower Water  
 Size  
 Starch  
 T10<sup>2</sup> Slurry  
 Mill Water  
 Wet Ends Additives  
 Cooling Water  
 Dyes  
 Pump Seal Water

### PETROLEUM

Amine  
 Reduced Crudes  
 Feedstocks  
 Pump Seal Water  
 Naphtha  
 Fuel Oil  
 Motor Oil  
 Hydraulic Oil  
 Synthetic Lubricants  
 Completion Fluids  
 Injection Fluids  
 Cooling Tower Water

### MISC.

Adhesives  
 Solvents  
 Resins  
 Liquors  
 Paints  
 Shampoo  
 Dyes  
 Cooling Water  
 Beer  
 Beverages  
 Pharmaceutical  
 Toothpaste

## Rosedale Filter Vessel Data

MODEL	PRESSURE RATING PSI	WALL THK.  inches	VOLUME ENTIRE HOUSING  gallons	**	NO. BELOW LUG ASSY	NO. OF LUGS	LUG SIZE
4-6 4-12	200, 300, 500 200, 300, 500	.110, .120 .110, .120	0.65 1.02	- -	1 1	3 3	1/2-13 1/2-13
6-12 6-18 6-30	150, 300 150, 300 150, 300 100, 125	.109 .109 .109	2.16 2.83 4.20	- - -	1 1 1	3 3 3 N/A	5/8-11 5/8-11 5/8-11 N/A
8-15 8-30	100, 125, 150, 300 100, 125, 150, 300 300	.109 .109	5.61 9.23	- -	1 1	3 3 6	5/8-11 5/8-11 5/8-11
16-30	150	.188	28.03	-	2	5	7/8-9
18-30	150	.188	36.83	-	3	5	7/8-9

Above this line vessels are "UM" stamp. Below this line vessels are "U" stamp unless specified otherwise or by special requirements.

### "UM" Vessels not to exceed the following

- 5 CU. FT. (FT<sup>3</sup>) IN VOLUME AND 250 PSI DESIGN PRESSURE  
OR
- 1.5 CU. FT. (FT<sup>3</sup>) IN VOLUME AND 600 PSI DESIGN PRESSURE

22-30	150	.188	57.56	-	4	8	7/8-9
24-30	150	.188	70.00	-	6	8	7/8-9
30-30	150	.250	115.00	-	8	12	7/8-9
32-30	150	.250	133.00	-	9	12	7/8-9
36-30	150	.313	174.00	-	12	14	1-8
42-30	150	.313	249.00	-	17	20	1-8
48-30	150	.375	340.00	-	*24	24	1-8
60-30	150	.500		-	*35	24	1-1/4-7

\* SPECIAL

\*\* DOES NOT INCLUDE FLUID CAPACITY OF IN-OUT NOZZLES (ELBOWS, FLANGES, ETC).

### CONVERSION FORMULAS:

CAPACITY IN CUBIC FEET (ft<sup>3</sup>) = 1728 in<sup>3</sup>  
 CAPACITY IN GALLONS = 231 in<sup>3</sup>  
 CAPACITY IN CUBIC FEET (ft<sup>3</sup>) = GAL. x .1337  
 CAPACITY IN GALLON = ft<sup>3</sup> x 7.48  
 1 GALLON = 8.34 lb. x SPECIFIC GRAVITY  
 1 ft<sup>3</sup> = 62.4 lb. x SPECIFIC GRAVITY

## Rosedale Products Basket Data

BASKET STYLE	STRAINER BASKET AREA ft <sup>2</sup>	FILTER BAG BASKET AREA ft <sup>2</sup>	STRAINER BASKET VOLUME GAL.	FILTER BAG BASKET VOLUME GAL.	RBS BASKET STYLE	BS / RBS BASKET VOLUME GAL.
4-6	.5	.5	.30	.30	Model 4	0.20
4-12	1.0	1.0	.60	.60	Model 6	0.60
					Model 8	1.25
6-12	1.4	1.4	.97	.97	Model 10	3.00
6-18	2.0	2.0	1.50	1.50	Model 12	4.50
6-30	3.3	3.3	2.54	2.54	Model 14	8.50
					Model 16	13.00
8-15	1.7	2.0	1.87	2.31	Model 18	15.00
8-30	4.4	4.2	4.71	4.63	Model 22	
					Model 24	32.00
MULTI	4.4	4.2	4.56	4.49	Model 30	70.00
					Model 36	110.0
LCO	5.6	5.6	6.0	6.0	Model 42	220.0
					Model 48	

### CONVERSION FORMULAS:

CAPACITY IN CUBIC FEET (ft<sup>3</sup>) = in. 3/1728

CAPACITY IN CUBIC FEET (ft<sup>3</sup>) = GAL. x .1337

CAPACITY IN GALLONS = in<sup>3</sup>/231

CAPACITY IN GALLONS = ft<sup>3</sup> x 7.48

1 GALLON = 8.34 lb. x SPECIFIC GRAVITY

1 ft<sup>3</sup> = 62.4 lb. x SPECIFIC GRAVITY



## Recommended Maximum $\Delta P$ for Standard Rosedale Baskets

The recommended maximum operating  $\Delta P$  for standard Rosedale Baskets is 15-20 psid. The baskets should not fail catastrophically until they reach a  $\Delta P$  of 60-70 psid. We must consider the fact that there is a rapid rise in  $\Delta P$  once the differential pressure reaches 30 psid. The time required for the  $\Delta P$  to increase from 30 psid to 60-70 psid is very short (the actual time depends on many factors, dirt load, viscosity, etc.), this is why it is recommended that the filter basket be serviced at a differential of 15-20 psid.


If cyclical loadings or pulses must be considered, a reduction in the recommended maximum  $\Delta P$  should be taken (reduction dependent on severity of pulse, viscosity, etc.). These pressure spikes will adversely affect the integrity of the filter basket.

The above information is for filter baskets only. If a filter bag is utilized, it is critical that the  $\Delta P$  never exceeds 15 psid. A filter bag can not withstand a high differential pressure.

## **Rosedale Cartridge Sealing Options For Standard Vessels**




## FILTRATION RANGES





Relative Size of Particles


Magnification 500 times



Micron Comparisons

Substance	Microns
Table salt	100
Human hair (average dia.)	50-70
White blood cell	25
Talcum powder	10
Cocoa	8-10
Red blood cell	8
Bacteria (cocci)	2
<b>Note:</b> Lower limit of visibility (naked eye)–40 Microns	

## ISO 4406 Code



Each number refers to ISO Range Code, which is determined by number of particles for that size (4/6/14) and larger present in 1 ml of fluid.

### EXAMPLE:

- ▶ Larger Than 4 µm = **22,340**
- ▶ Larger Than 6 µm = **1,950**
- ▶ Larger Than 14 µm = **43**


ISO Code = **22 / 18 / 13**

MINUTES CONVERTED TO DECIMALS OF A DEGREE		DECIMAL EQUIVALENTS OF FRACTIONS		WATER PRESSURE (PSI) TO FEET OF HEAD		WATER FEET OF HEAD TO PSI	
MINUTE	DEGREE	INCHES	DECIMAL	POUNDS PER SQUARE INCH	FEET HEAD	FEET HEAD	POUNDS PER SQUARE INCH
1	.0166	1/64	.015625	1	2.31	1	.43
2	.0333	1/32	.03125	2	4.62	2	.87
3	.05	3/64	.046875	3	6.93	3	1.30
4	.0666	1/20	.05	4	9.24	4	1.73
5	.0833	1/16	.0625	5	11.54	5	2.17
6	.1000	1/13	.0769	6	13.85	6	2.60
7	.1166	5/64	.078125	7	16.16	7	3.03
8	.1333	1/12	.0833	8	18.47	8	3.46
9	.1500	1/11	.0909	9	20.78	9	3.90
10	.1666	3/32	.09375	10	23.09	10	4.33
11	.1833	1/10	.10	15	34.63	15	6.50
12	.2000	7/64	.109375	20	46.18	20	8.66
13	.2166	1/9	.111	25	57.72	25	10.83
14	.2333	1/8	.125	30	69.27	30	12.99
15	.2500	9/64	.140625	40	92.36	40	17.32
16	.2666	1/7	.1429	50	115.45	50	21.65
17	.2833	5/32	.15625	60	138.54	60	25.99
18	.3000	1/6	.1667	70	161.63	70	30.32
19	.3166	11/64	.171875	80	184.72	80	34.65
20	.3333	3/16	.1875	90	207.81	90	39.98
21	.3500	1/5	.2	100	230.90	100	43.31
22	.3666	13/64	.203125	110	253.98	110	47.64
23	.3833	7/32	.21875	120	277.07	120	51.97
24	.4000	15/64	.234375	130	300.16	130	56.30
25	.4166	1/4	.25	140	323.25	140	60.63
26	.4333	17/64	.265625	150	346.34	150	64.96
27	.4500	9/32	.28125	160	369.43	160	69.29
28	.4666	19/64	.296875	170	392.52	170	73.63
29	.4833	5/16	.3125	180	415.61	180	77.96
30	.5000	21/64	.328125	200	461.78	200	86.62
31	.5166	1/3	.333	250	577.24	250	108.27
32	.5333	11/32	.34375	300	692.69	300	129.93
33	.5500	23/64	.359375	350	808.13	350	151.58
34	.5666	3/8	.375	400	922.58	400	173.24
35	.5833	25/64	.390625	500	1154.48	500	216.55
36	.6000	13/32	.40625	600	1385.39	600	259.85
37	.6166	27/64	.421875	700	1616.30	700	303.16
38	.6333	7/16	.4375	800	1847.20	800	346.47
39	.6500	29/64	.453125	900	2078.10	900	389.78
40	.666	15/32	.46875	1000	2309.00	1000	433.00
41	.6833	31/64	.484375				
42	.7000	1/2	.5				
43	.7166	33/64	.515625				
44	.7333	17/32	.53125				
45	.7500	35/64	.546875				
46	.7666	9/16	.5625				
47	.7833	37/64	.578125				
48	.8000	19/32	.59375				
49	.8166	39/64	.609375				
50	.8333	5/8	.625				
51	.8500	41/64	.640625				
52	.8666	21/32	.65625				
53	.8833	43/64	.671875				
54	.9000	11/16	.6875				
55	.9166	45/64	.703125				
56	.9333	23/32	.71875				
57	.9500	47/64	.734375				
58	.9666	3/4	.75				
59	.9833	49/64	.765625				
60	1.0000	25/32	.78125				
		51/64	.796875				
		13/16	.8125				
		53/64	.828125				
		27/32	.84375				
		55/64	.859375				
		7/8	.875				
		57/64	.890625				
		29/32	.90625				
		59/64	.921875				
		15/16	.9375				
		61/64	.953125				
		31/32	.96875				
		63/64	.984375				
		1	1.				


**Note:** One pound of pressure per sq. inch of water equals 2.309 feet of water at 62° F. To find the feet head of water for any pressure not given in the table, multiply the pressure pounds per sq. inch by 2.309

**Note:** One foot of water at 62° F equals .433 pound pressure per sq. inch. To find the pressure per sq. inch for any feet head not given in the table, multiply the feet head by .433

## Velocity vs. Flow Table



## Flow Rate in Pipe






# **Flow Conversion Chart**

This Nomograph/Chart provides flow rate data in cubic feet per minute (column D), gallons per minute (column E), Or pounds of water per minute (column F) for inside pipe diameters from 0.2 to 16 inches for velocities from 0.03 to 30 feet per second (column C). Similarly, velocities may be determined from flow rates.

An example is shown for 2 inch standard pipe (2.07" ID) at 2 feet per second. A line is drawn connecting these two values in columns A and C. At it's intersection with column B a line is drawn horizontally using columns H1 and H2 for guidance. Flow rates are now seen in columns D, E, and F.

A second example uses 4 inch extra heavy pipe at 10 feet per second. A horizontal line is drawn to the left from column B to column A and this intersection is connected to the 10 feet per second location on column C. At the intersection of this slanting line with column B a horizontal line is drawn to show the flow rates resulting.



## **Converting Air Flow to Liquid Flow Equivalents**

You must first establish the gas flow rate in units of standard cubic feet per minute (SCFM). (A "standard cubic foot" of gas is measured at 14.7 psia ( pounds per square inch, absolute) at 60° F.

$$\text{SCFM} = \text{CFM} \times \left( \frac{14.7 + \text{PSIG}}{14.7} \right) \times \left( \frac{530}{460 + F} \right)$$

**SCFM** = Gas flow in standard cubic feet per min.

**CFM** = Actual gas flow in cubic feet per min.

**PSIG** = Actual gas pressure, pounds per square inch, gauge.

**F** = Actual gas temperature, F°.

Next we find the gallons-per-minute equivalent to your particular gas flow, temperature, and pressure:

$$\text{GPM} = \frac{\text{SCFM}}{4.1} \times \sqrt{\frac{14.7 + \text{PSIG}}{14.7}} \times \sqrt{\frac{460 + F}{530}} \times \sqrt{\text{SG}}$$

**SG** = Specific Gravity of the gas, relative to air. (See chart below.)

<b>GAS</b>	<b>SG</b>	<b>GAS</b>	<b>SG</b>
Air	1.00	Hellum	.14
Ammonia	.59	Nitric Oxide	1.03
Argon	1.38	Nitrogen	.97
Carbon Dioxide	1.52	Nitrous Oxide	.59
Chlorine	2.45	Sulphur Dioxide	2.21


**Note:** Steam and explosive gases are not recommended.

### **For Vacuum Applications:**


Use the following formula for converting vacuum applications to GPM.

$$\text{GPM} = \frac{\text{SCFM}}{4.1} \times \sqrt{\frac{14.7 + \text{PSIG}}{14.7}} \times \sqrt{\frac{460 + F}{530}} \times \sqrt{\text{SG}}$$


## Viscosity vs. Temperature



## Viscosity vs. Temperature



# **A.S.T.M. Standard Viscosity-Temperatures For Liquid Petroleum Products (D341-43)**





## Enclosure Types for Non-Hazardous Locations

Type	NEMA NEMA National Electrical Manufacturers Association (Nema Standard 250) and Electrical and Electronic Manufacturers Association of Canada (EEMAC)	UL Underwriters Laboratories Inc. (UL 50 and UL 508)	CSA Canadian Standards Association (Standard C22.2 No. 94)
<b>1</b>	Enclosures are intended for indoor use primarily to provide a degree of protection against contact with the enclosed equipment or locations where unusual service conditions do not exist.	Indoor use primarily to provide protection against contact with the enclosed equipment and against a limited amount of falling dirt.	General purpose enclosure. Protects against accidental contact with live parts.
<b>2</b>	Enclosures are intended for indoor use primarily to provide a degree of protection against limited amounts of falling water and dirt.	Indoor use to provide a degree of protection against limited amounts of falling water and dirt.	Indoor use to provide a degree of protection against dripping and light splashing of noncorrosive liquids and falling dirt.
<b>3</b>	Enclosures are intended for outdoor use primarily to provide a degree of protection against windblown dust, rain, and sleet; undamaged by the formation of ice on the enclosure.	Outdoor use to provide a degree of protection against windblown dust and windblown rain; undamaged by the formation of ice on the enclosure.	Indoor or outdoor use provides a degree of protection against rain, snow, and windblown dust; undamaged by the external formation of ice on the enclosure.
<b>3R</b>	Enclosures are intended for outdoor use primarily to provide a degree of protection against falling rain and sleet; undamaged by the formation of ice on the enclosure.	Outdoor use to provide a degree of protection against falling rain; undamaged by the formation of ice on the enclosure.	Indoor or outdoor use provides a degree of protection against rain and snow; undamaged by the external formation of ice on the enclosure.
<b>4</b>	Enclosures are intended for indoor or outdoor use primarily to provide a degree of protection against windblown dust and rain, splashing water, and hose directed water; undamaged by the formation of ice on the enclosure.	Either indoor or outdoor use to provide a degree of protection against falling rain, splashing water, and hose-directed water; undamaged by the formation of ice on the enclosure.	Indoor or outdoor use, provides a degree of protection against rain, snow, wind-blown dust, splashing and hose-directed water; undamaged by the external formation of ice on the enclosure.
<b>4X</b>	Enclosures are intended for indoor or outdoor use primarily to provide a degree of protection against corrosion, windblown dust and rain, splashing water, and hose-directed water; undamaged by the formation of ice on the enclosure.	Either indoor or outdoor use to provide a degree of protection against falling rain, splashing water, and hose-directed water; undamaged by the formation of ice on the enclosure: resists corrosion.	Indoor or outdoor use provides a degree of protection against rain, snow, wind-blown dust, splashing and hose-directed water; undamaged by the external formation of ice on the enclosure: resist corrosion.
<b>6</b>	Enclosures are intended for use indoors or outdoors where occasional submersion is encountered.	Indoor or outdoor use to provide a degree of protection against entry of water during temporary submersion of a limited depth undamaged by the formation of ice on the enclosure.	Indoor or outdoor use provides a degree of protection against the entry of water during temporary submersion at a limited depth, undamaged by the external formation of ice on the enclosure, resists corrosion.
<b>12</b>	Enclosures are intended for use primarily to provide a degree of protection against dust, falling dirt and dripping noncorrosive liquids.	Indoor use to provide a degree of protection against dust, dirt, flying fibers, dripping water and external condensation of noncorrosive liquids.	Indoor use a degree of protection against circulating dust, lint, fibers and flyings, dripping and light splashing of noncorrosive liquids, not provided with knockouts.
<b>13</b>	Enclosures are intended for indoor use primarily to provide a degree of protection against dust, spraying of water, oil and noncorrosive coolant.	Indoor use to provide a degree of protection against lint, dust seepage, external condensation and spraying of water, oil and noncorrosive liquids.	Indoor use provides a degree of protection against circulation dust, lint, fibers and flyings, seepage and spraying of noncorrosive liquids, including oils and coolants.
This material is reproduced with permission from NEMA. The preceding descriptions, however, are not intended to be complete representations of National Electrical Manufacturers Association standards for enclosures nor those of the Electrical and Electronic Manufacturers Association of Canada.		This material is reproduced with permission from Underwriters Laboratories Inc. Standard for Safety for Cabinets and Boxes, UL 50, Copyright 1985 and Industrial Control Equipment, UL 508, Copyright 1984 by Underwriters Laboratories Inc. Underwriters Laboratories Inc. (UL) shall not be responsible to anyone for the use of or reliance upon a UL Standard by anyone. UL shall not incur any obligation or liability for damages, including consequential damages, arising out of or connection with the use, interpretation of or reliance upon a UL Standard.	
		This material is reproduced with permission from the Canadian Standards Association.	

## Comparison of Specific Non-Hazardous Applications


### Indoor Locations

Provides a Degree of Protection Against the Following Environmental Conditions	Type of Enclosure										
	1*	2*	4	4X	5	6	6P	11	12	12K	13
Incidental contact with enclosed equipment	■	■	■	■	■	■	■	■	■	■	■
Falling dirt	■	■	■	■	■	■	■	■	■	■	■
Falling liquids and light splashing		■	■	■	■		■	■	■	■	■
Dust, lint, fibers, and flyings †			■	■	■	■	■		■	■	■
Hosedown and splashing water			■	■		■	■				
Oil and coolant seepage								■	■	■	
Oil or coolant spraying and splashing										■	
Corrosive agents				■			■	■			
Occasional temporary submersion						■	■				
Occasional prolonged submersion							■				

■ These enclosures may be ventilated. However, Type I may not provide protection against small particles of falling dirt when ventilation is provided in the enclosure top. Consult Hoffman Engineering for more information.

† These fibers and flyings are non-hazardous materials and are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or combustible flyings see the National Electrical Code, Section 500-6(a).

# Conductor I.D. Selection Chart




# **Pressure Loss (psi/Foot Length) In Pipes At Average Velocity (ft/sec)**

Material						Pressure Loss (psi/foot length) in Pipes at Average Flow Velocity (ft/sec)														Equivalent Pipe Lengths (ft.) for Circuit Components							
Size (Inches)	Pipe Hose	O.D. Inches	I.D. Inches	Wall Inches	I.D. Area Sq. In.	5		7		10		15		20		25		30		Tee				Elbow			
						Loss	GPM	Loss	GPM	Loss	GPM	Loss	GPM	Loss	GPM	Loss	GPM	Loss	GPM								
1/8	PIPE-SCH 40	.405	.269	.068	.057	1.25	.89	1.79	1.24	2.60	1.75	3.16	2.67	5.47	3.56	6.20	4.45	7.07	5.34								
	PIPE-SCH 80	.405	.215	.095	.036	1.89	.56	3.05	.78	4.26	1.12	5.20	1.68	8.38	2.24	11.1	2.80	12.7	3.36								
	HOSE	—	.125	—	.012	5.96	.186	8.37	.260	11.9	.372	18.0	.558	24.0	.744	30.0	.930	35.7	1.11								
1/4	PIPE-SCH 40	.540	.364	.088	.104	.67	1.62	1.05	2.27	1.64	3.24	1.92	4.96	2.97	6.48	3.23	8.10	3.73	9.72								
	PIPE-SCH 80	.540	.302	.119	0.72	1.11	1.12	1.49	1.57	2.11	2.24	2.84	3.36	4.15	4.48	5.08	5.60	6.30	6.72								
	HOSE	—	.250	—	.049	1.57	.758	2.17	1.08	3.00	1.49	4.49	2.23	6.04	2.98	7.49	3.72	8.95	4.44								
3/8	PIPE-SCH 40	.675	.493	.091	.191	.39	2.98	.57	4.18	.86	5.96	1.05	8.94	1.69	11.92	4.27	14.9	5.78	16.9	2.7	.8	2.7	1.2	2.7	.6		
	PIPE-SCH 80	.675	.423	.126	.140	.54	2.18	.74	3.06	1.10	4.36	1.34	6.54	1.97	8.72	5.19	10.9	7.20	13.1								
	HOSE	—	.375	—	.110	.685	1.71	.97	2.43	1.34	3.35	2.02	5.03	2.68	6.71	3.33	8.36	3.99	10.0								
1/2	PIPE-SCH 40	.840	.622	.109	.304	.24	4.74	.36	6.65	.49	9.48	.68	14.22	2.09	18.98	3.38	23.7	4.28	28.4	3.5	1.05	3.5	1.5	3.5	.75		
	PIPE-SCH 80	.840	.147	.234	.30	3.65	.45	5.12	.71	7.30	.78	10.9	10.9	2.47	14.6	3.61	18.2	5.00	21.9	2.9	.9	2.9	1.4	2.9	.68		
	PIPE-SCH XX	.840	.252	.294	.050	1.54	.78	2.19	1.09	3.08	1.56	3.65	2.34	6.13	3.12	7.48	3.90	9.55	4.68								
	HOSE	—	.500	—	.196	.387	3.03	.547	4.08	.755	5.94	1.13	8.90	2.4	11.9	3.15	15.3	4.5	17.7								
3/4	PIPE-SCH 40	1.050	.824	.113	.533	.14	8.32	.22	11.7	.27	16.6	.78	25.0	1.47	33.3	2.19	41.6	3.00	49.9	4.5	1.4	4.5	2.1	4.5	1.0		
	PIPE-SCH 80	1.050	.742	.154	.432	.16	6.74	.26	9.45	.37	13.5	.87	20.2	1.71	27.0	2.48	33.7	3.52	40.4	4.0	1.2	4.0	1.6	4.0	.8		
	PIPE-SCH XX	1.050	.434	.308	.148	.53	2.31	.67	3.24	1.05	4.62	1.31	6.93	1.94	9.24	5.06	11.6	7.02	13.9								
	HOSE	—	.750	—	.442	.171	6.82	.248	9.92	.336	13.4	.502	20.1	1.33	26.8	2.02	33.4	2.90	41.3								
1	PIPE-SCH 40	1.315	1.049	.133	.863	.10	13.5	.13	18.9	.34	26.9	.57	40.4	1.42	53.8	1.64	67.3	2.24	80.7	5.7	1.7	5.7	2.6	5.7	1.2		
	PIPE-SCH 80	1.315	.957	.179	.719	.11	11.2	.15	15.7	.24	22.4	.62	33.6	1.23	44.8	1.84	56.1	2.93	67.3	5.2	1.6	5.2	2.5	5.2	1.1		
	PIPE-SCH XX	1.315	.599	.358	.863	.26	4.39	.37	6.16	.53	8.78	.67	13.2	2.25	17.6	3.29	22.0	4.20	26.3	3.0	1.0	3.0	1.5	3.0	.75		
	HOSE	—	1.00	—	.785	.097	12.2	.136	17.1	.194	24.4	.610	36.6	.987	48.8	1.51	61.2	2.02	73.4								
1-1/4	PIPE-SCH 40	1.660	1.380	.140	1.496	.05	23.4	.08	31.7	.25	46.7	.39	70.1	.78	93.4	1.18	117	1.47	140	7.5	2.4	7.5	3.7	7.5	1.6		
	PIPE-SCH 80	1.660	1.278	.191	1.280	.07	20.0	.09	28.1	.26	39.9	.44	58.9	.85	79.8	1.27	99.8	1.80	120	7.0	2.1	7.0	3.5	7.0	1.5		
	PIPE-SCH XX	1.660	.896	.382	.630	.13	9.83	.16	13.8	.24	19.7	.71	29.5	1.35	39.3	2.01	49.2	2.76	59.0	4.9	1.5	4.9	2.3	4.9	1.1		
	HOSE	—	1.25	—	1.23	.062	19.1	.087	26.8	.125	38.2	.436	57.3	.738	76.4	1.08	95.5	1.52	115								
1-1/2	PIPE-SCH 40	1.900	1.610	.145	2.046	.04	31.8	.06	44.5	.19	63.5	.33	95.3	.64	127	.96	159	1.26	191	9.0	2.8	9.0	4.3	9.0	2.0		
	PIPE-SCH 80	1.900	1.500	.200	1.767	.04	27.6	.06	38.6	.21	55.1	.42	82.7	.71	110	1.06	138	1.36	166	8.2	2.6	8.2	4.2	8.2	1.8		
	PIPE-SCH XX	1.900	1.100	.400	.950	.09	14.8	.09	20.8	.32	29.6	.51	44.4	1.05	59.2	1.51	74.1	2.14	88.9	6.5	2.0	6.5	3.0	6.5	1.4		
	HOSE	—	1.50	—	1.77	.044	27.7	.061	38.6	.180	55.1	.353	82.7	.59	110	.86	138	1.21	166								
2	PIPE-SCH 40	2.375	2.067	.154	3.355	.03	52.3	.08	73.4	.14	105	.24	159	.48	209	.69	262	.85	324	11.0	3.5	11.0	5.5	11.0	2.5		
	PIPE-SCH 80	2.375	1.939	.218	2.953	.03	46.0	.09	64.6	.15	92.0	.26	138	.52	184	.73	230	.98	275	10.8	3.4	10.8	5.0	10.8	2.4		
	PIPE-SCH XX	2.375	1.503	.436	1.773	.04	27.7	.12	38.8	.21	55.3	.36	82.9	.72	111	1.34	138	1.36	166	8.2	2.6	8.2	4.0	8.2	1.8		
	HOSE	—	2.00	—	3.14	.024	48.9	.034	68.6	.123	97.8	.256	147	.41	196	.60	245	.80	293								
2-1/2	PIPE-SCH 40	2.875	2.469	.203	4.788	.03	74.8	.07	105	.11	149	.20	224	.37	299	.53	374	.72	449	14.0	4.2	14.0	6.5	14.0	3.0		
	PIPE-SCH 80	2.875	2.323	.276	4.238	.03	66.1	.07	92.6	.12	132	.21	198	.39	264	.57	331	.87	397	13.0	4.0	13.0	6.1	13.0	2.9		
	PIPE-SCH XX	2.875	1.771	.552	2.464	.03	38.5	.10	53.4	.17	76.9	.30	115	.59	154	.79	193	1.15	231	10.3	3.1	10.3	4.8	10.3	2.2		
	HOSE	—	2.50	—	4.91	.016	76.5	.045	107	.09	153	.18	229	.30	306	.43	382	.617	459								

# Orifice Pressure Drop

Approximate data. Based on specific gravity = 0.9, viscosity = 100 SSU.





## Pressure Conversion Table

Multiply no. of by to obtain	Atmos- pheres	Bars	Dynes/ cm <sup>2</sup>	In. of Hg (0°C)	In. of H <sub>2</sub> O(4°C)	kg/m <sup>2</sup>	(psi)	Lb/in <sup>2</sup> Lb/ft <sup>2</sup>	(torr)	mm of Hg Microns	Pascals
Atmospheres		9.86923 X10 <sup>-1</sup>	9.86923 X10 <sup>-7</sup>	3.34207 X10 <sup>-2</sup>	2.458 X10 <sup>-3</sup>	9.678 X10 <sup>-5</sup>	.068046	4.7254 X10 <sup>-4</sup>	1.316 X10 <sup>-3</sup>	1.316 X10 <sup>-6</sup>	9.869 X10 <sup>-6</sup>
Bars	1.01325		10 <sup>-6</sup> X10 <sup>-2</sup>	3.3864 X10 <sup>-3</sup>	2.491 X10 <sup>-5</sup>	9.8067	6.8948 X10 <sup>-2</sup>	4.788 X10 <sup>-4</sup>	1.333 X10 <sup>-3</sup>	1.333 X10 <sup>-6</sup>	10 <sup>5</sup>
Dynes/ cm <sup>2</sup>	1.01325 X10 <sup>6</sup>	10 <sup>6</sup>		3.386 X10 <sup>-4</sup>	2.491 X10 <sup>-3</sup>	98.067	6.8948	478.8 X10 <sup>-4</sup>	1.333	1.333 X10 <sup>-3</sup>	10
In. of Hg (0°C)	29.9213	29.53	2.953 X10 <sup>-5</sup>		7.355 X10 <sup>-2</sup>	2.896 X10 <sup>-3</sup>	2.036	.014139	3.937 X10 <sup>-2</sup>	3.937 X10 <sup>-5</sup>	2.953 X10 <sup>-4</sup>
In. of H <sub>2</sub> O(4°C)	406.8	401.48	4.0148 X10 <sup>-4</sup>	13.60		3.937 X10 <sup>-2</sup>	27.68	.1922	.5354	5.354 X10 <sup>-4</sup>	4.014 X10 <sup>-3</sup>
kg / m <sup>2</sup>	1.033227 X10 <sup>4</sup>	1.0197 X10 <sup>4</sup>	1.0197 X10 <sup>-2</sup>	345.3	25.40		7.0306 X10 <sup>-2</sup>	4.882	13.59	13.59 X10 <sup>-3</sup>	1.019 X10 <sup>-1</sup>
Lb /in.2 (psi )	14.695595	14.4504	1.4504 X10 <sup>-5</sup>	.4912	3.6126 X10 <sup>-2</sup>	1.423 X10 <sup>-3</sup>		6.9444 X10 <sup>-3</sup>	1.934 X10 <sup>-2</sup>	1.934 X10 <sup>-5</sup>	1.450 X10 <sup>-4</sup>
Lb / f <sup>12</sup>	2116.22	2088.5	2.0885 X10 <sup>-3</sup>	70.726	5.202	.2048	144.0		2.7844	2.7844 X10 <sup>-3</sup>	2.089 X10 <sup>-2</sup>
mm of Hg (torr)	760	750.06	7.5006 X10 <sup>-4</sup>	25.400	1.868	7.3558 X10 <sup>-2</sup>	51.715	0.35913		10 <sup>-3</sup>	7.502 X10 <sup>-3</sup>
Microns	760 X10 <sup>3</sup>	750.06 X10 <sup>3</sup>	.75006	2.54 X10 <sup>-4</sup>	1.868 X10 <sup>-3</sup>	73.558	51.715 X10 <sup>-3</sup>	359.1	1X10 <sup>3</sup>		7 502
Pascals	1.01325 X10 <sup>5</sup>	1X10 <sup>5</sup>	10 <sup>-1</sup>	3.386 X10 <sup>-3</sup>	2.491 X10 <sup>-2</sup>	9.8067	6.8948 X10 <sup>-3</sup>	4.788 X10 <sup>-1</sup>	1.333 X10 <sup>-2</sup>	1.333 X10 <sup>-1</sup>	

## Temperature Data

The accompanying chart not only lists the melting points of various alloys and metals but also serves as a convenient means for conversion between Centigrade and Fahrenheit temperature scales. In addition, on the far right of the scale are shown the color designations that are commonly used in judging the temperatures of hot metal by color.


### Melting Points

This chart should prove useful to all welding operators for it contains basic information on working with metals at elevated temperatures. Reference to the chart, for instance, shows why aluminum and aluminum alloys, because of their low melting points, give little or no indication by change in color when they approach welding heat. On the other hand, the high melting point of wrought iron explains why considerably more heat is required to weld this metal than is required for cast iron, for instance.

### Temperature Color Scale

Another use for the chart is in estimating the temperature by color. For instance, instructions may require that the part be preheated to 1,100 deg. F. before welding. If you are without a thermocouple or other means for accurately measuring high temperatures, reference to the chart shows the part, at 1,100 deg. F. would have a blood-red color. With a little experience, you can estimate this fairly closely by eye. In this connection, it should be mentioned that the color scale is for observations made in a fairly dark place and without

### MELTING POINT OF METALS AND ALLOYS OF PRACTICAL IMPORTANCE



welding goggles. As the light increases, the color groups on the scale will apply to higher temperatures.

### Conversion Data

Finally, the chart is a ready means for converting Fahrenheit to Centigrade, and vice versa. Suppose you are familiar with the Fahrenheit scale, yet instructions call for the quenching of a welded part from 900 deg. C. Reference to the chart shows this to be approximately 1,650 deg. F.

### (Stuff You Probably Know)

1. PASCAL'S LAW: Pressure exerted on a confined fluid is transmitted undiminished in all directions and acts with equal force on all equal areas and at right angles to them.

2. Hydraulics is a means of power transmission.

3. Work is force acting through a distance.  
WORK = FORCE X DISTANCE.

**Example:** Work (in. lbs.) =  
Force (lbs.) x Distance (in.)

4. Power is the rate of doing work.  
$$\text{Power} = \frac{\text{Work}}{\text{Time}} = \frac{\text{Force} \times \text{Distance}}{\text{Time}}$$

5. The force (pounds) exerted by a piston can be determined by multiplying the piston area (square inches) by the pressure applied. (PSI)

$$\text{Force} = \text{Pressure} \times \text{Area}$$

(To find the area, square the diameter and multiply by .7854)  $A = D^2 \times .7854$  or

$$\text{Area} = \text{Diameter}^2 \times .7854$$

6. To determine the volume (cubic inches) required to move a piston a given distance, multiply the piston cross sectional area (sq. Inches) by the stroke required (inches).

$$\text{Volume} = \text{Area} \times L$$

7. Hydraulic oil serves as a lubricant and is practically non-compressible. It will compress approximately .4 of 1% at 1000 PSI and 1.1% at 3000PSI. at 120°F.

8. The weight of hydraulic oil may vary with a change in viscosity, however, 55 to 58 lbs. per cubic foot covers the viscosity range from 150 SSU to 900 SSU at 100°F.

9. Pressure at the bottom of a one foot column of oil will be approximately 0.4 PSI. To find the approximate pressure in psi at the bottom of any column of oil, multiply the height in feet by 0.4.

10. Atmospheric pressure equals 14.7 PSIA at sea level.  $\Delta P$  means pressure difference.

11. Gage readings do not include atmospheric pressure unless marked PSIA.

12. There must be a pressure drop (pressure difference) across an orifice or restriction to cause flow through it. Conversely, if there is no flow there will be no pressure drop.


$$F = P \times A$$

13. A fluid is pushed, not drawn, into a pump. If pumping from an open reservoir, atmospheric pressure pushes the fluid into the pump. Some pumps are used specifically to create pressure, any resulting flow is incidental.

14. A pump does not pump pressure; its purpose is to create flow. Pumps used to transmit power are usually positive displacement type.

15. Pressure is caused by resistance to flow. A pressure gage indicates the pressure in some unit as psi.

## Force Equals Pressure Times Area



Most differential pressure indicators use a piston connected through a small hole in the side of the filter. This hole could clog, or the piston could easily be blocked or restricted. Rosedale's piston is much larger in diameter and surface area, requiring a greater blockage to restrict it, and since it is inside the housing, there is no outside hole to clog. It produces a cleaner, more accurate and reliable unit, providing excellent performance and value.

	Standard	Rosedale Model 4
Piston Diameter	.38	4.38
(F=P X A) Force Exerted @ 15 psi	1.65 lbs. of force	225.00 lbs. of force

# **Properties of American National Standard Schedule 40 and 80 Welded and Seamless Wrought Steel Pipe**

**Properties of American National Standard Schedule 40 Welded and Seamless Wrought Steel Pipe**

Diameter, Inches			Wall Thickness (Inches)	Cross-Sectional Area of Metal	Weight per Foot, Pounds		Capacity per Foot of Length		Length of Pipe in Feet to Contain		Properties of Sections		
Nominal	Actual Inside	Actual Outside			Of Pipe	Of Water in Pipe	In Cubic Inches	In Gallons	One Cubic Foot	One Gallon	Moment Of Inertia	Radius of Gyration	Section Modulus
1/8	0.269	0.405	0.068	0.072	0.24	0.025	0.682	0.003	2532.	338.7	0.00106	0.122	0.00525
1/4	0.364	0.540	0.088	0.125	0.42	0.045	1.249	0.005	1384.	185.0	0.00331	0.163	0.01227
3/8	0.493	0.675	0.091	0.167	0.57	0.083	2.291	0.010	754.4	100.8	0.00729	0.209	0.02160
1/2	0.622	0.840	0.109	0.250	0.85	0.123	3.646	0.016	473.9	63.35	0.01709	0.261	0.04070
3/4	0.824	1.050	0.113	0.333	1.13	0.231	6.399	0.028	270.0	36.10	0.03704	0.334	0.07055
1	1.049	1.315	0.133	0.494	1.68	0.374	10.37	0.045	166.6	22.27	0.08734	0.421	0.1328
1-1/4	1.380	1.660	0.140	0.669	2.27	0.648	17.95	0.078	96.28	12.87	0.1947	0.539	0.2346
1-1/2	1.610	1.900	0.145	0.799	2.72	0.882	24.43	0.106	70.73	9.456	0.3099	0.623	0.3262
2	2.067	2.375	0.154	1.075	3.65	1.454	40.27	0.174	42.91	5.737	0.6658	0.787	0.5607
2-1/2	2.469	2.875	0.203	1.704	5.79	2.074	57.45	0.249	30.08	4.021	1.530	0.947	1.064
3	3.068	3.500	0.216	2.228	7.58	3.202	88.71	0.384	19.48	2.604	3.017	1.163	1.724
3-1/2	3.548	4.000	0.226	2.680	9.11	4.283	118.6	0.514	14.56	1.947	4.788	1.337	2.394
4	4.026	4.500	0.237	3.174	10.79	5.515	152.8	0.661	11.31	1.512	7.233	1.510	3.215
5	5.047	5.563	0.258	4.300	14.62	8.666	240.1	1.04	7.198	0.9622	15.16	1.878	5.451
6	6.065	6.625	0.280	5.581	18.97	12.52	346.7	1.50	4.984	0.6663	28.14	2.245	8.496
8	7.981	8.625	0.322	8.399	28.55	21.67	600.3	2.60	2.878	0.3848	72.49	2.938	16.81
10	10.020	10.750	0.365	11.91	40.48	34.16	946.3	4.10	1.826	0.2441	160.7	3.674	29.91
12	11.938	12.750	0.406	15.74	53.52	48.49	1343.	5.81	1.286	0.1720	300.2	4.364	47.09
16	15.000	16.000	0.500	24.35	82.77	76.55	2121.	9.18	0.8149	0.1089	732.0	5.484	91.50
18	16.876	18.000	0.562	30.79	104.7	96.90	2684.	11.62	0.6438	0.0861	1172.	6.168	130.2
20	18.812	20.000	0.594	36.21	123.1	120.4	3335.	14.44	0.5181	0.0693	1706.	6.864	170.6
24	22.624	24.000	0.688	50.39	171.3	174.1	4824.	20.88	0.3582	0.0479	3426.	8.246	285.5
32	30.624	32.000	0.688	67.68	230.1	319.1	8839.	38.26	0.1955	0.0261	8299.	11.07	518.7

Note: Torsional Section Modulus Equals Twice Section Modulus.

**Properties of American National Standard Schedule 80 Welded and Seamless Wrought Steel Pipe**

Diameter, Inches			Wall Thickness (Inches)	Cross-Sectional Area of Metal	Weight per Foot, Pounds		Capacity per Foot of Length		Length of Pipe in Feet to Contain		Properties of Sections		
Nominal	Actual Inside	Actual Outside			Of Pipe	Of Water in Pipe	In Cubic Inches	In Gallons	One Cubic Foot	One Gallon	Moment Of Inertia	Radius of Gyration	Section Modulus
1/8	0.215	0.405	0.095	0.093	0.315	0.016	0.436	0.0019	3966.	530.2	0.00122	0.115	0.00600
1/4	0.302	0.540	0.119	0.157	0.537	0.031	0.860	0.0037	2010.	268.7	0.00377	0.155	0.01395
3/8	0.423	0.675	0.126	0.217	0.739	0.061	1.686	0.0073	1025.	137.0	0.00862	0.199	0.02554
1/2	0.546	0.840	0.147	0.320	1.088	0.101	2.810	0.0122	615.0	82.22	0.02008	0.250	0.04780
3/4	0.742	1.050	0.154	0.433	1.474	0.187	5.189	0.0225	333.0	44.52	0.04479	0.321	0.08531
1	0.957	1.315	0.179	0.639	2.172	0.312	8.632	0.0374	200.2	26.76	0.1056	0.407	0.1606
1-1/4	1.278	1.660	0.191	0.881	2.997	0.556	15.39	0.0667	112.3	15.01	0.2418	0.524	0.2913
1-1/2	1.500	1.900	0.200	1.068	3.631	0.766	21.21	0.0918	81.49	10.89	0.3912	0.605	0.4118
2	1.939	2.375	0.218	1.477	5.022	1.279	35.43	0.1534	48.77	6.519	0.8680	0.766	0.7309
2-1/2	2.323	2.875	0.276	2.254	7.661	1.836	50.86	0.2202	33.98	4.542	1.924	0.924	1.339
3	2.900	3.500	0.300	3.016	10.25	2.861	79.26	0.3431	21.80	2.914	3.895	1.136	2.225
3-1/2	3.364	4.000	0.318	3.678	12.50	3.850	106.7	0.4617	16.20	2.166	6.280	1.307	3.140
4	3.826	4.500	0.337	4.407	14.98	4.980	138.0	0.5972	12.53	1.674	9.611	1.477	4.272
5	4.813	5.563	0.375	6.112	20.78	7.882	218.3	0.9451	7.915	1.058	20.67	1.839	7.432
6	5.761	6.625	0.432	8.405	28.57	11.29	312.8	1.354	5.524	0.738	40.49	2.195	12.22
8	7.625	8.625	0.500	12.76	43.39	19.78	548.0	2.372	3.153	0.422	105.7	2.878	24.52
10	9.562	10.750	0.594	18.95	64.42	31.11	861.7	3.730	2.005	0.268	245.2	3.597	45.62
12	11.374	12.750	0.688	26.07	88.63	44.02	1219.	5.278	1.417	0.189	475.7	4.271	74.62
14	12.500	14.000	0.750	31.22	106.1	53.16	1473.	6.375	1.173	0.157	687.4	4.692	98.19
16	14.312	16.000	0.844	40.19	136.6	69.69	1931.	8.357	0.895	0.120	1158.	5.366	144.7
18	16.124	18.000	0.938	50.28	170.9	88.46	2450.	10.61	0.705	0.094	1835.	6.041	203.9
20	17.938	20.000	1.031	61.44	208.9	109.5	3033.	13.13	0.570	0.076	2772.	6.716	277.2
22	19.750	22.000	1.125	73.78	250.8	132.7	3676.	15.91	0.470	0.063	4031.	7.391	366.4

Note: Torsional Section Modulus Equals Twice Section Modulus.

## Hardness-Tensile Strength Conversion Chart For Steels

Hardness Number								Tensile Strength,
Vickers <sup>a</sup>	Brinell <sup>b</sup>		Rockwell				Shore	
	Steel Ball	WC Ball	A <sup>c</sup>	B <sup>d</sup>	C <sup>e</sup>	D <sup>f</sup>		
680	...	638	80.8	...	59.2	70.1	80	329
640	...	601	79.8	...	57.3	68.7	77	309
600	...	564	78.6	...	55.2	67.0	74	289
550	505	517	77.0	...	52.3	64.8	...	264
500	465	471	75.3	...	49.1	62.2	66	240
480	448	452	74.5	...	47.7	61.3	64	230
460	433	433	73.6	...	46.1	60.0	62	220
440	415	415	72.8	...	44.5	58.8	59	210
420	397	397	71.8	...	42.7	57.5	57	200
400	379	379	70.8	...	40.8	56.0	55	190
390	369	369	70.3	...	39.8	55.2	...	185
380	360	360	69.8	(110.0)	38.8	54.4	52	180
370	350	350	69.2	...	37.7	53.6	...	175
360	341	341	68.7	(109.0)	36.6	52.8	50	170
350	331	331	68.1	...	35.5	51.9	...	166
340	322	322	67.6	(108.0)	34.4	51.1	47	161
330	313	313	67.0	...	33.3	50.2	...	156
320	303	303	66.4	(107.0)	32.2	49.4	45151	
310	294	294	65.8	...	31.0	48.4	...	146
300	284	284	65.2	(105.5)	29.8	47.5	42	141
295	280	280	64.8	...	29.2	47.1	...	139
290	275	275	64.5	(104.5)	28.5	46.5	41	136
285	270	270	64.2	...	27.8	46.0	...	134
280	265	265	63.8	(103.5)	27.1	45.3	40	131
275	261	261	63.5	...	26.4	44.9	...	129
270	256	256	63.1	(120.0)	25.6	44.3	38	126
265	252	252	62.7	...	24.8	43.7	...	124
260	247	247	62.4	(101.0)	24.0	43.1	37	121
255	243	243	62.0	...	23.1	42.2	...	119
250	238	238	61.6	99.5	22.2	41.7	36	116
245	233	233	61.2	...	21.3	41.1	...	114
240	228	228	60.7	98.1	20.3	40.3	34	111
230	219	219	...	96.7	(18.0)	...	33	106
220	209	...	95.0	(15.7)	...	32	101	
210	200	200	...	93.4	(13.4)	...	30	97
200	190	190	...	91.5	(11.0)	...	29	92
190	181	181	...	89.5	(8.5)	...	28	88
180	171	171	...	(6.0)	...	26	84	
170	162	162	...	85.0	(3.0)	...	25	79
160	152	152	...	81.7	(0.0)	...	24	75
150	143	143	...	78.7	...	...	22	71
140	133	133	...	75.0	...	...	21	66
130	124	124	...	71.2	...	...	20	62
120	114	114	...	66.7	...	...	...	57
110	105	105	...	62.3	...	...	...	...
100	95	95	...	56.2	...	...	...	...
95	90	90	...	52.0	...	...	...	...
90	86	86	...	48.0	...	...	...	...
85	81	81	...	41.0	...	...	...	...

a. Diamond pyramid indenter; 5-120 kg load. b. 10mm diameter ball, hardened steel or tungsten carbide; 3,000 kg load.

c. Brale (diamond cone) indenter; 60 kg load. d. 1/16-inch diameter steel ball; 100 kg load. e. Brale (diamond cone) indenter; 150 kg load. f. Brale (diamond cone) indenter; 100 kg load. g. Scleroscope; Diamond-tipped hammer.

Note: Vickers, Brinell, and Rockwell tests indicate hardness by indentation measurements; Shore test indicates hardness by height of rebound. Values in parentheses are approximate. Reference: ASM Metals Handbook, 8th Edition, Vol 11, Nondestructive Inspection and Quality Control.



## **ASME Coded Vessels and Radiography**

**1. Full Vacuum:** All filter vessels are designed with Full Vacuum as a design condition. If the customer requires this, it can be documented. It is typically not stated on the ASME nameplate that the vessel is designed for Full Vacuum.

**2. Jacketed housings:** All standard filter vessels are designed with consideration of a jacket rated at 1/2 vessel pressure (ex. 150 psi vessel, 75 psi jacket) without modifying the body shell. This condition is valid for a body shell jacket only; any other type of jacket or pressure ratings may not meet the code requirements (ex. full jacket, head & body), please consult Engineering.

**3. Canadian Registry:** We hold several "CRN" (Canadian Registration Number) registration numbers for our vessels in Ontario and British Columbia.

Please consult Engineering for this list. To obtain a "CRN", each province has its own requirements and timetable, consult Engineering.

**4. Closure Assemblies:** Our standard closure assembly for all of our products conform to ASME specification (rod end and clevis pins meet SA-193-B7, eye nuts meet SA-194-2H). Some of our customers request different materials. The only other available material is a 304 stainless steel closure, which is available in all sizes.

**5. Welded Attachments:** Welded attachments to 316 S.S. vessels (legs, lugs, davit arm bracket, lifting rod, nameplate bracket, etc.) are typically 304 series stainless steel unless specified by customer.

## **Radiography**

Radiography is one of the methods of NDE (Non Destructive Examination) tools utilized in the fabrication of pressure vessels (i.e., Rosedale Filter Vessels). Radiography is a tool used to verify that the welds of the pressure vessel are within allowable quality limits.

The "ASME Code Section VIII, Division 1 Pressure Vessels" gives guidelines for the use of radiography. Radiography is required in Code fabrication for vessels used to contain lethal substances (Lethal Service), when weld joints exceed thickness limits and in unfired steam boilers. For all of Rosedale's standard filter vessels, radiography is not a Code requirement.

When designing a pressure vessel, joint efficiencies are established based on the degree of radiographic examination (Full, Spot or None). Higher joint efficiencies are assigned to higher degrees of examination. Determining the joint efficiency is one design parameter that is critical to optimizing the design of a pressure vessel. This optimization allows for the most economical and efficient usage of components to fabricate the pressure vessel. Therefore, Rosedale can provide a competitively priced filter vessel based on your requirements.

The ASME Code defines several levels of examination. These defined below:

### **RT-1 Full Radiography**

When the complete vessel satisfies the full radiography requirements of UW-11(a) and when the spot radiography provisions of UW-11(a)(5) have not been applied.

### **RT-2 Full Radiography**

When the complete vessel satisfies the full radiography requirements of UW-11(a)(5) and when the spot radiography provisions of UW-11(a)(5)(b) have been applied.

### **RT-3 Spot Radiography**

When the complete vessel satisfies the spot radiography requirements of UW-11(b).

### **RT-4 Radiography by Designer**

When only part of the vessel has satisfied the radiographic requirements of UW-11(a) or when none of the markings RT-1, RT-2, or RT-3 are applicable.

The implications of each of the above levels of radiography can vary depending on the design of your filter vessel. The interpretation of what is required should be determined by Rosedale's engineering staff.

These definitions can also be misleading because of changes in definitions over the years by ASME, misinterpretation of "Full" vs. "Spot" radiography requirements, and customer defined radiography requirements.

Often customers, engineering firms, or end users will specify radiography or other NDE requirements beyond what is specified by the ASME Code. Rosedale can ensure compliance with the requirements of the ASME Code or customers specifications.

## Glossary

### **A**

**ABRASION:** Migration of foreign material which enters the fluid stream from system components that wear from close tolerances, vibration, or shock.

**ABRASIVE:** Any solid material, such as grit, with erosive properties.

**ABRASIVES:** Hard structurally strong solid.

**ABSOLUTE:** An arbitrary term used to describe or define a degree of filtration. The filtration industry uses various methods of determining absolute ratings which are not necessarily interchangeable. Generally absolute references 100% removal of solids (glass beads) above a specified micron rating on a single pass basis. See nominal.

**ABSOLUTE:** The sum of gage pressure and atmospheric pressure.

**ABSORB:** To take up by cohesive, chemical or molecular action.

**ABSORBENT:** A filter medium that holds contaminants by mechanical means. When one substance soaks completely through another, sometimes undergoing a chemical change.

**ACIDITY:** The quality, state, or degree of being acid. In lubricating oils, acidity denotes the presence of acid-type constituents whose concentration is usually defined in terms of a neutralization number. The constituents vary in nature and may or may not markedly influence the behavior of the fluid.

**ADDITIVE:** A material, usually chemical, added to a product to impart new or unusual characteristics or to improve existing characteristics.

**ADSORB:** To take up by adhesion of molecules of gases or dissolved substances to the surface of solid bodies, resulting in high concentration of the gas or solution at place of contact. Gas or solution is condensed on the surface of the adsorbent, while in adsorption, the material absorbed penetrates throughout the mass of adsorbent.

**ADSORBATE:** The material which is adsorbed; i.e., the gas, vapor, or liquid which adheres or is chemically attracted to the surface of the solid.

**ADSORBENT:** A material which adsorbs; i.e., the solid which attracts and holds on its surface the gas, vapor, or liquid. Also materials added to liquors to decolorize or purify by adsorbing the color or impurity. Fuller's earth, activated carbon, activate alumina, etc. are all adsorbents.

**ADSORBENT:** A filter medium primarily intended to hold soluble and insoluble contaminants on its surface by molecular adhesion - no chemical change.

**ADSORPTION:** The natural phenomenon of a gas, vapor, or liquid being attracted to and held on the surface of a solid. To some extent adsorption takes place on any solid surface, but certain materials have sufficient adsorbent capacity because of the finely divided material to make them useful in such industrial applications as the purification and separation of gases and liquids.

**AGGLOMERATE:** A group of two or more particles combined, joined, or clustered, by any means.

**AGGREGATE:** A relatively stable assembly of dry particles formed under the influence of physical forces.

**AMBIENT:** Surrounding. For example, ambient operating temperatures of a vessel is temperature essentially the same as that surrounding the vessel.

**ASME:** American Society of Mechanical Engineers.

**ASPHALTINE:** Product of partial oxidation of oil.

**ATMOSPHERIC PRESSURE:** The force exerted on a unit area by the weight of the atmosphere.

**ATOM:** Smallest particle of an element which retains properties of the element.  
Example: Carbon atom (C).

**AUTOCLAVE:** Sterilizing apparatus which uses steam at high pressure.

### **B**

**BACK PRESSURE:** In filter use, resistance offered by filter, usually measured in PSI.

**BACKWASH:** To clean a filter element by reversing the direction of flow through it.

**BASKET STRAINER:** Vessel for the removal of coarse bulk solids from liquid, air, or gas; element is a basket covered with a screen of a given mesh.

**BED (CAKE):** Mass of impurities which form on a filter element.

**BLEEDER:** A system in which part of

**BETA RATIO:** An accurate indication of how the filter performs throughout the life of the filter. The Beta Ratio is an average filtration rating.

the fluid from the main flow is diverted.

**BLOTTER TEST:** A visible means of checking oil clarity; one drop on a blotter will concentrate dirt or foreign matter in the center of the ring.

**BLOWBACK:** To reverse flow air, steam, or fluid through the media to effect solids removal. Sometimes referred to as backwash.

**BRIDGING:** A condition of filter element loading in which contaminant spans the space between adjacent sections of a filter element thus blocking a portion of the useful filtration area.

**BUNA N:** Gasket material. A synthetic rubber frequently used for vessel closures, flanges, and filter elements.

**BURST:** An outward structural failure of the filter element caused by excessive differential pressure.

**BY-PASS:** Condition resulting from the product flowing through a vessel other than through the media. Also a filtering system which filters only part of the stream on a continuous basis.

**BY-PASS INSTALLATION:** A system where part of the main flow is diverted to pass through a filter.

**BY-PASS VALVE:** Valve to pass the flow around the media or the vessel, usually activated at a given differential pressure setting.



**CAKE:** Solids deposited on the filter medium during filtration in sufficient thickness to be removed in sheets of sizable pieces. In many cases, cake may provide its own filter media by adding to the surface of media. Also referred to as discharged solids or residue.

**CANISTER:** Container or mounting mechanism for elements.

**CAPACITY:** Volume of product which a vessel will accommodate. This is expressed in gallons or similar units. Also amount which will filter at a given efficiency and flow rate, expressed in gallons per minute or similar units.

**CARTRIDGE:** Removable medium used in a vessel to perform the function of coalescing, filtering, or separating. Also referred to as element, media, repack, etc. Made in a specified physical shape to be mounted by use of hardware designed for that purpose.

**CARTRIDGE:** The porous device, usually fitting in a filter housing, which performs the actual process of filtration.

**CENTER PIPE:** Component of a vessel which is used as a mount for cartridges. Made with perforated effect to accommodate flow. A center rod is used for the same purpose but is not perforated and does not accommodate flow.

**CENTER-ROD:** Components of a vessel used for mounting cartridges in the vessel. Usually made of a round bar material. A center pipe can also be used for the same purpose, but is made with perforated effect and directs flow through the cartridge.

**CENTER SEAL:** Part which forms seal between two elements when one element is on the top of another element. Can also be called an adaptor.

**CENTER TUBE:** Component of an element or cartridge which supports the media at the center or smallest diameter.

**CENTIPOISE:** One one-hundredth of a poise. A poise is the unit of viscosity expressed as one dyne per second per square centimeter.

**CENTISTOKE:** One one-hundredth of a stoke. A stoke is equal to the viscosity in poises times the density of the fluid in grams per cubic centimeter.

**CHANNEL:** To cut grooves or lines in or through the solids deposited on the media, or through the media itself. Also may be described as a break-through in the media which would result in a by-pass.

**CLEANER BLADES:** Stationary blades located between stacked discs of a metallic self cleaning filter cartridge to comb out dirt particles as the cartridge is rotated.

**CLOUD POINT:** Temperature of a petroleum oil at which paraffin, wax or other solid substances begin to crystallize out or separate from solution when the oil is chilled under definite prescribed conditions.

**COAGULANT:** That which produces agglomeration of suspended solids.

**COALESCER:** A mechanical device which unites discrete droplets of one phase prior to being separated from a second phase. Can be accomplished only when both phases are immiscible. Requires a tight media which is preferentially wettable and, by its nature of being tight, the media is also a good filtering material. Good coalescing permits gravity separation of the discontinuous phase. Coalescing may be accomplished by only a coalescer cartridge when the specific gravities of the two phases are widely separated. As the gravities difference become less, the two stage principle is generally required where finely coalesced discontinuous droplets are repelled by the second stage separator cartridge.

**COALESCING:** The action of uniting of small droplets of one liquid preparatory to its being separated from another liquid.

**COLLAPSE PRESSURE:** The pressure impressed across a filter element (cartridge), sufficient to cause collapse of the element.

**COMBINATION:** A filter medium composed of two or more types, grade or arrangements of filter media to provide proportion which are not available in a single filter medium.

**CONTAMINANT:** Anything in the fluid that should not be there.

**CONTAMINATE:** The foreign matter in a fluid which is accumulated from various sources such as system dirt, residue from wear of moving parts, atmospheric solids which settle in an open system. Contaminates tend to discolor a liquid, cause additional wear on moving parts, cause system upsets in process stream, or reduce the efficiency of a fluid. Water as well as solid may be considered a contaminate when the presence of water causes adverse results. The presence of contaminates, whether liquid or solid, is the basis on which the use of filters or separator/filters are sought.

**CORE:** Material used for the center of an element, generally of the wound design. May also be called a center tube when used in the coalescer, separator, or other type filter element.

**CORROSION:** The conversion of metals into oxides, hydrated oxides, carbonates, or other compounds due to the action of air or water, or both. Salts and sulphur are also important sources of corrosion. Removal of solids and water reduces the effect or speed of corrosion in many cases; and in other cases, corrosion inhibitors are used to reduce the effect of corrosion.

**CP:** A section of less dense material in the media which allow a cold liquid to flow through the element controlling pressure drop below bypass opening.

**D DEGRADATION:** Wearing down, or reduction in the efficiency, of a media.

**DEGREE OF FILTRATION:** Fineness of a filter medium-size of the smallest particles filtered out.

**DELTA "P":** A Symbol (P) designating pressure drop. The difference in pressure between two points, generally measured at the inlet and outlet of a filter, separator/filter, etc. Normally measured in pounds per square inch (psi), inches of mercury (In. Hg.), or inches of water (In. H<sub>2</sub>O).

**DENSITY:** The weight per unit volume of a substance (specific weight).

**DEPTH:** A filter medium which primarily retains contaminants within the tortuous passages within the thickness of the element wall.

**DEPTH TYPE FILTRATION:** Filtration accomplished by flowing a fluid through a mass filter media providing a tortuous path with many entrapments to stop the contaminates. Flow may be cross flow such as from the outside to inside and then down the center of an element, or from end to end. Certain types of solids, or combinations of solids, do not lend to surface filtration and depth type filtration is found to be more suitable.

**DETERGENT OILS:** Lubricating oils possessing special sludge dispersing properties commonly used in internal combustion engines. These properties are incorporated in the oil by the use of special additives.

**DIELECTRIC:** A substance which will not conduct electricity.

**DIFFERENTIAL PRESSURE:** The difference in pressure between two given points of a filter, separator/filter, etc.

**DILATANT:** A flow condition where certain liquids will show an increase in viscosity as the rate of shear or flow volume is increased.

**DIRT HOLDING PRESSURE:** The volume of contaminate an element can hold before reaching the maximum allowable pressure drop. Volume will vary depending on the size and design of the element and the density of the solid particles. Usually reported by weight such as grams or pounds per element. Also called solids retention or solids holding capacity.

**DISCHARGE:** Flow rate through a filter.

**DISPOSABLE:** Describes element which is to be discarded after use and replaced with an identical element. Same as replaceable. Opposite of reusable.

**DUAL DENSITY:** A depth element that is constructed of two different medias not blended into a homogeneous mixture but remaining as two different distinctive medias.

**DROP:** The quantity of fluid which falls into one spherical mass; a liquid globule. May also be described as several to many droplets.

**DROPLET:** A minute drop which mates to form larger drops capable of falling by gravity.

**E** **EDGE FILTER:** Filter using shearing edges to separate solids from a liquid by shearing the oil film surrounding the particles (solid particles).

**EDGE TYPE:** Applies to liquid filters constructed of metal or paper discs, or specially constructed wire wound cylinders; contaminants are entrapped at the edges of the medium. Generally used to remove small quantities of very fine particles. Some have knife or blade cleaners to remove the accumulated solids.

**EFFECTIVE AREA:** The area of a medium that is exposed to flow and usable for its intended purpose: coalescing, filtering, or separating. Opposite of blind spots or dead area.

**EFFECTIVE OPEN AREA:** Area of the filtering medium through which the fluid may flow.

**EFFICIENCY:** Degree to which element will perform in removing solids and/or liquids. Output divided by input.

**ELEMENT:** Medium used in vessel to perform the function of coalescing, filtering, or separating. Also referred to as a cartridge, repack, etc. The porous device which performs the actual process of filtration.

**ELEMENT BY-PASS VALVE:** A valve within a filter to limit the differential pressure which can be impressed across the filter element.

**EMULSIFICATION:** A dispersion of one substance in the form of minute drops within another substance.

**EMULSION:** A dispersion of fine liquid particles in a liquid stream which do not necessarily dissolve in each other but are held in suspension. Many emulsions may be broken by coalescing if the liquids are immiscible. Emulsion stabilizers modify the surface tension of the droplets which makes coalescing difficult, if not impossible.

**ENTRAINED WATER:** Discrete water droplets carried by a continuous liquid or gas phase when water is immiscible with the liquid. May be separated from the continuous phase by coalescing and gravity separation. Usually picked up in a system by condensation or a water washing used in process.

**ENTRAINMENT:** Mist, fog, or droplets of a liquid which is usually considered to be a contaminate when used in the filtration industry.

**EXTENDED AREA:** Principal of shaping the element to give it more effective area than a simple cylinder of the same size.

**F** **FELTED ELEMENT:** Constructed by random layer of fibers, usually strengthened by a resin binder.



**FIBER:** Flexible material with two relatively small dimensions and one long dimension.

**FILTER:** A term generally applied to a device used to remove solid contaminate from a liquid or gas, or separate one liquid from another liquid or gas. A filter, as referred to in the industry today, is a device which removes contaminants. If a device is used to remove solids and liquids contaminants, it is referred to in general terms as a separator, separator/filter, or entrainment separator. A filter may be one of a number of such types as replaceable cartridge, cyclone, edge, leaf, baffle, plate and frame, pre-coat, and centrifuge. The term filter is sometimes erroneously used to describe the media used inside the vessel or filter case, but the correct use should be filter element, cartridge, etc.

**FILTER/COALESCER:** Single stage vessel for coalescing and separating one immiscible fluid from another and the removal of solids. Generally recommended for use where continuous phase has light gravity. Available with various efficiencies.

**FILTER EFFICIENCY:** Expressed as a percent of contaminant introduced to the system, it is the ability of a filter to remove specified contaminants at a given contaminant concentration under specified test condition.

**FILTER ELEMENT LIFE:** Span of operation from clean unit to a predetermined pressure drop build up - usually measured in lapsed time.

**FILTER LIFE:** Span of operation from start to complete plugging usually measured in hours of operation.

**FILTER MEDIUM:** The porous material mounted on a plate or frame which separates the solids from the liquids in filtering. Also referred to as filter cloth, filter plate, or septum. The material that performs the actual process of filtration.

**FILTRATE:** Filtered fluid which flows out of a filter.

**FILTRATION RATING, ABSOLUTE:** The diameter of the largest hard spherical particle that will pass through a filter under specified test conditions. This is an indication of the largest opening in the filter medium.

**KARL FISCHER:** Analytical method of determining amount of water present in a sample by titration.

**FLOW CHARACTERISTICS:** The nature of fluid movement as being turbulent, laminar, constant or variable rate to various degrees.

**FILTRATION RATING, MEAN:** A measurement of the average size of the pores of the filter medium.

**FILTRATION RATING, NOMINAL MICRON:** An arbitrary micron value indicated by the manufacturer. Often defined: 95% of all particles this size, and larger, retained by the filter medium.

**FLOW RATE:** The rate at which a product is passed through a vessel or system; generally expressed as gallons per minute, barrels per hour, barrels per day, actual or standard cubic feet per minute, hour, day, etc.

**FLUID:** A liquid or gas which can be filtered by passing through a filter.

**FREE WATER:** Water entrained in a lubricating oil or fuel forming two distinct phases with the fluid and having a tendency to separate as a result of the differences in densities.

**FULL FLOW:** Product flow through the vessel at the rate for which the vessel is designed to operate. Also refers to all products passing through a medium. The opposite of a by-pass filter which is designed to filter only a portion of the stream on a continuous basis.

**FULL FLOW FILTRATION:** System which provides for filtering all the fluid which is pumped to or from wear surfaces or work stations each pass.

**G GAGE PRESSURE:** All pressure greater than atmospheric pressure - as read on a pressure gage.

**GAS SCRUBBER:** A vessel designed to remove liquid and solid contaminants by impingement on a series of baffles or demister pads. Accomplished by drastic reduction of velocity as the gas enters the scrubber. Recent advances made in entrainment separation would expand the general use of the term to include mechanical cartridge type separators.



**GEL:** A semi-solid susceptible to pressure deformation. Has habit of sticking to surfaces.

**GRADUAL DENSITY:** A media of different densities. One media of a dense type packed around the center tube with a media of less density around the outside. Both medias are tapered at opposite directions. This allows high flow through the less dense media and tighter filtration through the dense media. Similar to the CP element in performance.

**GRAM LIFE:** Grams weight of contaminant introduced to a filter element at controlled rate to a determined differential pressure.

**GRAVIMETRIC EFFICIENCY:** Measure of efficiency in terms of weight.

**H** **HOLDING CAPACITY:** In general usage refers to the amount of solids, particulate or foreign material one or more elements is capable of retaining up to the terminal or maximum differential pressure. Also can refer to volumetric holding capacity of either a solid or a liquid.

**HOUSING:** Container for a filter element (s).

**HYDRAULIC FILTER, DUAL:** A hydraulic filter having two filter elements in parallel.

**HYDRAULIC FILTER, DUPLEX:** An assembly of two hydraulic filters with valving for selection of either or both filters.

**HYDRAULIC FILTER, FULL FLOW:**  
A hydraulic filter, which under specified conditions filters all influent flow.

**HYDRAULIC FILTER, TWO STAGE:**  
A hydraulic filter having two filter elements in series.

**HYDRAULICS:** The study of fluids at rest or in motion.

**HYDROPHILIC:** Water accepting or water wetting. Having an affinity for water. Capable of uniting with or dissolving in water. Effective coalescing requires a media to have hydrophilic characteristics which cause free or entrained water to commingle into droplets which, when mated with other droplets, form into drops which separate by gravity. Opposite of hydrophobic.

**HYDROPHOBIC:** Non-water wetting. Having an antagonism for water. Not capable of uniting or mixing with water. Hydrophobic features are induced in the process of cellulose manufacture. Opposite of hydrophilic.

**HYDROSTATIC TEST:** A test conducted with either air, water, or other fluids at a given value over design pressure, to prove the structural integrity of a pressure vessel.

**I** **IMMISCIBLE:** Incapable of being mixed; insoluble; opposite of miscible.

**IMPREGNATION:** Process of treating a coarse filter medium with resins.

**IMPURITY:** See "contaminant" - any undesirable material in the fluid.

**INDICATOR, BY-PASS:** An indicator which signals alternate flow.

**INDICATOR DIFFERENTIAL PRESSURE:**  
An indicator which signals the difference in pressure at two points.

**INITIAL PRESSURE DROP:** Loss in differential pressure between two points upon the start of flow through a vessel using new elements.

**IN-LINE:** Describes inlet and outlet connections which are positioned at the same height on opposite sides of a vessel so that an imaginary straight line can be drawn connecting one to the other. Also describes a small filtration unit that fits into a line and forms a similar image to the line, as in the case of a hose.

**INSOLUBLE:** Incapable of being dissolved in a fluid; opposite of soluble.

**INTERFACE:** Surface over which continuous phase and discontinuous phase are in contact.

**IMPINGEMENT:** The direct high velocity impact of the fluid flow upon or against an internal portion of the filter.

**K** **KEROSENE:** A petroleum liquid used as a fuel for commercial jet powered aircraft, or for heating purposes.

**KNIFE EDGE PLEATS:** The sharply defined creases at the outer edge of a pleated element.

**L LACQUER:** A natural or synthetic resin which is dissolved in a suitable solvent such as hydrocarbon oil rich in aromatics. When applied, the oil solvent evaporates, leaving behind a lacquer film.

**LINE SIZE:** The size of line used to carry the product in a system, such as a six-inch line.

**LUBRICATION:** Substituting fluid friction for solid friction by inserting oil between two moving parts.

**M MAGNETIC SEPARATOR:** A separator that uses a magnetic field to attract and hold ferro magnetic particles.

**MATRIX:** The structural support yarn or twine in wound elements is usually wound in a diamond.

**MAXIMUM DIFFERENTIAL PRESSURE:** The highest pressure differential which an element is required to withstand without structural failure or collapse.

**MAXIMUM OPERATING PRESSURE:** The maximum pressure allowed in a system.

**MEDIA:** Plural of medium. Material of which elements are made.

**MEDIA (MEDIUM):** A porous or slotted mass in a filter element to separate solids from a fluid by difference in size of openings and contaminant.

**MEDIA MIGRATION:** Carry-over of fibers from filter, separator elements, or other filter material into the effluent. Less definitive than fiber migration and is quantitative.

**MEDIUM:** The principle component of an element. A material of controlled pore size or mass through which a product is passed to remove foreign particles held in suspension or to repel droplets of coalesced water; or material without controlled pore size such as glass fiber mats which contribute to filtration, coalescence, or separation of two immiscible liquids.

**MEMBRANE:** In filtration the term membrane is used to describe the media through which the liquid stream is to be passed or exchanged. Membranes are normally associated with ion exchanged media such as dialysis, osmosis, diffusion, etc., although filter paper itself could be classed as a membrane.

**MERCAPTANS:** Unsaturated sulphurs.

**MICRON:** A short unit of length in the metric system. One millionth of a meter, 10-4 centimeter, 10-3 millimeter, or 0.000039 of one inch. Used as a criterion to evaluate the performance or efficiency of a filter media or to describe the condition of either the influent or effluent. Usually stated in terms of being either absolute or nominal. Nominal micron rating is generally taken to mean that 98% of all articles over a given micron value have been removed by a specific media or medium. Absolute micron rating is generally taken to mean that all particles over a given micron value have been removed. The naked eye can see a particle 40 microns or larger.

**MIGRATION:** Contaminant or media released to pass downstream from filter element.

**MMSCFD:** Million Standard Cubic Feet per Day.

**MMSCFH:** Million Standard Cubic Feet per Hour.

**MMSCFM:** Million Standard Cubic Feet per Minute.

**MODULAR:** A filter element which has no separate housing of its own, but whose housing is incorporated into the equipment which it services. It may also incorporate a suitable enclosure for the filter cavity.

**N NEWTONIAN:** A liquid which does not change in viscosity with a change in rate of shear, agitation or flow rate.

**NPT:** National Pipe Thread Standard.

**NTP:** Normal conditions of temperature and pressure. Whenever this term is used, it refers to a gas measured at pressure one (1) atmosphere absolute (760 mm. of Hg.) and a temperature of 0°C. However, some sources use a different reference temperature to define NTP.

**O** **OPEN AREA RATIO:** The ratio of pore area of a filter medium expressed as a percent of total area.

**OPERATING PRESSURE:** The normal pressure at which a system operates.

**OPERATING PRESSURE, CRITICAL:** Pressure above the normal or design limits which may cause damage or rupture.

**OPERATING PRESSURE, MAXIMUM:** The maximum pressure allowed in the system.

**OUTER SHELL:** Outer covering of element, usually perforated or screen.

**OUTER WRAP:** Outside covering of an element.

**OUTSIDE IN:** Flow of product from outside to inside of an element.

**P** **PAPER:** Medium used in many elements. A very general term applied to resin impregnated cellulose. Many types of paper or cellulose are used as filter media made to specifications.

**PARTIAL FLOW:** See "by-pass installation" - a system that diverts part of the main flow and passes it through a filter.

**PARTICLE COUNT:** A practice of counting particles of solid matter in groups based on relative size. Frequently used in engineering, a filter to a specific task or to evaluate the performance of a filter under specific operating conditions. When used as data to engineer a filter, proper consideration can be given to the type of media to be used, expectant life of the media, and the true cost of operation.

**PARTICLE SIZE DISTRIBUTION:** A tabulation resulting from a particle count of solids grouped by specified micron sizes to determine the condition of either the influent or effluent stream. Usually expressed in percentage of total solids to the specific group. Example: 31% in the 6 to 10 micron group. See particle count.

**PERCENT FREE AREA:** Quantitatively, proportion of an element's surface area.

**PLAIN:** A filter element whose medium is not pleated or otherwise extended, and has the geometric shape of a cylinder, cone disc, plate, etc.

**PLEATED:** A filter element whose medium consists of a series of uniform folds and has the geometric shape of a cylinder, cone, disc, plate, etc.

**PLASTISOL:** A suspension of thermosetting plastic which can be molded into any desired shape. Used as a combination end cap and gasket on element.

**PLUGGED:** Condition of a filter when it has collected its full capacity of contaminants and will not pass any more fluid.

**POROSITY:** The ratio of void volume to total cake volume. Also describes filter media which may have larger pores than other media.

**POUR POINT:** The lowest temperature at which a liquid will pour or flow without disturbance under specified conditions.

**PRE-COAT:** A filter medium in loose powder form, such as Fuller's or Diatomaceous earth, introduced into the upstream fluid to condition a filter element.

**PREFILTER:** Filter for removing gross contaminate before the product stream enters a separator/filter.

**PRESSURE:** The force exerted per unit area by a fluid.

**PRESSURE ABSOLUTE:** Gage pressure plus 14.7 psi.

**PRESSURE ATMOSPHERIC:** The force exerted by the atmosphere at sea level, which is equivalent to 14.7 psi.

**PRESSURE DIFFERENTIAL:** The difference in pressure between two points.

**PRESSURE DROP:** The difference in pressure between two points, generally at the inlet and outlet of a filter or a separator/filter. Measured in pounds per square inch gage, or inches of mercury.

**PRESSURE RATING, OPERATING:** The normal pressure at which a filter housing is capable of operating at specified operating conditions.

**PRESSURE RELIEF:** Valve which permits enough liquid or gas to escape from the vessel to prevent extreme pressure build up within the vessel.

**PSI:** Pounds per Square Inch.

**PSIA:** Pounds per Square Inch Absolute.

**PSID:** Pounds per Square Inch Differential.

**PSIG:** Pounds per Square Inch Gage.

**R RATE OF FLOW:** The rate at which a product is passed through a vessel or system; generally expressed as gallons per minute, barrels per hour, barrels per day, actual or standard cubic feet per minute, hour, day, etc. Same as flow rate.

**RATED FLOW:** Normal operating flow rate at which a product is passed through a vessel; flow rate which a vessel and media are designed to accommodate.

**REPLACEABLE:** Describes element which is to be removed after use and replaced with an identical element.

**REPLACEMENT ELEMENT:** An element or a cartridge used to replace a disposable which has been loaded to its capacity with (cartridge) contaminants.

**REUSABLE:** Describes element which may be cleaned and used again. Opposite of disposable or replaceable.

**S SAE:** Society of Automotive Engineers.

**SAE NUMBER:** A classification of lubricating oils for crankcase and transmissions in terms of viscosity as standardized by the Society of Automotive Engineers.

**SAYBOLD SECONDS UNIVERSAL (SSU):** Units of viscosity as measured by observing the time in seconds required for 60 ml. of a fluid to drain through a tubular orifice 0.483 inches long by 0.0695 inches in diameter at stated conditions of temperature, and pressure.

**SCFD:** Standard Cubic Feet per Day.

**SCFH:** Standard Cubic Feet per Hour.

**SCFM:** Standard Cubic Feet per Minute.

**SELF CLEANING:** A filter element designed to be cleaned without removing it from the filter assembly, or interrupting flow.

**SEPARATION:** The action of separating solids or liquids from fluids. May be accomplished by impingement, filtration, or by coalescing. The term "separation" is used in some circles when referring to the separation of liquids. Also used to describe the action in the second stage of two-stage separation.

**SEPARATOR:** A device whose primary function is to isolate contaminants by physical properties other than size.

**SEPARATOR/FILTER:** Vessel which removes solids and entrained liquids from another liquid or gas. Uses some combination of a baffle and/or coalescer, filter, or separator element. May be single stage, two stage, or single or two stage with prefilter section for gross solids removal. Common application is the removal of water from gas or another immiscible liquid. General reference to term applies the equipment is capable of both separation and filtration to specific degrees of efficiencies.

**SERVICE LIFE:** The length of time an element operates before reaching the maximum allowable pressure drop.

**SHELL:** Outer wall of a vessel. Also referred to as body.

**SHUNT INSTALLATION:** A system with a filter paralleled by a metering device both in the main supply line.

**SINTERED:** Media, usually metallic, processed to cause diffusion bonds at all contacting points, retaining openings the passage of filtrate.

**SKID MOUNTED:** Describes one or more vessels with pump and motor, all mounted on a portable platform.

**SLOT AREA:** Sum of the area of all the fluid path openings in a metal - edge filter element.

**SLUDGE:** Dirt, carbon, water and chemical compounds as found in oils.

**SOLID SUSPENSION:** A mixture of solids suspended in a fluid.

**SOLIDS:** A mass, or matter, contained in a stream which is considered undesirable and should be removed.

**SOLUTION:** A single phase combination of liquid and non-liquid substances, or two or more liquids.

**SPACING:** The distance between adjacent surfaces of stacked discs, edge wound ribbons, or single layer filaments. This dimension determines the smallest dimension of solid particles to be retained.

**SPECIFIC GRAVITY:** Ratio of substance's weight to that of some standard substance. (Water for liquids and solids, air or hydrogen for gases)

**SURFACE:** A filter medium which primarily retains contaminant on the influent face.

**SURFACE AREA:** Total area of an element that is exposed to approaching flow. See "percent free area".

**SURFACTANTS:** Coined expression for surface active agents which are sometimes called emulsifiers or wetting agents. First appeared in hydrocarbons with the advent of the catalytic cracking process in refining. Caused by the forming of sodium sulfonate and sodium naphthanate molecules. Affects liquid/liquid separation by reducing interfacial tension and forming into a slime which binds off the fibers used in coalescing media.

**SURGE:** The peak system pressure rise measured as a function of restricting or blocking fluid flow.

**SUSPENSION:** Solids or liquids held in other liquids.

**SUSPENDED SOLIDS:** Non-settled particles in fluid.

**SWING BOLT:** A type of vessel closure which reduces service time. Opposite of thru-bolt flange where studs and nuts are used, such as with ASA type flanges.

**T THIXOTROPIC:** A liquid which shows a marked reduction in viscosity as the rate of shear, agitation, or flow rate is increased.

**TORTUOSITY:** The ratio of the average effective flow path length to minimum theoretical flow path length (thickness) of a filter medium.

**TURBID METRIC EFFICIENCY:** (Filter inlet turbidity - Outlet turbidity)/by Inlet turbidity.

**TURBIDITY:** Stirred up sediment or contaminant in a fluid.

**TURN-OVER:** Number of times the contents of the system pass through a filter per unit time.

**U ULTRAFILTER:** Membrane type to remove very fine suspended submicronic particles as well as some dissolved solids.

**UNLOADING:** Release downstream of trapped contaminate, due to change in flow rate, mechanical shock and vibration, or as excessive pressure builds up, or media failure.

**V VACUUM:** Reference to pressure below atmospheric.

**VISCOSITY:** Degree of fluidity; property of fluid's molecular structure by virtue of which they resist flow. The resistance of flow exhibited by a liquid resulting from the combined effects of cohesion and adhesion. The units of measurement are the poise and the stoke. A liquid has a viscosity of one poise if a force of one dyne per square centimeter causes two parallel liquid surfaces one square centimeter in area and one centimeter apart to move past one another at a rate of one centimeter per second. There are a great many crude and empirical methods for measuring viscosity which generally involve measurement for the time of flow or movement of a ball, ring, or other object in a specially shaped or sized apparatus. The internal molecular friction of a liquid, or that property which resists any force tending to produce flow.

**W WOUND:** A filter medium comprised of two or more layers of helical wraps of a continuous strand or filament in a predetermined pattern.

**WOVEN:** A filter medium made from strands of fiber, thread, or wire interlaced into a cloth on a loom.

## **Chemical Resistance Guide**

### MAXIMUM RECOMMENDED OPERATING TEMPERATURES

<b>GASKET MATERIALS</b>	BUNA N	250°F
	ETHYLENE PROPYLENE	350°F
	VITON	450°F
	TEFLON	500°F
<b>FILTER MEDIA</b>	POLYESTER	300°F
	POLYPROPYLENE	180°F
	NYLON	325°F
<b>HOUSING MATERIALS</b>	CARBON STEEL	400°F
	304 STAINLESS STEEL	400°F
	316 STAINLESS STEEL	400°F
	PVC	150°F
	POLYPROPYLENE	150°F

**NOTES:** Maximum temperature at standard vessel design pressure.  
For higher temperatures consult Rosedale Products, Inc.



**Key**

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Acetaldehyde	●	●	●	●	●	●	●	●	●	●	●	120
Acetamide	●	●	●	●	●	●	●	●	○	○	○	○
Acetic Acid 5%	●	●	●	●	200	●	200	●	●	70	●	●
Acetic Acid 50%	●	●	●	●	200	●	70	●	●	70	●	●
Acetic Acid 80%	●	●	●	●	200	●	70	●	●	70	●	●
Acetic Acid 100%	●	●	●	●	200	150	70	●	●	●	●	●
Acetic Anhydride	●	●	●	●	○	●	○	●	●	●	●	●
Acetone	●	●	●	●	★	80	●	●	●	●	●	70
Acetophenone	●	●	●	●	●	●	●	200	●	●	○	●
Acetyl Chloride	●	●	●	●	●	●	●	●	●	○	●	●
Acetylene	●	●	●	●	○	●	●	●	●	70	○	○
Acrylic Acid	○	○	●	●	70	150	●	●	○	○	○	●
Acrylonitrile	●	●	70	●	70	70	70	●	●	○	○	70
Adipic Acid	○	○	○	○	○	●	●	●	●	70	○	○
Air-Compressed	●	●	●	●	●	●	●	●	●	70	●	●
Aluminum Acetate	●	●	●	●	○	70	○	●	●	70	○	○
Aluminum Ammonium Sulfate	○	○	○	○	○	●	○	○	○	○	○	●
Aluminum Chloride 5%	●	●	●	●	70	200	70	●	●	70	●	●
Aluminum Fluoride 5%	●	●	●	●	○	70	○	●	●	70	70	70
Aluminum Hydroxide	●	○	●	●	●	70	●	●	●	70	70	70
Aluminum Nitrate	●	●	●	●	○	70	○	●	●	70	70	70
Aluminum Sulfate	●	●	●	●	70	180	70	●	●	70	●	●
Amino Acids	○	○	●	●	○	○	○	○	●	○	○	○
Ammonia Gas (Dry)	70	●	●	○	150	20	○	●	●	70	●	●
Ammonium Bicarbonate	●	●	●	●	○	70	○	●	●	○	○	○
Ammonium Bromide 10%	●	●	●	●	○	○	○	○	○	○	○	○
Ammonium Carbonate 10%	●	●	●	●	●	180	●	●	●	70	●	●
Ammonium Chloride 10%	●	●	●	●	70	180	●	●	●	70	●	●
Ammonium Fluoride 10%	●	●	○	●	○	70	○	○	●	70	70	70
Ammonium Hydroxide 30%	●	●	●	●	70	200	100	●	●	70	●	●
Ammonium Nitrate 5%	●	●	●	●	70	●	●	●	●	70	●	●
Ammonium Phosphate	●	●	●	●	○	140	○	●	●	70	●	●
Ammonium Sulfate 5%	●	●	●	●	70	170	○	●	●	70	70	70
Ammonium Thiocyanate	●	●	○	●	70	○	70	●	●	70	○	○
Amyl Acetate	●	●	●	●	●	70	70	○	○	○	○	●
Amyl Alcohol	●	●	●	●	70	70	70	●	●	70	●	●
Aniline	●	●	160	●	70	180	70	●	●	●	●	●
Aqua Regia	●	●	●	●	●	75	●	●	●	70	●	●
Arsenic Acid	●	●	●	●	○	●	●	●	●	70	●	●

**Key**

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Asphalt	●	●	●	●	○ 70	○		●	●	●	○	○
Aviation Fuel	●	●	●	●	70	80	●	●	●	●	○	●
Banana Oil	●	●	●	●	70	●	70	●	●	●	●	70
Barium Carbonate	●	●	●	●	●	70	●	●	●	●	70	○
Beer	●	●	●	●	○	●	○	●	●	●	70	○
Beet Sugar Liquors	●	●	●	○	●	○	●	●	●	●	70	○
Benzene	●	●	70	●	●	●	●	●	●	●	●	●
Bromine (Dry)	●	●	●	●	●	70	●	●	●	●	80	○
Bromine (Wet)	●	●	●	●	●	●	●	●	●	●	80	○
Butane	●	●	●	●	250	70	●	●	●	●	70	○
Butanoic Acid	○	○	○	○	○	○	●	○	●	●	○	○
Butyl Acetate	●	●	●	●	●	200	●	●	●	●	70	○
Butyl Alcohol	●	●	●	●	100	●	●	●	●	●	70	●
Butyl Cellosolve	●	●	●	○	○	70	○	○	●	●	○	○
Butyl Chloride	○	○	○	○	○	○	○	●	●	●	○	○
Butylene	●	●	●	●	○	○	70	●	○	●	○	○
Butyric Acid	●	●	●	●	●	●	●	●	●	●	●	●
Calcium Chloride	●	●	●	200	●	●	●	●	●	●	70	●
Calcium Hydroxide 5%	●	●	●	●	100	200	●	●	●	●	70	●
Calcium Hypochlorite	●	●	●	●	●	200	●	●	●	●	70	●
Cane Sugar Liquors	●	●	●	●	●	●	●	●	●	●	70	●
Carbolic Acid (Phenol)	●	●	●	●	●	70	●	●	●	●	70	●
Carbon Dioxide (Dry)	●	●	●	●	○	●	100	●	●	●	●	●
Carbon Disulfide	●	●	●	●	70	●	70	●	●	●	●	●
Carbon Tetrachloride	●	●	●	●	●	100	●	●	●	●	80	70
Carbonated Water	●	●	●	●	○	●	100	●	●	●	70	●
Carbonic Acid	●	●	●	●	○	●	100	●	●	●	70	70
Castor Oil	●	●	●	●	○	●	○	●	●	●	70	●
Caustic Potash	●	●	●	●	○	●	●	☆	●	●	70	●
Caustic Soda	●	●	●	●	○	●	●	100	●	●	70	●
Cellosolve	●	●	●	○	○	70	○	100	○	100	70	○
Chloracetic Acid	●	●	●	●	●	70	●	●	●	●	70	●
Chlorine Gas (Dry)	●	●	●	●	○	●	●	70	●	●	80	●
Chlorine Gas (Wet)	●	●	●	●	○	●	●	●	●	●	80	●
Chlorobenzene	●	●	●	●	200	●	200	●	●	●	●	70
Chloroform (Dry)	●	●	●	●	70	70	●	●	●	●	●	●
Chromic Acid	●	●	●	●	●	80	●	●	●	●	80	80
Cider	●	●	●	●	○	●	○	●	●	●	70	●

**Key**

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Citric Acid	●	●	●	●	●	●	●	●	●	70	●	●
Cod Liver Oil	●	●	●	●	○	●	○	●	●	70	●	●
Coffee Extract	●	○	●	●	○	●	○	●	●	●	●	●
Cola Syrup	○	○	○	●	70	70	70	○	●	●	○	70
Copper Sulfate	●	●	●	●	70	●	●	●	●	70	●	●
Corn Oil	●	●	●	●	○	100	●	●	●	70	70	70
Cottonseed Oil	●	●	●	●	●	100	●	●	●	70	70	70
Creosol	○	●	●	●	●	●	●	○	○	○	○	○
Creosote	●	●	●	●	○	●	○	●	●	70	●	●
Cresylic Acid	●	●	●	●	●	●	●	○	○	70	●	●
Cyclohexane	●	●	●	●	200	●	○	●	●	●	●	●
Cyclohexanol	○	○	○	○	○	150	○	○	○	○	○	○
Cyclohexamine	●	●	●	●	200	●	●	70	○	70	●	●
DDT Solution	○	○	●	●	○	●	○	○	●	●	○	●
Dextrose	●	●	●	●	○	●	○	●	●	70	70	70
Diacetone Alcohol	●	●	●	●	○	70	○	●	●	●	●	●
Dibutyl Phthalate	●	●	●	●	○	70	○	●	●	●	○	●
Dichloroethane	●	●	●	●	○	●	○	○	●	●	○	○
Dichloroethylene	○	○	○	○	○	70	70	○	○	○	○	○
Diesel Fuel	●	●	●	●	○	120	●	●	●	80	120	120
Diethanolamine	●	●	●	●	●	●	●	○	○	○	○	●
Diethylene Glycol	●	●	●	●	●	●	●	○	○	○	○	●
Dimethyl Formamide	●	○	○	200	200	200	200	○	70	70	○	●
Diphenyl Oxide	●	●	●	●	○	70	○	●	●	●	○	70
Dowtherm	●	●	●	●	○	70	○	●	●	●	○	70
Epichlorohydrin	●	●	●	●	●	120	●	○	○	○	○	120
Ethanol	●	●	●	●	○	70	○	●	●	●	○	70
Ethanolamine	●	●	●	●	○	70	○	●	●	●	○	70
Ether	●	●	●	●	95	●	●	●	●	●	●	●
Ethyl Acetate	●	●	●	●	●	120	●	●	●	●	●	120
Ethyl Cellulose	●	●	●	●	○	70	○	○	○	○	○	70
Ethyl Chloride (Dry)	●	●	●	●	○	●	○	200	●	●	●	●
Ethylene Diamine	●	●	●	●	○	70	70	70	●	70	○	70
Ethylene Glycol	●	●	●	●	●	70	●	●	●	70	●	●
Ethylene Oxide	●	●	●	●	○	●	○	●	●	●	●	●
Fatty Acids	●	●	●	●	●	●	●	●	●	70	●	●
Ferric Chloride 1%	●	●	●	●	200	●	●	●	●	70	●	●

# Key

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Ferric Chloride	●	●	●	●	200	○	●	●	●	●	70	70
Ferric Nitrate	●	●	●	●	70	○	○	○	○	●	70	○
Ferric Sulfate 5%	●	●	●	●	70	●	70	●	●	●	70	●
Ferrous Chloride	●	○	○	●	70	●	70	●	○	70	○	●
Fish Oils	●	○	○	●	○	70	○	●	●	●	70	●
Fluosilicic Acid	●	●	●	●	○	70	○	●	○	●	70	●
Formaldehyde 10%	80	●	●	●	●	●	●	●	●	●	70	●
Formalin 40%	●	●	●	●	○	●	○	●	●	●	70	70
Formic Acid (Dilute)	●	●	●	●	●	●	●	●	●	●	70	70
Formic Acid (Conc.)	●	●	●	○	70	●	●	●	●	○	○	○
Freon 12	●	●	●	●	○	●	100	●	●	●	●	●
Freon 22	●	●	●	●	○	●	100	●	●	●	●	●
Fruit Juices	●	○	●	●	○	70	○	●	●	●	70	70
Fuel Oils	●	●	●	●	●	70	●	●	●	●	70	70
Furfural	●	●	●	●	○	70	○	●	●	●	●	●
Gas-Natural	●	●	●	●	●	70	●	●	●	●	70	70
Gasoline-Sour	●	●	●	●	○	●	70	●	●	●	80	●
Gasoline-Motor	●	●	●	●	○	●	●	●	●	●	80	●
Gasoline-Aviation	●	●	●	●	○	●	●	●	●	●	80	●
Gelatin	●	●	●	●	●	●	●	●	●	●	70	70
Glucose	●	●	●	●	○	●	○	●	●	●	70	70
Glycerine-Glycerol	●	●	●	●	●	●	●	●	●	●	70	70
Glycol	●	●	●	●	●	●	●	●	●	●	70	●
Glycol Monoether	●	●	●	●	○	70	○	○	●	●	70	70
Grease	●	●	●	●	○	●	○	●	●	●	70	●
Green Sulfate Liquor	●	●	●	●	○	70	●	●	●	○	○	○
Gum Arabic	○	●	○	●	○	○	○	○	●	○	○	○
Helium	●	●	●	●	●	●	●	●	●	○	70	70
Hexane	●	●	●	●	●	70	●	●	●	●	80	70
Honey	●	●	●	●	○	○	○	○	●	●	○	○
Hydraulic Oil-Petroleum Base	●	●	●	●	●	70	●	●	●	●	70	70
Hydraulic Oil-Phosphate Ester	●	●	●	●	●	70	●	●	●	○	70	70
Hydrazine	●	●	●	●	○	○	○	○	○	●	○	○
Hydrobromic Acid 10%	●	●	●	●	70	150	●	●	●	●	70	●
Hydrobromic Acid 50%	●	●	●	●	○	150	●	●	●	●	70	●
Hydrochloric Acid 5%	160	●	●	●	●	●	●	●	●	●	●	●

# Key

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Hydrochloric Acid 30%	70	70	70	●	●	●	●	●	●	●	●	70
Hydrocyanic Acid 5%	●	●	●	●	○	70	○	●	●	●	70	70
Hydrocyanic Acid	●	●	●	●	○	70	○	●	●	●	70	70
Hydrofluoric Acid 10%	80	70	○	●	●	●	●	●	●	●	80	●
Hydrofluoric Acid 50%	○	○	●	●	○	70	●	●	●	●	○	70
Hydrogen Gas	●	●	●	●	○	●	○	●	●	●	70	●
Hydrogen Peroxide 5%	●	●	●	●	●	150	●	●	●	●	70	140
Hydrogen Peroxide 30%	●	●	●	●	●	70	●	●	●	●	70	70
Hydrogen Sulfide (Dry)	70	●	●	●	○	70	○	●	●	●	80	70
Hydrogen Sulfide (Wet)	●	●	●	●	○	●	○	●	●	●	70	●
Hydroquinone	●	●	●	●	70	70	○	○	●	●	70	70
Insulating Oil	●	●	●	●	○	○	○	●	●	●	○	○
Iodine	●	●	●	●	●	●	●	●	●	●	●	70
Isopropyl Acete	●	●	●	●	○	○	○	○	○	●	○	○
Isopropyl Alcohol	●	●	●	●	70	●	○	●	●	●	70	●
Kerosene	●	●	●	●	●	70	●	●	●	●	70	70
Ketchup	●	○	●	●	○	70	○	○	●	●	○	70
Lactic Acid	70	70	●	●	70	●	70	○	●	●	70	●
Lard Oil	●	●	●	●	●	80	●	●	●	●	70	80
Latex (Natural)	●	○	●	●	○	70	○	●	●	●	○	70
Lead Acetate	●	●	●	●	●	●	●	●	●	●	70	70
Lime-Sulfur	●	●	●	●	○	70	○	○	●	●	○	70
Linoleic Acid	●	●	●	●	○	●	●	●	●	●	70	●
Linseed Oil	●	●	●	●	●	●	●	●	●	●	70	100
Lithium Bromide	○	○	○	●	○	70	○	●	○	●	○	70
Lithium Carbonate	●	○	○	●	○	70	○	○	○	○	○	70
Lithium Chloride	●	●	○	○	●	●	●	●	●	●	○	70
Lithium Hydroxide	●	●	○	○	○	●	●	●	●	●	○	70
Lube Oil	●	●	●	●	○	70	●	●	●	●	70	70
Lye	●	●	●	●	●	●	●	130	●	●	70	●
Magnesium Chloride	●	●	●	●	70	180	70	●	●	●	70	●
Magnesium Hydroxide	●	●	●	●	○	●	○	●	●	●	70	●
Magnesium Sulfate	●	●	●	●	○	180	○	●	●	●	70	70
Mayonnaise	●	○	●	●	○	70	○	●	●	●	○	70
Melamine Resins	●	○	●	●	○	70	○	○	●	●	○	70
Mercuric Chloride 10%	●	●	●	●	70	70	○	●	●	●	70	70
Mercurous Nitrate	●	●	○	●	○	70	○	●	●	●	70	70

**Key**

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Mercury	●	●	●	●	70	70	70	●	●	●	70	70
Methane	●	●	●	●	○	70	○	●	●	●	70	70
Methylene Chloride	●	●	●	●	100	●	100	100	150	212	●	●
Methyl Alcohol	●	●	●	●	●	●	●	●	●	●	70	●
Methyl Acetate	●	●	●	●	●	70	●	●	●	●	○	70
Methyl Cellosolve	●	●	●	●	○	70	○	●	●	●	●	70
Methyl Ethyl Ketone	●	●	●	●	70	●	●	●	●	●	●	70
Milk	●	●	●	●	●	●	●	●	●	●	●	●
Mineral Oil	●	●	●	●	○	70	○	●	●	●	70	70
Molasses	●	●	●	●	200	70	200	●	●	●	70	70
Monoethanolamine	●	●	●	●	○	70	○	●	●	●	○	70
Mustard	●	○	●	●	○	70	○	●	●	●	○	70
Naptha	●	●	●	●	200	70	200	●	●	●	70	70
Napthalene	●	●	●	●	70	70	70	●	●	●	●	●
Nickel Chloride	●	●	●	●	70	200	●	●	●	●	70	100
Nickel Sulfate	●	●	●	●	○	●	●	●	●	●	70	●
Nitric Acid 10%	●	●	70	●	●	210	●	●	●	●	70	100
Nitric Acid 20%	●	●	70	●	●	180	●	●	●	212	70	70
Nitric Acid 50%	●	●	70	●	●	70	●	●	212	212	70	70
Nitric Acid Fuming	●	●	●	●	●	●	●	●	125	125	●	●
Nitrobenzene 10%	●	●	●	●	200	●	200	●	●	●	●	●
Nitrobenzene	●	●	●	●	200	●	200	●	●	●	●	●
Nitrogen	●	●	●	●	●	●	●	●	●	●	○	●
Nitrous Oxide	●	○	○	●	○	○	○	●	●	●	70	70
Oil, Crude	●	●	●	●	●	70	●	●	●	●	70	70
Oleic Acid 5%	●	●	●	●	○	180	●	●	●	●	70	70
Oleic Acid	●	●	●	●	150	120	●	●	●	●	●	●
Oleum	●	●	●	●	○	●	●	●	●	●	●	●
Olive Oil	●	●	●	●	○	70	○	●	●	●	70	70
Oxalic Acid 5%	●	●	●	●	●	180	70	○	●	●	70	●
Palm Oil	●	○	●	●	○	70	○	●	●	●	○	70
Pentane	●	●	●	●	○	70	●	●	●	●	80	70
Perchloroethylene (Dry)	●	●	●	●	200	●	200	●	●	●	70	●
Petroleum Ether	●	●	●	●	●	70	●	●	●	●	70	70
Petroleum Oil-Refined	●	●	●	●	●	70	●	●	●	●	70	70
Petroleum Oil-Sour	●	●	●	●	●	70	●	●	●	●	70	70
Phenol	●	●	●	●	●	190	●	●	●	●	70	●



**Key**

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Phenol-Formaldehyde Resin	○	●	○	●	○	○	○	●	●	●	○	○
Phosphoric Acid 1%	●	●	●	●	210	210	●	●	212	●	70	●
Phosphoric Acid 10%	●	●	●	●	210	210	70	●	212	●	70	●
Phosphoric Acid 50%	70	●	●	●	●	180	●	●	212	●	70	●
Phosphoric Acid 80%	70	●	●	●	●	180	●	●	●	●	70	●
Picric Acid (H <sub>2</sub> O Sol'n.)	●	●	●	●	○	120	○	●	●	●	●	120
Pine Oil	●	●	●	●	70	70	70	●	●	●	○	70
Plating Solutions												
–Arsenic	●	●	●	●	○	150	○	●	○	●	○	150
–Brass Cyanide	●	●	○	●	○	●	○	●	●	○	70	●
–Bronze Cyanide	●	●	●	●	○	70	○	●	○	○	70	70
–Cadmium Cyanide	●	●	●	●	○	●	○	●	●	●	70	●
–Cadmium Fluoborate	●	●	●	●	○	70	○	○	●	●	70	70
–Copper Cyanide	●	●	●	●	○	●	○	●	●	●	70	●
–Gold Cyanide	●	●	●	●	○	●	○	○	●	●	●	●
–Iron Chloride	●	●	●	●	○	●	●	○	●	●	●	●
–Iron Sulfate	●	●	●	●	○	140	140	●	○	●	●	140
–Lead Alkali	●	●	●	●	○	●	●	●	○	●	70	●
–Lead Fluoborate	●	●	●	●	○	○	100	○	●	●	70	○
–Nickel Bright Chloride	●	●	●	●	○	70	○	○	●	●	70	70
–Nickel Dull Chloride	○	●	●	●	○	○	○	○	●	●	70	○
–Nickel Dull Fluoborate	●	●	●	●	○	●	170	○	○	●	●	●
–Silver	●	●	●	●	○	80	○	●	●	●	70	80
–Tin Acid	●	●	●	●	○	70	70	○	○	○	80	70
–Tin Fluoborate	●	●	●	●	○	100	100	○	●	●	80	100
–Zinc Cyanide	●	●	●	●	○	100	○	●	●	●	70	100
–Zinc Fluoborate	○	●	●	●	○	○	130	○	○	●	70	○
Potassium Acetate 10%	●	●	●	●	○	70	○	●	●	●	○	70
Potassium Bisulfate 10%	○	○	○	●	●	70	●	○	●	●	○	70
Potassium Carbonate 10%	●	●	●	●	●	180	●	●	●	●	●	●
Potassium Chloride 5%	●	●	●	●	70	180	○	●	●	●	70	●
Potassium Chromate 10%	●	●	●	●	○	70	○	○	●	●	70	70
Potassium Cyanide 5%	●	●	●	●	○	●	●	●	●	●	70	●
Potassium Ferrocyanide 10%	●	●	●	●	○	70	○	●	●	●	70	70
Potassium Permanganate 5%	●	●	●	●	●	150	●	●	●	●	70	70
Potassium Sulfate 5%	●	●	●	●	120	180	120	●	●	●	70	●
Propane	●	●	●	●	250	100	200	●	●	●	80	100
Propionic Acid	○	●	○	●	●	70	●	●	●	●	○	70
Propylene Glycol	●	●	●	●	●	70	●	●	●	●	○	70

**Key**

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Propylene Oxide	●	●	●	●	○ 70	○	○	○	○	○	○	70
Pyridine	●	●	●	○	●	●	●	●	●	○	○	●
Sea Water	●	●	●	●	210	●	240	●	●	●	●	●
Shellac	●	●	○	●	○ 70	○	○	●	●	●	○	70
Silver Nitrate	●	●	●	●	●	●	●	●	●	●	70	●
Soda Ash	●	●	●	●	70	70	●	●	●	●	70	70
Sodium Acetate	●	●	●	●	●	●	●	●	●	●	70	●
Sodium Bicarbonate	●	●	●	●	○	●	○	●	●	●	70	●
Sodium Bisulfate	●	●	●	●	70	150	●	●	●	●	70	70
Sodium Bisulfite	●	●	●	●	●	180	●	●	○	100	○	70
Sodium Borate	●	●	●	●	○	70	○	●	●	●	70	70
Sodium Carbonate	●	●	●	●	●	●	●	●	●	●	70	70
Sodium Chlorate	●	○	●	●	○	180	○	○	●	●	70	120
Sodium Chloride 10%	●	●	●	●	●	●	●	●	●	●	70	●
Sodium Cyanide	●	●	●	●	●	●	●	●	●	●	70	●
Sodium Fluoride 5%	●	●	●	●	○	70	○	●	●	●	70	●
Sodium Hydroxide 5%	●	●	●	●	70	●	●	●	●	●	70	70
Sodium Hydroxide 20%	●	●	●	●	●	●	●	●	●	●	70	70
Sodium Hydroxide 40%	●	●	●	●	●	●	●	●	●	●	70	70
Sodium Hypochlorite 5%	●	●	●	●	●	120	●	●	●	●	70	70
Sodium Metaphosphate	●	●	●	●	○	70	○	●	●	●	70	70
Sodium Nitrate 5%	●	●	○	●	70	180	70	●	●	●	70	70
Sodium Perborate 1%	●	●	●	●	160	180	○	●	●	●	70	●
Sodium Peroxide	●	●	●	●	●	70	○	●	●	●	70	70
Sodium Phosphate	●	●	●	●	70	180	●	●	●	120	●	●
Sodium Polysulfide	○	○	○	●	○	○	○	○	●	●	○	○
Sodium Silicate	●	●	●	●	○	180	○	●	●	●	70	●
Sodium Sulfate	●	●	●	●	70	180	70	●	●	●	70	●
Sodium Sulfide	●	●	●	●	●	180	●	●	●	●	70	70
Sodium Thiosulfate	○	○	○	●	70	70	70	●	●	●	70	70
Soybean Oil	●	●	●	●	70	180	○	●	●	●	70	●
Stannic Chloride 5%	●	●	●	●	○	100	●	●	●	●	70	100
Stannous Chloride 5%	●	●	●	●	70	70	70	●	●	●	70	70
Starch	●	●	●	●	○	●	○	●	●	●	70	70
Steam	○	●	○	●	○	220	240	●	●	●	70	●
Steacates	●	●	●	●	○	●	●	●	●	●	70	●
Stearic Acid	●	●	○	●	○	●	●	●	●	●	70	●
Stoddard Solvent	●	●	●	●	70	70	70	●	●	●	70	70

# Key

● = Recommended for most conditions up to the maximum temperature of the material.

● = Fair. May be acceptable, but testing is recommended.

● = Not recommended.

○ = No data available. Customer testing required.

Number (i.e. 70) = Maximum temperature in degrees F°

	GASKET MATERIALS				FILTER MEDIA			HOUSING MATERIALS				
	Buna N	Ethylene Propylene	Viton	Teflon® Fluorocarbon	Polyester	Polypropylene	Nylon	Carbon Steel	304 Stainless Steel	316 Stainless Steel	PVC	Polypropylene
Sucrose Solutions	●	●	●	●	○	●	○	●	●	70	70	●
Sulfate Liquors	●	●	●	●	○	70	●	○	●	70	●	●
Sulfur Dioxide (Dry)	●	●	●	●	○	●	●	●	●	70	●	●
Sulfur Trioxide (Dry)	●	●	●	●	○	●	●	●	●	70	●	●
Sulfuric Acid 5%	●	●	●	●	150	●	●	●	●	70	●	●
Sulfuric Acid 50%	●	●	●	●	70	180	●	●	●	70	70	●
Sulfuric Acid 96%	●	●	●	●	●	70	●	●	●	70	●	●
Sulfuric Acid Fuming	●	●	●	●	●	●	●	●	●	70	●	●
Sulfurous Acid	●	●	●	●	○	●	●	●	●	70	●	●
Tannic Acid 10%	●	●	●	●	70	●	70	●	●	70	●	●
Tartaric Acid	●	●	●	●	○	150	○	●	●	70	70	●
Tetrachlorethylene (Dry)	●	●	●	●	○	212	●	●	●	70	●	●
Tetrachloroethane	●	●	●	○	70	70	70	75	●	70	70	●
Tetrahydrofuran	●	●	●	●	○	70	100	●	●	70	●	●
Toluene	●	●	●	●	70	120	●	●	●	120	●	●
Transformer Oil	●	●	●	●	○	120	○	●	●	70	120	●
Trichloroethylene (Dry)	●	●	●	●	70	70	70	●	●	70	●	●
Triethanolamine	●	●	●	●	70	70	○	●	●	70	●	●
Trisodium Phosphate	●	●	○	●	70	120	70	○	●	70	120	●
Tung Oil	●	●	●	●	○	70	○	●	●	70	●	●
Turpentine	●	●	●	●	70	70	●	●	●	80	70	●
Urea-Formaldehyde Resin	○	○	○	●	○	○	○	●	○	○	○	○
Vanilla Extract	○	○	○	●	○	●	○	○	●	○	70	●
Varnish	●	●	●	●	○	●	●	●	●	○	●	●
Vegetables Oils	●	●	●	●	○	100	●	●	●	○	100	●
Vinegar	●	●	●	●	○	150	●	●	●	70	●	●
Water-Fresh	●	●	●	●	210	●	240	●	●	70	●	●
Water-Salt	●	●	●	●	210	●	240	●	●	70	●	●
Waxes	○	○	●	●	○	70	○	●	●	○	●	●
Whiskey	●	●	●	●	○	70	●	●	●	70	70	●
Wine	●	●	●	●	○	70	●	●	●	70	70	●
Xylene	●	●	●	●	●	●	●	●	●	●	●	●
Zinc Bromide	●	○	○	●	○	●	●	○	○	○	●	●
Zinc Cyanide	●	○	○	○	○	●	●	●	●	○	●	●
Zinc Sulfate	●	●	●	●	●	●	●	●	●	70	●	●



## Conversion Information

### Conversion Information U.S. Mesh to Micron Particle Size

#### COMPARATIVE PARTICLE SIZE

U. S. MESH	INCHES	MICRONS	U.S. MESH	INCHES	MICRONS
3	.265	6730	40	.0165	420
3-1/2	.223	5660	45	.0138	354
4	.187	4760	50	.0117	297
5	.157	4000	60	.0098	250
6	.132	3360	70	.0083	210
7	.111	2830	80	.0070	177
8	.0937	2380	100	.0059	149
10	.0787	2000	120	.0049	125
12	.0661	1680	140	.0041	105
14	.0555	1410	170	.0035	88
16	.0469	1190	200	.0029	74
18	.0394	1000	230	.0024	63
20	.0331	841	270	.0021	53
25	.0280	707	325	.0017	44
30	.0232	595	400	.0015	37
35	.0197	500			

#### SCREEN MICRON AND MESH RATINGS

MICRON or MESH RATING	ROSEDALE MESH USED	MIN. BUBBLE POINT IN INCHES (H <sub>2</sub> O)
2 MICRON	325X2300DT*	12.0
5 MICRON	200X1400DT	9.5
10 MICRON	165X1400DT	6.0
20 MICRON	165X800DT	4.8
40 MICRON	80X700DT	3.5
200 MESH	200P**	-
150 MESH	150P	-
100 MESH	100P	-
80 MESH	80P	-
60 MESH	60P	-
40 MESH	40P	-

\* DT = Dutch Twilled Weave    \*\*P = Plain Weave

**VISCOSITY CONVERSION CHART**

Viscosity Measurement Method	CPS							TEMPERATURE = 77°F				
	10	20	50	100	200	500	1000	2000	5000	10,000	20,000	50,000
ASTM, 07				72	143	357	715	1430	3750	7150	14,300	35,700
ASTM, 10					42	104	208	417	1041	2080	4170	10,410
ASTM, 15						24	48	95	238	476	953	2,380
ASTM, 20						8	16	33	82	164	328	820
ASTM, 25							7	14	36	72	143	357
Brookfield	10	20	50	100	200	500	1000	2000	5000	10,000	20,000	50,000
Demmer #1				32	63	156	312					
Demmer #10				3	6	15	31					
Engler (degrees)				14	27	68	137	274	685	1370	2,740	6,850
Engler (sec.)				690	1300	3460	7000	4,000		70,500		
Ford #3				42	84	208	416	834	2081	4160	8,340	20,810
Ford #4				30	55	135	270	540	1350	2700	5,400	13,500
Fisher #1	200	30										
Fisher #2		15	24	50								
Gardner-Holdt (units)	A-3	A-2	A	D	H	S	W	Y-Z	Z3	Z5	Z6-Z7	Z7-Z8
Gardner-Holdt (sec.)						5	10	20	50	100	200	500
Gardner-Verticle (sec.)						5	10	20	50	100	200	500
Krebs-Stormer (units)	85	105	140			67	85	105	140			
Parlin 7				77	154	385	770	1540	3850	7700	15,400	38,500
Parlin 10				21	42	104	208	416	1040	2080	4,160	10,400
Parlin 15					10	25	47	93	232	465	930	2,320
Parlin 20						8	17	33	83	167	333	833
Parlin 25								15	36	72	143	357
Parlin 30									19	38	77	192
Saybolt Furol			24	48	96	238	476	954	2380	4760	9,540	23,800
Saybolt Universal (SUS)		96	238	476	954	2380	4760	9540	23,800	47,600	95,400	
Zahn G1		38	60	100	267	667	1332	2670	6670	13,320	26,700	66,700
Zahn G2		16	24	42	82	161	323	645	1610	3,230	6,450	16,100
Zahn G3					27	58	113	204	510	1,020	2,040	5,100
Zahn G4					19	38	71	160	400	800	1,600	4,000
Zahn G5					13	27	50	97	212	424	848	2,120

**COMPARATIVE FINENESS DATA**

HEGMAN(S) SCALE	PRODUCTION CLUB SCALE	DEPTH OF MILS	WELLS MICRON	CLOSEST U.S. MESH SIZE
0	0.00	4.0	100.00	140
1	1.25	3.50	87.50	170
2	2.50	3.00	75.00	200
3	3.75	2.50	62.50	230
4	5.00	2.00	50.00	325
5	6.25	1.50	37.50	—
6	7.50	1.00	25.00	400
7	8.75	0.50	12.50	—
7-1/2		0.25	6.25	—
8	10.00	0.00	0.00	—

**APPROXIMATE VISCOSITY OF COMMON LIQUIDS**

LIQUID	VISCOSITY CPS	@ TEMPERATURE °F	LIQUID	VISCOSITY CPS	@ TEMPERATURE °F
Asphalt, Virgin	7,250	250	Neasfoot Oil	230	100
Asphalt Emulsion	2,100	300		130	130
Type I	4,000	100	Oils—		
	1,025	100	Fuel Oil No. 1	37	70
Asphalt Emulsion,			Fuel Oil No. 2	33	100
Types II, V & VI	575	77	Fuel Oil No. 5	500	100
	220	100		175	130
Black Liquor	3,100	122	Fuel Oil No. 6	1,725	122
	1,525	130		480	160
Bone Oil	220	130	SAE No. 10	200	100
	65	212		105	130
Carbolic Acid	65	65	SAE No. 20	320	100
Castor Oil	1,350	100		150	130
	525	130	SAE No. 30	490	100
Caustic Soda Solution				220	130
20% NaOH	40	65	SAE No. 50	1,275	100
30%NaOH	58	65		95	210
40%NaOH	110	65	SAE No. 70	2,700	100
Cocanut Oil	144	100		140	210
	78	130	SAE No. 90 Trans-		
Cod Oil	150	100	mission Lube	1,150	100
	95	130		400	130
Cottonseed Oil	176	100	SAE No. 140 Trans-		
	100	130	mission lube	1,625	130
Glucose	67,500	100		160	210
	7,500	150	Olive Oil	200	100
Glycerine (100%)	2,950	68.6		115	130
	813	100	Peanut Oil	250	100
Glycol:				145	130
Propylene	240	70	Petrolatum	100	130
Triethylene	190	70		77	160
Diethylene	150	70	Printers' Ink	6,250	100
Ethylene	90	70		2,100	130
Insulating Oil	115	70	Rosin (Wood)	25,500	190
	65	100		10,300	200
Kerosene	35	68	Sulfuric Acid (100%)	75.7	68
	32.6	100	Turbine Lube Oil	420	100
Lard	287	100	Turpentine	33	60
	160	130		32.6	100
Linseed Oil, Raw	143	100	Varnish—Spar	1,425	68
	93	130		650	100
Molasses, C	135,000	100			
(Blackstrap of final)	40,000	130			



**DISCLAIMER OF WARRANTY:** To the best of our knowledge, the data contained in this publication is correct; however, we do not assume any liability for the accuracy or completeness of the information. Users should perform their own tests to determine final suitability. Final determination of the suitability of any information or product for the use contemplated by any user, the manner of that use, and whether there is any infringement of patents is the sole responsibility of the user. Copyright Rosedale Products, Inc. 2014



Rosedale inventory of Multi-Bag housings





Catalog 6 – 08/2014

## ROSEDALE FILTRATION PRODUCTS, INC.

3730 W. Liberty / Ann Arbor, Michigan 48103 / 800-821-5373 or 734-665-8201  
Fax 734-665-2214 / [filters@rosedaleproducts.com](mailto:filters@rosedaleproducts.com) / [www.rosedaleproducts.com](http://www.rosedaleproducts.com)